

# 1 Dp

## 1.1 01\_knapsack

```
1 for(int i = 0; i < 100005; i++) dp[i] = dp1[i] = 205;
2 dp[0] = dp1[0] = 0;
3 for(int i = 1; i <= n; i++) {
4     for(int j = 1e5+1; j >= a[i]; j--) { // 到著做回
5         dp[j] = min(dp[j-a[i]] + 1, dp[j]);
6     }
7 }
```

## 1.2 Josephus

```
1 int josephus(int n, int k) { // n people, kth is killed
2     if (n == 1) return 1;
3     else return (josephus(n - 1, k) + k - 1) % n + 1;
4     /* The position returned by josephus(n - 1, k)
5      is adjusted because the recursive call
6      josephus(n - 1, k) considers the
7      original position k % n + 1 as position 1 */
8 }
```

## 1.3 Bitmask

```
1 // n個城市, m個單向邊, 求從1出發走到n的所有 徑數
2 // 遞迴版本, 存反向圖
3 ll alln;
4 ll tbl[20][1<<20]; // 建表
5 ll dp(int i, ll vs) {
6     if(tbl[i][vs]) return tbl[i][vs];
7     if(vs == alln && i == 0) return 1;
8     if(vs == alln || i == 0) return 0;
9     ll r = 0;
10    For(j, n) {
11        if(!g[i][j]) continue;
12        if(vs & (1<<j)) continue;
13        r += dp(j, vs | (1<<j)) * g[i][j];
14        r %= mod;
15    }
16    return tbl[i][vs] = r % mod;
17 }
18
19 alln = (1<<n)-1;
20 ans = dp(n-1, 1<<(n-1))%mod; //從最後一點遞迴回去, bitmask n
    -1位為1, 其餘為0
21
22 // TLE版本, 迴圈版很難壓常, 存正向圖
23 N = (1<<n)-1; // 可表示n個bit的bitmask
24 dp[0][1] = 1;
25 for(int mask = 1; mask <= N; mask++) {
26     for(int i = 0; i < n; i++) {
27         if(!(1 & mask>>i)) continue;
28         int mask2 = mask - (1<<i);
29         for(int j = 0; j < n; j++) {
30             if(!(1 & mask2>>j) || g[j][i] == 0) continue;
```

```
31         dp[i][mask] += dp[j][mask2]*g[j][i]; // 非簡單
    圖, 可能有重複單向邊, g[i][j]存邊數
32         dp[i][mask] %= mod;
33     }
34 }
35 }
36 cout << dp[n-1][N] % mod << '\n';
```

## 1.4 InfinitKnapsack

```
1 // 找零問題
2 int main() { //O(n^2)
3     dp[0] = 1;
4     for(ll i = 1; i <= n; i++) {
5         for(ll j = a[i]; j < 30001; j++) { // 順著做過去
6             dp[j] += dp[j-a[i]];
7             if(dp[j-a[i]]) coin[j] = i; // 此 額當前拿ㄌ哪一
    個錢幣
8         }
9     }
10    ll ans = dp[sum]; // sum = 所求 額
11    while (sum) {
12        ans.push_back(coin[sum]);
13        sum -= a[coin[sum]]; // 遞迴找用過哪些錢幣
14    }
15 }
```

# 2 Data Structure

## 2.1 DSU

```
1 class DSU{
2 public:
3     DSU(int n) {
4         this->n = n;
5         reset();
6     }
7     int n;
8     vector<int> boss;
9     vector<int> rank;
10    vector<int> size;
11    void reset() {
12        this->boss.resize(n);
13        this->rank.resize(n,0);
14        this->size.resize(n,0);
15        for(int i = 0; i < n; i++) {
16            boss[i] = i;
17        }
18    }
19    int find(int x) {
20        if(boss[x] != x) {
21            boss[x] = find(boss[x]);
22        }
23        return boss[x];
24    }
25    int get_size(int x) {
26        return size[find(x)];
```

```
27 }
28 void merge(int x, int y) {
29     int a = find(x);
30     int b = find(y);
31     if(a!=b) {
32         if(rank[a]<rank[b]) {
33             boss[a] = b;
34             size[b] += size[a];
35         }else if (rank[a]<rank[b]) {
36             boss[b] = a;
37             size[a] += size[b];
38         }else{
39             boss[a] = b;
40             size[b] += size[a];
41             rank[b]++;
42         }
43     }
44 }
45 bool aresame(int a,int b){
46     return find(a)==find(b);
47 }
48 };
```

## 2.2 Monotonic Queue

```
1 class Monotonic_queue{
2 private:
3     deque<int> qu;
4 public:
5     void push(int n){
6         while(!qu.empty() && qu.back() < n) {
7             qu.pop_back();
8         }
9         qu.push_back(n);
10    }
11    int max() {
12        return qu.front();
13    }
14    int min() {
15        return qu.back();
16    }
17    int size() {
18        return qu.size();
19    }
20    void pop() {
21        qu.pop_front();
22    }
23 };
```

## 2.3 BIT

```
1 class BIT{
2 public:
3     vector<int> bit;
4     int N;
5     BIT(int n) {
6         this->N = n;
7         this->bit.resize(n);
8     }
9     void update(int x,int d) {
```

```

10 while(x<=N){
11     bit[x] +=d;
12     x +=x&(-x); // lowest bit in x;
13 }
14
15 int query(int x){
16     int res = 0;
17     while(x){
18         res+= bit[x];
19         x -= x&-x;
20     }
21     return res;
22 }
23 };

```

## 2.4 Treap

```

1 // 區間加值、反轉、rotate、刪除、插入元素、求區間
2 // srand(time(0))
3 class Treap {
4     private:
5     struct Node {
6         int pri = rand(), size = 1;
7         ll val, mn, inc = 0; bool rev = 0;
8         Node *lc = 0, *rc = 0;
9         Node(ll v) { val = mn = v; }
10    };
11    Node* root = 0;
12    void rev(Node* t) {
13        if (!t) return;
14        swap(t->lc, t->rc), t->rev ^= 1;
15    }
16    void update(Node* t, ll v) {
17        if (!t) return;
18        t->val += v, t->inc += v, t->mn += v;
19    }
20    void push(Node* t) {
21        if (t->rev) rev(t->lc), rev(t->rc), t->rev = 0;
22        update(t->lc, t->inc), update(t->rc, t->inc);
23        t->inc = 0;
24    }
25    void pull(Node* t) {
26        t->size = 1 + size(t->lc) + size(t->rc);
27        t->mn = t->val;
28        if (t->lc) t->mn = min(t->mn, t->lc->mn);
29        if (t->rc) t->mn = min(t->mn, t->rc->mn);
30    }
31    void discard(Node* t) { // 看要不要釋放記憶體
32        if (!t) return;
33        discard(t->lc), discard(t->rc);
34        delete t;
35    }
36    void split(Node* t, Node*& a, Node*& b, int k) {
37        if (!t) return a = b = 0, void();
38        push(t);
39        if (size(t->lc) < k) {
40            a = t;
41            split(t->rc, a->rc, b, k - size(t->lc) - 1);
42            pull(a);
43        } else {
44            b = t;
45            split(t->lc, a, b->lc, k);
46            pull(b);

```

```

47    }
48    }
49    Node* merge(Node* a, Node* b) {
50        if (!a || !b) return a ? a : b;
51        if (a->pri > b->pri) {
52            push(a);
53            a->rc = merge(a->rc, b);
54            pull(a);
55            return a;
56        } else {
57            push(b);
58            b->lc = merge(a, b->lc);
59            pull(b);
60            return b;
61        }
62    }
63    inline int size(Node* t) { return t ? t->size : 0; }
64    public:
65    int size() { return size(root); }
66    void add(int l, int r, ll val) {
67        Node *a, *b, *c, *d;
68        split(root, a, b, r);
69        split(a, c, d, l - 1);
70        update(d, val);
71        root = merge(merge(c, d), b);
72    }
73    // 反轉區間 [l, r]
74    void reverse(int l, int r) {
75        Node *a, *b, *c, *d;
76        split(root, a, b, r);
77        split(a, c, d, l - 1);
78        swap(d->lc, d->rc);
79        d->rev ^= 1;
80        root = merge(merge(c, d), b);
81    }
82    // 區間 [l, r] 向右 rotate k 次, k < 0 表向左 rotate
83    void rotate(int l, int r, int k) {
84        int len = r - l + 1;
85        Node *a, *b, *c, *d, *e, *f;
86        split(root, a, b, r);
87        split(a, c, d, l - 1);
88        k = (k + len) % len;
89        split(d, e, f, len - k);
90        root = merge(merge(c, merge(f, e)), b);
91    }
92    // 插入一個元素 val 使其 index = i <= size
93    void insert(int i, ll val) {
94        if (i == size() + 1) {
95            push_back(val); return;
96        }
97        assert(i <= size());
98        Node *a, *b;
99        split(root, a, b, i - 1);
100        root = merge(merge(a, new Node(val)), b);
101    }
102    void push_back(ll val) {
103        root = merge(root, new Node(val));
104    }
105    void remove(int l, int r) {
106        int len = r - l + 1;
107        Node *a, *b, *c, *d;
108        split(root, a, b, l - 1);
109        split(b, c, d, len);
110        discard(c); // 看你要不要釋放記憶體
111        root = merge(a, d);

```

```

112    }
113    ll minn(int l, int r) {
114        Node *a, *b, *c, *d;
115        split(root, a, b, r);
116        split(a, c, d, l - 1);
117        int ans = d->mn;
118        root = merge(merge(c, d), b);
119        return ans;
120    }
121 };

```

## 2.5 Segment Tree

```

1 class SegmentTree{
2     private:
3     const int n;
4     const vl arr;
5     // vl st;
6     vl summ;
7     vl minn;
8     vl maxx;
9     vl tag;
10    void pull(int l,int r,int v){
11        if(r-l==1)
12            return;
13        // st[v]=st[2*v+1]+st[2*v+2];
14        int mid=(l+r)/2;
15        push(l,mid,2*v+1);
16        push(mid,r,2*v+2);
17        summ[v]=summ[2*v+1]+summ[2*v+2];
18        // minn[v]=min(minn[2*v+1],minn[2*v+2]);
19        // maxx[v]=max(maxx[2*v+1],maxx[2*v+2]);
20    }
21    void push(int l,int r,int v){
22        summ[v]+=tag[v]*(r-l);
23        if(r-l==1)
24            return tag[v]=0,void();
25        tag[2*v+1]+=tag[v];
26        tag[2*v+2]+=tag[v];
27        tag[v]=0;
28    }
29    void build(int l,int r,int v=0){
30        if(r-l==1){
31            summ[v]=arr[l];
32            // summ[v]=minn[v]=maxx[v]=arr[l];
33            return;
34        }
35        int mid=(l+r)/2;
36        build(l,mid,2*v+1);
37        build(mid,r,2*v+2);
38        pull(l,r,v);
39    }
40    public:
41    SegmentTree(vl&_arr,int _n):arr(_arr),n(_n){
42        assert(arr.size()==n);
43        summ.assign(4*n,0);
44        // minn.assign(4*n,1e9);
45        // maxx.assign(4*n,-1e9);
46        tag.assign(4*n,0);
47        build(0,arr.size());
48    }
49    void modify(int x,int val,int l,int r,int v=0){
50

```

```

51 }
52 // query sum
53 loli query(int L,int R,int l,int r,int v=0) {
54     // dbn(L,R,l,r,v)
55     push(l,r,v);
56     if(l==L && R==r) {
57         return summ[v];
58         return minn[v];
59         return maxx[v];
60     }
61     int mid=(l+r)/2;
62     if(R<=mid)
63         return query(L,R,l,mid,2*v+1);
64     else if(mid<=L)
65         return query(L,R,mid,r,2*v+2);
66     else
67         return query(L,mid,l,mid,2*v+1)+query(mid,R,mid,r,2*v+2);
68 }
69 // plus `val` to every element in [L,R)
70 void update(int L,int R,loli val,int l,int r,int v=0) {
71     // dbn(L,R,l,r,v)
72     push(l,r,v);
73     if(l==L && R==r) {
74         tag[v]+=val;
75         push(l,r,v);
76         return;
77     }
78     int mid=(l+r)/2;
79     if(R<=mid)
80         update(L,R,val,l,mid,2*v+1);
81     else if(mid<=L)
82         update(L,R,val,mid,r,2*v+2);
83     else
84         update(L,mid,val,l,mid,2*v+1),update(mid,R,val,
85             mid,r,2*v+2);
86     pull(l,r,v);
87 }
88 };
89 void solve() {
90     int n,q;
91     cin>>n>>q;
92     vl arr(n);
93     for(auto&x:arr)
94         cin>>x;
95     SegmentTree st(arr,n);
96     while(q--){
97         int op=0;
98         // str op;
99         cin>>op;
100         if(op&1){
101             loli l,r,val;
102             cin>>l>>r>>val;
103             assert(r>=l);
104             st.update(l-1,r,val,0,n);
105             // loli k,u;
106             // cin>>k>>u;
107             // st.update(k-1,k,u-arr[k-1],0,n);
108             // arr[k-1]=u;
109         }else{
110             int x,y;
111             cin>>x>>y;
112             assert(y>=x);
113             cout<<st.query(x-1,y,0,n)<<endl;
114 }

```

```

115 }
116 }
117 }

```

## 2.6 Sparse Table

```

1 int a[N], sp[___lg(N) + 1][N];
2 void init(int n) { //0-based
3     for (int i = 0; i < n; ++i) {
4         sp[0][i] = a[i];
5     }
6     for (int i = 0; i < ___lg(n); ++i) {
7         for (int j = 0; j+(1<<i) < n; ++j) {
8             sp[i + 1][j] = max(sp[i][j], sp[i][j+(1<<i)]);
9         }
10    }
11 }
12 int query(int l, int r) { //[l, r)
13     int p = ___lg(r - l + 1);
14     return max(sp[p][l], sp[p][r - (1<<p) + 1]);
15 }

```

## 2.7 Monotonic Stack

```

1 vector<int> monotonic_stack(vector<int> nums){
2     int n = nums.size();
3     vector<int> res(n);
4     stack<int> st;
5     for(int i = n-1;i>=0;i--){
6         while(!st.empty() && st.top()<=nums[i]){
7             st.pop();
8         }
9         if(st.empty())res[i] = -1;
10        else res[i] = st.top();
11        st.push(nums[i]);
12    }
13    return res;
14 }

```

## 3 Flow

### 3.1 Maximum Simple Graph Matching

```

1 struct GenMatch { // 1-base
2     int V, pr[N];
3     bool el[N][N], inq[N], inp[N], inb[N];
4     int st, ed, nb, bk[N], djs[N], ans;
5     void init(int _V) {
6         V = _V;
7         for (int i = 0; i <= V; ++i) {
8             for (int j = 0; j <= V; ++j) el[i][j] = 0;
9             pr[i] = bk[i] = djs[i] = 0;
10            inq[i] = inp[i] = inb[i] = 0;
11        }
12    }

```

```

12 }
13 void add_edge(int u, int v) {
14     el[u][v] = el[v][u] = 1;
15 }
16 int lca(int u, int v) {
17     fill_n(inp, V + 1, 0);
18     while (1)
19         if (u = djs[u], inp[u] = true, u == st) break;
20     else u = bk[pr[u]];
21     while (1)
22         if (v = djs[v], inp[v]) return v;
23     else v = bk[pr[v]];
24     return v;
25 }
26 void upd(int u) {
27     for (int v; djs[u] != nb;) {
28         v = pr[u], inb[djs[u]] = inb[djs[v]] = true;
29         u = bk[v];
30         if (djs[u] != nb) bk[u] = v;
31     }
32 }
33 void blo(int u, int v, queue<int> &qe) {
34     nb = lca(u, v), fill_n(inb, V + 1, 0);
35     upd(u), upd(v);
36     if (djs[u] != nb) bk[u] = v;
37     if (djs[v] != nb) bk[v] = u;
38     for (int tu = 1; tu <= V; ++tu)
39         if (inb[djs[tu]])
40             if (djs[tu] = nb, !inq[tu])
41                 qe.push(tu), inq[tu] = 1;
42 }
43 void flow() {
44     fill_n(inq + 1, V, 0), fill_n(bk + 1, V, 0);
45     iota(djs + 1, djs + V + 1, 1);
46     queue<int> qe;
47     qe.push(st), inq[st] = 1, ed = 0;
48     while (!qe.empty()) {
49         int u = qe.front();
50         qe.pop();
51         for (int v = 1; v <= V; ++v)
52             if (el[u][v] && djs[u] != djs[v] &&
53                 pr[u] != v) {
54                 if ((v == st) ||
55                     (pr[v] > 0 && bk[pr[v]] > 0))
56                     blo(u, v, qe);
57                 else if (!bk[v]) {
58                     if (bk[v] = u, pr[v] > 0) {
59                         if (!inq[pr[v]]) qe.push(pr[v]);
60                     } else
61                         return ed = v, void();
62                 }
63             }
64     }
65 }
66 void aug() {
67     for (int u = ed, v, w; u > 0;)
68         v = bk[u], w = pr[v], pr[v] = u, pr[u] = v,
69         u = w;
70 }
71 int solve() {
72     fill_n(pr, V + 1, 0), ans = 0;
73     for (int u = 1; u <= V; ++u)
74         if (!pr[u])
75             if (st = u, flow(), ed > 0) aug(), ++ans;
76     return ans;
77 }

```

78 };

## 3.2 Dinic

```

1 #define maxn 2005
2 #define INF 0x3f3f3f3f
3 struct MaxFlow{
4     struct edge{
5         int to, cap, flow, rev;
6         edge( int v, int c, int f, int r) : to(v), cap(c),
7             flow(f), rev(r) {}
8     };
9     vector<edge> G[maxn];
10    int s, t, dis[maxn], cur[maxn], vis[maxn];
11    void add_edge(int from, int to, int cap) {
12        G[from].push_back(edge(to, cap, 0, G[to].size()));
13        G[to].push_back(edge(from, 0, 0, G[from].size()-1));
14    }
15    bool bfs() {
16        memset(dis, -1, sizeof(dis));
17        queue<int> qu;
18        qu.push(s);
19        dis[s] = 0;
20        while (!qu.empty()) {
21            int from = qu.front();
22            qu.pop();
23            for (auto &e: G[from]) {
24                if (dis[e.to]==-1 && e.cap != e.flow) {
25                    dis[e.to] = dis[from] + 1;
26                    qu.push(e.to);
27                }
28            }
29        }
30        return dis[t]!=-1;
31    }
32    int dfs(int from, int cap) {
33        if (from==t || cap==0) return cap;
34        for (int &i = cur[from]; i<G[from].size(); i++) {
35            edge &e = G[from][i];
36            if (dis[e.to]==dis[from]+1 && e.flow!=e.cap) {
37                int df = dfs(e.to, min(e.cap-e.flow, cap));
38                if (df) {
39                    e.flow+=df;
40                    G[e.to][e.rev].flow-=df;
41                    return df;
42                }
43            }
44        }
45        dis[from] = -1;
46        return 0;
47    }
48    int Maxflow(int s, int t) {
49        this->s = s, this->t = t;
50        int flow = 0;
51        int df;
52        while (bfs()) {
53            memset(cur, 0, sizeof(cur));
54            while (df = dfs(s, INF)) {
55                flow += df;
56            }
57        }
58        return flow;

```

```

59 };
60 int main() {
61     int n = 4, m = 6;
62     MaxFlow maxflow;
63     for (int i = 0; i < m; i++) {
64         int a, b, cap;
65         cin >> a >> b >> cap;
66         maxflow.add_edge(a, b, cap);
67     }
68     cout << maxflow.Maxflow(1, 3) << endl;
69 }

```

## 4 Formula

### 4.1 formula

#### 4.1.1 Pick 公式

給定頂點坐標均是整點的簡單多邊形，面積 = 內部格點數 + 邊上格點數/2 - 1

#### 4.1.2 圖論

- 對於平面圖， $F = E - V + C + 1$ ， $C$  是連通分數
- 對於平面圖， $E \leq 3V - 6$
- 對於連通圖  $G$ ，最大獨立點集的大小設為  $I(G)$ ，最大匹配大小設為  $M(G)$ ，最小點覆蓋設為  $C_v(G)$ ，最小邊覆蓋設為  $C_e(G)$ 。對於任意連通圖：

- $I(G) + C_v(G) = |V|$
- $M(G) + C_e(G) = |V|$

- 對於連通二分圖：

- $I(G) = C_v(G)$
- $M(G) = C_e(G)$

- 最大權閉合圖：

- $C(u, v) = \infty, (u, v) \in E$
- $C(S, v) = W_v, W_v > 0$
- $C(v, T) = -W_v, W_v < 0$
- $ans = \sum_{W_v > 0} W_v - flow(S, T)$

- 最大密度子圖：

- 求  $\max \left( \frac{W_e + W_v}{|V'|} \right), e \in E', v \in V'$
- $U = \sum_{v \in V} 2W_v + \sum_{e \in E} W_e$
- $C(u, v) = W_{(u, v)}, (u, v) \in E$ ，雙向邊
- $C(S, v) = U, v \in V$
- $D_u = \sum_{(u, v) \in E} W_{(u, v)}$
- $C(v, T) = U + 2g - D_v - 2W_v, v \in V$
- 二分搜  $g$ ：  
 $l = 0, r = U, eps = 1/n^2$   
 if  $((U \times |V| - flow(S, T))/2 > 0)$   $l = mid$   
 else  $r = mid$
- $ans = min\_cut(S, T)$
- $|E| = 0$  要特殊判斷

- 弦圖：

- 點數大於 3 的環都要有一條弦

- 完美消除序：從後往前依次給每個點染色，給每個點染上可以染的最小顏色
- 最大團大小 = 色數
- 最大獨立集：完美消除序，從前往後能選就選
- 最小團覆蓋：最大獨立集的點和他延伸的邊構成
- 區間圖是弦圖
- 區間圖的完美消除序：將區間按造又端點由小到大排序
- 區間圖染色：用線段樹做

#### 4.1.3 dinic 特殊圖複雜度

- 單位流： $O\left(\min\left(V^{3/2}, E^{1/2}\right)E\right)$
- 二分圖： $O\left(V^{1/2}E\right)$

#### 4.1.4 0-1 分數規劃

$x_i \in \{0, 1\}$ ， $x_i$  可能會有其他限制，求  $\max \left( \frac{\sum B_i x_i}{\sum C_i x_i} \right)$

- $D(i, g) = B_i - g \times C_i$
- $f(g) = \sum D(i, g) x_i$
- $f(g) = 0$  時  $g$  為最佳解， $f(g) < 0$  沒有意義
- 因為  $f(g)$  單調可以二分搜  $g$
- 或用 Dinkelbach 通常比較快

```

1 binary_search() {
2     while (r - l > eps) {
3         g = (l + r) / 2;
4         for (i: 所有元素) D[i] = B[i] - g * C[i]; // D(i, g)
5         找出一組合法 x[i] 使 f(g) 最大;
6         if (f(g) > 0) l = g;
7         else r = g;
8     }
9     Ans = r;
10 }
11 Dinkelbach() {
12     g = 任意 態 (通常設為 0);
13     do {
14         Ans = g;
15         for (i: 所有元素) D[i] = B[i] - g * C[i]; // D(i, g)
16         找出一組合法 x[i] 使 f(g) 最大;
17         p = 0, q = 0;
18         for (i: 所有元素)
19             if (x[i] * p + B[i] - g * C[i] > 0) q += C[i];
20         g = p / q; // 新解，注意 g=0 的情況
21     } while (abs(Ans - g) > EPS);
22     return Ans;
23 }

```

#### 4.1.5 學長公式

- $\sum_{d|n} \phi(n) = n$
- $g(n) = \sum_{d|n} f(d) \Rightarrow f(n) = \sum_{d|n} \mu(d) \times g(n/d)$
- Harmonic series  $H_n = \ln(n) + \gamma + 1/(2n) - 1/(12n^2) + 1/(120n^4)$
- $\gamma = 0.57721566490153286060651209008240243104215$
- 格雷碼  $= n \oplus (n >> 1)$
- $SG(A + B) = SG(A) \oplus SG(B)$
- 旋轉矩陣  $M(\theta) = \begin{pmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{pmatrix}$

### 4.1.6 基本數論

1.  $\sum_{d|n} \mu(n) = [n == 1]$
2.  $g(m) = \sum_{d|m} f(d) \Leftrightarrow f(m) = \sum_{d|m} \mu(d) \times g(m/d)$
3.  $\sum_{i=1}^n \sum_{j=1}^m \text{互質數} = \sum \mu(d) \lfloor \frac{n}{d} \rfloor \lfloor \frac{m}{d} \rfloor$
4.  $\sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = n \sum_{d|n} d \times \phi(d)$

### 4.1.7 排組公式

1. k 卡特  $\frac{C_n^{kn}}{n(k-1)+1}, C_m^n = \frac{n!}{m!(n-m)!}$
2.  $H(n, m) \cong x_1 + x_2 + \dots + x_n = k, num = C_k^{n+k-1}$
3. Stirling number of  $2^{nd}, n$  人分  $k$  組方法數目
  - (a)  $S(0, 0) = S(n, n) = 1$
  - (b)  $S(n, 0) = 0$
  - (c)  $S(n, k) = kS(n-1, k) + S(n-1, k-1)$
4. Bell number,  $n$  人分任意多組方法數目
  - (a)  $B_0 = 1$
  - (b)  $B_n = \sum_{i=0}^n S(n, i)$
  - (c)  $B_{n+1} = \sum_{k=0}^n C_n^k B_k$
  - (d)  $B_{p+n} \equiv B_n + B_{n+1} \pmod{p}$ ,  $p$  is prime
  - (e)  $B_{p^m+n} \equiv mB_n + B_{n+1} \pmod{p}$ ,  $p$  is prime
  - (f) From  $B_0: 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, 115975$
5. Derangement, 錯排, 沒有人在自己位置上
  - (a)  $D_n = n!(1 - \frac{1}{1!} + \frac{1}{2!} - \frac{1}{3!} + \dots + (-1)^n \frac{1}{n!})$
  - (b)  $D_n = (n-1)(D_{n-1} + D_{n-2}), D_0 = 1, D_1 = 0$
  - (c) From  $D_0: 1, 0, 1, 2, 9, 44, 265, 1854, 14833, 133496$

### 6. Binomial Equality

- (a)  $\sum_k \binom{r}{m+k} \binom{s}{n-k} = \binom{r+s}{m+n}$
- (b)  $\sum_k \binom{l}{m+k} \binom{s}{n+k} = \binom{l+s}{l-m+n}$
- (c)  $\sum_k \binom{l}{m+k} \binom{s+k}{n-k} (-1)^k = (-1)^{l+m} \binom{s-m}{l-n-m}$
- (d)  $\sum_{k \leq l} \binom{l-k}{m} \binom{s}{k-n} (-1)^k = (-1)^{l+m} \binom{s-m-1}{l-n-m}$
- (e)  $\sum_{0 \leq k \leq l} \binom{l-k}{m} \binom{q+k}{n} = \binom{l+q+1}{m+n+1}$
- (f)  $\binom{r}{k} = (-1)^k \binom{r-k}{k}$
- (g)  $\binom{r}{m} \binom{r}{k} = \binom{r}{m-k} \binom{r-k}{k}$
- (h)  $\sum_{k \leq n} \binom{r+k}{k} = \binom{r+n+1}{n}$
- (i)  $\sum_{0 \leq k \leq n} \binom{k}{m} = \binom{n+1}{m+1}$
- (j)  $\sum_{k \leq m} \binom{m+r}{k} x^k y^{m-k} = \sum_{k \leq m} \binom{-r}{k} (-x)^k (x+y)^{m-k}$

### 4.1.8 冪次, 冪次和

1.  $a^b \% P = a^{b \% (p) + \varphi(p)}, b \geq \varphi(p)$
2.  $1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^4}{4} + \frac{n^3}{2} + \frac{n^2}{4}$
3.  $1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n^5}{5} + \frac{n^4}{2} + \frac{n^3}{3} - \frac{n}{30}$
4.  $1^5 + 2^5 + 3^5 + \dots + n^5 = \frac{n^6}{6} + \frac{n^5}{2} + \frac{5n^4}{12} - \frac{n^2}{12}$
5.  $0^k + 1^k + 2^k + \dots + n^k = P(k), P(k) = \frac{(n+1)^{k+1} - \sum_{i=0}^{k-1} C_i^{k+1} P(i)}{k+1}, P(0) = n+1$
6.  $\sum_{k=0}^{m-1} k^n = \frac{1}{n+1} \sum_{k=0}^n C_k^{n+1} B_k m^{n+1-k}$

7.  $\sum_{j=0}^m C_j^{m+1} B_j = 0, B_0 = 1$
8. 除  $B_1 = -1/2$ , 剩下的奇數項都是 0
9.  $B_2 = 1/6, B_4 = -1/30, B_6 = 1/42, B_8 = -1/30, B_{10} = 5/66, B_{12} = -691/2730, B_{14} = 7/6, B_{16} = -3617/510, B_{18} = 43867/798, B_{20} = -174611/330,$

### 4.1.9 Burnside's lemma

1.  $|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$
2.  $X^g = t^{c(g)}$
3.  $G$  表示有幾種轉法,  $X^g$  表示在那種轉法下, 有幾種是會保持對稱的,  $t$  是顏色數,  $c(g)$  是循環不動的面數。
4. 正立方體塗三顏色, 轉 0 有  $3^6$  個元素不變, 轉 90 有 6 種, 每種有  $3^3$  不變, 180 有  $3 \times 3^4$ , 120 (角) 有  $8 \times 3^2$ , 180 (邊) 有  $6 \times 3^3$ , 全部  $\frac{1}{24} (3^6 + 6 \times 3^3 + 3 \times 3^4 + 8 \times 3^2 + 6 \times 3^3) = 57$

### 4.1.10 Count on a tree

1. Rooted tree:  $s_{n+1} = \frac{1}{n} \sum_{i=1}^n (i \times a_i \times \sum_{j=1}^{[n/i]} a_{n+1-i \times j})$
2. Unrooted tree:
  - (a) Odd:  $a_n - \sum_{i=1}^{n/2} a_i a_{n-i}$
  - (b) Even:  $Odd + \frac{1}{2} a_{n/2} (a_{n/2} + 1)$
3. Spanning Tree
  - (a) 完全圖  $n^{n-2}$
  - (b) 一般圖 (Kirchhoff's theorem)  $M[i][i] = \text{degree}(V_i), M[i][j] = -1, \text{if have } E(i, j), 0 \text{ if no edge.}$   
delete any one row and col in  $A$ ,  $ans = \det(A)$

## 5 Geometry

### 5.1 Sort by Angle

```

1 bool cmp(pii a, pii b) {
2     #define is_neg(k) (k.y < 0 || (k.y == 0 && k.x < 0));
3     int A = is_neg(a), B = is_neg(b);
4     if (A != B)
5         return A < B;
6     if (cross(a, b) == 0)
7         return (a.x*a.x + a.y*a.y) < (b.x*b.x + b.y*b.y);
8     return cross(a, b) > 0;
9 }

```

### 5.2 Geometry

```

1 const double PI=atan2(0.0,-1.0);
2 template<typename T>
3 struct point{
4     T x,y;
5     point() {}
6     point(const T&x, const T&y):x(x),y(y) {}
7     point operator+(const point &b) const {

```

```

8         return point(x+b.x,y+b.y); }
9     point operator-(const point &b) const {
10        return point(x-b.x,y-b.y); }
11    point operator*(const T &b) const {
12        return point(x*b,y*b); }
13    point operator/(const T &b) const {
14        return point(x/b,y/b); }
15    bool operator==(const point &b) const {
16        return x==b.x&&y==b.y; }
17    T dot(const point &b) const {
18        return x*b.x+y*b.y; }
19    T cross(const point &b) const {
20        return x*b.y-y*b.x; }
21    point normal() const { //求法向
22        return point(-y,x); }
23    T abs2() const { //向 長度的平方
24        return dot(*this); }
25    T rad(const point &b) const { // 向 的弧度
26    return fabs(atan2(fabs(cross(b)),dot(b))); }
27    T getA() const { //對x軸的弧度
28        T A=atan2(y,x); //超過180度會變負的
29        if (A<=-PI/2) A+=PI*2;
30        return A;
31    }
32 };
33 template<typename T>
34 struct line{
35     line() {}
36     point<T> p1,p2;
37     T a,b,c; //ax+by+c=0
38     line(const point<T>&x, const point<T>&y):p1(x),p2(y) {}
39     void pton() { //轉成一般式
40         a=p1.y-p2.y;
41         b=p2.x-p1.x;
42         c=-a*p1.x-b*p1.y;
43     }
44     T ori(const point<T> &p) const { //點和有向直線的關係, >0左
45         邊, =0在線上, <0右邊
46         return (p2-p1).cross(p-p1);
47     }
48     T btw(const point<T> &p) const { //點投影 在線段上 <=0
49         return (p1-p).dot(p2-p);
50     }
51     bool point_on_segment(const point<T>&p) const { //點是否在线段
52         上
53         return ori(p)==0&&btw(p)<=0;
54     }
55     T dis2(const point<T> &p, bool is_segment=0) const { //點跟直線
56         /線段的距離平方
57         point<T> v=p2-p1,v1=p-p1;
58         if (is_segment) {
59             point<T> v2=p-p2;
60             if (v.dot(v1)<=0) return v1.abs2();
61             if (v.dot(v2)>=0) return v2.abs2();
62         }
63         T tmp=v.cross(v1);
64         return tmp*tmp/v.abs2();
65     }
66     T seg_dis2(const line<T> &l) const { // 線段距離平方
67         return min({dis2(l.p1,l),dis2(l.p2,l),l.dis2(p1,l),l.dis2
68             (p2,l)});
69     }

```

```

66 point<T> projection(const point<T> &p) const { // 點對直線的投影
67     point<T> n = (p2 - p1).normal();
68     return p - n * (p - p1).dot(n) / n.abs2();
69 }
70 point<T> mirror(const point<T> &p) const {
71     // 點對直線的鏡射，要先呼叫 pton 轉成一般式
72     point<T> R;
73     T d = a * b * b;
74     R.x = (b * b * p.x - a * a * p.x - 2 * a * b * p.y - 2 * a * c) / d;
75     R.y = (a * a * p.y - b * b * p.y - 2 * a * b * p.x - 2 * b * c) / d;
76     return R;
77 }
78 bool equal(const line &l) const { // 直線相等
79     return ori(1.p1) == 0 && ori(1.p2) == 0;
80 }
81 bool parallel(const line &l) const {
82     return (p1 - p2).cross(1.p1 - 1.p2) == 0;
83 }
84 bool cross_seg(const line &l) const {
85     return (p2 - p1).cross(1.p1 - p1) * (p2 - p1).cross(1.p2 - p1) <= 0;
86     // 直線是否交線段
87 }
88 int line_intersect(const line &l) const { // 直線相交情況，-1 無
89     // 限多點、1 交於一點、0 不相交
90     return parallel(1) ? (ori(1.p1) == 0 ? -1 : 0) : 1;
91 }
92 int seg_intersect(const line &l) const {
93     T c1 = ori(1.p1), c2 = ori(1.p2);
94     T c3 = l.ori(p1), c4 = l.ori(p2);
95     if (c1 == 0 && c2 == 0) { // 共線
96         bool b1 = btw(1.p1) >= 0, b2 = btw(1.p2) >= 0;
97         T a3 = l.btw(p1), a4 = l.btw(p2);
98         if (b1 && b2 && a3 == 0 && a4 >= 0) return 2;
99         if (b1 && b2 && a3 >= 0 && a4 == 0) return 3;
100         if (b1 && b2 && a3 >= 0 && a4 >= 0) return 0;
101         return -1; // 無限交點
102     } else if (c1 * c2 <= 0 && c3 * c4 <= 0) return 1;
103     return 0; // 不相交
104 }
105 point<T> line_intersection(const line &l) const { // 直線交點
106     point<T> a = p2 - p1, b = l.p2 - l.p1, s = l.p1 - p1;
107     // if (a.cross(b) == 0) return INF;
108     return p1 + a * (s.cross(b) / a.cross(b));
109 }
110 point<T> seg_intersection(const line &l) const { // 線段交點
111     int res = seg_intersect(1);
112     if (res <= 0) assert(0);
113     if (res == 2) return p1;
114     if (res == 3) return p2;
115     return line_intersection(1);
116 }
117 };
118 template<typename T>
119 struct polygon {
120     polygon() {}
121     vector<point<T>> > p; // 逆時針順序
122     T area() const { // 面積
123         T ans = 0;
124         for (int i = p.size() - 1, j = 0; j < (int)p.size(); i = j++)
125             ans += p[i].cross(p[j]);
126         return ans / 2;
127     }
128 };
129 point<T> center_of_mass() const { // 重心
130     T cx = 0, cy = 0, w = 0;
131     for (int i = p.size() - 1, j = 0; j < (int)p.size(); i = j++) {
132         T a = p[i].cross(p[j]);
133         cx += (p[i].x + p[j].x) * a;
134         cy += (p[i].y + p[j].y) * a;
135         w += a;
136     }
137     return point<T>(cx / 3 / w, cy / 3 / w);
138 }
139 char ahas(const point<T> &t) const { // 點是否在簡單多邊形內，
140     // 是的話回傳 1、在邊上回傳 -1、否則回傳 0
141     bool c = 0;
142     for (int i = 0, j = p.size() - 1; i < p.size(); j = i++)
143         if (line<T>(p[i], p[j]).point_on_segment(t)) return -1;
144     else if ((p[i].y > t.y) != (p[j].y > t.y) &&
145             t.x < (p[j].x - p[i].x) * (t.y - p[i].y) / (p[j].y - p[i].y) + p[i].x
146             )
147         c = !c;
148     return c;
149 }
150 char point_in_convex(const point<T> &x) const {
151     int l = 1, r = (int)p.size() - 2;
152     while (l < r) { // 點是否在凸多邊形內，是的話回傳 1、在邊上回傳
153         // -1、否則回傳 0
154         int mid = (l + r) / 2;
155         T a1 = (p[mid] - p[0]).cross(x - p[0]);
156         T a2 = (p[mid + 1] - p[0]).cross(x - p[0]);
157         if (a1 >= 0 && a2 <= 0) {
158             T res = (p[mid + 1] - p[mid]).cross(x - p[mid]);
159             return res > 0 ? 1 : (res >= 0 ? -1 : 0);
160         } else if (a1 < 0) r = mid - 1;
161         else l = mid + 1;
162     }
163     return 0;
164 }
165 vector<T> getA() const { // 凸包邊對 x 軸的夾角
166     vector<T> res; // 一定是遞增的
167     for (size_t i = 0; i < p.size(); i++)
168         res.push_back((p[(i + 1) % p.size()] - p[i]).getA());
169     return res;
170 }
171 bool line_intersect(const vector<T> &A, const line<T> &l)
172     const { // O(logN)
173     int f1 = upper_bound(A.begin(), A.end(), (l.p1 - l.p2).getA()) -
174         A.begin();
175     int f2 = upper_bound(A.begin(), A.end(), (l.p2 - l.p1).getA()) -
176         A.begin();
177     return l.cross_seg(line<T>(p[f1], p[f2]));
178 }
179 polygon cut(const line<T> &l) const { // 凸包對直線切割，得到直
180     // 線 l 左側的凸包
181     polygon ans;
182     for (int n = p.size(), i = n - 1, j = 0; j < n; i = j++) {
183         if (1.ori(p[i]) >= 0) {
184             ans.p.push_back(p[i]);
185             if (1.ori(p[j]) < 0)
186                 ans.p.push_back(1.line_intersection(line<T>(p[i], p[
187                     j]])));
188             } else if (1.ori(p[j]) > 0)
189                 ans.p.push_back(1.line_intersection(line<T>(p[i], p[
190                     j]])));
191             }
192         }
193     return ans;
194 }
195 }
196 static bool graham_cmp(const point<T> &a, const point<T> &b)
197     { // 凸包排序函數
198     return (a.x < b.x) || (a.x == b.x && a.y < b.y);
199 }
200 void graham(vector<point<T>> &s) { // 凸包
201     sort(s.begin(), s.end(), graham_cmp);
202     p.resize(s.size() + 1);
203     int m = 0;
204     for (size_t i = 0; i < s.size(); i++) {
205         while (m >= 2 && (p[m - 1] - p[m - 2]).cross(s[i] - p[m - 2]) <= 0) --m;
206         p[m++] = s[i];
207     }
208     for (int i = s.size() - 2, t = m + 1; i >= 0; --i) {
209         while (m >= 2 && (p[m - 1] - p[m - 2]).cross(s[i] - p[m - 2]) <= 0) --m;
210         p[m++] = s[i];
211     }
212     if (s.size() > 1) --m;
213     p.resize(m);
214 }
215 T diam() { // 直徑
216     int n = p.size(), t = 1;
217     T ans = 0;
218     p.push_back(p[0]);
219     for (int i = 0; i < n; i++) {
220         point<T> now = p[i + 1] - p[i];
221         while (now.cross(p[t + 1] - p[i]) > now.cross(p[t] - p[i])) t = (t
222             + 1) % n;
223         ans = max(ans, (p[i] - p[t]).abs2());
224     }
225     return p.pop_back(), ans;
226 }
227 T min_cover_rectangle() { // 最小覆蓋矩形
228     int n = p.size(), t = 1, r = 1, l = 1;
229     if (n < 3) return 0; // 也可以做最小周長矩形
230     T ans = 1e99;
231     p.push_back(p[0]);
232     for (int i = 0; i < n; i++) {
233         point<T> now = p[i + 1] - p[i];
234         while (now.cross(p[t + 1] - p[i]) > now.cross(p[t] - p[i])) t = (t
235             + 1) % n;
236         while (now.dot(p[r + 1] - p[i]) > now.dot(p[r] - p[i])) r = (r + 1) % n;
237         if (!l) l = r;
238         while (now.dot(p[l + 1] - p[i]) <= now.dot(p[l] - p[i])) l = (l + 1) % n;
239         T d = now.abs2();
240         T tmp = now.cross(p[t] - p[i]) * (now.dot(p[r] - p[i]) - now.dot(
241             p[l] - p[i])) / d;
242         ans = min(ans, tmp);
243     }
244     return p.pop_back(), ans;
245 }
246 T dis2(polygon &p1) { // 凸包最近距離平方
247     vector<point<T>> > &P = p, &Q = p1.p;
248     int n = P.size(), m = Q.size(), l = 0, r = 0;
249     for (int i = 0; i < n; i++) if (P[i].y < P[l].y) l = i;
250     for (int i = 0; i < m; i++) if (Q[i].y < Q[r].y) r = i;
251     P.push_back(P[0]), Q.push_back(Q[0]);
252     T ans = 1e99;
253     for (int i = 0; i < n; i++) {
254         while ((P[l] - P[l + 1]).cross(Q[r + 1] - Q[r]) < 0) r = (r + 1) % m;
255         ans = min(ans, line<T>(P[l], P[l + 1]).seg_dis2(line<T>(Q[r],
256             Q[r + 1])));
257         l = (l + 1) % n;
258     }
259     return P.pop_back(), Q.pop_back(), ans;
260 }

```



```

239 }
240 static char sign(const point<T>&t){
241     return (t.y==0?t.x:t.y)<0;
242 }
243 static bool angle_cmp(const line<T>& A,const line<T>& B){
244     point<T> a=A.p2-A.p1,b=B.p2-B.p1;
245     return sign(a)<sign(b)|| (sign(a)==sign(b)&&a.cross(b)>0);
246 }
247 int halfplane_intersection(vector<line<T> > &s){//半平面交
248     sort(s.begin(),s.end(),angle_cmp);//線段左側為該線段半平面
249     int L,R,n=s.size();
250     vector<point<T> > px(n);
251     vector<line<T> > q(n);
252     q[L=R=0]=s[0];
253     for(int i=1;i<n;++i){
254         while(L<R&&s[i].ori(px[R-1])<=0)--R;
255         while(L<R&&s[i].ori(px[L])<=0)++L;
256         q[++R]=s[i];
257         if(q[R].parallel(q[R-1])){
258             --R;
259             if(q[R].ori(s[i].p1)>0)q[R]=s[i];
260         }
261         if(L<R)px[R-1]=q[R-1].line_intersection(q[R]);
262     }
263     while(L<R&&q[L].ori(px[R-1])<=0)--R;
264     p.clear();
265     if(R-L<=1) return 0;
266     px[R]=q[R].line_intersection(q[L]);
267     for(int i=L;i<=R;++i)p.push_back(px[i]);
268     return R-L+1;
269 }
270 };
271 template<typename T>
272 struct triangle{
273     point<T> a,b,c;
274     triangle(){}
275     triangle(const point<T> &a,const point<T> &b,const point<T> &c):a(a),b(b),c(c){}
276     T area() const{
277         T t=(b-a).cross(c-a)/2;
278         return t>0?t:-t;
279     }
280     point<T> barycenter() const//重心
281         return (a+b+c)/3;
282     }
283     point<T> circumcenter() const//外心
284         static line<T> u,v;
285         u.p1=(a+b)/2;
286         u.p2=point<T>(u.p1.x-a.y+b.y,u.p1.y+a.x-b.x);
287         v.p1=(a+c)/2;
288         v.p2=point<T>(v.p1.x-a.y+c.y,v.p1.y+a.x-c.x);
289         return u.line_intersection(v);
290     }
291     point<T> incenter() const//內心
292         T A=sqrt((b-c).abs2()),B=sqrt((a-c).abs2()),C=sqrt((a-b).abs2());
293         return point<T>(A*a.x+B*b.x+C*c.x,A*a.y+B*b.y+C*c.y)/(A+B+C);
294     }
295     point<T> perpencenter() const//垂心
296         return barycenter()*3-circumcenter()*2;
297     }
298 };
299 template<typename T>
300 struct point3D{
301     T x,y,z;
302     point3D(){}
303     point3D(const T&x,const T&y,const T&z):x(x),y(y),z(z){}
304     point3D operator+(const point3D &b) const{
305         return point3D(x+b.x,y+b.y,z+b.z);
306     }
307     point3D operator-(const point3D &b) const{
308         return point3D(x-b.x,y-b.y,z-b.z);
309     }
310     point3D operator*(const T &b) const{
311         return point3D(x*b,y*b,z*b);
312     }
313     point3D operator/(const T &b) const{
314         return point3D(x/b,y/b,z/b);
315     }
316     bool operator==(const point3D &b) const{
317         return x==b.x&&y==b.y&&z==b.z;
318     }
319     T dot(const point3D &b) const{
320         return x*b.x+y*b.y+z*b.z;
321     }
322     point3D cross(const point3D &b) const{
323         return point3D(y*b.z-z*b.y,z*b.x-x*b.z,x*b.y-y*b.x);
324     }
325     T abs2() const//向 長度的平方
326         return dot(*this);
327     }
328     T area2(const point3D &b) const//和b、原點圍成面積的平方
329         return cross(b).abs2()/4;
330     };
331 template<typename T>
332 struct line3D{
333     point3D<T> p1,p2;
334     line3D(){}
335     line3D(const point3D<T> &p1,const point3D<T> &p2):p1(p1),p2(p2){}
336     T dis2(const point3D<T> &p,bool is_segment=0) const//點跟直線/線段的距離平方
337         point3D<T> v=p2-p1,v1=p-p1;
338         if(is_segment){
339             point3D<T> v2=p-p2;
340             if(v.dot(v1)<=0) return v1.abs2();
341             if(v.dot(v2)>=0) return v2.abs2();
342         }
343         point3D<T> tmp=v.cross(v1);
344         return tmp.abs2()/v.abs2();
345     }
346     pair<point3D<T>,point3D<T> > closest_pair(const line3D<T> &l) const{
347         point3D<T> v1=(p1-p2),v2=(l.p1-l.p2);
348         point3D<T> N=v1.cross(v2),ab(p1-l.p1);
349         //if(N.abs2()==0) return NULL; 平 或重合
350         T tmp=N.dot(ab),ans=tmp*tmp/N.abs2();//最近點對距離
351         point3D<T> d1=p2-p1,d2=l.p2-l.p1,D=d1.cross(d2),G=l.p1-p1;
352         T t1=(G.cross(d2)).dot(D)/D.abs2();
353         T t2=(G.cross(d1)).dot(D)/D.abs2();
354         return make_pair(p1+d1*t1,l.p1+d2*t2);
355     }
356     bool same_side(const point3D<T> &a,const point3D<T> &b) const{
357         return (p2-p1).cross(a-p1).dot((p2-p1).cross(b-p1))>0;
358     }
359 };
360 template<typename T>
361 struct plane{
362     point3D<T> p0,n;//平面上的點和法向
363     plane(){}
364     plane(const point3D<T> &p0,const point3D<T> &n):p0(p0),n(n){}
365     T dis2(const point3D<T> &p) const//點到平面距離的平方
366         T tmp=(p-p0).dot(n);
367         return tmp*tmp/n.abs2();
368     }
369     point3D<T> projection(const point3D<T> &p) const{
370         return p-n*(p-p0).dot(n)/n.abs2();
371     }
372     point3D<T> line_intersection(const line3D<T> &l) const{
373         T tmp=n.dot(l.p2-l.p1);//等於0表示平 或重合該平面
374         return l.p1+(l.p2-l.p1)*(n.dot(p0-l.p1)/tmp);
375     }
376     line3D<T> plane_intersection(const plane &p1) const{
377         point3D<T> e=n.cross(p1.n),v=n.cross(e);
378         T tmp=p1.n.dot(v);//等於0表示平 或重合該平面
379         point3D<T> q=p0+(v*(p1.n.dot(p1.p0-p0))/tmp);
380         return line3D<T>(q,q+e);
381     }
382 };
383 template<typename T>
384 struct triangle3D{
385     point3D<T> a,b,c;
386     triangle3D(){}
387     triangle3D(const point3D<T> &a,const point3D<T> &b,const point3D<T> &c):a(a),b(b),c(c){}
388     bool point_in(const point3D<T> &p) const//點在該平面上的投影在三角形中
389         return line3D<T>(b,c).same_side(p,a)&&line3D<T>(a,c).same_side(p,b)&&line3D<T>(a,b).same_side(p,c);
390     }
391 };
392 template<typename T>
393 struct tetrahedron//四面體{
394     point3D<T> a,b,c,d;
395     tetrahedron(){}
396     tetrahedron(const point3D<T> &a,const point3D<T> &b,const point3D<T> &c,const point3D<T> &d):a(a),b(b),c(c),d(d){}
397     T volume6() const//體積的六倍
398         return (d-a).dot((b-a).cross(c-a));
399     }
400     point3D<T> centroid() const{
401         return (a+b+c+d)/4;
402     }
403     bool point_in(const point3D<T> &p) const{
404         return triangle3D<T>(a,b,c).point_in(p)&&triangle3D<T>(c,d,a).point_in(p);
405     }
406 };
407 template<typename T>
408 struct convexhull3D{
409     static const int MAXN=1005;
410     struct face{
411         int a,b,c;
412         face(int a,int b,int c):a(a),b(b),c(c){}
413     };
414     vector<point3D<T>> pt;
415     vector<face> ans;
416     int fid[MAXN][MAXN];
417     void build(){
418         int n=pt.size();
419         ans.clear();
420         memset(fid,0,sizeof(fid));
421         ans.emplace_back(0,1,2);//注意不能共線
422         ans.emplace_back(2,1,0);
423         int ftop = 0;

```

```

416 for(int i=3, ftop=1; i<n; ++i, ++ftop){
417     vector<face> next;
418     for(auto &f:ans){
419         T d=(pt[i]-pt[f.a]).dot((pt[f.b]-pt[f.a]).cross(pt[f.
420             c]-pt[f.a]));
421         if(d<=0) next.push_back(f);
422         int ff=0;
423         if(d>0) ff=ftop;
424         else if(d<0) ff=-ftop;
425         fid[f.a][f.b]=fid[f.b][f.c]=fid[f.c][f.a]=ff;
426     }
427     for(auto &f:ans){
428         if(fid[f.a][f.b]>0 && fid[f.a][f.b]!=fid[f.b][f.a])
429             next.emplace_back(f,a,f.b,i);
430         if(fid[f.b][f.c]>0 && fid[f.b][f.c]!=fid[f.c][f.b])
431             next.emplace_back(f,b,f.c,i);
432         if(fid[f.c][f.a]>0 && fid[f.c][f.a]!=fid[f.a][f.c])
433             next.emplace_back(f,c,f.a,i);
434     }
435     ans=next;
436 }
437 point3D<T> centroid()const{
438     point3D<T> res(0,0,0);
439     T vol=0;
440     for(auto &f:ans){
441         T tmp=pt[f.a].dot(pt[f.b].cross(pt[f.c]));
442         res=res+(pt[f.a]+pt[f.b]+pt[f.c])*tmp;
443         vol+=tmp;
444     }
445     return res/(vol*4);
446 }
447 };

```

### 5.3 Convex Hull

```

1 using pdd = pair<double, double>;
2 #define F first
3 #define S second
4 pdd operator-(pdd a, pdd b) {
5     return {a.F - b.F, a.S - b.S};
6 }
7 double cross(pdd a, pdd b) {
8     return a.F * b.S - a.S * b.F;
9 }
10 void solve() {
11     int n;
12     cin >> n;
13     vector<pdd> pnts;
14     for (int i = 0; i < n; ++i) {
15         double x, y;
16         cin >> x >> y;
17         pnts.push_back(x, y);
18     }
19     sort(iter(pnts));
20     vector<pdd> hull;
21     for (int i = 0; i < 2; ++i) {
22         int t = hull.size();
23         for (pdd j: pnts) {
24             while(hull.size() - t >= 2 && cross(j - hull[hull.size()
25                 () - 2], hull.back() - hull[hull.size() - 2]) >=
                0)
                hull.pop_back();

```

```

26         hull.push_back(j);
27     }
28     hull.pop_back();
29     reverse(iter(pnts));
30 }
31 double area = 0;
32 for (int i=0; i < hull.size(); ++i){
33     area += cross(hull[i], hull[(i + 1) % hull.size()]);
34 }
35 area /= 2.0;
36 }

```

### 5.4 Min Covering Circle

```

1 double dis(pdd a, pdd b) {
2     double dx = a.x - b.x, dy = a.y - b.y;
3     return sqrt(dx*dx + dy*dy);
4 }
5 double sq(double x) {
6     return x * x;
7 }
8 pdd excenter(pdd p1, pdd p2, pdd p3) {
9     double a1 = p1.x - p2.x, a2 = p1.x - p3.x;
10    double b1 = p1.y - p2.y, b2 = p1.y - p3.y;
11    double c1 = (sq(p1.x) - sq(p2.x) + sq(p1.y) - sq(p2.y)) /
12        2;
13    double c2 = (sq(p1.x) - sq(p3.x) + sq(p1.y) - sq(p3.y)) /
14        2;
15    double dd = a1*b2 - a2*b1;
16    return {(c1*b2 - c2*b1) / dd, (a1*c2 - a2*c1) / dd};
17 }
18 void solve(pdd a[], int n) {
19     shuffle(a, a + n, rng);
20     pdd center = a[0];
21     double r = 0;
22     for (int i = 1; i < n; ++i) {
23         if (dis(center, a[i]) <= r) continue;
24         center = a[i], r = 0;
25         for (int j = 0; j < i; ++j) {
26             if (dis(center, a[j]) <= r) continue;
27             center.x = (a[i].x + a[j].x) / 2;
28             center.y = (a[i].y + a[j].y) / 2;
29             r = dis(center, a[i]);
30             for (int k = 0; k < j; ++k) {
31                 if (dis(center, a[k]) <= r) continue;
32                 center = excenter(a[i], a[j], a[k]);
33                 r = dis(center, a[i]);
34             }
35         }
36     }
37     cout << fixed << setprecision(10) << r << '\n';
38     cout << center.x << ' ' << center.y << '\n';
39 }

```

### 5.5 Point in Polygon

```

1 const ll inf = 2000000000;
2 struct Point {
3     ll x, y;
4     Point(ll x = 0, ll y = 0):x(x), y(y) {}

```

```

5     Point operator+(const Point p) const {
6         return Point(x + p.x, y + p.y);
7     }
8     Point operator-(const Point p) const {
9         return Point(x - p.x, y - p.y);
10    }
11    ll operator*(const Point p) const { //dot
12        return x * p.x + y * p.y;
13    }
14    ll operator^(const Point p) const { //cross
15        return x * p.y - y * p.x;
16    }
17    bool onseg(Point a, Point b, Point o) {
18        return ((a - o) ^ (b - o)) == 0 && ((a - o) * (b - o)) <=
19            0;
20    }
21    int ori(Point a, Point b, Point o) {
22        ll w = (a - o) ^ (b - o);
23        return (w > 0 ? 1 : -1) : 0;
24    }
25    bool inters(Point a, Point b, Point c, Point d) {
26        if (onseg(a, b, c) || onseg(a, b, d)) return 1;
27        if (onseg(c, d, a) || onseg(c, d, b)) return 1;
28        if (ori(a, b, c) * ori(a, b, d) < 0 && ori(c, d, a) * ori(c,
29            d, b) < 0) return 1;
30        return 0;
31    }
32    Point poly[maxn];
33    void solve(int n, Point p) {
34        poly[n] = poly[0];
35        int cnt = 0;
36        for (int i = 0; i < n; ++i) {
37            if (onseg(poly[i], poly[i + 1], p)) {
38                cnt = -1;
39                break;
40            }
41            if (inters(poly[i], poly[i + 1], p, Point(inf, p.y))) {
42                ++cnt;
43            }
44            Point hi = (poly[i].y > poly[i + 1].y ? poly[i] : poly[i
45                + 1]);
46            if (hi.y == p.y && hi.x > p.x) {
47                --cnt;
48            }
49        }
50        if (cnt < 0)
51            cout << "BOUNDARY\n";
52        else if (cnt % 2)
53            cout << "INSIDE\n";
54        else
55            cout << "OUTSIDE\n";
56    }

```

## 6 Graph

### 6.1 Bipartite Matching

```

1 const int MAXN = 100;
2
3 struct Bipartite_matching{
4     int mx[MAXN], my[MAXN], vy[MAXN]; //matchX, matchY,
5     vector<int> edge[MAXN]; //adjacent list;
6     int x_cnt;

```



```

7 bool dfs(int x){
8     for(auto y: edge[x]){ //對 x 可以碰到的邊進 檢查
9         if(vy[y] == 1) continue; //避免遞迴 error
10
11         vy[y] = 1;
12         if(my[y] == -1 || dfs(my[y])){ //分析 3
13             mx[x] = y;
14             my[y] = x;
15             return true;
16         }
17     }
18     return false; //分析 4
19 }
20
21 int bipartite_matching(){
22     memset(mx, -1, sizeof(mx)); //分析 1,2
23     memset(my, -1, sizeof(my));
24     int ans = 0;
25     for(int i = 0; i < x_cnt; i++){ //對每一個 x 節點進
26         DFS(最大匹配)
27         memset(vy, 0, sizeof(vy));
28         if(dfs(i)) ans++;
29     }
30     return ans;
31 }
32 vector<vector<int>> get_match(){
33     vector<vector<int>> res;
34     for(int i = 0; i < x_cnt; i++){
35         if(mx[i] != -1){
36             res.push_back({i, mx[i]});
37         }
38     }
39     return res;
40 }
41 void add_edge(int i, int j){
42     edge[i].push_back(j);
43 }
44 void init(int x){
45     x_cnt = x;
46 }
47
48 int main(){
49     int n, m;
50     Bipartite_matching bm;
51     for(int i = 0; i < m; i++){
52         int a, b; cin >> a >> b;
53         bm.add_edge(a, b);
54     }
55     bm.init(n);
56     cout << bm.bipartite_matching() << endl;
57     auto match = bm.get_match();
58     for(auto t: match){
59         cout << t[0] << " " << t[1] << endl;
60     }
61 }

```

## 6.2 Tarjan SCC

```

1 const int n = 16;
2 vector<vector<int>> graph;
3 int visit[n], low[n], t = 0;

```

```

4 int st[n], top = 0;
5 bool instack[n];
6 int contract[n]; // 每個點收縮到的點
7 vector<vector<int>> block;
8 void dfs(int x, int parent){
9     // cout << x << endl;
10    visit[x] = low[x] = ++t;
11    st[top++] = x;
12    instack[x] = true;
13    for(auto to: graph[x]){
14        if(!visit[to])
15            dfs(to, x);
16
17        if(instack[to])
18            low[x] = min(low[x], low[to]);
19    }
20    if(visit[x] == low[x]){ //scc 裡最早拜訪的
21        int j;
22        block.push_back({});
23        do{
24            j = st[--top];
25            instack[j] = false;
26            block[block.size() - 1].push_back(j);
27            contract[j] = x;
28        }while(j != x);
29    }
30 }
31 int main(){
32     for(int i = 0; i < n; i++){
33         if (!visit[i])
34             dfs(i, i);
35     }
36     for(auto t: block){
37         for(auto x: t){
38             cout << x << " ";
39         } cout << endl;
40     }
41 }

```

## 6.3 Bridge

```

1 const int n = 9;
2 vector<vector<int>> graph;
3 vector<int> visit(n, 0);
4 vector<int> trace(n, 0);
5 vector<vector<int>> bridge;
6 int t = 0;
7 void dfs(int x, int parent){
8     visit[x] = ++t;
9     trace[x] = x; // 最高祖先預設為自己
10    for (auto to : graph[x]){
11        if (visit[to]) { // back edge
12            if (to != parent){
13                trace[x] = to;
14            }
15        }
16        else { // tree edge
17            dfs(to, x);
18            if (visit[trace[to]] < visit[trace[x]])
19                trace[x] = trace[to];
20        }
21    }

```

// 子樹回不到祖先暨自身。

```

22         if (visit[trace[to]] > visit[x])
23             bridge.push_back({x, to});
24     }
25 }
26 //call for()dfs(i, -1)
27 int main(){
28     for(int i = 0; i < 9; i++){
29         if(!visit[i])
30             dfs(i, -1);
31     }
32     for(auto x: bridge){
33         cout << x[0] << " " << x[1] << endl;
34     }
35 }

```

## 6.4 2 SAT

```

1 class TwoSAT{
2 public:
3     TwoSAT(int n) : n(n), graph(2 * n), visited(2 * n, false)
4     {}
5     void addClause(int a, int b) { // 0-base;
6         a *= 2;
7         b *= 2;
8         // Add implications (~a => b) and (~b => a)
9         graph[a ^ 1].push_back(b);
10        graph[b ^ 1].push_back(a);
11    }
12    bool solve() { // Find SCCs and check for contradictions
13        for (int i = 0; i < 2 * n; ++i) {
14            if (!visited[i]) {
15                dfs1(i);
16            }
17        }
18        reverse(processOrder.begin(), processOrder.end());
19        //topological sort
20        for (int i = 0; i < 2 * n; ++i) {
21            visited[i] = false;
22        }
23        for (int node : processOrder) {
24            if (!visited[node]) {
25                scc.clear();
26                dfs2(node);
27                if (!checkSCCConsistency()) {
28                    return false;
29                }
30            }
31        }
32        return true;
33    }
34 private:
35     int n;
36     vector<vector<int>> graph;
37     vector<bool> visited;
38     vector<int> processOrder;
39     vector<int> scc;
40
41     void dfs1(int node) {
42         visited[node] = true;
43         for (int neighbor : graph[node]) {
44             if (!visited[neighbor]) {

```

```

45         dfs1(neighbor);
46     }
47 }
48 processingOrder.push_back(node);
49 }
50
51 void dfs2(int node) {
52     visited[node] = true;
53     scc.push_back(node);
54     for (int neighbor : graph[node]) {
55         if (!visited[neighbor]) {
56             dfs2(neighbor);
57         }
58     }
59 }
60
61 bool checkSCCConsistency() {
62     for (int node : scc) {
63         if (find(scc.begin(), scc.end(), node ^ 1) != scc
64             .end()) {
65             return false; // Contradiction found in the
66                             same SCC
67         }
68     }
69     return true;
70 }
71
72 int main() {
73     int n, m; // Number of variables and clauses
74     TwoSAT twoSat(n);
75     for (int i = 0; i < m; ++i) {
76         int a, b;
77         twoSat.addClause(a, b);
78     }
79     if (twoSat.solve()) {
80         cout << "Satisfiable" << endl;
81     } else {
82         cout << "Unsatisfiable" << endl;
83     }
84 }

```

## 6.5 Kosaraju 2DFS

```

1 const int n = 16;
2 vector<vector<int>> graph;
3 vector<vector<int>> reverse_graph;
4 int visit[n];
5 int contract[n]; // 每個點收縮到的點
6 vector<vector<int>> block;
7 vector<int> finish; // fake topological sort
8 // need graph and reverse graph
9 void dfs1(int x) {
10     visit[x] = true;
11     for (auto to : graph[x]) {
12         if (!visit[to]) {
13             dfs1(to);
14         }
15     }
16     finish.push_back(x);
17 }
18 void dfs2(int x, int c) {
19     contract[x] = c;
20     block[c].push_back(x);

```

```

21     visit[x] = true;
22     for (auto to : reverse_graph[x]) {
23         if (!visit[to]) {
24             dfs2(to, c);
25         }
26     }
27 }
28 int main() {
29     graph = {};
30     reverse_graph = {};
31
32     for (int i = 0; i < n; ++i) {
33         if (!visit[i]) {
34             dfs1(i);
35         }
36         int c = 0;
37         memset(visit, 0, sizeof(visit));
38         for (int i = n - 1; i >= 0; i--) {
39             if (!visit[finish[i]]) {
40                 block.push_back({});
41                 dfs2(finish[i], c++);
42             }
43         }
44         for (auto t : block) {
45             for (auto x : t) {
46                 cout << x << " ";
47             }
48             cout << endl;
49         }
50     }
51 }

```

## 6.6 Minimum Steiner Tree

```

1 // Minimum Steiner Tree
2 // O(V^3 AT + V^2 2^AT)
3 struct SteinerTree { // 0-base
4     static const int T = 10, N = 105, INF = 1e9;
5     int n, dst[N][N], dp[1 << T][N], tdst[N];
6     int vcost[N]; // the cost of vertices
7     void init(int _n) {
8         n = _n;
9         for (int i = 0; i < n; ++i) {
10             for (int j = 0; j < n; ++j) dst[i][j] = INF;
11             dst[i][i] = vcost[i] = 0;
12         }
13     }
14     void add_edge(int ui, int vi, int wi) {
15         dst[ui][vi] = min(dst[ui][vi], wi);
16     }
17     void shortest_path() {
18         for (int k = 0; k < n; ++k)
19             for (int i = 0; i < n; ++i)
20                 for (int j = 0; j < n; ++j)
21                     dst[i][j] =
22                         min(dst[i][j], dst[i][k] + dst[k][j]);
23     }
24     int solve(const vector<int> &ter) {
25         shortest_path();
26         int t = SZ(ter);
27         for (int i = 0; i < (1 << t); ++i)
28             for (int j = 0; j < n; ++j) dp[i][j] = INF;
29         for (int i = 0; i < n; ++i) dp[0][i] = vcost[i];
30         for (int msk = 1; msk < (1 << t); ++msk) {
31             if (!(msk & (msk - 1))) {

```

```

32         int who = __lg(msk);
33         for (int i = 0; i < n; ++i)
34             dp[msk][i] =
35                 vcost[ter[who]] + dst[ter[who]][i];
36     }
37     for (int i = 0; i < n; ++i)
38         for (int submsk = (msk - 1) & msk; submsk;
39             submsk = (submsk - 1) & msk)
40             dp[msk][i] = min(dp[msk][i],
41                 dp[submsk][i] + dp[msk ^ submsk][i] -
42                 vcost[i]);
43     for (int i = 0; i < n; ++i) {
44         tdst[i] = INF;
45         for (int j = 0; j < n; ++j)
46             tdst[i] =
47                 min(tdst[i], dp[msk][j] + dst[j][i]);
48     }
49     for (int i = 0; i < n; ++i) dp[msk][i] = tdst[i];
50 }
51 int ans = INF;
52 for (int i = 0; i < n; ++i)
53     ans = min(ans, dp[(1 << t) - 1][i]);
54 return ans;
55 }
56 }

```

## 6.7 Dijkstra

```

1 #define maxn 200005
2 vector<int> dis(maxn, -1);
3 vector<int> parent(maxn, -1);
4 vector<bool> vis(maxn, false);
5 vector<vector<pair<int, int>>> graph;
6 void dijkstra(int source) {
7     dis[source] = 0;
8
9     priority_queue<pair<int, int>, vector<pair<int, int>>,
10         greater<pair<int, int>>> pq;
11     pq.push({0, source});
12     while (!pq.empty()) {
13         int from = pq.top().second;
14         pq.pop();
15         // cout << vis[from] << endl;
16         if (vis[from]) continue;
17         vis[from] = true;
18         for (auto next : graph[from]) {
19             int to = next.second;
20             int weight = next.first;
21             // cout << from << " " << to << " " << weight;
22             if (dis[from] + weight < dis[to] || dis[to] == -1) {
23                 dis[to] = dis[from] + weight;
24                 parent[to] = from;
25                 pq.push({dis[from] + weight, to});
26             }
27         }
28     }
29 }
30 int main() {
31     int startpoint;
32     dijkstra(startpoint);
33     // dis and parent
34 }

```

## 6.8 Maximum Clique Dyn

```

1 const int N = 150;
2 struct MaxClique { // Maximum Clique
3     bitset<N> a[N], cs[N];
4     int ans, sol[N], q, cur[N], d[N], n;
5     void init(int _n) {
6         n = _n;
7         for (int i = 0; i < n; i++) a[i].reset();
8     }
9     void addEdge(int u, int v) { a[u][v] = a[v][u] = 1; }
10    void csort(vector<int> &r, vector<int> &c) {
11        int mx = 1, km = max(ans - q + 1, 1), t = 0,
12            m = r.size();
13        cs[1].reset(), cs[2].reset();
14        for (int i = 0; i < m; i++) {
15            int p = r[i], k = 1;
16            while ((cs[k] & a[p]).count()) k++;
17            if (k > mx) mx++, cs[mx + 1].reset();
18            cs[k][p] = 1;
19            if (k < km) r[t++] = p;
20        }
21        c.resize(m);
22        if (t) c[t - 1] = 0;
23        for (int k = km; k <= mx; k++)
24            for (int p = cs[k]._Find_first(); p < N;
25                p = cs[k]._Find_next(p))
26                r[t] = p, c[t] = k, t++;
27    }
28    void dfs(vector<int> &r, vector<int> &c, int l,
29            bitset<N> mask) {
30        while (!r.empty()) {
31            int p = r.back();
32            r.pop_back(), mask[p] = 0;
33            if (q + c.back() <= ans) return;
34            cur[q++] = p;
35            vector<int> nr, nc;
36            bitset<N> nmask = mask & a[p];
37            for (int i : r)
38                if (a[p][i]) nr.push_back(i);
39            if (!nr.empty()) {
40                if (l < 4) {
41                    for (int i : nr)
42                        d[i] = (a[i] & nmask).count();
43                    sort(nr.begin(), nr.end(),
44                        [&](int x, int y) { return d[x] > d[y]; });
45                }
46                csort(nr, nc), dfs(nr, nc, l + 1, nmask);
47            } else if (q > ans) ans = q, copy_n(cur, q, sol);
48            c.pop_back(), q--;
49        }
50    }
51    int solve(bitset<N> mask = bitset<N>(),
52            string(N, '1')) { // vertex mask
53        vector<int> r, c;
54        ans = q = 0;
55        for (int i = 0; i < n; i++)
56            if (mask[i]) r.push_back(i);
57        for (int i = 0; i < n; i++)
58            d[i] = (a[i] & mask).count();
59        sort(r.begin(), r.end(),
60            [&](int i, int j) { return d[i] > d[j]; });
61        csort(r, c), dfs(r, c, 1, mask);
62        return ans; // sol[0 ~ ans-1]
63    }

```

```

64 } graph;

```

## 6.9 Minimum Clique Cover

```

1 struct Clique_Cover { // 0-base, O(n2^Nn)
2     int co[1 << N], n, E[N];
3     int dp[1 << N];
4     void init(int _n) {
5         n = _n, fill_n(dp, 1 << n, 0);
6         fill_n(E, n, 0), fill_n(co, 1 << n, 0);
7     }
8     void add_edge(int u, int v) {
9         E[u] |= 1 << v, E[v] |= 1 << u;
10    }
11    int solve() {
12        for (int i = 0; i < n; ++i)
13            co[1 << i] = E[i] | (1 << i);
14        co[0] = (1 << n) - 1;
15        dp[0] = (n & 1) * 2 - 1;
16        for (int i = 1; i < (1 << n); ++i) {
17            int t = i & -i;
18            dp[i] = -dp[i ^ t];
19            co[i] = co[i ^ t] & co[t];
20        }
21        for (int i = 0; i < (1 << n); ++i)
22            co[i] = (co[i] & i) == i;
23        fwt(co, 1 << n);
24        for (int ans = 1; ans < n; ++ans) {
25            int sum = 0;
26            for (int i = 0; i < (1 << n); ++i)
27                sum += (dp[i] * co[i]);
28            if (sum) return ans;
29        }
30        return n;
31    }
32 };

```

## 6.10 Floyd Warshall

```

1 #define maxn 2005
2 vector<vector<int>> dis(maxn, vector<int>(maxn, 9999999));
3 vector<vector<int>> mid(maxn, vector<int>(maxn, -1));
4 vector<vector<pair<int, int>>> graph;
5
6 void floyd_warshall(int n) { // n is n nodes
7     for (int i = 0; i < n; i++) {
8         for (auto path : graph[i]) {
9             dis[i][path.second] = path.first;
10        }
11    }
12    for (int i = 0; i < n; i++)
13        dis[i][i] = 0;
14    for (int k = 0; k < n; k++) {
15        for (int i = 0; i < n; i++) {
16            for (int j = 0; j < n; j++) {
17                if (dis[i][k] + dis[k][j] < dis[i][j] || dis[i][j]
18                    ] == -1) {
19                    dis[i][j] = dis[i][k] + dis[k][j];
20                    mid[i][j] = k; // 由 i 點走到 j 點經過 k 點
21                }
22            }
23        }
24    }
25 }

```

```

20     }
21     }
22     }
23 }
24
25 void find_path(int s, int t) { // 印出最短徑
26     if (mid[s][t] == -1) return; // 沒有中繼點就結束
27     find_path(s, mid[s][t]); // 前半段最短徑
28     cout << mid[s][t]; // 中繼點
29     find_path(mid[s][t], t); // 後半段最短徑
30 }
31
32 int main() {
33     int n;
34     floyd_warshall(n);
35     for (int i = 0; i < 4; i++) {
36         for (int j = 0; j < 4; j++)
37             cout << dis[i][j] << " ";
38     }
39     find_path(0, 2);
40 }

```

## 6.11 Articulation Vertex

```

1 const int n = 9;
2 int t = 0;
3 vector<int> disc(n, -1); // Discovery time
4 vector<int> low(n, -1); // Low time
5 vector<int> parent_array(n, -1); // Parent in DFS tree
6 vector<bool> visited(n, false);
7 vector<bool> is_articulation(n, false);
8 vector<vector<int>> graph;
9 void dfs_articulation(int node, int parent) {
10     visited[node] = true;
11     disc[node] = t;
12     low[node] = t;
13     t++;
14     int children = 0;
15
16     for (int neighbor : graph[node])
17     {
18         if (!visited[neighbor])
19         {
20             children++;
21             parent_array[neighbor] = node;
22             dfs_articulation(neighbor, node);
23             low[node] = min(low[node], low[neighbor]);
24
25             if (low[neighbor] >= disc[node] && parent != -1)
26             {
27                 is_articulation[node] = true;
28             }
29         }
30         else if (neighbor != parent)
31         {
32             low[node] = min(low[node], disc[neighbor]);
33         }
34     }
35
36     if (parent == -1 && children > 1)
37     {
38         is_articulation[node] = true;
39     }
40 }

```

```

39 }
40 } //call for() dfs(i, -1)
41 int main() {
42     for (int i = 0; i < n; ++i) {
43         if (!visited[i]) {
44             dfs_articulation(i, -1);
45         }
46     }
47     cout << "Articulation Points: ";
48     for (int i = 0; i < n; ++i) {
49         if (is_articulation[i]) {
50             cout << i << " ";
51         }
52     } cout << endl;
53 }

```

## 6.12 Number of Maximal Clique

```

1 struct BronKerbosch { // 1-base
2     int n, a[N], g[N][N];
3     int S, all[N][N], some[N][N], none[N][N];
4     void init(int _n) {
5         n = _n;
6         for (int i = 1; i <= n; ++i)
7             for (int j = 1; j <= n; ++j) g[i][j] = 0;
8     }
9     void add_edge(int u, int v) {
10         g[u][v] = g[v][u] = 1;
11     }
12     void dfs(int d, int an, int sn, int nn) {
13         if (S > 1000) return; // pruning
14         if (sn == 0 && nn == 0) ++S;
15         int u = some[d][0];
16         for (int i = 0; i < sn; ++i) {
17             int v = some[d][i];
18             if (g[u][v]) continue;
19             int tsu = 0, tnn = 0;
20             copy_n(all[d], an, all[d + 1]);
21             all[d + 1][an] = v;
22             for (int j = 0; j < sn; ++j)
23                 if (g[v][some[d][j]])
24                     some[d + 1][tsu++] = some[d][j];
25             for (int j = 0; j < nn; ++j)
26                 if (g[v][none[d][j]])
27                     none[d + 1][tnn++] = none[d][j];
28             dfs(d + 1, an + 1, tsu, tnn);
29             some[d][i] = 0, none[d][nn++] = v;
30         }
31     }
32     int solve() {
33         iota(some[0], some[0] + n, 1);
34         S = 0, dfs(0, 0, n, 0);
35         return S;
36     }
37 };

```

## 6.13 DominatorTree

```

1 struct dominator_tree { // 1-base
2     vector<int> G[N], rG[N];

```

```

3     int n, pa[N], dfn[N], id[N], Time;
4     int semi[N], idom[N], best[N];
5     vector<int> tree[N]; // dominator_tree
6     void init(int _n) {
7         n = _n;
8         for (int i = 1; i <= n; ++i)
9             G[i].clear(), rG[i].clear();
10    }
11    void add_edge(int u, int v) {
12        G[u].pb(v), rG[v].pb(u);
13    }
14    void dfs(int u) {
15        id[dfn[u] = ++Time] = u;
16        for (auto v : G[u])
17            if (!dfn[v]) dfs(v), pa[dfn[v]] = dfn[u];
18    }
19    int find(int y, int x) {
20        if (y <= x) return y;
21        int tmp = find(pa[y], x);
22        if (semi[best[y]] > semi[best[pa[y]]])
23            best[y] = best[pa[y]];
24        return pa[y] = tmp;
25    }
26    void tarjan(int root) {
27        Time = 0;
28        for (int i = 1; i <= n; ++i) {
29            dfn[i] = idom[i] = 0;
30            tree[i].clear();
31            best[i] = semi[i] = i;
32        }
33        dfs(root);
34        for (int i = Time; i > 1; --i) {
35            int u = id[i];
36            for (auto v : rG[u])
37                if (v = dfn[v]) {
38                    find(v, i);
39                    semi[i] = min(semi[i], semi[best[v]]);
40                }
41            tree[semi[i]].pb(i);
42            for (auto v : tree[pa[i]]) {
43                find(v, pa[i]);
44                idom[v] =
45                    semi[best[v]] == pa[i] ? pa[i] : best[v];
46            }
47            tree[pa[i]].clear();
48        }
49        for (int i = 2; i <= Time; ++i) {
50            if (idom[i] != semi[i]) idom[i] = idom[idom[i]];
51            tree[id[idom[i]]].pb(id[i]);
52        }
53    }
54 };

```

## 6.14 Topological Sort

```

1 vector<vector<int>> graph;
2 vector<int> visit(10, 0);
3 vector<int> order;
4 int n;
5 bool cycle; // 記錄DFS的過程中是否偵測到環
6 void DFS(int i) { //reverse(order) is topo
7     if (visit[i] == 1) {cycle = true; return;}
8     if (visit[i] == 2) return;

```

```

9     visit[i] = 1;
10    for(auto to :graph[i])
11        DFS(to);
12    visit[i] = 2;
13    order.push_back(i);
14 } //for() if(!vis[i])DFS(i)
15 int main() {
16     for (int i=0; i<n; ++i){
17         if (!visit[i])
18             DFS(i);
19     }
20     if (cycle)
21         cout << "圖上有環";
22     else
23         for (int i=n-1; i>=0; --i)
24             cout << order[i];
25 }

```

## 6.15 Closest Pair

```

1 template<typename _IT=point<T>*>
2 T cloest_pair(_IT L, _IT R) {
3     if (R-L <= 1) return INF;
4     _IT mid = L+(R-L)/2;
5     T x = mid->x;
6     T d = min(cloest_pair(L, mid), cloest_pair(mid, R));
7     inplace_merge(L, mid, R, ycmp);
8     static vector<point> b; b.clear();
9     for(auto u=L; u<R; ++u) {
10         if ((u->x-x)*(u->x-x)>=d) continue;
11         for(auto v=b.rbegin(); v!=b.rend(); ++v) {
12             T dx=u->x-v->x, dy=u->y-v->y;
13             if (dy*dy>=d) break;
14             d=min(d, dx*dx+dy*dy);
15         }
16         b.push_back(*u);
17     }
18     return d;
19 }
20 T closest_pair(vector<point<T>> &v) {
21     sort(v.begin(), v.end(), xcmp);
22     return closest_pair(v.begin(), v.end());
23 }

```

## 6.16 Minimum Mean Cycle

```

1 ll road[N][N]; // input here
2 struct MinimumMeanCycle {
3     ll dp[N + 5][N], n;
4     pll solve() {
5         ll a = -1, b = -1, L = n + 1;
6         for (int i = 2; i <= L; ++i)
7             for (int k = 0; k < n; ++k)
8                 for (int j = 0; j < n; ++j)
9                     dp[i][j] =
10                         min(dp[i - 1][k] + road[k][j], dp[i][j]);
11         for (int i = 0; i < n; ++i) {
12             if (dp[L][i] >= INF) continue;
13             ll ta = 0, tb = 1;

```

```

14     for (int j = 1; j < n; ++j)
15         if (dp[j][i] < INF &&
16             ta * (L - j) < (dp[L][i] - dp[j][i]) * tb)
17             ta = dp[L][i] - dp[j][i], tb = L - j;
18     if (ta == 0) continue;
19     if (a == -1 || a * tb > ta * b) a = ta, b = tb;
20 }
21 if (a != -1) {
22     ll g = __gcd(a, b);
23     return pll(a / g, b / g);
24 }
25 return pll(-1LL, -1LL);
26 }
27 void init(int _n) {
28     n = _n;
29     for (int i = 0; i < n; ++i)
30         for (int j = 0; j < n; ++j) dp[i + 2][j] = INF;
31 }
32 };

```

## 6.17 Planar

```

1 class Graph {
2 public:
3     int V;
4     vector<vector<int>>> adj;
5     Graph(int vertices) : V(vertices), adj(vertices) {}
6     void addEdge(int u, int v) {
7         adj[u].push_back(v);
8         adj[v].push_back(u);
9     }
10 };
11
12 bool containsSubgraph(const Graph& graph, const vector<int>&
13     subgraph) {
14     unordered_set<int> subgraphVertices(subgraph.begin(),
15         subgraph.end());
16     for (int vertex : subgraphVertices) {
17         for (int neighbor : graph.adj[vertex]) {
18             if (subgraphVertices.count(neighbor) == 0) {
19                 bool found = true;
20                 for (int v : subgraph) {
21                     if (v != vertex && v != neighbor) {
22                         if (graph.adj[v].size() < 3) {
23                             found = false;
24                             break;
25                         }
26                     }
27                 }
28                 if (found)
29                     return true;
30             }
31         }
32     }
33     return false;
34 }
35
36 bool isPlanar(const Graph& graph) {
37     // Subgraphs isomorphic to K and K ,
38     vector<int> k5 = {0, 1, 2, 3, 4}; // Vertices of K
39     vector<int> k33a = {0, 1, 2}; // Vertices of K
40     , (part A)

```

```

38     vector<int> k33b = {3, 4, 5}; // Vertices of K 39 }
39     , (part B)
40
41     if (containsSubgraph(graph, k5) || containsSubgraph(graph,
42         k33a) || containsSubgraph(graph, k33b)) {
43         return false; // The graph is non-planar
44     }
45     return true; // The graph is planar
46 }
47
48 int main() {
49     int vertices, edges;
50     Graph graph(vertices);
51     for (int i = 0; i < edges; ++i) {
52         int u, v; cin >> u >> v;
53         graph.addEdge(u, v);
54     }
55     if (isPlanar(graph)) {
56         cout << "The graph is planar." << endl;
57     } else {
58         cout << "The graph is non-planar." << endl;
59     }
60 }

```

## 6.18 Heavy Light Decomposition

```

1 int dep[N], pa[N], sz[N], nxt[N];
2 int id[N], rt[N];
3 int dfs(int u, int lst, int d = 0) {
4     dep[u] = d;
5     pa[u] = lst;
6     sz[u] = 1;
7     nxt[u] = -1;
8     for (int v : g[u]) {
9         if (v == lst) continue;
10        sz[u] += dfs(v, u, d + 1);
11        if (nxt[u] == -1 || sz[v] > sz[nxt[u]]) {
12            nxt[u] = v;
13        }
14    }
15    return sz[u];
16 }
17 int tn = 0;
18 void mapId(int u, int lst, int root) {
19     id[u] = ++tn;
20     rt[u] = root;
21     if (~nxt[u]) mapId(nxt[u], u, root);
22     for (int v : g[u]) {
23         if (v == lst || v == nxt[u]) continue;
24         mapId(v, u, v);
25     }
26 }
27 void solve() {
28     while (rt[a] != rt[b]) {
29         if (dep[rt[a]] > dep[rt[b]]) swap(a, b);
30         //...
31         b = pa[rt[b]];
32     }
33     if (a != b) {
34         if (id[a] > id[b]) swap(a, b);
35         //...
36     } else {
37         //...
38     }

```

## 6.19 Centroid Decomposition

```

1 int sz[maxn]{};
2 bool ok[maxn]{};
3 int get_subtree_size(int u, int lst) {
4     sz[u] = 1;
5     for (int v : g[u]) {
6         if (v == lst || ok[v]) continue;
7         sz[u] += get_subtree_size(v, u);
8     }
9     return sz[u];
10 }
11 int get_centroid(int u, int lst, int tree_size) {
12     for (int v : g[u]) {
13         if (v == lst || ok[v]) continue;
14         if (2 * sz[v] >= tree_size) {
15             return get_centroid(v, u, tree_size);
16         }
17     }
18     return u;
19 }
20 void centroid_decomp(int u = 1) { //1-based
21     int centroid = get_centroid(u, u, get_subtree_size(u, u));
22     //...
23     ok[centroid] = 1;
24     for (int v : g[centroid]) if (!ok[v]) {
25         centroid_decomp(v);
26     }
27 }

```

## 6.20 KM\_O

```

1 // 二分圖最大權完美匹配
2 #define MAXN 100
3 #define INF INT_MAX
4 int g[MAXN][MAXN], lx[MAXN], ly[MAXN], slack_y[MAXN];
5 int px[MAXN], py[MAXN], match_y[MAXN], par[MAXN];
6 int n;
7 void adjust(int y) { //把增廣 上所有邊反轉
8     match_y[y] = py[y];
9     if (px[match_y[y]] != -2)
10         adjust(px[match_y[y]]);
11 }
12 bool dfs(int x) { //DFS找增廣
13     for (int y = 0; y < n; ++y) {
14         if (py[y] != -1) continue;
15         int t = lx[x] + ly[y] - g[x][y];
16         if (t == 0) {
17             py[y] = x;
18             if (match_y[y] == -1) {
19                 adjust(y);
20                 return 1;
21             }
22             if (px[match_y[y]] != -1) continue;
23             px[match_y[y]] = y;
24             if (dfs(match_y[y])) return 1;
25         } else if (slack_y[y] > t) {

```

```

26     slack_y[y]=t;
27     par[y]=x;
28 }
29 }
30 return 0;
31 }
32 inline int km() {
33     memset(ly, 0, sizeof(int)*n);
34     memset(match_y, -1, sizeof(int)*n);
35     for(int x=0; x<n; ++x) {
36         lx[x] = -INF;
37         for(int y=0; y<n; ++y) {
38             lx[x] = max(lx[x], g[x][y]);
39         }
40     }
41     for(int x=0; x<n; ++x) {
42         for(int y=0; y<n; ++y) slack_y[y] = INF;
43         memset(px, -1, sizeof(int)*n);
44         memset(py, -1, sizeof(int)*n);
45         px[x] = -2;
46         if(dfs(x)) continue;
47         bool flag = 1;
48         while(flag) {
49             int cut = INF;
50             for(int y=0; y<n; ++y)
51                 if(py[y] == -1 && cut > slack_y[y]) cut = slack_y[y];
52             for(int j=0; j<n; ++j) {
53                 if(px[j] != -1) lx[j] -= cut;
54                 if(py[j] != -1) ly[j] += cut;
55                 else slack_y[j] -= cut;
56             }
57             for(int y=0; y<n; ++y) {
58                 if(py[y] == -1 && slack_y[y] == 0) {
59                     py[y] = par[y];
60                     if(match_y[y] == -1) {
61                         adjust(y);
62                         flag = 0;
63                         break;
64                     }
65                     px[match_y[y]] = y;
66                     if(dfs(match_y[y])) {
67                         flag = 0;
68                         break;
69                     }
70                 }
71             }
72         }
73     }
74     int ans = 0;
75     for(int y=0; y<n; ++y) if(g[match_y[y]][y] != -INF) ans += g[match_y[y]][y];
76     return ans;
77 }

```

## 6.21 Minimum Arborescence

```

1 struct zhu_liu { // O(VE)
2     struct edge {
3         int u, v;
4         ll w;
5     };
6     vector<edge> E; // 0-base
7     int pe[N], id[N], vis[N];

```

```

8     ll in[N];
9     void init() { E.clear(); }
10    void add_edge(int u, int v, ll w) {
11        if (u != v) E.pb(edge{u, v, w});
12    }
13    ll build(int root, int n) {
14        ll ans = 0;
15        for(;;) {
16            fill_n(in, n, INF);
17            for(int i = 0; i < SZ(E); ++i)
18                if (E[i].u != E[i].v && E[i].w < in[E[i].v])
19                    pe[E[i].v] = i, in[E[i].v] = E[i].w;
20            for(int u = 0; u < n; ++u) // no solution
21                if (u != root && in[u] == INF) return -INF;
22            int cntnode = 0;
23            fill_n(id, n, -1), fill_n(vis, n, -1);
24            for(int u = 0; u < n; ++u) {
25                if (u != root) ans += in[u];
26                int v = u;
27                while (vis[v] != u && !~id[v] && v != root)
28                    vis[v] = u, v = E[pe[v]].u;
29                if (v != root && !~id[v]) {
30                    for(int x = E[pe[v]].u; x != v;
31                        x = E[pe[x]].u)
32                        id[x] = cntnode;
33                    id[v] = cntnode++;
34                }
35                if (!cntnode) break; // no cycle
36            }
37            for(int u = 0; u < n; ++u)
38                if (!~id[u]) id[u] = cntnode++;
39            for(int i = 0; i < SZ(E); ++i) {
40                int v = E[i].v;
41                E[i].u = id[E[i].u], E[i].v = id[E[i].v];
42                if (E[i].u != E[i].v) E[i].w -= in[v];
43            }
44            n = cntnode, root = id[root];
45        }
46        return ans;
47    }
48 };

```

## 6.22 Maximum Clique

```

1 struct Maximum_Clique {
2     typedef bitset<MAXN> bst;
3     bst N[MAXN], empty;
4     int p[MAXN], n, ans;
5     void BronKerbosch2(bst R, bst P, bst X) {
6         if (P == empty && X == empty)
7             return ans = max(ans, (int)R.count()), void();
8         bst tmp = P | X;
9         int u;
10        if ((R | P | X).count() <= ans) return;
11        for(int uu = 0; uu < n; ++uu) {
12            u = p[uu];
13            if (tmp[u] == 1) break;
14        }
15        // if (double(clock())/CLOCKS_PER_SEC > .999)
16        // return;
17        bst now2 = P & ~N[u];
18        for(int vv = 0; vv < n; ++vv) {
19            int v = p[vv];

```

```

20        if (now2[v] == 1) {
21            R[v] = 1;
22            BronKerbosch2(R, P & N[v], X & N[v]);
23            R[v] = 0, P[v] = 0, X[v] = 1;
24        }
25    }
26 }
27 void init(int _n) {
28     n = _n;
29     for(int i = 0; i < n; ++i) N[i].reset();
30 }
31 void add_edge(int u, int v) {
32     N[u][v] = N[v][u] = 1;
33 }
34 int solve() { // remember srand
35     bst R, P, X;
36     ans = 0, P.flip();
37     for(int i = 0; i < n; ++i) p[i] = i;
38     random_shuffle(p, p + n), BronKerbosch2(R, P, X);
39     return ans;
40 }
41 };

```

## 7 Math

### 7.1 Miller Robin

```

1 // n < 4,759,123,141      3 : 2, 7, 61
2 // n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
3 // n < 3,474,749,660,383  6 : pirmses <= 13
4 // n < 2^64              7 : 2, 325, 9375, 28178, 450775,
5 //                        9780504, 1795265022
6 //From jacky860226
7 typedef long long LL;
8 inline LL mul(LL a, LL b, LL m) { //a*b%m
9     return (a%m)*(b%m)%m;
10 }
11 /*LL mul(LL a, LL b, LL m) { //a*b%m
12     a %= m, b %= m;
13     LL y = (LL)((double)a*b/m+0.5); //fast for m < 2^58
14     LL r = (a*b-y*m)%m;
15     return r<0 ? r+m : r;
16 }*/
17 template<typename T> T
18 pow(T a, T b, T mod) { //a^b%mod
19     T ans = 1;
20     while(b) {
21         if(b&1) ans = mul(ans, a, mod);
22         a = mul(a, a, mod);
23         b >>= 1;
24     } return ans;
25 }
26 template<typename T>
27 bool isprime(T n, int num) { //num = 3,7
28     int sprp[3] = {2, 7, 61}; //int範圍可解
29     //int llsprp[7] =
30         {2, 325, 9375, 28178, 450775, 9780504, 1795265022}; //至少
31         unsigned long long範圍
32     if(n==2) return true;

```



```

31 if(n<2 || n%2==0) return false;
32 //n-1 = u * 2^t
33 int t = 0; T u = n-1;
34 while(u%2==0) u >>= 1, t++;
35 for(int i=0; i<num; i++) {
36     T a = sprp[i]*n;
37     if(a==0 || a==1 || a==n-1) continue;
38     T x = pow(a,u,n);
39     if(x==1 || x==n-1) continue;
40     for(int j=1; j<t; j++) {
41         x = mul(x,x,n);
42         if(x==1) return false;
43         if(x==n-1) break;
44     }
45     if(x!=n-1) return false;
46 } return true;
47 }

```

## 7.2 fpow

```

1 ll fpow(ll b, ll p, ll mod) {
2     ll res = 1;
3     while (p) {
4         if (p & 1) res = res * b % mod;
5         b = b * b % mod, p >>= 1;
6     }
7     return res;
8 }

```

## 7.3 Big Number

```

1 template<typename T>
2 inline string to_string(const T& x) {
3     stringstream ss;
4     return ss<<x,ss.str();
5 }
6 struct bigN:vector<ll>{
7     const static int base=1000000000,width=log10(base);
8     bool negative;
9     bigN(const_iterator a,const_iterator b):vector<ll>(a,b){}
10    bigN(string s){
11        if(s.empty())return;
12        if(s[0]=='-')negative=1,s=s.substr(1);
13        else negative=0;
14        for(int i=int(s.size())-1;i>=0;i-=width){
15            ll t=0;
16            for(int j=max(0,i-width+1);j<=i;j++)
17                t=t*10+s[j]-'0';
18            push_back(t);
19        }
20        trim();
21    }
22    template<typename T>
23    bigN(const T &x):bigN(to_string(x)){}
24    bigN():negative(0){}
25    void trim(){
26        while(size()&&!back())pop_back();
27        if(empty())negative=0;
28    }
29    void carry(int _base=base){

```

```

30    for(size_t i=0;i<size();++i){
31        if(at(i)>=0&&at(i)<_base)continue;
32        if(i+1==size())push_back(0);
33        int r=at(i)%_base;
34        if(r<0)r+=_base;
35        at(i+1)+=(at(i)-r)/_base,at(i)=r;
36    }
37 }
38 int abscmp(const bigN &b)const{
39     if(size()>b.size())return 1;
40     if(size()<b.size())return -1;
41     for(int i=int(size())-1;i>=0;--i){
42         if(at(i)>b[i])return 1;
43         if(at(i)<b[i])return -1;
44     }
45     return 0;
46 }
47 int cmp(const bigN &b)const{
48     if(negative!=b.negative)return negative?-1:1;
49     return negative?-abscmp(b):abscmp(b);
50 }
51 bool operator<(const bigN&b)const{return cmp(b)<0;}
52 bool operator>(const bigN&b)const{return cmp(b)>0;}
53 bool operator<=(const bigN&b)const{return cmp(b)<=0;}
54 bool operator>=(const bigN&b)const{return cmp(b)>=0;}
55 bool operator==(const bigN&b)const{return !cmp(b);}
56 bool operator!=(const bigN&b)const{return cmp(b)!=0;}
57 bigN abs()const{
58     bigN res=*this;
59     return res.negative=0, res;
60 }
61 bigN operator-()const{
62     bigN res=*this;
63     return res.negative=!negative,res.trim(),res;
64 }
65 bigN operator+(const bigN &b)const{
66     if(negative)return -(-(*this)+(-b));
67     if(b.negative)return *this-(-b);
68     bigN res=*this;
69     if(b.size()>size())res.resize(b.size());
70     for(size_t i=0;i<b.size();++i)res[i]+=b[i];
71     return res.carry(),res.trim(),res;
72 }
73 bigN operator-(const bigN &b)const{
74     if(negative)return -(-(*this)-(-b));
75     if(b.negative)return *this+(-b);
76     if(abscmp(b)<0)return -(b-(*this));
77     bigN res=*this;
78     if(b.size()>size())res.resize(b.size());
79     for(size_t i=0;i<b.size();++i)res[i]-=b[i];
80     return res.carry(),res.trim(),res;
81 }
82 bigN operator*(const bigN &b)const{
83     bigN res;
84     res.negative=negative!=b.negative;
85     res.resize(size()+b.size());
86     for(size_t i=0;i<size();++i)
87         for(size_t j=0;j<b.size();++j)
88             if((res[i+j]+=at(i)*b[j])>=base){
89                 res[i+j+1]+=res[i+j]/base;
90                 res[i+j]%=base;
91             }
92     return res.trim(),res;
93 }
94 bigN operator/(const bigN &b)const{
95     int norm=base/(b.back()+1);

```

```

96    bigN x=abs()*norm;
97    bigN y=b.abs()*norm;
98    bigN q,r;
99    q.resize(x.size());
100    for(int i=int(x.size())-1;i>=0;--i){
101        r=r*base+x[i];
102        int s1=r.size()<=y.size()?0:r[y.size()];
103        int s2=r.size()<y.size()?0:r[y.size()-1];
104        int d=(ll(base)*s1+s2)/y.back();
105        r=r-y*d;
106        while(r.negative)r=r+y,--d;
107        q[i]=d;
108    }
109    q.negative=negative!=b.negative;
110    return q.trim(),q;
111 }
112 bigN operator%(const bigN &b)const{
113     return *this-(*this/b)*b;
114 }
115 friend istream& operator>>(istream &ss,bigN &b){
116     string s;
117     return ss>>s, b=s, ss;
118 }
119 friend ostream& operator<<(ostream &ss,const bigN &b){
120     if(b.negative)ss<<"-";
121     ss<<(b.empty()?0:b.back());
122     for(int i=int(b.size())-2;i>=0;--i)
123         ss<<setw(width)<<setfill('0')<<b[i];
124     return ss;
125 }
126 template<typename T>
127 operator T(){
128     stringstream ss;
129     ss<<*this;
130     T res;
131     return ss>>res,res;
132 }
133 };

```

## 7.4 modinv

```

1 // 解 (ax == 1) mod p * p 必須是質數, a 是正整數。
2 ll modinv(ll a, ll p) {
3     if (p == 1) return 0;
4     ll pp = p, y = 0, x = 1;
5     while (a > 1) {
6         ll q = a / p, t = p;
7         p = a % p, a = t, t = y, y = x - q * y, x = t;
8     }
9     if (x < 0) x += pp;
10    return x;
11 }
12 // 解 (ax == b) mod p * p 必須是質數, a 和 b 是正整數。
13 ll modinv(ll a, ll b, ll p) {
14     ll ret = modinv(a, p);
15     return ret * b % p;
16 }

```

## 7.5 Matrix

• 旋轉矩陣

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

• 縮放矩陣

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} s_x & 0 \\ 0 & s_y \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

• 反射矩陣

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} 2u_x^2 - 1 & 2u_x u_y \\ 2u_x u_y & 2u_y^2 - 1 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

• 正投影

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} u_x^2 & u_x u_y \\ u_x u_y & u_y^2 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

## 7.6 PollardRho

```
1 // does not work when n is prime
2 ll f(ll x, ll mod) { return add(mul(x, x, mod), 1, mod); }
3 ll pollard_rho(ll n) {
4     if(!(n&1)) return 2;
5     while(1) {
6         ll y=2, x=rand()%(n-1)+1, res=1;
7         for(int sz=2; res==1; y=x, sz*=2)
8             for(int i=0; i<sz&&res<=1; ++i)
9                 x=f(x, n), res=__gcd(abs(x-y), n);
10        if(res!=0&&res!=n) return res;
11    }
12 }
```

## 7.7 Euler Totient Function

```
1 ll phi[maxn];
2 for (int i = 0; i < maxn; ++i) {
3     phi[i] = i;
4 }
5 for (int i = 2; i < maxn; ++i) if (phi[i] == i) {
6     phi[i] = i - 1; //prime
7     for (int j = 2; i*j < maxn; ++j) { //overflow
8         phi[i*j] = (phi[i*j] / i) * (i - 1);
9     }
10 }
```

## 7.8 extGCD

```
(1) 1 int extgcd(int a, int b, int &x, int &y) { //a*x + b*y = 1
2     if(b==0) {
3         x = 1;
4         y = 0;
5         return a; //到達遞歸邊界開始向上一層返回
6     }
7     int r = extgcd(b, a%b, x, y);
8     int temp=y; //把x y變成上一層的
9     y = x - (a / b) * y;
10    x = temp;
11    return r; //得到a b的最大公因數
12 }
13 int main() {
14     int a = 55, b = 80;
15     int x, y; //a*x+b*y = 1;
16     int GCD = extgcd(a, b, x, y);
17 }
```

## 7.9 random

```
(4) 1 inline int ran() {
2     static int x = 20167122;
3     return x = (x * 0xdefaced + 1) & INT_MAX;
4 }
```

## 7.10 FFT

```
1 //OI Wiki
2 #include <complex>
3 using cd = complex<double>;
4 const double PI = acos(-1);
5 void change(vector<cd> &y) {
6     vector<int> rev(y.size());
7     for (int i = 0; i < y.size(); ++i) {
8         rev[i] = rev[i >> 1] >> 1;
9         if (i & 1) {
10            rev[i] |= y.size() >> 1;
11        }
12    }
13    for (int i = 0; i < y.size(); ++i) {
14        if (i < rev[i]) {
15            swap(y[i], y[rev[i]]);
16        }
17    }
18 }
19 void fft(vector<cd> &y, bool inv) {
20     change(y);
21     for (int h = 2; h <= y.size(); h <= 1) {
22         cd wn(cos(2 * PI / h), sin(2 * PI / h));
23         for (int j = 0; j < y.size(); j += h) {
24             cd w(1, 0);
25             for (int k = j; k < j + h / 2; ++k) {
26                 cd u = y[k];
27                 cd t = w * y[k + h / 2];
28                 y[k] = u + t;
29                 y[k + h / 2] = u - t;
30                 w = w * wn;
31             }
32         }
33     }
```

```
33 }
34 if (inv) {
35     reverse(begin(y) + 1, end(y));
36     for (int i = 0; i < y.size(); ++i) {
37         y[i] /= y.size();
38     }
39 }
40 }
41 void solve() {
42     int n;
43     int m = 1 << (lg(n) + 1); //power of 2
44     vector<cd> a(m), b(m);
45     //...
46     fft(a, 0);
47     fft(b, 0);
48     vector<cd> c(m);
49     for (int i = 0; i < m; ++i) {
50         c[i] = a[i] * b[i];
51     }
52     fft(c, 1);
53     for (auto p: c) {
54         int ans = int(p.real() + 0.25);
55     }
56 }
```

## 7.11 mu

```
1 int mu[MAXN];
2 bool isnp[MAXN];
3 vector<int> primes;
4 void init(int n)
5 {
6     mu[1] = 1;
7     for (int i = 2; i <= n; i++)
8     {
9         if (!isnp[i])
10            primes.push_back(i), mu[i] = -1; // 质数为 -1
11        for (int p : primes)
12        {
13            if (p * i > n)
14                break;
15            isnp[p * i] = 1;
16            if (i % p == 0)
17            {
18                mu[p * i] = 0; // 有平方因数为 0
19                break;
20            }
21            else
22                mu[p * i] = mu[p] * mu[i]; // 互质， 用积性
23                函数性质
24        }
25 }
```

## 7.12 Chinese Remainder

```

1 // Chinese remainder theorem (special case): find z such that
2 //  $z \equiv a \pmod{x}$ ,  $z \equiv b \pmod{y}$ . Here, z is unique modulo  $M = \text{lcm}(x, y)$ .
3 // Return (z,M). On failure, M = -1.
4 PII chinese_remainder_theorem(int x, int a, int y, int b) {
5     int s, t;
6     int d = extended_euclid(x, y, s, t);
7     if (a*d != b*d) return make_pair(0, -1);
8     return make_pair(mod(s*b*x+t*a*y,x*y)/d, x*y/d);
9 }
10
11 // Chinese remainder theorem: find z such that
12 //  $z \equiv x[i] \pmod{a[i]}$  for all i. Note that the solution is
13 // unique modulo  $M = \text{lcm}_i(a[i])$ . Return (z,M). On
14 // failure, M = -1. Note that we do not require the  $a[i]$ 's
15 // to be relatively prime.
16 PII chinese_remainder_theorem(const VI &x, const VI &a) {
17     PII ret = make_pair(a[0], x[0]);
18     for (int i = 1; i < x.size(); i++) {
19         ret = chinese_remainder_theorem(ret.second, ret.first, x[i], a[i]);
20         if (ret.second == -1) break;
21     }
22     return ret;
23 }
24
25 // computes x and y such that  $ax + by = c$ ; on failure, x = y = -1
26 void linear_diophantine(int a, int b, int c, int &x, int &y) {
27     int d = gcd(a,b);
28     if (c%d) {
29         x = y = -1;
30     } else {
31         x = c/d * mod_inverse(a/d, b/d);
32         y = (c-a*x)/b;
33     }
34 }

```

## 8 Misc

### 8.1 Mo's Algorithm

```

1 struct Query {
2     int L, R;
3     //...
4 };
5 vector<Query> query;
6 void solve() { //K = n / sqrt(q)
7     sort(iter(query), [&](Query &a, Query &b) {
8         if (a.L / K != b.L / K) return a.L < b.L;
9         return a.L / K % 2 ? a.R < b.R : a.R > b.R;
10    });
11    int L = 0, R = 0;
12    for (auto x: query) {
13        while (R < x.R) add(arr[++R]);
14        while (L > x.L) add(arr[--L]);
15        while (R > x.R) sub(arr[R--]);

```

```

16        while (L < x.L) sub(arr[L++]);
17        //...
18    }
19 }

```

### 8.2 pbds

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 #include <ext/pb_ds/tree_policy.hpp>
3 using namespace __gnu_pbds;
4
5 template<typename T>
6 using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
7     tree_order_statistics_node_update>;
8
9 int32_t main() {
10     ordered_set<int64_t> rbt;
11     // .insert(x); .erase(x)
12     // .lower_bound(x); .upper_bound(x): iter
13     // .find_by_order(k): find k-th small value(iter)
14     // .order_of_key(x): return x is k-th big
15     // .join(rbt2): merge with no mutiple same element
16     // .split(key, rbt2): rbt keeps value <= key, others to rbt2
17 }

```

### 8.3 Misc

```

1 mt19937 rng(chrono::steady_clock::now().time_since_epoch().
2     count());
3 int randint(int lb, int ub) {
4     return uniform_int_distribution<int>(lb, ub)(rng);
5 } //static unsigned x = 19; ++(x *= 0xdefaced);
6
7 #define SECS ((double)clock() / CLOCKS_PER_SEC)
8
9 struct KeyHasher {
10     size_t operator()(const Key& k) const {
11         return k.first + k.second * 100000;
12     };
13 };
14 typedef unordered_map<Key,int,KeyHasher> map_t;
15
16 __lg
17 __gcd
18
19 int __builtin_ffs(unsigned int x)
20 int __builtin_ffsl(unsigned long)
21 int __builtin_ffsll(unsigned long long)
22 返回右起第一個1的位置
23 Returns one plus the index of the least significant 1-bit of
24 x, or if x is zero, returns zero.
25
26 int __builtin_clz(unsigned int x)
27 int __builtin_clzl(unsigned long)
28 int __builtin_clzll(unsigned long long)
29 返回左起第一個1之前0的個數
30 Returns the number of leading 0-bits in x, starting at the
31 most significant bit position. If x is 0, the result is
32 undefined.

```

```

28 int __builtin_ctz(unsigned int x)
29 int __builtin_ctzl(unsigned long)
30 int __builtin_ctzll(unsigned long long)
31 返回右起第一個1之後的0的個數
32 Returns the number of trailing 0-bits in x, starting at the
33 least significant bit position. If x is 0, the result is
34 undefined.
35
36 int __builtin_popcount(unsigned int x)
37 int __builtin_popcountl(unsigned long)
38 int __builtin_popcountll(unsigned long long)
39 返回1的個數
40 Returns the number of 1-bits in x.
41
42 int __builtin_parity(unsigned int x)
43 int __builtin_parityl(unsigned long)
44 int __builtin_parityll(unsigned long long)
45 返回1的個數的奇偶性(1的個數 mod 2的值)
46 Returns the parity of x, i.e. the number of 1-bits in x
47 modulo 2.

```

## 9 String

### 9.1 Hashing

```

1 const ll P = 401, M = 998244353;
2
3 ll hashes[10005], modp[10005];
4 ll hashp(string s, bool saveval) {
5     ll val = 0;
6     int index = 0;
7     for (char c: s) {
8         val = ((val * P) % M + c) % M;
9         if (saveval) hashes[index++] = val;
10    }
11    return val;
12 }
13 void init(int base, int exp) {
14     ll b = 1;
15     modp[0] = 1;
16     for (int i = 0; i < exp; i++) {
17         b = (b * base) % M;
18         modp[i + 1] = b;
19     }
20 }
21 ll subseq(int l, int r) { //[l, r]
22     if (l == 0) return hashes[r];
23     return ((hashes[r] - hashes[l-1] * modp[r-l+1]) % M + M) %
24     M;
25 }

```

### 9.2 Trie

```

1 struct node {
2     int ch[26]{};
3     int cnt = 0;

```

```

4};
5struct Trie {
6    vector<node> t;
7    void init() {
8        t.clear();
9        t.emplace_back(node());
10    }
11    void insert(string s) {
12        int ptr = 0;
13        for (char i: s) {
14            if (!t[ptr].ch[i - 'a']) {
15                t[ptr].ch[i - 'a'] = (int)t.size();
16                t.emplace_back(node());
17            }
18            ptr = t[ptr].ch[i - 'a'];
19        }
20        t[ptr].cnt++;
21    }
22} trie;

```

### 9.3 Zvalue

```

1vector<int> Zvalue(string &s) { //t + # + s
2    vector<int> Z(s.size());
3    int x = 0, y = 0;
4    for (int i=0; i<s.size(); ++i) {
5        Z[i] = max(0, min(y - i + 1, Z[i - x]));
6        while (i + Z[i] < s.size() && s[Z[i]] == s[i + Z[i]])
7            x = i, y = i + Z[i], ++Z[i];
8    }
9    return Z;
10}

```

### 9.4 KMP

```

1int F[maxn]{};
2vector<int> match(string& s, string& t) {
3    int p = F[0] = -1;
4    for (int i = 1; i < t.size(); ++i) {
5        while (p != -1 && t[p + 1] != t[i]) p = F[p];
6        if (t[p + 1] == t[i]) ++p;
7        F[i] = p;
8    }
9    p = -1;
10    vector<int> v;
11    for (int i = 0; i < s.size(); ++i) {
12        while (p != -1 && t[p + 1] != s[i]) p = F[p];
13        if (t[p + 1] == s[i]) ++p;
14        if (p == t.size() - 1) v.push_back(i - p), p = F[p];
15    }
16    return v; //0-based
17}

```

### 9.5 Manacher

```

1int z[maxn * 2]{};
2int manacher(string& s) {
3    string t = "#";
4    for (char c: s) t += c, t += '#';
5    int l = 0, r = 0, ans = 0; //l: mid, r: right
6    for (int i = 1; i < t.size(); ++i) {
7        z[i] = (r > i ? min(z[2 * l - i], r - i) : 1);
8        while (i - z[i] >= 0 && i + z[i] < t.size()) {
9            if (t[i - z[i]] == t[i + z[i]])
10                ++z[i];
11            else
12                break;
13        }
14        if (i + z[i] > r) r = i + z[i], l = i;
15    }
16    for (int i = 1; i < t.size(); ++i) ans = max(ans, z[i] - 1);
17    string res;
18    for (int i = 1; i < t.size(); ++i) if (ans == z[i] - 1) {
19        for (int j = i - ans + 1; j < i + ans; ++j) if (t[j] != '#'
20            res += t[j];
21        break;
22    }
23    return ans;
24}
25}

```

## 10 Tree

### 10.1 LCA

```

1int n, logn, t=0;
2vector<vector<int>> graph;
3vector<vector<int>> ancestor;
4vector<int> tin, tout;
5void dfs(int x) {
6    tin[x] = t++;
7    for (auto y: graph[x]) {
8        if (y != ancestor[x][0]) {
9            ancestor[y][0] = x;
10            dfs(y);
11        }
12    }
13    tout[x] = t++;
14}
15bool is_ancestor(int x, int y) {
16    return tin[x] <= tin[y] && tout[x] >= tout[y];
17}
18void table() {
19    for (int i=1; i<logn; i++) // 上 輩祖先、上四輩祖先、上八輩
20        祖先、.....
21        for (int x=0; x<n; ++x)
22            ancestor[x][i] = ancestor[ancestor[x][i-1]][i-1];
23}
24int kth_ancestor(int x, int k) {
25    for (int i=0; i<logn; i++) // k拆分成二進位位數，找到第k祖
26        先。不斷上升逼近之。
27        if (k & (1<<i))

```

```

27        x = ancestor[x][i];
28        return x;
29    }
30}
31void rooted_tree(int root) { // build the tree with root at "
32    root"
33    ancestor[root][0] = root;
34    dfs(root);
35    table();
36}
37int LCA(int x, int y) {
38    if (is_ancestor(x, y)) return x;
39    if (is_ancestor(y, x)) return y;
40    for (int i=logn-1; i>=0; i--)
41        if (!is_ancestor(ancestor[x][i], y))
42            x = ancestor[x][i];
43    return ancestor[x][0];
44}
45int main() {
46    graph = {
47        {1, 2},
48        {3},
49        {5, 6},
50        {7},
51        {},
52        {},
53        {8},
54        {4},
55    };
56    n = 9;
57    logn = ceil(log2(n));
58    ancestor.resize(n, vector<int>(logn));
59    tin.resize(n);
60    tout.resize(n);
61    rooted_tree(0);
62    while (true) {
63        int a, b;
64        cin >> a >> b;
65        cout << LCA(a, b) << endl;
66    }
67}
68}
69int main() {
70    n = 9;
71    logn = ceil(log2(n));
72    ancestor.resize(n, vector<int>(logn));
73    tin.resize(n);
74    tout.resize(n);
75    rooted_tree(0);
76    while (true) {
77        int a, b;
78        cin >> a >> b;
79        cout << LCA(a, b) << endl;
80    }
81}

```

### 10.2 Diameter

```

1vector<vector<int>> graph;
2int diameter = 0;
3int dfs(int start, int parent) {
4    int h1 = 0, h2 = 0;

```

```

5   for (auto child : graph[start]){
6       if (child != parent){
7           int h = dfs(child, start) + 1;
8           if (h > h1){
9               h2 = h1;
10              h1 = h;
11          }
12          else if (h > h2){
13              h2 = h;
14          }
15      }
16  }
17  diameter = max(diameter, h1 + h2);
18  return h1;
19 }
20 // call diameter
21 int main(){
22     dfs(0, -1);
23     cout << diameter<<endl;
24 }

```

### 10.3 Radius

```

1  // Perform DFS to find the farthest node and its distance
   from the given node
2  pair<int, int> dfs(int node, int distance, vector<bool> &
   visited, const vector<vector<int>> &adj_list){
3      visited[node] = true;
4      int max_distance = distance;
5      int farthest_node = node;
6
7      for (int neighbor : adj_list[node]){
8          if (!visited[neighbor]){
9              auto result = dfs(neighbor, distance + 1, visited
10                 , adj_list);
11              if (result.first > max_distance){
12                  max_distance = result.first;
13                  farthest_node = result.second;
14              }
15          }
16      }
17      return make_pair(max_distance, farthest_node);
18  }
19
20 // Calculate the radius of the tree using DFS
21 int tree_radius(const vector<vector<int>> &adj_list){
22     int num_nodes = adj_list.size();
23     vector<bool> visited(num_nodes, false);
24
25     // Find the farthest node from the root (node 0)
26     auto farthest_result = dfs(0, 0, visited, adj_list);
27
28     // Reset visited array
29     fill(visited.begin(), visited.end(), false);
30
31     // Calculate the distance from the farthest node
32     int radius = dfs(farthest_result.second, 0, visited,
33         adj_list).first;
34
35     return radius;
36 }
37 int main() {

```

```

37     vector<vector<int>> adj_list;
38     int radius = tree_radius(adj_list);
39     cout << "Tree radius: " << radius << endl;
40     return 0;
41 }

```

### 10.4 Spanning Tree

```

1  const int V = 100, E = 1000;
2  struct Edge {int a, b, c;} e[E]; // edge list
3  bool operator<(Edge e1, Edge e2) {return e1.c < e2.c;}
4
5  int p[V];
6  void init() {for (int i=0; i<V; ++i) p[i] = i;}
7  int find(int x) {return x == p[x] ? x : (p[x] = find(p[x]));}
8  void merge(int x, int y) {p[find(x)] = find(y);}
9
10 void Kruskal() {
11     init();
12     sort(e, e+E);
13     int i, j;
14     for (i = 0, j = 0; i < V-1 && j < E; ++i){
15         while (find(e[j].a) == find(e[j].b)) j++;
16         merge(e[j].a, e[j].b);
17         cout << "起點: " << e[j].a << "終點: " << e[j].b << "權重: "
18             << e[j].c;
19         j++;
20     }
21     if (i == V-1) cout << "得到最小生成樹";
22     else cout << "得到最小生成森 ";
23 }

```

NYCU\_Segmenttree  
Codebook

# Contents

1	Dp	1
1.1	01_knapsack . . . . .	1
1.2	Josephus . . . . .	1
1.3	Bitmask . . . . .	1
1.4	InfinittKnapsack . . . . .	1
2	Data Structure	1
2.1	DSU . . . . .	1
2.2	Monotonic Queue . . . . .	1
2.3	BIT . . . . .	1
2.4	Treap . . . . .	2
2.5	Segment Tree . . . . .	2
2.6	Sparse Table . . . . .	3
2.7	Monotonic Stack . . . . .	3
3	Flow	3
3.1	Maximum Simple Graph Matching .	3
3.2	Dinic . . . . .	4
4	Formula	4
4.1	formula . . . . .	4
4.1.1	Pick 公式 . . . . .	4
4.1.2	圖論 . . . . .	4
4.1.3	dinic 特殊圖複雜度 . . . . .	4
4.1.4	0-1 分數規劃 . . . . .	4

4.1.5	學長公式	4
4.1.6	基本數論	5
4.1.7	排組公式	5
4.1.8	冪次, 冪次和	5
4.1.9	Burnside's lemma	5
4.1.10	Count on a tree	5
5	Geometry	5
5.1	Sort by Angle	5
5.2	Geometry	5
5.3	Convex Hull	8
5.4	Min Covering Circle	8
5.5	Point in Polygon	8
6	Graph	8
6.1	Bipartite Matching	8
6.2	Tarjan SCC	9
6.3	Bridge	9
6.4	2 SAT	9
6.5	Kosaraju 2DFS	10
6.6	Minimum Steiner Tree	10
6.7	Dijkstra	10
6.8	Maximum Clique Dyn	11
6.9	Minimum Clique Cover	11
6.10	Floyd Warshall	11
6.11	Articulation Vertex	11
6.12	Number of Maximal Clique	12
6.13	Dominator Tree	12
6.14	Topological Sort	12
6.15	Closest Pair	12
6.16	Minimum Mean Cycle	12
6.17	Planar	13
6.18	Heavy Light Decomposition	13
6.19	Centroid Decomposition	13

6.20	KM_O . . . . .	13
6.21	Minimum Arborescence . . . . .	14
6.22	Maximum Clique . . . . .	14
<b>7</b>	<b>Math</b>	<b>14</b>
7.1	Miller Robin . . . . .	14
7.2	fpow . . . . .	15
7.3	Big Number . . . . .	15
7.4	modinv . . . . .	15
7.5	Matrix . . . . .	15
7.6	PollardRho . . . . .	16
7.7	Euler Totient Function . . . . .	16
7.8	extGCD . . . . .	16
7.9	random . . . . .	16
7.10	FFT . . . . .	16
7.11	mu . . . . .	16
7.12	Chinese Remainder . . . . .	17
<b>8</b>	<b>Misc</b>	<b>17</b>
8.1	Mo's Algorithm . . . . .	17
8.2	pbds . . . . .	17
8.3	Misc . . . . .	17
<b>9</b>	<b>String</b>	<b>17</b>
9.1	Hashing . . . . .	17
9.2	Trie . . . . .	17
9.3	Zvalue . . . . .	18
9.4	KMP . . . . .	18
9.5	Manacher . . . . .	18
<b>10</b>	<b>Tree</b>	<b>18</b>
10.1	LCA . . . . .	18
10.2	Diameter . . . . .	18
10.3	Radius . . . . .	19
10.4	Spanning Tree . . . . .	19