

Advancing image security and compliance through Container Image Encryption!


Brandon Lum, IBM



Contents

- Container Image Security
- OCI Container Image Encryption
- End-to-end demo, build, distribute, run!
- Advanced Compliance usecase: Geo-fencing

Container Image Security



📄 **MUST READ:** Don't let cyber security be driven by fear, warns NCSC chief

Docker Hub hack exposed data of 190,000 users

Docker Hub usernames, hashed passwords, GitHub and Bitbucket access tokens exposed in the hack.



By [Catalin Cimpanu](#) for [Zero Day](#) | April 27, 2019 -- 09:11 GMT (02:11 PDT) | Topic: [Security](#)

Recommended Content:

White Papers: Illustrated Guide to Container Security

Download this Illustrated Guide to Container Security that provides visuals and easy-to-digest diagrams that answer questions about cloud security. ...

[Learn More](#)


RECOMMENDED FOR YOU

Illustrated Guide to Container Security

White Papers provided by [Aqua Security](#)


[LEARN MORE](#)

Container Image Security



- Registries and Cloud may be compromised/untrusted
- Compliance perspective: some of these services in between are not auditable

What does this mean for your images?



RedHat Signing


Image Signing will ensure the integrity of your deployment images! *Technologies: Docker Content Trust (DCT) or RedHat Simple Signing*

But...

Private Images' sensitive content will be exposed!



Container Image Encryption



Build

- Build as normal
- **Encrypt**
- Push



Encrypt

- Encrypted image stored
- Cannot be read




Run

- Pull
- **Decrypt**
- Run



Benefits?

- Image Confidentiality & Deprivileged Registry
- Execution Boundary Control
 - ***“If my code is running, I know it’s in my cluster”***
 - Encrypted Containers Images + Key management could provide guarantees about where an image can run.
 - i.e. Image X can only run in the EU nodes.

Encryption Primer



Encryption Primer - Assym Enc.



Each user has a Public-Private key pair, where Public Key is not secret, can be published.

Bob


sends an encrypted image to

Alice

- 1 Alice creates an RSA private/public keypair, publishing her public key





```
openssl genrsa -out alicePrivate.pem 2048  
openssl rsa -in alicePrivate.pem -pubout ...
```




- 2 Bob encrypts his image and pushes it to the registry

```
buildah push --encryption- alicePublic.pem ...
```



- 3 Alice pulls and decrypts the image with her private key




Simple Encrypt/Decrypt Demo

OCI Spec Details

OCI Spec



OCI Spec +encrypted






*+enc = +encrypted abbreviated

*org..enc.keys annotations represent encryption metadata

Container Encryption Features

- Encrypt on layers means images can still benefit from deduplication of non-sensitive layers
- Encrypt once for multiple recipients. Registry deduplication on large encrypted data blob.






Bob

sends an encrypted image to

Alice





Bob

sends an encrypted image to

Alice



I want to run these images on my
Kubernetes cluster!

Bob


sends an encrypted image to

Alice

- 1 Alice creates an RSA private/public keypair, publishing her public key




```
openssl genrsa -out alicePrivate.pem 2048  
openssl rsa -in alicePrivate.pem -pubout ...
```



- 2 Bob encrypts his image and pushes it to the registry


```
buildah push --encryption- alicePublic.pem ...
```




+



=



+



=



Alice's k8s cluster

- 3 ~~Alice~~ pulls and decrypts the image with her private key

Adding Decryption to K8s Nodes

How is decryption done in k8s?

- Decryption is done when image is pulled by the container runtime, i.e. containerd/cri-o
- Configuration is on the node level


Runtime

cri-o
containerd

Key Location


/etc/crio/keys
<set in config.toml>

- Alice configures the nodes in the Kubernetes cluster with the private key for decryption
- The encrypted image is pulled from the registry and decrypted with the private key provided




Cluster Decryption Demo

Adding Decryption to K8s Nodes




Adding Decryption to K8s Nodes



Decryption keys can be protected behind cluster authorization

- Proof stemming from cluster CA
- Proof stemming from hardware root of trust attestation


Geofencing Execution




Summary

- Encrypted Container Images can be used for confidentiality of images
- With key management, can create geofencing based policies
- Encrypted Container Images is supported today in:
 - Runtimes: Containerd, Cri-o
 - Build Tools: Buildah, Skopeo
 - Registries: Docker Distribution
- **Call for contribution!**
 - Build Tools: kaniko, docker CLI
 - Registries: Quay

Encryption Primer




Encryption Primer - Assym Enc.



Addresses key sharing: Each user has a Public-Private key pair, where Public Key is not secret, can be published.

903nsvlvn391x
kshu9282jks91
0alfde=

+



=

This is a secret message.



Slow

Encryption Primer - Symm Enc.





Fast, good for large data





Key needs to be securely shared somehow



Encrypt and distribution flow




Encrypt and distribution flow




Encrypt and distribution flow



Encrypt and distribution flow



Encrypt and distribution flow



Encrypt and distribution flow

