

1. Test your neighbor.

What is the C preprocessor? Give 3 examples of its use in a .c file

When is sizeof evaluated?

What would be a good name for the following macro? What must be true for A?

```
#define NAME(A)    sizeof(A) / sizeof(A[0])
```

2. Complete the following code to return 1 if the c string contains @ character, 0 otherwise.

Where will the code crash if called with NULL  
containsAt(NULL);

```
01 int containsAt(char* ptr) {  
02  
03  
04  
05  
06  
07  
08
```

3. Explain how C uses memory from the process address space in each line of the following. (eg. stack, text segment, heap, global).  
Where do you expect this code to fail?

```
01 int global;  
02  
03 void test() {  
04     char* t1 = "hi";  
05     char t2[] = "ab";  
06  
07     *t2 = 'A';  
08     *(t2 + 1) = 'B';  
09     t2[1] = 'B';  
10     *t1 = 'H';  
11     t1 = malloc(123);  
12 }
```

4. Why is this code broken?

```
01 #define max(a,b) a<b ? a : b  
02 int result = max(10,5) + 1;  
03 printf("Result:%d", result);
```

5. Spot the error(s)

```
01 double* f1(int n) {  
02     int i;  
03     double* r = malloc( n* sizeof (double*) );  
04     while( i < n) r[i++] = 12.3;  
05     return r;  
06 }
```

6. Is the following line valid?

```
printf("%p %p", main, malloc);
```

7. Pointer arithmetic

Write a function to return the number of items in an int array before a value of -1 is found. Tricky: Use pointer arithmetic (no counters allowed!)

```
01 count_before(int* array) {  
02     int* ptr = array;
```

8. What would you call at line 2 such that p1 can be equal to p2?

```
01 void* p1 = malloc( 10 );  
02 ??_____  
03 void *p2 = malloc(8);
```

## 9 When are `sprintf` and `fprintf` useful?

---

### 10. For the start of the program, `main(int argc, char** argv)`

What is special about `argv[0]`

What is special about `argv[argc]`

How do you print out all of the arguments of a program?

```
01 int main(int argc, char** argv) {
02
```

---

### 11. Which of the following would print out an address in the stack?

```
01 int abc = 5;
02
03 int main() { f1( 10, &abc); return 0;}
04
05 int f1(int v1, int* v2) {
06     printf("%p", &v1);
07
08     printf("%p", &v2);
09
10     printf("%p", v2);
11 }
```

---

### 12. Can you write examples of using `strcpy`, `strcat`, `strlen`, `strcmp`?

## 13. Which of the following is incorrect? Can you fix it?

```
01 const char* f1() {
02     const char blah[] = "Hello";
03     return blah;
04 }
05
06 const char* f2() {
07     const char* foo = "Hi";
08     return foo;
09 }
10
11 const char* f3() {
12     const char* yo = malloc(2);
13     strcat(yo, "Hi");
14     return yo;
15 }
```

---

### 14. How do I change your variable? Complete the main function to print the message created by the `getMessage` function

```
01 int main() {
02     ?
03
04     puts( _____);
05 }
06 void getMessage(char**mesg) {
07     *mesg = malloc(10);
08     strcpy(*mesg, "I C!");
09 }
```