Customization Guide

A friendly, beginner-oriented map of this portfolio site. For each thing you might want to change, this guide tells you **which file to open**, **where to look inside it**, and **what to change**.

Table of contents

1. The big picture
2. Running the site
3. The most important file: `src/data.js`
4. The Home page (hero, song card, metrics)
5. The About page (bio, profile photo, stat cards)
6. The Resume page (skills, experience, education)
7. The Projects page
8. The Contact page (form)
9. The Navbar
10. The Command Palette (Cmd-K menu)
11. Global styles, colors, and fonts
12. Scroll-fade animations (`<Reveal>`)
13. Images, PDFs, and other assets
14. Site title, favicon, and social preview
15. Adding a brand-new page
16. The ocean background
17. Deployment (GitHub Pages)

---

1. The big picture

The site is built with **React** (a JavaScript UI library) and **Vite** (the build tool that turns your code into something a browser can run).

Top-level layout of the project:

```
portfolio-v2/
├── index.html              ← page title, favicon, social preview tags
├── package.json            ← list of dependencies + scripts
├── vite.config.js          ← build config (incl. GitHub Pages base path)
├── public/                 ← static files served as-is (resume PDF,
images)
└── src/
    ├── main.jsx            ← React entry point (rarely edited)
    ├── App.jsx             ← which page shows for which tab
    ├── App.css             ← navbar styles + page transition
    ├── index.css           ← global styles, colors, fonts
    ├── data.js             ← ★ all the text content of the site
    ├── assets/             ← images imported into components (profile,
```

```
song)
    ├── components/         ← reusable UI pieces (Navbar, OceanHero, etc.)
    ├── hooks/              ← custom React hooks (currently just
useReveal)
    └── pages/              ← one file per page (Home, About, Resume, …)
```

Rule of thumb:

- Want to **change words**? Open `src/data.js` first.
- Want to **change layout or styling**? Open the matching `.css` file in `src/pages/`.
- Want to **change behavior**? Open the matching `.jsx` file in `src/pages/` or `src/components/`.

---

2. Running the site

Open Terminal, `cd` into the project, and run:

```
npm install        # one time only — installs dependencies
npm run dev        # start the dev server (usually http://localhost:5173)
npm run build      # build the production version into dist/
npm run preview    # preview the built version locally
```

While `npm run dev` is running, every save you make hot-reloads the browser instantly.

---

3. The most important file: `src/data.js`

This file is the **source of truth for almost all the words on the site**. Almost every page imports from it. Editing data here is the easiest way to update the site without touching component code.

Here is what each export controls:

Export	Where it shows up	What it controls
`METRICS`	Home page bottom strip	The "Projects / Core Stacks / Years Building" boxes
`ABOUT_PARTS`	About page	The three labeled paragraphs (building / outside of code / goal)
`ABOUT_STATS`	About page	The grid of small fact cards (Location, University, Age, …)
`SKILL_GROUPS`	Resume page	Skill chips, grouped by Languages / Frameworks / Databases / Tools
`EXPERIENCE`	Resume page	Job entries in the timeline
`EDUCATION`	Resume page	School entries in the timeline
`PROJECTS`	Projects page	Each project card

> Some exports (`PARTICLES`, `CODE_SNIPPETS`, `TERMINAL_LINES`, `NAME_LETTERS`, `PORTFOLIO_NARRATIVE`, `RESUME_SKILL_HIGHLIGHTS`, `CURRENTLY_BUILDING`, `RADAR_SKILLS`) exist but **aren't currently used** on any page. Safe to leave alone or delete.

Examples

To change a metric on the home page, edit `METRICS`:

```
export const METRICS = [
  { label: "Projects",       value: "8" },     // bumped from 7 → 8
  { label: "Core Stacks",    value: "3" },
  { label: "Years Building", value: "3+" }
];
```

To add a new job to the resume, push a new object into `EXPERIENCE`:

```
{
  title: "Software Engineering Intern",
  org: "Some Company",
  location: "Remote",
  dates: "May 2027 – August 2027",
  bullets: [
    "Shipped feature X used by 10k users.",
    "Reduced API latency by 30%."
  ]
}
```

To add a new project, push a new object into `PROJECTS`:

```
{
  title: "MyNewApp",
  description: "One-sentence pitch of what it is.",
  link: "https://github.com/yourname/MyNewApp", // optional
  status: "WIP",                                // optional badge
  stack: ["React", "TypeScript", "Node.js"],
  outcomes: [                                    // optional bullet list
    "Did one impressive thing.",
    "Did another impressive thing."
  ]
}
```

> **Tip:** Anything marked "optional" can be omitted entirely — the card will simply hide that piece.

---

4. The Home page

File: `src/pages/Home.jsx` · **Styles:** `src/pages/Home.css`

The home page has four parts:

1. The **animated ocean background** (`<OceanHero />`)
2. A **dark gradient overlay** (so text stays readable)
3. The **left column**: cycling label, name, bio, buttons, social icons
4. The **right column**: the "current favorite" song card
5. The **bottom strip**: metrics from `data.js`

Change your name or bio

In `Home.jsx`, look for the `<h1 className="home-name">` block (around line 86) and the `<p className="home-bio">` block (around line 90). Edit the text directly.

Change the cycling words ("full-stack developer", "cs student", …)

In `Home.jsx`, edit the `PHRASES` array near the top:

```
const PHRASES = [
  "full-stack developer",
  "cs student",
  "problem solver",
  "builder",
];
```

To slow down or speed up the cycle, change the `3000` (milliseconds) inside `setInterval` in `CyclingLabel`.

Change the buttons (resume download, view projects)

In `Home.jsx`, find `<div className="home-buttons">`. The first button downloads `/roger-torres-resume.pdf` from the `public/` folder. The second button switches to the projects tab via `window.setActiveSection("projects")`.

Change the social links

In `Home.jsx`, find `<div className="home-socials">`. Each `<a>` is one icon. Update the `href` (URL) and the icon class inside `<i>` (e.g. `fab fa-github`, `fab fa-linkedin-in`, `fas fa-envelope`).

Change the "current favorite" song

In `Home.jsx`, edit the `SONG` object near the top:

```
const SONG = {
  title: "Hotel in Minsk",
  artist: "jonatan leandoer96",
  url: "https://open.spotify.com/track/4cOdK2wGLETKBW3PvgPWqT"
};
```

To change the album art, replace `src/assets/hotel-in-minsk.png` with a new image, then update the import line at the top of `Home.jsx`:

```
import albumArt from "../assets/your-new-art.png";
```

The Spotify-green accent color and the bouncing equalizer bars come from `Home.css` — search for `.song-card` and `song-eq-bounce`.

Change the bottom-strip metrics

These come from `METRICS` in `src/data.js` (see section 3).

---

5. The About page

File: `src/pages/About.jsx` · **Styles:** `src/pages/About.css`

The page has three sections: the heading, your **profile photo**, three labeled **paragraphs**, and a grid of small **stat cards**.

Change the bio paragraphs

Edit `ABOUT_PARTS` in `src/data.js`. Each entry has a `label` (the small uppercase tag) and `text` (the paragraph).

Change the stat cards

Edit `ABOUT_STATS` in `src/data.js`. Each entry has:

- `icon` — a Font Awesome class name (e.g. `"fas fa-map-marker-alt"`). Browse icons at fontawesome.com/icons.
- `value` — the big text (e.g. `"Pittsburgh, PA"`)
- `label` — the small uppercase tag underneath (e.g. `"Location"`)

Change the profile photo

Replace `src/assets/profile.jpeg` with a new image (any common format works — `.jpg`, `.png`, `.webp`). If you change the filename or extension, update the import in `About.jsx`:

```
import profilePhoto from "../assets/profile.jpeg";  // ← match this to
your file
```

Change the photo size or border color

In `About.css`, find `.about-photo` (line 27). Adjust:

- `width` and `height` — diameter of the circle (currently `180px`)
- `border` — accent ring around the photo

- `box-shadow` — outer glow

The mobile-screen size is set separately at the bottom of the file (`@media (max-width: 480px)`, currently `96px`).

---

6. The Resume page

File: `src/pages/Resume.jsx` · **Styles:** `src/pages/Resume.css`

The page renders three sections — Skills, Experience, Education — all from `src/data.js`.

Add or remove a skill

Edit `SKILL_GROUPS` in `src/data.js`. Add a string to the `items` array of any group:

```
{
  title: "Languages",
  icon: "fas fa-code",
  items: ["Java", "Python", "C++", "JavaScript", "TypeScript", "HTML",
"CSS", "Rust"]
  //
^^^^^^ added
}
```

Add a colored tech-logo icon next to a skill

Skills get small colored logos via the **devicons** library. The mapping lives at the top of `Resume.jsx`:

```
const DEVICONS = {
  "Java":      "devicon-java-plain",
  "Python":    "devicon-python-plain",
  // ...
};
```

If you add a new skill (e.g. "Rust") and want an icon, add a line:

```
"Rust": "devicon-rust-plain",
```

Browse names at devicon.dev. Skills not in this map simply render with no icon — the chip still works.

Add a new skill *group*

Add a whole new object to `SKILL_GROUPS` in `data.js`:

```
{
  title: "Cloud",
  icon: "fas fa-cloud",
  items: ["AWS", "GCP", "Vercel"]
}
```

Add an experience entry

Push a new object onto `EXPERIENCE` in `data.js`. See section 3 for the shape.

Add an education entry

Same idea, but push into `EDUCATION`. The fields are: `school`, `location`, `dates`, `detail`, `bullets` (an array — pass `[]` if none).

---

7. The Projects page

File: `src/pages/Projects.jsx` · **Styles:** `src/pages/Projects.css`

Cards are rendered from `PROJECTS` in `src/data.js`. Each card supports these fields:

Field	Required	What it does
`title`	yes	The card heading
`description`	yes	The paragraph under the title
`stack`	yes	Array of strings — shown as small chips
`link`	no	If present, shows a "View on GitHub" link at the bottom
`status`	no	If present, shows a small badge (e.g. `"WIP"`) next to the title
`outcomes`	no	Array of strings — shown as a bullet list
`image`	no	Filename in `public/` (e.g. `"queued-preview.jpg"`) — shown at top of card
`imageAlt`	no	Alt text for that image

Add a project preview image

1. Drop the image into `public/` (e.g. `public/myproject-preview.jpg`)
2. Add `image: "myproject-preview.jpg"` to that project's entry in `data.js`
3. Optionally `imageAlt: "Screenshot of MyProject"`

Change card layout (1 column vs 2)

In `Projects.css`:

```
.projects-grid {
  display: grid;
  grid-template-columns: repeat(2, 1fr);  /* ← 2 columns on desktop */
}

@media (max-width: 700px) {
  .projects-grid {
    grid-template-columns: 1fr;            /* ← 1 column on small screens
*/
  }
}
```

Tweak the hover tilt effect

In `Projects.jsx`, look at `onMove` (around line 31). The `* 8` numbers control how much the card tilts in degrees:

```
card.style.transform =
  `perspective(600px) rotateY(${x * 8}deg) rotateX(${-y * 8}deg)`;
```

Lower the `8` for a subtler tilt; raise it for more drama. Set both to `0` to disable.

---

8. The Contact page

File: `src/pages/Contact.jsx` · **Styles:** `src/pages/Contact.css`

The form is wired up to **Formspree** (a free service that emails you whatever the user submits — no backend needed).

Change where messages go

At the top of `Contact.jsx`:

```
const FORMSPREE = "https://formspree.io/f/xvzppbqj";
```

Sign up at formspree.io, create a new form, and replace the URL.

Add or remove form fields

Each field is wrapped in a `<Reveal className="contact-row">` block. Copy one of the existing rows and change three things: the `id`, the `name`, and the label text. Example — adding a "Company" field:

```
<Reveal className="contact-row" delay={150}>
  <label className="contact-label" htmlFor="c-company">Company</label>
  <input
```

```
      id="c-company"
      name="company"
      type="text"
      className="contact-input"
      placeholder="Where do you work?"
    />
  </Reveal>
```

Change the success/error messages

Edit the text inside the `<div className="contact-feedback contact-success">` and `contact-error` blocks.

---

9. The Navbar

File: `src/components/Navbar.jsx` · **Styles:** `src/App.css` (the `.navbar*` rules)

Rename the brand text

In `Navbar.jsx`, line 21:

```
<span className="navbar-brand">roger torres</span>
```

Rename the navigation links

The labels live in the `LINKS` array at the top of `Navbar.jsx`:

```
const LINKS = [
  { id: "home",     label: "~/home" },
  { id: "about",    label: "~/about" },
  // ...
];
```

The `id` must match a section in `App.jsx` (see adding a page below). The `label` is just visual.

Change desktop vs mobile behavior

The mobile hamburger menu kicks in at 768px. To change that breakpoint, edit the `@media (max-width: 768px)` block near the bottom of `App.css`.

---

10. The Command Palette

File: `src/components/CommandPalette.jsx` · **Styles:** `src/components/CommandPalette.css`

A searchable popup that opens with **Cmd-K** (or **Ctrl-K**).

Add a new command

Edit the `COMMANDS` array at the top of `CommandPalette.jsx`. Each entry is one line:

```
{
  id: "blog",
  icon: "fas fa-pen-nib",
  label: "Open Blog",
  group: "Links",
  action: () => window.open("https://yourblog.com", "_blank")
}
```

The `action` is just a function — it runs when the user picks the command.

Change the keyboard shortcut

Search for `e.key === "k"` in `CommandPalette.jsx` (line 36) and change `"k"` to your preferred letter.

---

11. Global styles, colors, and fonts

File: `src/index.css`

Colors and fonts are defined as **CSS variables** at the top of this file:

```
:root {
  --bg: #0a0a0a;                    /* page background */
  --text: #e5e5e5;                   /* primary text */
  --text-muted: #888;                /* secondary text */
  --text-subtle: #555;               /* tertiary text */
  --accent: #7aa2f7;                 /* the blue accent everywhere */
  --accent-rgb: 122, 162, 247;       /* same color in RGB (used for
transparency) */
  --font-sans: "Inter", system-ui, …;
  --font-mono: "Share Tech Mono", …;
}
```

Change the accent color

Update both `--accent` (the hex code) AND `--accent-rgb` (the same color in `r, g, b` form). Both must match — the RGB version is used for translucent backgrounds (like `rgba(var(--accent-rgb), 0.1)`).

Example, switching to a green accent:

```
--accent: #4ade80;
--accent-rgb: 74, 222, 128;
```

Change a font

`--font-sans` and `--font-mono` are loaded from Google Fonts via the `@import` line at the very top of `index.css`. To use a different font:

1. Pick a font on fonts.google.com
2. Replace the `@import url(…)` line with the one Google gives you
3. Update `--font-sans` (or `--font-mono`) to use the new font name

Change page padding (whitespace around content)

Each page sets its own padding. Look for the `.page-home`, `.page-about`, `.page-resume`, `.page-projects`, `.page-contact` rules in their respective CSS files.

---

12. Scroll-fade animations

Files: `src/components/Reveal.jsx` and `src/hooks/useReveal.js`

Most elements fade in and slide up as you scroll. They're wrapped in `<Reveal>`:

```
<Reveal delay={100}>...</Reveal>
```

- `delay` (milliseconds) staggers the animation when you have a list.
- `as="div"` (default) controls what HTML tag is rendered — change to `as="img"`, `as="button"`, etc.
- All other props (like `className`, `src`, `href`) pass through to the underlying element.

The animation itself is defined in `src/index.css`:

```
.reveal {
  opacity: 0;
  transform: translateY(20px);
  transition: opacity 400ms ease-out, transform 400ms ease-out;
}
.reveal-in {
  opacity: 1;
  transform: none;
}
```

To make the slide bigger, change `translateY(20px)` to `translateY(40px)`. To make it slower, change `400ms` to `600ms`.

The system automatically respects users who prefer reduced motion (the `@media (prefers-reduced-motion: reduce)` block) — no action needed.

---

13. Images, PDFs, and other assets

There are **two places** to put files, and they behave differently:

`public/` — for files referenced by URL

Files here are served as-is at the site root. Use this for:

- The resume PDF (`public/roger-torres-resume.pdf`)
- The favicon (`public/favicon.svg`)
- Project preview images referenced by name in `data.js` (`public/queued-preview.jpg`)
- The water normal-map texture used by the ocean (`public/waternormals.jpg`)

To reference one in code, write `/filename.ext` (e.g. `/roger-torres-resume.pdf`). For files loaded inside a Three.js scene, the code uses `${import.meta.env.BASE_URL}filename` — that part handles the GitHub Pages base path automatically.

`src/assets/` — for files imported into React components

Files here are processed by Vite (hashed for caching, optimized). Use this for things imported at the top of a component:

```
import profilePhoto from "../assets/profile.jpeg";
import albumArt    from "../assets/hotel-in-minsk.png";
```

Then use the variable as the `src`:

```
<img src={profilePhoto} alt="..." />
```

Replacing the resume PDF

Drop your new PDF into `public/`, name it `roger-torres-resume.pdf` (or update the references in `Home.jsx` and `CommandPalette.jsx` to match a new filename).

Unused assets you can delete

- `src/assets/rayquaza.glb` — leftover from an earlier hero (no longer used)
- `src/components/GlobeHero.jsx` — old hero component, replaced by `OceanHero`
- `src/assets/hotel-in-minsk.jpg` — superseded by the `.png` version

---

14. Site title, favicon, and social preview

File: `index.html` (at the project root, NOT inside `src/`)

This is the HTML wrapper that loads your React app. Edit:

- `<title>` — the text in the browser tab
- `<meta name="description">` — the snippet that appears in Google search results

- `<meta property="og:title">` and `og:description` — what shows when someone shares your site on Twitter, LinkedIn, iMessage, Slack, etc.
- `<link rel="icon" href="/favicon.svg" />` — the tab icon (replace `public/favicon.svg`)
- `<meta name="theme-color">` — the address-bar tint on mobile

---

15. Adding a brand-new page

Say you want to add a page called **Blog**. You need to touch four files:

Step 1 — Create the page component

Create `src/pages/Blog.jsx`:

```
import "./Blog.css";

export default function Blog() {
  return (
    <section className="page-section page-blog">
      <h2 className="blog-heading">blog</h2>
      <p>Coming soon.</p>
    </section>
  );
}
```

And `src/pages/Blog.css` (copy structure from another page's CSS):

```
.page-blog {
  display: flex;
  flex-direction: column;
  padding: 48px 3rem 3rem;
  max-width: 820px;
  margin: 0 auto;
}

.blog-heading {
  font-family: var(--font-sans);
  font-weight: 500;
  font-size: clamp(32px, 5vw, 48px);
  color: var(--text);
  padding-top: 2rem;
}
```

Step 2 — Register the page in `App.jsx`

```
import Blog from "./pages/Blog.jsx";
```

```
const SECTIONS = ["home", "about", "resume", "projects", "blog",
"contact"];
//                                                        ^^^^^^^

const PAGES = {
  home: Home,
  about: About,
  resume: Resume,
  projects: Projects,
  blog: Blog,        // ← added
  contact: Contact,
};
```

Step 3 — Add the link to the navbar

In `src/components/Navbar.jsx`, add a row to `LINKS`:

```
const LINKS = [
  { id: "home",     label: "~/home" },
  { id: "about",    label: "~/about" },
  { id: "resume",   label: "~/resume" },
  { id: "projects", label: "~/projects" },
  { id: "blog",     label: "~/blog" },     // ← added
  { id: "contact",  label: "~/contact" },
];
```

Step 4 (optional) — Add it to the Cmd-K palette

In `src/components/CommandPalette.jsx`, add an entry to `COMMANDS`:

```
{
  id: "blog",
  icon: "fas fa-pen-nib",
  label: "Go to Blog",
  group: "Navigate",
  action: () => window.setActiveSection?.("blog")
}
```

That's it — the page is now reachable via the navbar, the URL hash (`#blog`), and the command palette.

---

16. The ocean background

File: `src/components/OceanHero.jsx` · Used by `src/pages/Home.jsx`

This is the animated ocean behind the home hero. It uses **Three.js** (a 3D library) with the `Water` and `Sky` examples.

A few knobs you can turn near the top of the file:

- `toneMappingExposure = 0.5` — overall brightness. Higher = brighter.
- `Sky` `turbidity`, `rayleigh`, `mieCoefficient`, `mieDirectionalG` — sky atmosphere. The current values give a moody dusk look.
- `phi = degToRad(90 - 2)` — sun height (the `2` is the elevation angle in degrees). Bigger numbers raise the sun (brighter sky).
- `Water` options: `sunColor` (hex), `waterColor` (hex), `distortionScale` (wave roughness).
- `scene.fog = new THREE.Fog(0x1a2030, 120, 1500)` — the haze over distant waves.

If WebGL isn't available, the component falls back to a plain dark background (`.ocean-fallback`), styled in `Home.css`.

The water-normal texture (`public/waternormals.jpg`) is what makes the wave surface look textured — don't delete it.

---

17. Deployment (GitHub Pages)

The site is configured to deploy at a subpath, set in `vite.config.js`:

```
export default defineConfig({
  base: '/Personal-Website-/',
  plugins: [react()],
})
```

This means the built site expects to live at `https://yourname.github.io/Personal-Website-/`. If you rename the GitHub repo, change the `base` value to match the new repo name (keep the leading and trailing slashes).

If you ever move the site to a custom domain or to the root of GitHub Pages, change `base` to `'/'`.

To build for production:

```
npm run build
```

This produces a `dist/` folder. GitHub Actions (already set up in this repo) handles the deployment when you push to `main`.

Quick "where do I edit X" cheat sheet

I want to change…	Open this file
Any text on Home, About, Resume, or Projects	`src/data.js`
The cycling phrases on the home page	`src/pages/Home.jsx` (top, `PHRASES`)

I want to change…	Open this file
The current favorite song	`src/pages/Home.jsx` (top, `SONG`)
Profile photo	Replace `src/assets/profile.jpeg`
Resume PDF	Replace `public/roger-torres-resume.pdf`
The accent color	`src/index.css` (`--accent` and `--accent-rgb`)
The fonts	`src/index.css` (top `@import` + `--font-sans` / `--font-mono`)
Navigation labels	`src/components/Navbar.jsx` (`LINKS`)
Cmd-K commands	`src/components/CommandPalette.jsx` (`COMMANDS`)
Where contact form sends	`src/pages/Contact.jsx` (`FORMSPREE`)
The browser tab title	`index.html` (`<title>`)
The ocean look	`src/components/OceanHero.jsx`
GitHub Pages URL path	`vite.config.js` (`base`)