

CSIT881

Programming and Data Structures

Dictionary



UNIVERSITY
OF WOLLONGONG
AUSTRALIA

Objectives

- Dictionary
- Problem solving with Dictionary

Dictionary

used to store key-value pairs

```
empty = {} # this is an empty dictionary
```

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
} # information about a person
```

```
state_abb = {  
    "NSW": "New South Wales",  
    "ACT": "Australian Capital Territory",  
    "NT": "Northern Territory",  
    "QLD": "Queensland",  
    "SA": "South Australia",  
    "TAS": "Tasmania",  
    "VIC": "Victoria",  
    "WA": "Western Australia"  
} # Australian state abbreviations
```

Dictionary

Two main purposes:

- Grouping data together (like class/object)

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

- Mapping

```
state_abb = {  
    "NSW": "New South Wales",  
    "ACT": "Australian Capital Territory",  
    "NT": "Northern Territory",  
    "QLD": "Queensland",  
    "SA": "South Australia",  
    "TAS": "Tasmania",  
    "VIC": "Victoria",  
    "WA": "Western Australia"  
}
```

Dictionary

- Mapping

```
digit_to_word = {  
    0: "zero",  
    1: "one",  
    2: "two",  
    3: "three",  
    4: "four",  
    5: "five",  
    6: "six",  
    7: "seven",  
    8: "eight",  
    9: "nine"  
}
```

Dictionary

- Mapping

```
word_to_digit = {  
    "zero": 0,  
    "one": 1,  
    "two": 2,  
    "three": 3,  
    "four": 4,  
    "five": 5,  
    "six": 6,  
    "seven": 7,  
    "eight": 8,  
    "nine": 9  
}
```

Dictionary

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

using function `print` to print out the whole dictionary

```
print(person)
```

Dictionary - **get value**

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

Values can be retrieved using function **get** with the corresponding keys:

```
first_name = person.get("first_name")    → "Amanda"
```

```
last_name = person.get("last_name")      → "Smith"
```

```
age = person.get("age")                  → 20
```

```
address = person.get("address")          → None
```


None

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

In Python, **None** is equivalent to **null** in other programming languages:

```
email = person.get("email")           # → None
```

```
if (email is None):  
    print("User has no email")  
else:  
    print("User email is " + email)
```

Dictionary - get value with default value

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

We can specify a **default value** in the function `get` if the key-value pair is not found:

```
std_type = person.get("student_type", "N/A")    # → "N/A"  
credit_point = person.get("credit_point", 0)    # → 0
```

Dictionary - get value

```
digit_to_word = {  
    0: "zero",  
    1: "one",  
    2: "two",  
    3: "three",  
    4: "four",  
    5: "five",  
    6: "six",  
    7: "seven",  
    8: "eight",  
    9: "nine"  
}  
  
print(digit_to_word.get(7))
```

Dictionary - get value

```
word_to_digit = {  
    "zero": 0,  
    "one": 1,  
    "two": 2,  
    "three": 3,  
    "four": 4,  
    "five": 5,  
    "six": 6,  
    "seven": 7,  
    "eight": 8,  
    "nine": 9  
}
```

```
print(word_to_digit.get("eight"))
```

Dictionary - update values

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

we can change the existing values:

```
person["first_name"] = "Mandy"  
person["last_name"] = "Jones"  
person["age"] = 24
```

Dictionary - add new key-value

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

we can add new key-value pair:

```
person["email"] = "Mandy.Jones@gmail.com"  
person["gpa_score"] = 3.5
```

Dictionary - delete key-value

```
person = {  
    "first_name": "Mandy",  
    "last_name": "Jones",  
    "age": 24,  
    "email": "Mandy.Jones@gmail.com"  
}
```

we can delete a key-value pair:

```
del person["email"]
```

we can delete **all** key-value pairs, the dictionary becomes empty:

```
person.clear()
```

Dictionary - get all keys

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

We can get the list of all keys:

```
all_keys = person.keys()  
  
for key in all_keys:  
    print(key)
```


Dictionary - get all values

```
person = {  
    "first_name": "Amanda",  
    "last_name": "Smith",  
    "age": 20  
}
```

We can get the list of all values:

```
all_values = person.values()  
  
for value in all_values:  
    print(value)
```

Capital cities

```
capital_city = {  
    "Australia": "Canberra",  
    "Denmark": "Copenhagen",  
    "Ireland": "Dublin",  
    "New Zealand": "Wellington",  
    "Nepal": "Kathmandu"  
}  
  
# ask user to enter country  
country = input("Enter country: ")  
  
# retrieve the capital city  
capital = capital_city.get(country)  
  
# display capital  
print("Capital city of {0} is {1}".format(country, capital))
```

Enter country: **Australia**
Capital city of Australia is Canberra

Capital cities

```
capital_city = ...

# ask user to enter country
country = input("Enter country: ")

# retrieve the capital city
capital = capital_city.get(country)

# display capital
if capital is None:
    print("Sorry I don't know the capital city of " + country)
else:
    print("Capital city of {0} is {1}".format(country, capital))
```

Enter country: **Atzovia**

Sorry I don't know the capital city of Atzovia

State abbreviation

```
state_abb = {
    "NSW": "New South Wales",
    "ACT": "Australian Capital Territory",
    "NT": "Northern Territory",
    "QLD": "Queensland",
    "SA": "South Australia",
    "TAS": "Tasmania",
    "VIC": "Victoria",
    "WA": "Western Australia"
}

# ask user to enter state code
state_code = input("Enter state NSW/ACT/NT/QLD/SA/TAS/VIC/WA: ")

# retrieve the state name
state_name = state_abb.get(state_code)

print("The state you entered is " + state_name)
```

```
Enter state NSW/ACT/NT/QLD/SA/TAS/VIC/WA: NT
The state you entered is Northern Territory
```

Example: Subject selection

Welcome to subject enrolment

Enter subject code: **MATH111**

Enter credit point: **10**

Add more subjects? Y/N: **Y**

Enter subject code: **CS222**

Enter credit point: **4**

Add more subjects? Y/N: **Y**

Enter subject code: **LOGIC333**

Enter credit point: **5**

Add more subjects? Y/N: **N**

Subject code	CP
MATH111	10
CS222	4
LOGIC333	5

Example: Subject selection

Welcome to subject enrolment

Enter subject code: **MATH111**

Enter credit point: **10**

Add more subjects? Y/N: **Y**

Enter subject code: **CS222**

Enter credit point: **4**

Add more subjects? Y/N: **Y**

Enter subject code: **LOGIC333**

Enter credit point: **5**

Add more subjects? Y/N: **N**

Subject code	CP
MATH111	10
CS222	4
LOGIC333	5

Put subject information into a **dictionary**

```
{  
  "code": "MATH111",  
  "cp": 10  
}
```

```
{  
  "code": "CS222",  
  "cp": 4  
}
```

```
{  
  "code": "LOGIC333",  
  "cp": 5  
}
```

Put all these dictionaries
into a **list**

Example: Subject selection

```
# display greeting
print("Welcome to subject enrolment")

# create a list to store subject dictionaries
subject_list = []

while True:
    # ask user to enter subject info
    ...

    # create a dictionary to hold subject info
    subject = ...

    # add subject to list
    subject_list.append(subject)

    # ask user if they want to continue
    more_subject = input("Add more subjects? Y/N: ")
    if (more_subject == "N"):
        break
```

Example: Subject selection

```
...
while True:
    # ask user to enter subject info
    subject_code = input("Enter subject code: ")
    user_input = input("Enter credit point: ")
    subject_cp = int(user_input)

    # create a dictionary to hold subject info
    subject = {
        "code": subject_code,
        "cp": subject_cp
    }

    # add subject to list
    subject_list.append(subject)

    # ask user if they want to continue
    more_subject = input("Add more subjects? Y/N: ")
    if (more_subject == "N"):
        break
```


Example: Subject selection

```
...
# display the selected subjects
print("{0:<15}{1:>15}".format("Subject code", "CP"))

for i in range(0, len(subject_list)):
    # get the ith subject from the list
    # which is a dictionary
    subject = subject_list[i]

    # get subject info out of the dictionary
    subject_code = subject.get("code")
    subject_cp = subject.get("cp")

    # display subject info
    print("{0:<15}{1:>15}".format(subject_code, subject_cp))
```

Subject code	CP
MATH111	10
CS222	4
LOGIC333	5

Problem solving

Please enter numerical code: **017689**

You have entered: zero-one-seven-six-eight-nine