String Immutable:

String Objects are immutable once we create modification is not possible Every time we are creating new objects s1, s2, s3 they are stored in SCP area but orginal string is not changing

```
String s1 = new String("Java"); In the above string is immutable its not changing orginal object data

String s2 = s1.concat("Python");

String s3 = s2.concat("JavaScript");

System.out.println(s1); // Java

System.out.println(s2); // JavaPython

System.out.println(s3); // JavaPythonJavaScript
```

StringBuffer:

StringBuffer is mutable we can change the content

```
StringBuffer sb1 = new StringBuffer("Java");

StringBuffer sb2 = sb1.append("Python");


StringBuffer sb3 = sb1.append("JavaScript");

System.out.println(sb1); //JavaPythonJavaScript

System.out.println(sb2); //JavaPythonJavaScript

System.out.println(sb3); //JavaPythonJavaScript
```

In the below stringbuffer is mutable its changing orginal object data directly



StringBuilder:

StringBuilder is mutable we can change the content

```
StringBuilder sb1 = new StringBuilder("Java");

StringBuilder sb2 = sb1.append("Python");


StringBuilder sb3 = sb1.append("JavaScript");

System.out.println(sb1); //JavaPythonJavaScript

System.out.println(sb2); //JavaPythonJavaScript

System.out.println(sb3); //JavaPythonJavaScript
```

stringbuilder is mutable its changing orginal object data directly



String	String Buffer 1.0	String Builder 1.5
String is non-synchronized i.e. not thread safe. It means two threads can call the methods of String simultaneously.	StringBuffer is synchronized i.e. thread safe. It means two threads can't call the methods of StringBuffer simultaneously.	StringBuilder is non-synchronized i.e. not thread safe. It means two threads can call the methods of StringBuilder simultaneously.
Immutable	Mutable	Mutable
Memory Allocation in String Pool Area	Memory Allocation in Heap Area	Memory Allocation in Heap Area
If we keep on changing the String object continiously new String object is created and allocates more memory and performance becomes slow	If we keep on changing the StringBuffer object continuously no new String object is created and consumes less memory so performanceis high compared to String	If we keep on changing the StringBuffer object continuously no new String object is created and consumes less memory so performanceis high compared to String Buffer
If data is not required to modify then use String	If data is required to modify then use String Buffer (Thread Safety)	If data is required to modify then use String Builder (No Thread Safety)