

Computer Science & IT

Database Management System



Query Languages

Lecture No. 09



By- Vishal Sir

Recap of Previous Lecture



Topic

Comparison with NULL



Topic

Comparison with regular expression



Topic

Practice questions



Topics to be Covered



Topic

Practice questions



Topic

Tuple relational calculus (TRC)



#Q.

H.W.

Consider The Following Relational Scheme

- ④ Student (school-id, sch-roll-no, sname, saddress)
- ④ School (school-id, sch-name, sch-address, sch-phone)
- ④ Enrolment (school-id, sch-roll-no, erollno, examname)
- ④ ExamResult (Errollno, examname, marks)

Sch-name may be same
for two schools with
different School-id

(A) for each school with more than 200 students appearing in exams, the name of the school and the number of 100s scored by its students

(B) for each school with more than 200 students in it, the name of the school and the number of 100s scored by its students

(C) for each school with more than 200 students in it, the name of the school and the number of its students scoring 100 in at least one exam

(D) nothing; the query has a syntax error

#Q.

What does the following SQL query output?

```
SELECT sch-name, COUNT (*)
FROM School C, Enrolment E, ExamResult R
WHERE E.school-id = C.school-id
      AND
      E.exaname = R.exaname
      AND
      E.erollno = R.erollno
      AND
      R.marks = 100
      AND
      E.school-id IN
      (SELECT school-id
       FROM student GROUP BY school-id HAVING COUNT (*) > 200)
```

GROUP BY School-id, Sch-name

H.W.

For option 'B' to be true

What changes needs to be performed in the query

When

- ✓ (i) Sch-name may be same for schools with different school-id
- (ii) Sch-name are also unique

Max

	School-id	Sch-name	E-roll no.	Exam	Marks
#Students > 200 ←	01	Saraswati	05	GATE	100
#Students > 200 ←	05	Saraswati	07	JEE	100
	05	Saraswati	09	GATE	100
#Student > 20 ←	06	St. Joseph	15	JEE	100

Sch-name	Count (*)
Saraswati	1
Saraswati	2

#Q.

What does the following SQL query output?

```
SELECT sch-name, COUNT (*)
FROM School C, Enrolment E, ExamResult R
WHERE E.school-id = C.school-id
      AND
      E.examname = R.examname
      AND
      E.erollno = R.erollno
      AND
      R.marks = 100
      AND
      E.school-id IN
      (SELECT school-id
       FROM student GROUP BY school-id HAVING COUNT (*) > 200)
```

GROUP BY Sch-name

H.W.

For option 'B' to be true

What changes needs to be performed in the query

When

(i) Sch-name may be same for schools with different school-id

(ii) Sch-name are also unique

	School-id	Sch-name	E-roll no.	Exam	Marks
#Students > 200 ←	01	Saraswati	05	GATE	100
#Students > 200 ←	05	St. Johns	07	JEE	100
	05	St. Johns	09	GATE	100

Sch-name	Count (*)
Saraswati	1
St. Johns	2

#Q.

H.W.

[MCQ: 2009: 2M]



Consider the following relational schema:

Suppliers(sid:integer, sname:string, city:string, street:string)

Parts(pid:integer, pname:string, color:string)

Catalog(sid:integer, pid:integer, cost:real)

Consider the following relational query on the above database:

SELECT S.sname

FROM Suppliers S

WHERE S.sid NOT IN

(SELECT C.sid

FROM Catalog C

WHERE C.pid NOT IN

(SELECT P.pid

FROM Parts P

WHERE P.color <> 'blue'))

(Options on the
Next Slide)

Hint: Just provide your answer

(None of the option given may be true)

Question Continues in Next Slide

#Q.

H.W.

Supplier

S₁
S₂
S₃
S₄

Parts

P₁ Red
P₂ Blue
P₃ Green

Catalog

S₁ P₁
S₁ P₂
S₂ P₂
S₃ P₃

Consider the following relational schema:

Suppliers(sid:integer, sname:string, city:string, street:string)

Parts(pid:integer, pname:string, color:string)

Catalog(sid:integer, pid:integer, cost:real)

Consider the following relational query on the above database:

```
SELECT S.sname
FROM Suppliers S
WHERE S.sid NOT IN
```

```
(SELECT C.sid
```

```
FROM Catalog C
```

```
WHERE C.pid NOT IN
```

```
(SELECT P.pid
```

```
FROM Parts P
```

```
WHERE P.color <> 'blue'))
```

Snames of suppliers who did not supply any blue color part.

o/p = { S₃, S₄ }

Sname

Sname

Sids of the suppliers who have supplied at least one blue color part

o/p = { S₁, S₂ }

o/p = Pids of non-blue color parts { P₁, P₃ }

Pid not in Pids of non-blue color part
i.e. Pid is actually of blue color part

Question Continues in Next Slide

[MCQ: 2009: 2M]



#Q. Assume that relations corresponding to the above schema are not empty. Which one of the following is the correct interpretation of the above query?

~~A.~~

Find the names of all suppliers who have supplied a non-blue part.

~~B.~~

Find the names of all suppliers who have not supplied a non-blue part.

is: Supplied only blue parts (or) no parts

~~C.~~

Find the names of all suppliers who have supplied only blue parts.

D.

Find the names of all suppliers who have not supplied only blue parts.

At least one blue + Some other Color Parts as well

Relational Calculus



Topic : Relational Calculus

- Relational Calculus is a non-procedural query language.
- It uses predicate calculus(First Order Logic) instead of algebra.
 \forall, \exists etc
- Relational calculus provides description about the query to get the result, whereas Relational Algebra gives the method to get the result.



Topic : Types of Relational Calculus

There are two types of Relational Calculus.

1. **Tuple Relational Calculus:** Works on tuple (or rows)
2. **Domain Relational Calculus:** Works on domain of attribute (column)



Topic : Syntax of TRC

A set of tuples t such that Predicate Condⁿ P is true

Basic syntax of TRC is $\{ t \mid P(t) \}$

for those tuples ' t ' it is called output tuple variable, it is used to produce O/p.

where t is a tuple variable and $P(t)$ is a predicate formula that describes the conditions that must be satisfied by the resulting tuples.

1. It results the set of tuples t , s.t. $P(t)$ is true for t .
2. $t \in \text{Relation}$ denotes that the ' t ' is a tuple from Relation, also denoted using $\text{Relation}(t)$.
3. If ' t ' is a tuple variable, then " $t[A]$ " / " $t.A$ " specify attribute A in tuple t .
4. P is a predicate formula similar to that of the predicate calculus.



Topic : Equivalence between SQL, RA and TRC

SQL ➤ SELECT distinct * FROM Employee

R.A ➤ (Employee)

TRC ➤ $\{ t \mid t \in \text{Employee} \}$
or
 $\{ t \mid \text{Employee}(t) \}$

it will be true for all tuples of Employee table,
∴ All tuples of Employee will be present in output

Predicate Condⁿ

$\{ t \mid t \in \text{Employee} \}$

$\{ t \mid \text{Employee}(t) \}$



Topic : Free and Bounded variables

- A variable which is preceded by a quantifier is called bounded variable.
- A variable which is not preceded by any quantifier is called free variable.
- **There is an important restriction:**
The variable 't' that appears before '|' symbol must be the only free variable in formula $P(t)$.
In other words all other variables must be bounded using quantifier



Topic : Equivalence between SQL, RA and TRC

SQL ➤ SELECT distinct ename FROM Employee

$\{ t[ename] \mid t \in \text{Employee} \}$

RA ➤ $\pi_{ename}(\text{Employee})$

$\{ t.ename \mid t \in \text{Employee} \}$

TRC ➤ $\{ t.ename \mid t \in \text{Employee} \}$

or

$\{ t[ename] \mid t \in \text{Employee} \}$

or

$\{ t \mid \exists S \in \text{Employee} (t[ename] = S[ename]) \}$

or

$\{ t \mid \exists S \in \text{Employee} (t.ename = S.ename) \}$

$\{ t.ename \mid \text{Employee}(t) \}$

$\{ t \mid \exists S \in \text{Employee} \wedge t = S.ename \}$

$\{ t \mid \exists S \in \text{Employee} (t.ename = S.ename) \}$ attribute Creation with tuple t'

#Q. Retrieve tuples from the relation student where marks are more than 50
Student(sid, name, marks)



$$\{ t \mid t \in \text{Student} \wedge t.\text{marks} > 50 \}$$

Predicate Condⁿ

$$\{ t \mid \exists S \in \text{Student} (S.\text{Marks} > 50 \wedge t.\text{Sid} = S.\text{Sid} \wedge t.\text{name} = S.\text{name} \wedge t.\text{marks} = S.\text{marks}) \}$$

Attribute Creation

#Q. Retrieve sids of all the students from the relation student whose marks are more than 50 .
Student(sid, name, marks)



$$\{t.sid \mid t \in \text{Student} \wedge t.marks > 50\}$$

$$\{t \mid \exists s \in \text{Student} \wedge s.marks > 50 \wedge t.sid = s.sid\}$$

#Q. Retrieve sids and names of all the students from the relation student whose marks are more than 50 .
Student(sid, name, marks)



$$\{ t.\text{sid}, t.\text{name} \mid t \in \text{Student} \wedge t.\text{marks} > 50 \}$$

$$\{ t \mid \exists s \in \text{Student} (s.\text{marks} > 50 \wedge t.\text{sid} = s.\text{sid} \wedge t.\text{name} = s.\text{name}) \}$$

#Q.

Consider the following relational schema:

Suppliers(sid, sname, city)

Parts(pid, pname, color)

Catalog(sid, pid, cost)

Find sid of all the suppliers who have supplied part with pid=P1

$$\{ t.sid \mid t \in \text{Catalog} \wedge t.pid = 'P1' \}$$

$$\{ t \mid \exists C \in \text{Catalog} (C.pid = 'P1' \wedge t.sid = C.sid) \}$$

#Q. Consider the following relational schema:

Suppliers(sid, sname, city)

Parts(pid, pname, color)

Catalog(sid, pid, cost)

Find sids of all the suppliers who have supplied some 'red' color parts

o/p from Catalog

$$\{ t.sid \mid t \in \text{Catalog} \wedge \exists P \in \text{Parts} (t.pid = P.pid \wedge P.color = 'Red') \}$$

$$\{ t \mid \exists C \in \text{Catalog} (\exists P \in \text{Parts} (C.pid = P.pid \wedge P.color = 'Red') \wedge t.sid = C.sid) \}$$

$$\{ t \mid \exists C \in \text{Catalog} (\underline{t.sid = C.sid} \wedge \exists P \in \text{Parts} (C.pid = P.pid \wedge P.color = 'Red')) \}$$

#Q.

Consider the following relational schema:

Suppliers(sid, sname, city)

Parts(pid, pname, color)

Catalog(sid, pid, cost)

Find Sid and Sname of all the suppliers who have supplied some 'red' color parts.

$$\left\{ \underbrace{t.sid, t.sname}_{\uparrow} \mid t \in \text{Supplier} \wedge \exists C \in \text{Catalog} \left(\exists P \in \text{Parts} \left(\begin{array}{l} C.pid = P.pid \\ P.color = 'Red' \end{array} \right) \wedge t.sid = C.sid \right) \right\}$$

$$\left\{ t.sid, t.sname \mid t \in \text{Supplier} \wedge \exists C \in \text{Catalog} \left(\underline{t.sid = C.sid} \wedge \exists P \in \text{Parts} (C.pid = P.pid \wedge P.color = 'Red') \right) \right\}$$

#Q. Consider the following relational schema:

Suppliers(sid, sname, city)

Parts(pid, pname, color)

Catalog(sid, pid, cost)

Retrieve Sids of suppliers who supplied some 'Red' color parts along with the 'pname' of that Red color part.

~~t.sid, t.pname~~ not possible

$\{ t \mid \exists C \in \text{Catalog} (\exists P \in \text{Parts} (C.\text{Pid} = P.\text{Pid} \wedge P.\text{Color} = \text{'Red'} \wedge t.\text{Sid} = C.\text{Sid} \wedge t.\text{pname} = P.\text{pname})) \}$



Topic : Unsafe TRC query

$\{ t \mid t \notin \text{Relation} \}$

or

$\{ t \mid \neg(t \in \text{Relation}) \}$

tuples belonging
to relation

Not, the tuples
belonging to relation

Here, We are trying
to select the tuples
that does not belong
to the relation

If domain of any
attribute happens to be
infinite, then
Unsafe TRC query
may produce
infinite number of
tuples.

Note:-

- ① Unsafe TRC query may produce infinite number of tuples.
- ② Given an unsafe TRC query, we can never write an Equivalent Relational Algebra Expression.
- ③ For every safe TRC query we can always write an Equivalent Relational Algebra Expression.

→

Power of TRC
(Safe + Unsafe)

\neq

Not Equal
because of
Unsafe TRC query

Power of Relational Algebra

Power of Safe TRC = Power of Relational Algebra

#Q. Which of the following tuple relational calculus expression(s) is/are equivalent to $\forall t \in r(P(t))$?

H.W.

I $\neg \exists t \in r(P(t))$

II $\exists t \notin r(P(t))$

III $\neg \exists t \in r(\neg P(t))$

IV $\neg \exists t \notin r(\neg P(t))$

A. I only

B. II only

C. III only

D. III and IV only

#Q. Which of the following relational calculus expressions is not safe?

H.W

- A. $\{t | \exists u \in R1 (t[A] = u[A]) \wedge \neg \exists s \in R2 (t[A] = s[A])\}$
- B. $\{t | \forall u \in R1 (u[A] = "x" \Rightarrow \exists s \in R2 (t[A] = s[A] \wedge s[A] = u[A]))\}$
- C. $\{t | \neg(t \in R1)\}$
- D. $\{t | \exists u \in R1 (t[A] = u[A]) \wedge \exists s \in R2 (t[A] = s[A])\}$

#Q.

Consider the relation employee (name, sex, supervisorName) with name as the key. Supervisor Name gives the name of the supervisor of the employee under consideration. What does the following Tuple Relational Calculus query produce?

$\{e.name \mid employee(e) \wedge (\forall x) [\neg employee(x) \vee x.supervisorName \neq e.name \vee x.sex = "male"]\}$

- A. Names of employees with a male supervisor.
- B. Names of employees with no immediate male subordinates
- C. Names of employees with no immediate female subordinates
- D. Names of employees with a female supervisor.

#Q.

H.W.

Consider The Following Relational Scheme

Student (school-id, sch-roll-no, sname, saddress)

School (school-id, sch-name, sch-address, sch-phone)

Enrolment (school-id, sch-roll-no, erollno, examname)

ExamResult (Erollno, examname, marks)

Consider the following tuple relational calculus query

$\{ t \mid \exists E \in \text{Enrolment } t = E.\text{school-id} \wedge$

$\{ x \mid x \in \text{Enrolment} \wedge x.\text{school-id} = t \wedge (\exists B \in \text{ExamResult } B.\text{erollno} = x.\text{erollno} \wedge$

$B.\text{examname} = x.\text{examname} \wedge B.\text{marks} > 35 \} \mid \div$

$\{ x \mid x \in \text{Enrolment} \wedge x.\text{school-id} = t \} \mid * 100 > 35 \}$

If a student needs to score more than 35 marks to pass an exam what does the query return?

Options on next slide

#Q.



- A. The empty set
- B. schools with more than 35% of its students enrolled in some exam or the other
- C. schools with a pass percentage above 35% over all exams taken together
- D. schools with a pass percentage above 35% over each exam

#Q.

H.W.

Consider a database that has the relation schemas
EMP(EmpId, EmpName, DeptId) and
DEPT(DeptName, DeptId).

Note that the DeptId can be permitted to a NULL in the relation EMP. Consider the following queries on the database expressed in tuple relational calculus.

- I. $\{t \mid \exists u \in \text{EMP} (t[\text{EMPName}] = u[\text{EmpName}] \wedge \forall v \in \text{DEPT} (t[\text{DeptId}] \neq \text{DeptId}))\}$
- II. $\{t \mid \exists u \in \text{EMP} (t[\text{EMPName}] = u[\text{EmpName}] \wedge \exists v \in \text{DEPT} (t[\text{DeptId}] \neq \text{DeptId}))\}$
- III. $\{t \mid \exists u \in \text{EMP} (t[\text{EMPName}] = u[\text{EmpName}] \wedge \exists v \in \text{DEPT} (t[\text{DeptId}] = \text{DeptId}))\}$

Which of the above queries are safe?

- A. I and II only
- B. I and III only
- C. II and III only
- D. I, II and III



2 mins Summary



✓ **Topic**

Practice questions

✓ **Topic**

Tuple relational calculus (TRC)

THANK - YOU