Problem Description: Ram has provide inputs two numbers 'p' and 'q' to Sakthi. He wants to creates a matrix of size p x q (p rows and q columns) in which every elements is either Y or 0. The Ys and 0s must be filled alternatively, the matrix should have outermost rectangle of Ys, then a rectangle of 0s, then a rectangle of Ys, and so on..

Constraints:

1 <= p, q <= 1000

Input Format:

Input lines must be how many rows and columns in that matrix, also values must be separate space.

Output Format:

Print the output in a separate lines.

Logical Test Cases

Test Case 1

INPUT (STDIN)

```
6 7
```

Test Case 2

INPUT (STDIN)

```
5 8
```

EXPECTED OUTPUT

```
Y Y Y Y Y Y Y
Y 0 0 0 0 0 Y
Y 0 Y Y Y 0 Y
Y 0 Y Y Y 0 Y
Y 0 0 0 0 0 Y
Y Y Y Y Y Y Y
```

EXPECTED OUTPUT

```
Y Y Y Y Y Y Y Y
Y 0 0 0 0 0 0 Y
Y 0 Y Y Y Y 0 Y
Y 0 0 0 0 0 0 Y
Y Y Y Y Y Y Y Y
```

Mandatory Test Cases

Test Case 1

KEYWORD

```
while(top<=bottom &&
right>=left)
```

Complexity Test Cases

Test Case 1

CYCLOMATIC COMPLEXITY

```
12
```

Test Case 2

TOKEN COUNT

```
290
```

Test Case 3

NLOC

```
52
```