

Chapter 7 Firewall for FortiOS 5.0

Chapter 8 Hardware Acceleration

Chapter 9 High Availability for FortiOS 5.0

Chapter 10 Install and System
Administration for FortiOS 5.0

Chapter 11 IPsec VPN for FortiOS 5.0

Chapter 12 IPv6 for FortiOS 5.0

Chapter 13 Load Balancing for FortiOS 5.0

Chapter 14 Logging and Reporting

Chapter 15 Managing Devices for
FortiOS 5.0Chapter 16 Unified Threat Management for
FortiOS 5.0

Chapter 17 SSL VPN for FortiOS 5.0

Chapter 18 Traffic Shaping for FortiOS 5.0

The purpose of traffic shaping

Traffic shaping methods

Traffic shaping options

Shared policy shaping

Per policy

All policies

Maximum and guaranteed
bandwidth

Traffic priority

VLAN, VDOM and virtual interfaces

Shared traffic shaper
configuration settings

Per-IP shaping

Per-IP traffic shaping
configuration settingsAdding Per-IP traffic shapers to a
security policy

Application control shaping

Enabling in the security policy

Type of Service priority

Differentiated Services

Tos and DSCP mapping

Traffic Shaper Monitor

Examples

Troubleshooting traffic shaping

Chapter 19 Troubleshooting

Chapter 20 Virtual Domains

Chapter 21 VM Installation for FortiOS 5.0

Chapter 22 VoIP Solutions: SIP for
FortiOS 5.0Chapter 23 WAN Optimization, Web
Cache, Explicit Proxy, and WCCP for
FortiOS 5.0[Chapter 17 Traffic Shaping for FortiOS 5.0](#) : [Traffic shaping methods](#) : Per-IP shaping

Per-IP shaping

Traffic shaping by IP enables you to apply traffic shaping to all source IP addresses in the security policy. As well as controlling the maximum bandwidth users of a selected policy, you can also define the maximum number of concurrent sessions.

Per-IP traffic shaping enables you limit the behavior of every member of a policy to avoid one user from using all the available bandwidth - it now is shared within a group equally. Using a per-IP shaper avoids having to create multiple policies for every user you want to apply a shaper. Per-IP traffic shaping is not supported over NP2 interfaces.

See also

- [Per-IP traffic shaping configuration settings](#)