

RABBIT CHAIN

A Permissionless EVM Layer 1
with Live Consensus Queue

TECHNICAL WHITEPAPER

Pre-Testnet Edition • Version 0.9 • 29 August 2026

ONE ELIGIBLE WALLET. ONE FAIR CHANCE.

rabbitchain.org

Contents

- Abstract
- 1. Motivation
- 2. System overview
- 3. Live Consensus Queue
- 4. Work V1 and RandomX
- 5. Block production and liveness
- 6. Committee and rewards
- 7. RAB economic model
- 8. Testnet participation program
- 9. EVM execution and fees
- 10. Networking and infrastructure
- 11. Security model
- 12. Validation evidence
- 13. Governance and upgrades
- 14. Roadmap and launch gates
- 15. Reproducibility and verification
- 16. Parameters snapshot
- 17. How to participate
- 18. Frequently asked questions
- 19. Glossary
- 20. Conclusion
- References and version history

Document status

This document describes the intended architecture and the implementation state of Rabbit Chain before the public testnet. It is a technical disclosure, not an offer of securities, a promise of profit, or a guarantee of network performance. Where this paper and executable network rules differ, the versioned source code, genesis file, and canonical chain state are authoritative.

Item	Status
Public testnet	Pre-launch; infrastructure not yet activated
Testnet chain ID	9280
Planned mainnet chain ID	928
Native asset	RAB
Execution	Ethereum Virtual Machine compatible
Consensus	LCQ — Live Consensus Queue
Work proof	RandomX-backed Work V1
Canonical source branch	testnet-release-v1
Validated source commit	e9875409dcf27e497812965296cece5d2e0f267a
Evidence checkpoint	b9967ca73cf5fe30b854d10ae55a48f2127efb2c

Abstract

Rabbit Chain is a permissionless, EVM-compatible Layer 1 network designed around a simple fairness objective: multiplying mining processes must not multiply a wallet's opportunity to obtain a canonical production seat. The protocol combines computational work, an on-chain participant registry, deterministic ordering, liveness rules, and committee participation in a mechanism called **Live Consensus Queue (LCQ)**.

Traditional proof-of-work systems tend to assign block-production probability in proportion to accumulated hash power. Rabbit Chain instead uses work as an admission and liveness signal for a time-bounded **WorkSeat**. Eligible identities are then ordered deterministically for block production. A participant may run redundant software and hardware, but duplicate work associated with the same wallet must not create duplicate canonical seats in the same epoch.

The network retains the Ethereum execution model so existing wallets, Solidity contracts, developer tooling, transaction formats, and JSON-RPC conventions can be used with limited adaptation. Consensus, however, is Rabbit-specific. LCQ separates work discovery from scheduled production and distributes protocol rewards between the producer and a selected committee.

Pre-launch gates have exercised fresh multi-node operation, restart behavior, Work V1 transport, canonical ticket handling, and the one-wallet/one-seat invariant. In the final extraordinary live gate, three independent miner processes using the same wallet produced exactly one canonical WorkSeat, with zero duplicate seat, followed by a successful re-audit after node restart.

1. Motivation

Public blockchains promise open participation, yet access to meaningful block production often concentrates around capital, specialized hardware, pools, privileged validator sets, or operational scale. Permissionless entry alone does not guarantee equal opportunity after entry.

Rabbit Chain addresses a narrower and measurable problem: **process multiplication should not become identity multiplication**. If one participant opens three miner processes with the same wallet, the protocol should observe redundancy, not three independent claims to selection.

The design follows five principles:

1. **Permissionless entry.** No manual approval, private validator list, or administrator transaction should be required to begin participating.
2. **Wallet-bounded opportunity.** One eligible wallet receives at most one canonical WorkSeat per epoch.
3. **Deterministic verification.** Honest nodes given the same canonical history must derive the same registry, eligible set, and queue.
4. **Recoverable liveness.** Temporary inactivity, node failure, or loss of producers should not require a trusted operator to rewrite the chain.
5. **EVM utility.** Consensus innovation should coexist with established smart-contract tooling and account semantics.

These goals do not eliminate every form of concentration. A person may control multiple wallets, and no permissionless protocol can prove unique human identity without additional assumptions. LCQ therefore enforces a precise technical invariant — one seat per eligible wallet per epoch — and combines it with bond, activity, work, delay, and penalty rules that raise the cost of mass identity creation.

2. System overview

Rabbit Chain has four cooperating layers:

- **Execution layer:** EVM state transition, accounts, transactions, receipts, logs, gas, and smart contracts.
- **Consensus layer:** LCQ validation, registry snapshots, queue resolution, producer signatures, timeout/fallback handling, and committee selection.
- **Work layer:** RandomX-backed proof generation and peer-to-peer Work V1 ticket transport.
- **Network layer:** peer discovery, transaction and block propagation, consensus messages, RPC access, and independently operated infrastructure.

The intended user path is deliberately short:

Download → run → use a wallet → mine.

Registration and activation are protocol-driven. The client resolves the local participant, submits valid work, observes activation rules, and joins the deterministic queue when eligible.

From RandomX work to a canonical Rabbit block

Work proves eligibility; LCQ schedules production; every validating node recomputes the result.




Figure 1. Work qualifies a wallet for a bounded canonical seat; the LCQ queue, rather than a continuing hash race, schedules block production.

2.1 Rabbit Chain at a glance

Question	Short answer
What is Rabbit Chain?	A permissionless EVM Layer 1 with its own LCQ consensus
What is LCQ?	A mechanism that converts valid work into a wallet-bounded position in a deterministic live production queue
What makes it different?	Running more miner processes with the same wallet

Question	Short answer
	must not create more canonical seats for that wallet in the same epoch
Is it ordinary PoW?	No. RandomX work qualifies participation; the LCQ queue schedules block production
Is it PoS?	No. Bonding supports eligibility and anti-abuse rules, but stake weight alone does not select the next producer
Can anyone join?	Yes, subject to the same public protocol rules, work, bond, activation, activity, and client requirements
Can Ethereum tools be used?	The goal is compatibility with common EVM wallets, Solidity, transactions, contracts, logs, and JSON-RPC tooling
What is the native asset?	RAB, used for gas, rewards, bonding, and protocol accounting
Is the public testnet live?	Not at this edition's publication checkpoint

2.2 LCQ compared with common models

Property	Conventional PoW	Conventional PoS	Rabbit LCQ
Primary admission signal	Computational work	Locked stake	Valid work plus protocol eligibility
Typical selection weight	Hash power	Stake weight	One canonical queue seat per eligible wallet per epoch
Block producer	Hash-race winner	Stake-selected validator	Deterministically scheduled eligible wallet
Duplicate processes on one wallet	Usually add hash rate	Usually operational redundancy	May help find the first proof but must not add canonical seats
Capital still matters?	Hardware and energy matter	Stake matters directly	Compute, bond, uptime, and multiple funded wallets can still matter
Unique-human guarantee	No	No	No

This comparison is conceptual. Individual PoW and PoS networks differ, and the Rabbit implementation is defined by its released source and configuration.

3. Live Consensus Queue

3.1 Core idea

LCQ converts valid computational work into a bounded right to participate in a deterministic production schedule. It is not conventional hash-race proof of work: the first valid hash does not automatically grant indefinite control over successive blocks. It is also not conventional proof of stake: capital weight alone does not determine the next producer.

The canonical chain maintains a participant registry. At each relevant height or epoch boundary, all honest nodes derive an eligible set from the same historical state. The set is ordered using canonical chain entropy, including the parent block context, and each eligible wallet occupies no more than one position.

Conceptually:

$$E_h = \{p \in R_h : \{Eligible\}(p, h) = \{true\}\}$$

$$Q_h = \{Order\}(E_h, H_{\{h-1\}}, e_h)$$

where (R_h) is the registry snapshot, $(H_{\{h-1\}})$ is canonical parent context, (e_h) is the epoch, and (Q_h) is the deterministic queue. The executable client defines the exact encoding, hashing, and tie-breaking rules.

3.2 Participant eligibility

A participant is eligible only when all active protocol checks pass. The implemented checks include a non-zero address, an acceptable jail state, a sufficient bond according to network parameters, and a valid recent activity record. Bootstrap treatment at the first block is explicit so a new network can begin without relying on pre-existing heartbeats.

Eligibility is evaluated from historical canonical state, not from an unverified local preference. A node cannot make a wallet eligible merely by configuring it locally.

3.3 Activation delay

Newly observed participants do not receive immediate influence over the current queue. An activation delay separates registration from eligibility. This reduces rapid join/leave manipulation and gives the network time to propagate and agree on the participant's canonical state. The final public-testnet value must be read from the released genesis and chain configuration; earlier validation used explicit activation-delay scenarios.

3.4 WorkSeat lifecycle

A WorkSeat is associated with a participant wallet and epoch. Its lifecycle is:

6. The client obtains the canonical work context.
7. A miner computes RandomX proofs against that context.

8. A valid ticket is submitted over the Work V1 transport.
9. Nodes validate the proof, context, participant status, epoch, and duplication rules.
10. An accepted ticket becomes eligible for canonical inclusion.
11. Canonical history grants at most one seat to the participant for that epoch.
12. The queue uses the canonical eligible-seat set for production ordering.

Tickets that are stale, malformed, invalid, ineligible, or duplicate must not create additional seats.

3.5 One wallet, one seat

For participant (p) and epoch (e) , the intended invariant is:

$$\{CanonicalSeats\}(p,e) \leq 1$$

This invariant applies even when multiple processes, machines, or submissions use the same wallet. Redundant mining can improve availability or the chance that the wallet finds its first valid proof, but it cannot create multiple canonical queue identities for that wallet during the same epoch.

This is wallet fairness, not proof of unique-personhood. The distinction is essential: the protocol does not claim that one wallet always equals one human.

3.6 A complete miner example

Consider Alice, who controls wallet A:

13. Alice installs the official or reproducibly built Rabbit software and verifies its hash.
14. Her node connects to peers and independently synchronizes the canonical chain.
15. The client resolves wallet A as the local participant and observes the current registry, epoch, work context, bond, activity, and activation rules.
16. Alice starts one miner process. It searches for a valid RandomX proof bound to the current challenge and dataset anchors.
17. After finding a proof, the client submits a Work V1 ticket. Nodes independently validate the proof and participant state.
18. Once the ticket is canonically recognized, wallet A may hold one WorkSeat for that epoch.
19. Every honest node derives the same queue from canonical history. When A reaches the permitted production position, Alice's client builds and signs a block.
20. Other nodes verify the expected producer, seal, transactions, EVM result, gas, rewards, and all LCQ rules before accepting it.
21. If Alice opens two additional miners with wallet A, they may search redundantly, but wallet A must still receive no more than one canonical seat in that epoch.
22. If Alice is offline during her turn, timeout and fallback rules allow the next permitted producer to advance liveness.

Alice never asks an administrator to approve her wallet. She also cannot make herself eligible merely by editing a local configuration: canonical nodes recompute every relevant rule.

4. Work V1 and RandomX

Rabbit Chain uses a RandomX-backed work path because RandomX is designed for general-purpose CPUs and uses randomized execution and memory-hard techniques to reduce the relative advantage of specialized hardware. Rabbit integrates this proof into LCQ ticket admission rather than adopting a conventional highest-hashpower-wins block race.

The work context binds a proof to canonical network state. It includes an epoch, a challenge anchor, a dataset anchor, and canonical runtime difficulty. A submitted proof is useful only for the context for which it was produced. Context binding helps prevent replay across epochs, networks, or unrelated chain histories.

Work V1 is carried by a dedicated peer-to-peer transport. Production activation is guarded by network identity and genesis markers so a laboratory transport configuration cannot silently activate on an unintended network.

The pre-launch validated difficulty was 100000 (0x186a0). This value is a network parameter, not a permanent promise; the public genesis and versioned client are authoritative.

5. Block production and liveness

5.1 Scheduled producer

For a given height, nodes independently derive the expected producer from the canonical queue and active rules. The producer constructs an EVM block, includes valid transactions, respects gas and fee rules, and signs the LCQ header material with the participant key.

5.2 Producer authentication

Rabbit headers carry LCQ-specific extra data and a producer seal. Nodes verify the seal against the expected participant and canonical header fields. A locally configured coinbase address is not sufficient authorization; the signature and queue-derived role must validate.

5.3 Timeout and fallback

If the scheduled producer does not publish a valid block within its slot, fallback rules advance liveness through subsequent allowed positions and bounded timing windows. Stale candidates are rejected against current canonical context. The objective is to preserve deterministic agreement while avoiding dependence on one online producer.

5.4 Network interruption and recovery

If participation falls to zero, the chain may stop rather than fabricate work or appoint a trusted emergency producer. When a valid participant returns, recovery rules derive from preserved

canonical state and resume after the last accepted block. Nodes must not delete history or reset to genesis to restore liveness.

This recovery model has a trade-off: safety remains tied to verifiable history, but time to resume depends on valid work, participant eligibility, and propagation.




Figure 2. A missed producer advances through public fallback rules. If no eligible participant remains, the chain waits and later resumes from preserved canonical history.

6. Committee and rewards

Each canonical block divides the configured protocol reward between the producer and an eligible committee:

Recipient	Share
Block producer	70%
Committee	30%

The committee is derived deterministically from canonical participant state and bounded by configured minimum and maximum sizes. Reference pre-launch parameters use a minimum of 32 and maximum of 128 committee members, with a committee ratio of 3000 basis points. Small

bootstrap or laboratory networks may operate under explicit special-case parameters; the released genesis controls the public network.

Committee distribution is intended to spread rewards beyond the single scheduled producer and reward active consensus participation. Exact rounding, zero-recipient handling, vesting, and state-transition behavior are defined by the client implementation.

Early mining rewards are subject to protocol-enforced locking during the first 100,000 blocks, followed by automatic release under the finalized network schedule. The definitive unlock and halving rules must be published in genesis-linked release documentation before public launch.

7. RAB economic model

RAB is the native asset used for gas, protocol rewards, bonding, and network-level economic accounting. The maximum supply and allocation ceiling is **15,000,000 RAB**. The testnet participation reserve is part of this fixed amount; it is not additional issuance.

Allocation	RAB	Share
Staking and protocol participation	10,000,000	66.67%
Liquidity	2,000,000	13.33%
Rabbit Club/community	1,000,000	6.67%
Operational costs	400,000	2.67%
Testnet participation rewards	100,000	0.67%
Creator and developers	1,500,000	10.00%
Total	15,000,000	100.00%

Percentages are rounded to two decimal places. The integer RAB amounts, whose sum is exactly 15,000,000 RAB, are authoritative.

The earlier 500,000 RAB operational allocation is therefore divided internally as follows:

Component of the former operational allocation	RAB	Rule
General operational costs	400,000	Infrastructure, security, legal/compliance, audits, software, communications, and documented project operations
Public-testnet participation program	100,000	Reserved exclusively for eligible miners, builders, testers, and valid bug hunters under the published program rules

Component of the former operational allocation	RAB	Rule
Combined amount	500,000	No change to total supply and no additional minting

Supply identity: 15,000,000 RAB = 10,000,000 + 2,000,000 + 1,000,000 + 400,000 + 100,000 + 1,500,000 RAB.

7.1 Supply invariant

The mainnet design must make the 15,000,000 RAB ceiling independently verifiable. No allocation table, website, multisig, vault, token interface, or off-chain statement may authorize balances beyond the rules enforced by the released genesis and consensus implementation.

Because RAB is the native asset of Rabbit Chain rather than an ordinary ERC-20 token, not every monetary rule belongs in one token contract. Transparency is divided between:

- **genesis and consensus rules**, which define initial native balances, issuance, rewards, locks, and supply behavior;
- **public vault/vesting contracts**, which hold allocations that require time-based or rule-based release;
- **public treasury addresses**, used only where human operational spending is unavoidable;
- **versioned disclosures**, which connect every allocation to an address, balance, contract, rule, and responsible signing policy.

The absence of a single ERC-20 contract must never be confused with absence of on-chain verification. Native balances, consensus issuance, contract balances, releases, and transfers remain observable through a validating node and block explorer.

7.2 Allocation enforcement plan

Before mainnet block 1, the final genesis and release package must publish the enforcement method for every allocation:

Allocation	Amount	Required enforcement and disclosure
Staking and protocol participation	10,000,000 RAB	Consensus-controlled issuance/reserve or an immutable distribution mechanism; exact reward, lock, halving, eligibility, and exhaustion rules published with source
Liquidity	2,000,000 RAB	Dedicated on-chain vault or disclosed address; release conditions, authorized destinations, liquidity

Allocation	Amount	Required enforcement and disclosure
		transactions, LP-token custody, and any lock disclosed
Rabbit Club/community	1,000,000 RAB	Dedicated community treasury or distribution vault; purpose, authority, voting/approval process if any, and every transfer visible
Operational costs	400,000 RAB	Dedicated operations treasury, separate from all other allocations; signer policy and categorized periodic reporting
Testnet participation rewards	100,000 RAB	Dedicated reward vault; cannot be spent for operations, liquidity, creator compensation, or unrelated community programs
Creator and developers	1,500,000 RAB	Public vesting vault enforcing the announced cliff and installment schedule

Logical contract names in this paper are descriptions, not deployed addresses. Final contract names, addresses, bytecode, verified source, compiler settings, constructor arguments, ownership, and transaction hashes will be inserted only after deployment. No placeholder address should be presented as final.

7.3 Creator and developer vesting

The creator/developer allocation is planned to remain locked until six months after official mainnet liquidity begins. Ten percent of that allocation is then scheduled for release, with the remaining ninety percent released over 24 subsequent installments. This is a policy commitment to be encoded or enforced through publicly auditable mechanisms before mainnet.

Applied to 1,500,000 RAB, the intended schedule is:

Stage	Amount	Cumulative released
Initial release after the six-month cliff	150,000 RAB	150,000 RAB
Remaining locked balance	1,350,000 RAB	—
Each of 24 subsequent equal installments	56,250 RAB	Up to 1,500,000 RAB after installment 24

The final contract must define the installment interval, liquidity-start reference, timestamp/block semantics, beneficiary addresses, rounding behavior, revocability, transferability, and treatment of compromised keys. Until those fields are frozen in verified code, this schedule is an economic commitment but not yet a deployed enforcement claim.

7.4 Transparency standard for contracts and treasuries

Every contract or address holding an allocated RAB reserve must have a public registry entry containing:

- allocation name and exact RAB amount;
- network and chain ID;
- genesis address or deployment address;
- deployment and funding transaction hashes;
- verified source code and exact Git commit;
- compiler version, optimization settings, constructor arguments, and linked libraries;
- immutable contract bytecode hash;
- owner, administrator, guardian, pauser, upgrader, and beneficiary powers;
- multisig signers by public address, signing threshold, and replacement procedure;
- timelock duration and every function exempt from the timelock;
- whether the contract is immutable, upgradeable, pausable, revocable, or recoverable;
- implementation and proxy addresses for any upgradeable design;
- release schedule and machine-readable next-unlock state;
- current balance, released amount, remaining amount, and destination history;
- security review status and known limitations.

Where discretion is unavoidable, Rabbit Chain should use separated allocation addresses, a multisig threshold greater than one signer, and an on-chain timelock appropriate to the action. The existence of a multisig does not by itself make a treasury decentralized; signer concentration and legal/operational relationships must also be disclosed.

No private agreement may override the public rules. Emergency, pause, upgrade, recovery, sweep, recipient-change, arbitrary-call, self-destruct, or token-rescue permissions must be documented prominently rather than hidden in source code.

7.5 Reporting and reconciliation

At launch and at regular intervals, Rabbit Chain should publish an allocation reconciliation that third parties can reproduce:

Network reconciliation: $\text{genesis allocations} + \text{protocol issuance} - \text{burned RAB} = \text{observable supply}$.

For each reserved allocation:

Allocation reconciliation: $\text{initial reserve} = \text{current balance} + \text{released amount} + \text{documented burn}$, if any.

Reports must link to raw addresses and transactions rather than rely only on screenshots or manually entered totals. Corrections must remain in public version history; an incorrect prior report should not be silently replaced.

How the fixed 15,000,000 RAB allocation is made auditable

The testnet pool is carved out of the former 500,000 RAB operations allocation — it is not extra supply.




Figure 3. Native consensus balances and public vault/treasury balances converge in one reproducible allocation registry.

The table is an allocation ceiling and disclosure, not a forecast of market value. Circulating supply at any moment depends on genesis allocation, protocol issuance, locks, vesting, rewards, fee burning where applicable, and any provably inaccessible balances.

8. Testnet participation program

The public testnet is intended to validate real activity from blocks 1 through 100,000. A planned **100,000 RAB mainnet reward pool** is reserved from the fixed 15,000,000 RAB allocation described in Section 7. It does not increase maximum supply and cannot also be counted as operational spending.

Category	Planned pool
Miners	50,000 RAB

Category	Planned pool
Builders	30,000 RAB
Testers	15,000 RAB
Valid bug hunters	5,000 RAB
Total reserved	100,000 RAB

Eligibility is based on verifiable testnet activity, such as mining, transactions, deployments, use, and accepted bug reports. Likes, follows, reposts, or other social engagement do not determine rewards. Full criteria, wallet-verification procedures, exclusions, anti-abuse rules, and dispute handling must be published before block 1.

Planned distribution occurs six months after official mainnet liquidity begins, subject to the final published program rules and legal review. Testnet assets themselves have no promised monetary value.

8.1 Reward-vault transparency

Before mainnet distribution, the 100,000 RAB must be held in a dedicated public reward vault or equivalently restrictive on-chain mechanism. Its balance must not be commingled with the 400,000 RAB operations treasury.

The recommended claim design is a verified, fixed-cap distribution contract whose total successful claims can never exceed 100,000 RAB. If a Merkle-root claim system is used, Rabbit Chain must publish the complete underlying allocation file so anyone can reconstruct the root and verify their proof. Publishing only a root is not sufficient transparency.

Before testnet block 1, separate program rules must freeze or explicitly define:

- the exact eligibility window: blocks 1 through 100,000, inclusive;
- recognized activity for each category and its measurement method;
- whether one wallet may qualify in multiple categories;
- per-wallet minimums, maximums, ties, rounding, and anti-Sybil treatment;
- prohibited behavior, exclusions, sanctions, and evidence standards;
- bug severity definitions, duplicate-report priority, and disclosure rules;
- preliminary-results publication, challenge procedure, and decision authority;
- final allocation dataset format and cryptographic hash;
- the objective on-chain event or timestamp that starts the six-month delay;
- claim opening, claim deadline, unclaimed-RAB destination, and recovery rules;
- tax, sanctions, jurisdiction, identity, and legal restrictions if applicable.

No social engagement metric may be introduced later as a hidden eligibility factor. Any rule amendment after block 1 must be versioned, dated, justified, and assessed for its effect on participants who acted under the earlier rules.

8.2 Public distribution dataset

The final distribution publication must contain at least:

Field	Purpose
Eligible wallet	Identifies the on-chain recipient
Category	Miner, builder, tester, or valid bug hunter
Measured contribution	Reproducible basis for eligibility
Assigned RAB	Exact mainnet amount
Calculation version	Links the row to the published methodology
Evidence references	Testnet blocks, transactions, deployments, reports, or accepted issues
Claim status	Unclaimed, claimed, rejected, expired, or otherwise resolved

Personal information should not be published merely for transparency. The public dataset should expose what is necessary to verify allocation correctness while avoiding unnecessary identity data.

9. EVM execution and fees

Rabbit Chain preserves the account-based Ethereum execution model and EVM semantics supplied by its versioned go-ethereum foundation. This enables Solidity smart contracts, familiar address formats, signed transactions, logs, receipts, ABI tooling, and standard wallet integration.

The network is designed to support EIP-1559-style dynamic fee transactions and base-fee accounting. Users specify fee limits and priority fees; the protocol calculates block base fees according to canonical gas usage rules. Compatibility claims always apply to the specific Rabbit release and activated fork schedule, not automatically to every future Ethereum change.

Consensus compatibility and EVM compatibility are different claims. Rabbit does not use Ethereum's present consensus protocol, validator set, finality gadget, network ID, or native asset.

10. Networking and infrastructure

Rabbit Chain uses peer-to-peer block, transaction, and consensus propagation. Official infrastructure is intended to provide an initial access path, not an exclusive gateway.

The public-testnet launch plan includes:

- two independently hosted discovery/boot entry points;
- one public HTTP/WebSocket RPC service;

- one block explorer and indexer;
- DNS, TLS, rate limiting, firewalling, monitoring, and backup procedures;
- public instructions for community-operated nodes, RPC endpoints, and explorers.

Bootnodes help peers find one another but do not grant consensus authority. An RPC endpoint exposes node functions but does not define canonical truth. An explorer indexes chain data but is not the chain. Users should be able to verify data using their own node.

Official launch infrastructure must use fresh datadirs, chaindata, node keys, databases, and runtime secrets. Laboratory state is never promoted into the public network. Only audited source, validated binaries, deliberately finalized genesis/configuration, and reproducible deployment procedures may be reused.

10.1 Official domains and stable endpoint plan

The following names are reserved as the stable official interface. A reserved endpoint is not evidence that a service is already live. Before activation, the website and repository must mark it **inactive**; after activation, DNS, TLS, service identity, chain ID, genesis hash, and health checks must all agree.

Purpose	Testnet	Mainnet	Pre-launch status
Website	https://rabbitchain.org/	https://rabbitchain.org/	Active project website
Documentation	https://docs.rabbitchain.org/	https://docs.rabbitchain.org/	Reserved until documentation deployment
HTTP RPC	https://rpc-testnet.rabbitchain.org/	https://rpc.rabbitchain.org/	Reserved; must not be presented as active before health verification
WebSocket RPC	wss://rpc-testnet.rabbitchain.org/ws	wss://rpc.rabbitchain.org/ws	Reserved; must not be presented as active before health verification
Explorer	https://explorer-testnet.rabbitchain.org/	https://explorer.rabbitchain.org/	Reserved until indexer verification
Faucet	https://faucet-testnet.rabbitchain.org/	Not applicable	Reserved; testnet assets only
Network status	https://status.rabbitchain.org/	https://status.rabbitchain.org/	Reserved until monitoring deployment
Downloads	https://rabbitchain.org/downloads	https://rabbitchain.org/downloads	Planned permanent release page
Source organization	https://github.com/rabbitmainnet	https://github.com/rabbitmainnet	Active official organization

The mainnet faucet cell is intentionally “Not applicable”: the project will not promise free mainnet RAB through a faucet. Community-operated endpoints may use other domains, but they must not be represented as official Rabbit Chain infrastructure.

10.2 Launch identity file

For machine-readable verification, each public network should publish a versioned `network-manifest.json` from the website and repository containing:

- network name, chain ID, native symbol, and genesis hash;
- canonical genesis/configuration download URL and SHA-256;
- release tag, source commit, binary names, platforms, and SHA-256 hashes;
- official bootnode records;
- HTTP RPC, WebSocket RPC, explorer, faucet where applicable, status, and documentation URLs;
- activation block/epoch for every consensus-relevant feature;
- contract registry URL and hash;
- creation timestamp, manifest version, and signature or equivalent authenticity proof.

Wallet setup pages, explorer metadata, releases, and third-party listings should be generated from or checked against this manifest to reduce copy-and-paste inconsistencies.

11. Security model

11.1 Protected properties

Rabbit's validation rules are designed to protect:

- deterministic agreement on the eligible set and queue;
- a maximum of one canonical seat per wallet per epoch;
- rejection of invalid, stale, replayed, or duplicate work;
- authentication of the expected producer;
- deterministic reward calculation;
- persistence of canonical state across restart;
- separation between laboratory and production activation contexts.

11.2 Sybil resistance and limitations

Wallet deduplication prevents process-level multiplication behind the same address. Bonding, work cost, activation delay, recent activity, and jailing increase the cost of operating many addresses. They do not make Sybil attacks impossible and do not prove civil identity.

An attacker with many funded, active wallets and sufficient compute may obtain many eligible seats. Security therefore depends on economic parameters, distribution of participants, client correctness, peer connectivity, key safety, and honest validation by independent nodes.

11.3 Key and operational risks

Participants are responsible for wallet and node-key security. Compromise can enable unauthorized signing, reward theft, or network impersonation. RPC operators must disable dangerous administrative namespaces, protect signing interfaces, rate-limit public methods, and separate public traffic from authenticated engine or management interfaces.

11.4 Smart-contract and bridge risks

EVM compatibility permits arbitrary contracts, including unsafe or malicious ones. The base protocol does not audit user contracts. Bridges and wrapped assets introduce separate custody, oracle, validator, liquidity, and upgrade risks. Users must distinguish native RAB from third-party tokens and representations.

11.5 Experimental status

Before mainnet, Rabbit Chain remains experimental software. Testnet results reduce uncertainty but do not prove absence of vulnerabilities. Independent source review, reproducible builds, adversarial testing, incident procedures, and an appropriately scoped bug-bounty process remain necessary.

12. Validation evidence

Rabbit's pre-server gate tested the production code path before public infrastructure was created. The extraordinary live-seat test resumed a preserved three-node chain, established full peer connectivity, launched three real RandomX miner processes using the same wallet, and waited for canonical inclusion.

Observed result:

Evidence	Result
Real miner processes	3
Unique mining wallets	1
Canonical WorkSeats for the wallet	1 per epoch
Duplicate wallet seat	0
Canonical ticket	Block 504, epoch 3
Re-audit after node restart	PASS
Genesis changed during gate	No
Source changed during gate	No
Public servers/mining started	No

Evidence file:

`docs/audits/rabbit-testnet-extraordinary-live-seat-e9875409d.txt`

SHA-256:

`6bb8cf1e20e5428ec9206cc0a552071cf16463818ba2b25e09efa6d748534b64`

The report was committed to the official `testnet-release-v1` branch at documentation checkpoint `b9967ca73cf5fe30b854d10ae55a48f2127efb2c`. Later documentation commits do not change the validated source commit used by the tested binaries.

This evidence supports the tested invariant under the tested conditions. It is not a mathematical proof of all possible executions and should not be presented as an independent security audit.

13. Governance and upgrades

Rabbit Chain's consensus should not depend on an administrator contract or an undisclosed privileged key. Protocol evolution occurs through public source changes, reviewable releases, explicit activation rules, and community adoption of compatible clients.

During the pre-testnet phase, the founding development team coordinates releases and infrastructure. This practical coordination is disclosed as a centralization risk. The long-term objective is to reduce dependency on official infrastructure by enabling independent nodes, miners, RPC operators, explorers, developers, and reviewers.

Any consensus upgrade should publish:

23. motivation and security analysis;
24. exact source diff and release commit;
25. activation network and block/epoch;
26. backward-compatibility and rollback implications;
27. reproducible binaries and hashes;
28. test evidence and migration instructions.

14. Roadmap and launch gates

The roadmap is gate-driven rather than date-driven.

Completed before infrastructure

- production Work V1 activation gates;
- fresh multi-node consensus and restart exercises;
- reward and canonical-state checks;
- live same-wallet multi-process seat deduplication;
- evidence committed to the official repository.

Required before public testnet block 1

- freeze and publish testnet genesis and chain configuration;
- reproducibly build and hash Windows, Linux, and macOS packages;
- deploy fresh bootnodes, RPC/archive node, and explorer/indexer;
- configure DNS, TLS, firewalls, rate limits, monitoring, and backups;
- publish miner, node, developer, and wallet instructions;
- publish testnet reward-program terms and risk disclosure;
- complete a public-infrastructure dry run without opening mining;
- announce an exact, verifiable start procedure.

Required before mainnet

- incorporate public-testnet findings;
- complete independent security review appropriate to the final scope;
- finalize issuance, halving, lock, vesting, and fee policies;
- finalize mainnet genesis with public hashes and review window;
- prepare incident-response and responsible-disclosure processes;
- launch entirely fresh mainnet infrastructure and state.

Mainnet publication substitution checklist

This pre-testnet edition deliberately fixes the document structure before final mainnet values exist. The mainnet publication process must replace every field below and must fail if any placeholder remains:

Field to finalize	Required evidence
Mainnet genesis hash	Published genesis file, SHA-256, and canonical block-0 hash
Final source/release commit	Signed tag, source archive, reproducible build record, and binary hashes
Bootnodes	Complete enode/ENR records, regions, operators, and connectivity test
RPC/explorer/status services	DNS, TLS certificate, health check, chain ID, genesis identity, and operator disclosure
Allocation addresses	Address, label, exact initial balance, funding/genesis proof, and allocation sum
Contract addresses	Deployment transaction, verified source, bytecode hash, constructor arguments, and security review
Multisigs and timelocks	Signer addresses, threshold, relationships, delay, guarded functions, and replacement policy
Vesting start reference	Objective liquidity activation transaction/event and

Field to finalize	Required evidence
	resulting timestamp/block
Testnet reward root	Full public allocation dataset, hash, reproducible root script, contract root, and claim proofs
Legal and risk disclosures	Version, effective date, jurisdictional limitations, and immutable publication hash

The final release must run an automated placeholder scan for strings such as TBD, TODO, PLACEHOLDER, {ADDRESS}, zero addresses used as unknown values, example domains, and unresolved template variables. Passing that scan does not prove correctness, so human and on-chain verification remain required.

15. Reproducibility and verification

A professional release must allow third parties to connect documents to executable artifacts. Each release should publish:

- Git commit and signed tag;
- genesis and configuration hashes;
- source archive hash;
- binary hashes by operating system and architecture;
- compiler, toolchain, build flags, dependencies, and build script;
- audit/gate evidence hashes;
- network identifiers, bootnode records, and official domains.

Users should verify downloaded binaries against published hashes and obtain hashes through more than one official channel where possible.

16. Parameters snapshot

The following values describe the current pre-launch reference configuration. The finalized public-testnet genesis supersedes this table.

Parameter	Reference value
Testnet chain ID	9280
Planned mainnet chain ID	928
Target block time	10,000 ms
Fallback slots	5
Fallback window	3,000 ms

Parameter	Reference value
Epoch length	128 blocks
Activity window	128 blocks
Committee minimum	32
Committee maximum	128
Committee reward ratio	3,000 bps
Producer reward ratio	7,000 bps
Work proof	RandomX / Work V1
Reference proof difficulty	100,000
Producer seal length	65 bytes

17. How to participate

Rabbit Chain is intended to support several independent roles. One person may perform more than one role, but each role has different responsibilities.

Role	What the participant does	What is required
User	Holds RAB, sends transactions, uses applications	EVM wallet, correct network configuration, RAB for gas
Miner/participant	Produces valid work and may receive an LCQ queue seat	Rabbit client, participant wallet, CPU resources, bond/activity required by the released rules
Node operator	Verifies and propagates blocks and transactions	Rabbit node, storage, bandwidth, uptime, secure configuration
RPC operator	Gives wallets and applications remote node access	Hardened node, HTTPS/WSS, rate limits, monitoring, restricted administrative APIs
Explorer operator	Indexes and presents public chain data	Indexer, database, archive-capable data source, web service
Builder	Deploys contracts, applications, tooling, or integrations	Solidity/EVM knowledge, test RAB, RPC access, development tools
Tester	Exercises wallets, transactions, contracts, mining, recovery, and UX	Test plan, reproducible reports, transaction hashes and logs
Reviewer	Reviews source, builds, cryptography integration, economics, or	Relevant expertise and precise, reproducible findings

Role	What the participant does	What is required
	documentation	

Before the public testnet begins, users should rely only on links published through Rabbit Chain's official website and repository. They should verify the chain ID, genesis hash, software hash, RPC endpoint, explorer domain, and release commit. No one should share a seed phrase or private key with a website, administrator, support agent, miner, faucet, or RPC operator.

17.1 First-day user flow

29. Open the official release page from rabbitchain.org or the verified GitHub organization.
30. Download the package for the correct operating system and verify its SHA-256 hash.
31. Create a new testnet-only wallet or import a deliberately selected test wallet; never expose its private key.
32. Add Rabbit Testnet using the published chain ID 9280, official RPC, currency symbol, and explorer URL.
33. Obtain valueless testnet RAB from the official faucet when available.
34. Send a small transaction and confirm it independently in the wallet, RPC, and explorer.
35. Builders may deploy a test contract; miners may follow the published node and mining guide.
36. Save transaction hashes, block numbers, logs, software version, and steps when reporting a problem.

The exact commands, ports, RPC URL, explorer URL, bootnodes, faucet URL, genesis hash, and release hashes are intentionally not frozen in this pre-launch whitepaper. They belong in versioned launch documentation because publishing placeholders as final values would create user risk.

18. Frequently asked questions

Is Rabbit Chain already public?

Not at the v0.9 checkpoint. Consensus gates were completed locally before public servers or public mining were activated.

Does one wallet always receive a block?

No. One wallet/one seat is an upper bound on canonical seats per epoch, not a guaranteed seat, block, reward, or income. The wallet must satisfy all protocol rules and valid work still has probabilistic cost.

Can I run more than one miner?

Yes, for redundancy or to search for the wallet's first valid proof. Multiple processes using the same wallet must not create multiple canonical seats for that wallet in one epoch.

Can one person create many wallets?

Yes. LCQ does not prove human identity. Work, bond, activation delay, activity, and penalty rules are intended to make mass participation costly and observable, but they cannot eliminate every Sybil strategy.

Is expensive mining hardware required?

RandomX is designed for general-purpose CPUs, but performance still varies by processor, memory, configuration, energy cost, software, and network difficulty. The project does not promise equal hardware performance or profit.

Is Rabbit Chain an Ethereum network?

Rabbit is an independent network with its own consensus, chain IDs, native asset, genesis, peers, and canonical history. EVM compatibility means it reuses the Ethereum execution environment and common tooling; it does not mean Ethereum secures Rabbit.

Who controls the queue?

No RPC, explorer, bootnode, website, or administrator should assign queue positions. Each validating node derives the queue from canonical protocol state.

What happens if the official RPC or explorer stops?

The chain can continue when independent peers and producers remain active. Users may run their own node, and community operators may provide alternative RPCs and explorers. Official services are access infrastructure, not consensus authorities.

What happens when no miner is online?

Block production may stop. When valid participation returns, recovery proceeds from preserved canonical history under the active rules; the chain is not supposed to erase history or appoint a secret emergency producer.

Are testnet tokens valuable?

Testnet assets have no promised monetary value. Any separate participation reward program follows its own published eligibility, verification, timing, legal, and anti-abuse rules.

Where are final parameters found?

In this order of authority: canonical chain state, released genesis/configuration, versioned source code, signed release artifacts, and then explanatory documentation such as this whitepaper.

19. Glossary

Term	Meaning in Rabbit Chain
Activation delay	Waiting period between participant recognition and eligibility for queue influence
Bond	Protocol-defined economic requirement associated with participant eligibility
Bootnode	Peer-discovery entry point; it does not control consensus
Canonical chain	The history accepted under the active consensus rules
Committee	Deterministically selected eligible participants sharing the configured committee reward
EVM	Ethereum Virtual Machine execution environment used for accounts and smart contracts
Epoch	Fixed block interval used to organize work, eligibility, or seat accounting
Fallback	Rule that permits another eligible producer after a scheduled producer misses its allowed window
Genesis	The network's initial block and configuration; its hash identifies the chain history
Jailing	Temporary protocol state that makes a sanctioned participant ineligible
LCQ	Live Consensus Queue, Rabbit's consensus and production-order mechanism
Participant	Wallet-addressed entity tracked by the canonical LCQ registry
Producer	Eligible participant scheduled to construct and sign a particular block
RandomX	CPU-oriented proof-of-work algorithm used by Rabbit's Work V1 path
Registry	Canonical participant state used to determine eligibility
RPC	Remote interface used by wallets and applications to query or submit data to a node

Term	Meaning in Rabbit Chain
Seat/WorkSeat	Wallet-bounded, epoch-scoped canonical participation position obtained through valid work and eligibility
Sybil attack	Attempt to gain influence by operating many apparent identities
Ticket	Work V1 proof submission bound to a canonical work context
Work context	Epoch, challenge, dataset, difficulty, and related canonical data against which a proof is produced

20. Conclusion

Rabbit Chain proposes a specific change to permissionless block production: computational effort admits an eligible wallet into a deterministic live queue, while canonical state prevents that wallet from multiplying seats by multiplying processes. LCQ combines this wallet-bounded opportunity with EVM execution, RandomX work, deterministic producer authentication, committee rewards, fallback rules, and recoverable canonical state.

The project should be judged by reproducible code and observable network behavior, not slogans. The next milestone is not a claim of completion; it is a fresh public-testnet deployment whose genesis, binaries, infrastructure, rules, and evidence can be independently inspected from block 1.

References

- 37. Rabbit Chain source repository: <https://github.com/rabbitmainnet/rabbit-geth>
- 38. Rabbit Chain website: <https://rabbitchain.org/>
- 39. Rabbit Chain community: <https://discord.gg/TBWspuEZss>
- 40. RandomX source and documentation: <https://github.com/tevador/RandomX>
- 41. Ethereum Yellow Paper: <https://ethereum.github.io/yellowpaper/paper.pdf>
- 42. EIP-1559 specification: <https://eips.ethereum.org/EIPS/eip-1559>

Version history

Version	Date	Description
0.9	29 August 2026	Pre-testnet technical edition; LCQ architecture, fixed 15,000,000 RAB allocation, 100,000 RAB testnet reserve sourced from the former operations allocation, contract/treasury transparency framework, validation evidence, risks, launch gates, participation guide, FAQ, and glossary

Contact and official channels

- Website: <https://rabbitchain.org/>
- GitHub: <https://github.com/rabbitmainnet>
- X: https://x.com/rabbit_mainnet
- Discord: <https://discord.gg/TBWspuEZss>

© 2026 Rabbit Chain contributors. Distribution permitted with attribution. Protocol behavior remains governed by the applicable open-source license and versioned source code.