

PVL WUUDPLY®

**Made from
Naturally Resistant &
Durable Timber**

www.wuudply.in





40

Years of Trust

Wuud Ply is one of the most trusted names in South India for authentic timber-based plywood since 1980s, from the house of Primeply Industries which also produces Prime Ply.

40

Years of Leadership

We're among the first Indian companies to introduce 100% Gurjan plywood, imported from our own factory in Myanmar, and among the first to get the IS710 certification.

40

Years of Quality

Using naturally resistant timber species, we avoid the use of harmful chemicals. Every Wuud Ply product passes stringent 5-point quality checks before shipping to dealerships.

40

Years of Service

Prime and Wuud Ply have one of the strongest dealer networks in South India. This means trust worthy service, quick response, and reliable supply of a wide range of plywood products.



Our Products



Plywoods



Doors




Boards



Veneers

Plywoods

A superior range of commercial
and waterproof plywood



WUUDPLY PLATINO

Marine Grade (IS710)

LIFETIME GUARANTEE

Made of 100% Gurjan core veneer
Bonded with Phenolic Resin
Highest density and superior strength
Naturally resistant characteristics of Gurjan
Best for industrial applications, kitchens

Technical Specification

	IS710
Density	0.72 to 0.80g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	50
MOE	9000
Knife Test	Excellent
Water Resistance	Excellent (72Hrs)

Calibrated to perfect and accurate thickness

WUUDPLY 101

Fire Retardant (IS5509) & Marine Grade (IS710)

15 YEARS GUARANTEE

Fire and Water resistant
Made of tropical hardwood
Best for kitchens, and bathrooms

Technical Specification

	IS5509
Density	0.72 to 0.80g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	40
MOE	9000
Knife Test	Excellent
Water Resistance	Excellent (72Hrs)

WUUDPLY ELITE

Marine Grade (IS710)

30 YEARS GUARANTEE

Made of Gurjan and tropical hardwood
Bonded with Phenolic Resin
100% Borer-proof
Best for industrial applications & kitchens

Technical Specification

	IS710
Density	0.72 to 0.80g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	50
MOE	8000
Knife Test	Excellent
Water Resistance	Excellent (72Hrs)

Calibrated to perfect and accurate thickness

WUUDPLY HD

Marine Grade (IS710)

20 YEARS GUARANTEE

Nilgiri Eucalyptus core veneers
Bonded with phenolic formaldehyde resin
Withstands wet conditions &
temperature variations.
Also available in commercial UF resin

Technical Specification

	IS710
Density	0.72 to 0.80g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	50
MOE	7500
Knife Test	Excellent
Water Resistance	Excellent (72Hrs)

Calibrated to perfect and accurate thickness

WUUDPLY STEEL

Shuttering Plywood (IS4990)

Naturally durable cross-band veneers
Bonded with Phenolic resin
Face veneer topped with phenolic resin film
Best for construction and industry

Technical Specification

	IS4990
Density	0.95 -1g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	50
MOE	7500
Knife Test	Excellent
Water Resistance	Excellent (72Hrs)

WUUDPLY DIAMOND

Chequered Ply (IS3513)

Chequered, anti-skid plywood
Bonded with phenolic resin
Best suited for vehicle flooring, containers
and industrial flooring.
100% water proof highly durable shutters.

Technical Specification

IS3513	
Density	0.80 - 0.90g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	50
MOE	7500
Knife Test	Excellent
Water Resistance	Excellent (72Hrs)

WUUDPLY DIAMOND

CHEQUERED PLYWOOD FOR TRUCK FLOORS



WUUDPLY FLEXI

Perfect Shape to Your Designs

Specially engineered for flexibility
Best for cabins, hemispherical shapes,
panels and pillars
No special equipment required

Technical Specification

Density	0.70- 0.80g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	40
MOE	5000
Knife Test	Excellent
Water Resistance	Excellent

WUUDPLY ECO

Commercial Grade (IS303)

Made of select hardwood
Available in water proof, water resistant & commercial UF resin

Technical Specification

	IS303
Density	0.72 to 0.80 g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	40
MOE	5000
Knife Test	Excellent
Water Resistance	Excellent

Doors

Pioneers of Total Vacuum
Pressure Treatment



WUUDBOARD FLUSH DOORS (IS2202)

Total Vacuum Pressure Treatment (VPT)
for entire frame and core

Guaranteed complete protection from
borer and fungus attacks

Innovative and Sophisticated Flush Doors
as per customer requirements

Mica or Paint finish can be added

Technical Specification

IS2202	
Density	0.72 to 0.80 g/cc
Moisture Content	8 - 12%
Knife Test	Excellent
Water Resistance	Excellent

WUUDBOARD MOULDED PANEL (SKIN) DOORS

Made from Imported High Quality
High Density Fibre Skins
Collaboration with leading branded door-skin
manufactures in the world
Access to the entire, original collection in a
variety of styles, finishes and textures
Excellent durability, superior finish and
resistance to stain and scratches

Technical Specification

Density	0.72 to 0.80 g/cc
Moisture Content	8 - 12%
Knife Test	Excellent
Water Resistance	Excellent

Block Boards

IS1659 Block Boards from select high-quality seasoned timber



WUUDBOARD


Wuudboard boards are made from carefully selected high quality timber that is seasoned under controlled temperate and humidity to get uniform moisture, and sterilized to kill wood-destroying organisms. Stringent quality controls are maintained to make these block boards absolutely free from corrugation and unevenness. Wuudboard boards can be easily laminated without any deformity.

Technical Specification

	IS1659
Density	0.72 to 0.80 g/cc
Moisture Content	8 - 12%
Bending Strength	
MOR	50
MOE	5500
Knife Test	Excellent
Water Resistance	Excellent

Veneers

Wide range of premium
decorative veneers



WUUDPLY KRAFT

Decorative veneers

One of our founding products, Wuudply Kraft Decorative Veneers are made available in accordance with customer preferences at competitive prices. They can be pasted on to plywood/boards to get a natural wood finish and polished to get a rich look. We’ve been closely following the changing demands in the market and updating our range constantly. Ask for the latest.

Species:
Teak, Wenge, Sapele, Red Oak, Walnut

Technical Specification

Density	0.72 to 0.80 g/cc
Moisture Content	8 - 12%
Glue Shear	135
Bending Strength	
MOR	50
MOE	7500
Knife Test	Excellent
Water Resistance	Excellent (72Hrs)

**Primeply Industries Ltd, Mill Road,
Valapattanam, Kerala 670010**

www.wuudply.in

info@wuudply.in

[instagram.com/wuudply](https://www.instagram.com/wuudply)

All information provided in this brochure is true at the time of printing and may be subject to change without notice at the discretion of Primeply Industries.© 2024 Primeply Industries Ltd.