

HEAP

Priority Queue (FAANG Cheat Sheet)

PAGE 1

Fundamentals & Java Basics

1 WHAT IS A HEAP?

- A Heap is a **Complete Binary Tree**.
- It satisfies the **Heap Property**.
- It is **NOT** a sorted data structure.
- Only the root element is guaranteed to be the minimum (Min Heap) or maximum (Max Heap).
- Heaps are used to implement **Priority Queue**.

2 MIN HEAP VS MAX HEAP

MIN HEAP

Parent $\leq$ ChildrenSmallest element
is at the root.

MAX HEAP

Parent $\geq$ ChildrenLargest element
is at the root.

```
graph TD
    classDef redNode fill:#fff,stroke:#ef4444,stroke-width:2px,color:#ef4444,font-weight:bold;
    A((10))::redNode --> B((9))::redNode
    A --> C((7))::redNode
    B --> D((3))::redNode
    B --> E((5))::redNode
    C --> F((1))::redNode
    C --> G((2))::redNode
```

3 COMPLETE BINARY TREE

All levels are completely filled except possibly the last level, and all nodes in the last level are as far left as possible.



```
graph TD
    classDef default fill:#e2e8f0,stroke:#94a3b8,stroke-width:2px,color:#3b82f6,font-weight:bold;
    A(( ))::default --> B(( ))::default
    A --> C(( ))::default
    B --> D(( ))::default
    B --> E(( ))::default
    C --> F(( ))::default
```



```
graph TD
    classDef default fill:#e2e8f0,stroke:#94a3b8,stroke-width:2px,color:#3b82f6,font-weight:bold;
    A(( ))::default --> B(( ))::default
    A --> C(( ))::default
    B --> D(( ))::default
    B --> E(( ))::default
    C --> F(( ))::default
    C --> G(( ))::default
```

4 ARRAY REPRESENTATION (0-INDEXED)

Example Tree

```
graph TD
    classDef blueNode fill:#fff,stroke:#3b82f6,stroke-width:2px,color:#3b82f6,font-weight:bold;
    A((1))::blueNode --> B((2))::blueNode
    A --> C((3))::blueNode
    B --> D((4))::blueNode
    B --> E((5))::blueNode
    C --> F((6))::blueNode
    C --> G((7))::blueNode
```

Index Relationships

```
Parent(i) = (i - 1) / 2
Left(i) = 2 * i + 1
Right(i) = 2 * i + 2
```

Array Representation

Index	0	1	2	3	4	5	6
Value	1	2	3	4	5	6	7

6 JAVA PRIORITYQUEUE

a) Min Heap (Default)

```
PriorityQueue<Integer> minHeap = new PriorityQueue<>();
// Smallest element at peek()
```

b) Max Heap (3 Ways)

1. Using Collections.reverseOrder() (Recommended)

```
PriorityQueue<Integer> maxHeap =
    new PriorityQueue<>(Collections.reverseOrder());
```

2. Using Comparator (Integer.compare)

```
PriorityQueue<Integer> maxHeap =
    new PriorityQueue<>((a, b) -> Integer.compare(b, a));
```

3. Using subtraction (Not recommended - overflow risk)

```
PriorityQueue<Integer> maxHeap =
    new PriorityQueue<>((a, b) -> b - a);
```

c) Common Operations

Method	Description
offer(x)	Inserts element x into heap.
poll()	Removes and returns root element (min or max).
peek()	Returns root element without removing.
size()	Returns number of elements.
isEmpty()	Checks if heap is empty.

7 IMPORTANT TERMINOLOGY

Root	: Topmost element.
Parent(i)	: $(i - 1) / 2$
Left Child(i)	: $2 * i + 1$
Right Child(i)	: $2 * i + 2$
Height	: Longest path from root to leaf.
Leaf Node	: Node with no children.
Heapify	: Process of restoring heap property (Bubble Up or Bubble Down).

5 TIME COMPLEXITIES

Operation	Min Heap	Max Heap	Why?
offer(x)	$O(\log n)$	$O(\log n)$	Heapify Up
poll()	$O(\log n)$	$O(\log n)$	Heapify Down
peek()	$O(1)$	$O(1)$	Root access
size()	$O(1)$	$O(1)$	Just length
isEmpty()	$O(1)$	$O(1)$	Just length
Build Heap (n elements)	$O(n)$	$O(n)$	Bottom-up heapify

★ **Build Heap** (Bottom-Up) is $O(n)$ which is better than inserting n elements one by one ($O(n \log n)$).

8 KEY POINTS TO REMEMBER

- ✓ Heap is a Complete Binary Tree.
- ✓ Heap $\neq$ Sorted Array.
- ✓ Heaps are used for **Priority**, not order.
- ✓ Choose **Min Heap** or **Max Heap** based on the problem goal.
- ✓ Heap operations are logarithmic time ($O(\log n)$).

9 COMMON MISTAKES

- ✗ Confusing Min Heap with Max Heap.
- ✗ Using wrong comparator.
- ✗ Forgetting that default PriorityQueue in Java is Min Heap.
- ✗ Not handling empty heap before poll/peek.
- ✗ Assuming heap gives sorted order.

💡 **Golden Rule: Heaps are all about PRIORITY.** → Next Page: Heap Patterns Overview
Ask: "What element should come out first?"

HEAP - PATTERNS

PAGE 2

Top Interview Patterns with Heaps (Priority Queue)

Max Heap → largest element on top **Min Heap** → smallest element on top **PQ** → PriorityQueue

PATTERN 1 REPEATED MAX / MIN RETRIEVAL (e.g., Last Stone Weight)

WHEN TO USE?

- We always take the largest (or smallest) element.
- Do something with it.
- Put the result back.
- Repeat until 1 (or none) left.

HEAP TO USE

Max Heap → largest
graph TD A((7)) → B((5))
A → C((6)) B → D((2)) B
→ E((4)) C → F((1)) C --
→ G((3))

IDEA / AHA



We always care about the current largest element.

Heap gives it in $O(1)$.

TEMPLATE (JAVA)

```
PriorityQueue<Integer> pq =
    new PriorityQueue<>
        (Collections.
            reverseOrder()); // Max Heap

// Build heap
for (int x : arr) pq.offer(x);

while (pq.size() > 1) {
    int a = pq.poll(); // largest
    int b = pq.poll(); // 2nd
    largest
    if (a != b) pq.offer(a - b);
}
return pq.isEmpty() ? 0 :
    pq.peek();
```

COMPLEXITY

- **Time:** $O(n \log n)$
(n insertions + up to n polls)
- **Space:** $O(n)$

EXAMPLES

- LeetCode 1046 Last Stone Weight

PATTERN 2 TOP-K ELEMENTS (e.g., Kth Largest, Top K Frequent)

WHEN TO USE?

- Need the K largest/smallest elements.
- Or K most frequent, top K, K closest, etc.
- We discard the rest.

HEAP TO USE

Top K Largest → **Min Heap (size K)**
graph TD A((1)) → B((2))
A → C((3))
(Keep K=3 largest seen so far)

Top K Smallest → **Max Heap (size K)**
graph TD D((9)) → E((8)) D → F((7))
(Keep K=3 smallest seen so far)

IDEA / AHA

Keep only K best candidates in heap.

If better element comes, replace root (worst among K).

TEMPLATE (JAVA)

→ **Top K Largest (Min Heap)**

```
PriorityQueue<Integer> pq = new
    PriorityQueue<>();
for (int x : nums) {
    pq.offer(x);
    if (pq.size() > k) pq.poll(); //
    remove smallest
}
// pq contains top K largest
List<Integer> res = new ArrayList<>
    (pq);
```

→ **Top K Smallest (Max Heap)**

```
PriorityQueue<Integer> pq = new
    PriorityQueue<>
        (Collections.reverseOrder());
for (int x : nums) {
    pq.offer(x);
    if (pq.size() > k) pq.poll(); //
    remove largest
}
// pq contains top K smallest
```

- **Time:** $O(n \log k)$
- **Space:** $O(k)$

EXAMPLES

- LC 215 Kth Largest Element in Array
- LC 347 Top K Frequent Elements
- LC 973 K Closest Points to Origin
- LC 692 Top K Frequent Words

PATTERN 3 MERGE K SORTED LISTS / ARRAYS (e.g., Merge K Sorted Lists)**WHEN TO USE?**

- We have K sorted lists/arrays.
- Need to merge into one sorted output.
- Always pick the smallest current candidate.

HEAP TO USE**Min Heap**

graph LR A((1)) → B((4))
 → C((7)) D((2)) → E((5))
 → F((8)) G((3)) →
 H((6)) → I((9)) A -.→
 J[Min Heap] D -.→ J G
 -.→ J

1	2	3	4	5	6	7	8	9
---	---	---	---	---	---	---	---	---

IDEA / AHA

Put the first element of each list into heap.

Pop smallest node, add its next node (if exists).

TEMPLATE (JAVA)

```
class Node { int val; Node next; }

PriorityQueue<Node> pq = new
PriorityQueue<>()
(a, b) → a.val - b.val); // Min
Heap

// 1. Add head of each list
for (Node head : lists)
    if (head != null) pq.offer(head);

Node dummy = new Node(0), tail =
dummy;

while (!pq.isEmpty()) {
    Node cur = pq.poll();
    tail.next = cur; tail =
tail.next;
    if (cur.next != null)
        pq.offer(cur.next);
}
return dummy.next;
```

- **Time:** $O(N \log k)$
(N = total nodes,
 k = number of lists)
- **Space:** $O(k)$

EXAMPLES

- LeetCode 23
Merge K Sorted
Lists
- LeetCode 373
Find K Pairs with
Smallest Sums

PATTERN 4 TWO HEAPS (MEDIAN FROM DATA STREAM) (e.g., Find Median from Data Stream)**WHEN TO USE?**

- Need median at any point in a stream of numbers.
- Insertions happen one by one.
- Need $O(\log n)$ insert and $O(1)$ median.

HEAP TO USE

Max Heap
(Smaller Half)
 graph TD
 A((5)) →
 B((2)) A →
 C((3)) B →
 D((1)) B →
 E((4))

Min Heap
(Larger Half)
 graph TD
 F((8)) --
 > G((9)) --
 F →
 H((10))

IDEA / AHA

Maintain two halves.

- 1) $\text{maxHeap.peek()} \leq \text{minHeap.peek()}$
- 2) Size difference ≤ 1

Median is either top of one heap or avg of both.

TEMPLATE (JAVA) - (Add Number)

```
// maxHeap: left half (max heap)
// minHeap: right half (min heap)
PriorityQueue<Integer> maxHeap =
    new PriorityQueue<>()
    (Collections.reverseOrder());
PriorityQueue<Integer> minHeap = new
PriorityQueue<>();

void addNum(int num) {
    if (maxHeap.isEmpty() || num <=
maxHeap.peek())
        maxHeap.offer(num);
    else
        minHeap.offer(num);

    // Rebalance
    if (maxHeap.size() > minHeap.size()
+ 1)
        minHeap.offer(maxHeap.poll());
    else if (minHeap.size() >
maxHeap.size())
        maxHeap.offer(minHeap.poll());
}

double findMedian() {
    if (maxHeap.size() ==
minHeap.size())
        return (maxHeap.peek() +
minHeap.peek()) / 2.0;
    return maxHeap.peek();
}
```

- **addNum:** $O(\log n)$
- **findMedian:** $O(1)$
- **Space:** $O(n)$

EXAMPLES

- LeetCode 295
Find Median from
Data Stream

**AHA SUMMARY**

- ✓ What do I care about most right now? Put it on top!
- ✓ Use heap to discard what I don't need.
- ✓ Heap $\neq$ Sorting. Heap gives priority, not full order.

**PATTERN RECOGNITION TRIGGERS**

- Top K / Kth / Most Frequent / Closest / Smallest / Largest / Merge K / Running Median / Priority / Stream / Scheduler

HEAP - CHEAT SHEET & DECISION GUIDE

Quick Reference for Interviews

PAGE
3

1. HEAP DECISION TREE

graph TD
 Goal[What is the Goal?] --> L[Need largest element repeatedly?]
 Goal --> S[Need smallest element repeatedly?]
 Goal --> TopK[Need Top-K elements?]
 Goal --> MergeK[Merge K sorted sources?]
 Goal --> Median[Find Median from data stream?]
 L --> UMax[Use Max Heap (largest on top)]
 S --> UMin[Use Min Heap (smallest on top)]
 TopK --> Discard[What should we discard?]
 Discard --> DSmall[Discard smallest]
 Discard --> DLarge[Discard largest]
 DSmall --> UMinK[Use Min Heap (size K)]
 DLarge --> UMaxK[Use Max Heap (size K)]
 MergeK --> UMinMerge[Use Min Heap (one candidate from each source)]
 Median --> UTwo[Use Two Heaps (Min + Max)]
 classDef default fill:#f8f9fc,stroke:#cbd5e1,stroke-width:1px;
 classDef yellow fill:#fff9c4,stroke:#fcd34d,stroke-width:1px;
 classDef green fill:#e8f5e9,stroke:#a5d6a7,stroke-width:1px;
 classDef red fill:#ffe0b2,stroke:#ffb74d,stroke-width:1px;
 class L, S, TopK, MergeK, Median green;
 class UMax, UMin, UMinK, UMaxK, UMinMerge, UTwo yellow;
 class Discard, DSmall, DLarge, UMaxK, UMinMerge, UTwo red;

3. COMPLEXITY TABLE

Operation	Min Heap	Max Heap	Notes
Insert (offer)	$O(\log n)$	$O(\log n)$	Heapify Up
Remove (poll)	$O(\log n)$	$O(\log n)$	Heapify Down
Peek	$O(1)$	$O(1)$	Root access
Size	$O(1)$	$O(1)$	Just length
isEmpty	$O(1)$	$O(1)$	Just length
Build Heap (from n elements)	$O(n)$	$O(n)$	Bottom-up heapify

4. KEY INVARIANTS

Min Heap

For every node i :
 $\text{parent}(i) \leq \text{child}(i)$

Root = smallest element

graph TD
 A((2)) --> B((3))
 A --> C((5))
 B --> D((4))
 B --> E((7))
 C --> F((6))
 C --> G((8))
 classDef node fill:white,stroke:#000,stroke-width:1px;

Always true for all nodes

Max Heap

For every node i :
 $\text{parent}(i) \geq \text{child}(i)$

Root = largest element

graph TD
 A((10)) --> B((9))
 A --> C((7))
 B --> D((3))
 B --> E((5))
 C --> F((1))
 C --> G((2))
 classDef node fill:white,stroke:#dc2626,stroke-width:1px,color:#dc2626;

Always true for all nodes

2. JAVA TEMPLATES (QUICK)

Min Heap (Default)

```
PriorityQueue<Integer> minHeap =
    new PriorityQueue<>();
// smallest element at peek()
```

Max Heap (Using reverseOrder)

```
PriorityQueue<Integer> maxHeap =
    new PriorityQueue<>(Collections.reverseOrder());
// largest element at peek()
```

Max Heap (Using Comparator)

```
PriorityQueue<Integer> maxHeap =
    new PriorityQueue<>((a, b) -> Integer.compare(b, a));
// largest element at peek()
```

Top-K Largest (Min Heap of size K)

```
PriorityQueue<Integer> pq = new PriorityQueue<>();
for (int x : nums) {
    pq.offer(x);
    if (pq.size() > k) pq.poll(); // remove smallest
}
// pq contains k largest
```

Top-K Smallest (Max Heap of size K)

```
PriorityQueue<Integer> pq =
    new PriorityQueue<>((a, b) -> Integer.compare(b, a));
for (int x : nums) {
    pq.offer(x);
    if (pq.size() > k) pq.poll(); // remove largest
}
// pq contains k smallest
```

5. COMMON INTERVIEW CHECKLIST

- ✓ Understand the goal clearly.
- ✓ Ask: What should I keep? What should I discard?
- ✓ Choose the right Heap (Min / Max).
- ✓ Decide the size (K or all elements).
- ✓ Maintain Heap invariant after every insertion/removal.
- ✓ Think about edge cases (empty, $k = 0$, $k > n$, duplicates).
- ✓ Analyze Time and Space Complexity.

6. COMMON MISTAKES

- ✗ Using Min Heap when Max Heap is required (or vice versa).
- ✗ Forgetting that PriorityQueue in Java is Min Heap by default.
- ✗ Not maintaining heap size while solving Top-K problems.
- ✗ Forgetting to add next element in Merge K after poll().
- ✗ Not handling empty heap before peek()/poll().
- ✗ Using subtraction in comparator $(a - b) \rightarrow$ overflow risk.
- ✗ Confusing Heap with Sorted Array / Tree.

**7. AHA MOMENTS**

- ★ Heap gives you the best element in $O(1)$.
- ★ It is about PRIORITY, not sorting.
- ★ Think: "What should I discard?" for Top-K problems.
- ★ Merge K = One candidate per source.
- ★ Median = Balance two halves.

**PATTERN RECOGNITION TRIGGERS**

- | | |
|--------------------------------------|--|
| → Top K / Kth Largest / Kth Smallest | → Find Median / Running Median |
| → Most Frequent / Least Frequent | → Task Scheduler / CPU Scheduling |
| → Merge K Sorted / K Sorted Lists | → Closest K / Smallest Range / Meeting Rooms |

★ Remember: Every Heap problem belongs to one of the [4 patterns on Page 2](#).

HEAP - FAANG HIDDEN TRIGGERS

How Interviewers Hide Heap Problems (Recognition Guide)

They won't say "Use Heap"
You must recognize it !

1 WHEN TO THINK HEAP ? (UNSEEN QUESTION CLUES)

Question Says...	Think Heap Because...
Top K / K largest / K smallest	We only care about best K elements.
K closest / K farthest	Keep best K based on distance / value.
Kth largest / Kth smallest	Heap gives Kth in optimal time.
Most frequent / Top frequent	Use heap on frequency map.
Continuously receive data ("data stream")	Need to maintain running result.
Running median / Median at any time	Two Heaps maintain middle efficiently.
Merge K sorted lists / arrays / streams	Pick smallest current from K sources.
Always need smallest / largest repeatedly	Heap gives min/max in $O(\log n)$ each time.
Scheduling / Highest priority task	Always process highest (or lowest) priority first.
Resource allocation	Allocate best resource (min waste / min cost).
Find N smallest among millions	Min Heap of size N.
Live leaderboard / Top scores	Maintain top K scores dynamically.
Sliding window maximum/minimum	(Usually Deque) but if K is large and needs frequent removal by value → Heap (advanced).

2 FAANG FAVORITE HEAP PROBLEM THEMES

	System Design Like Problems Design Twitter Feed, Task Scheduler, Rate Limiter, Job Scheduler	Heap (Max)
	Streaming / Real Time Data Running Median, Data Stream as Disjoint Intervals	Two Heaps
	Top K / Ranking Top K Frequent, Top K Elements, K Closest Points	Min Heap (size K)
	Merge / K Sorted Sources Merge K Sorted Lists, Smallest Range in K Lists	Min Heap
	Greedy + Priority IPO, Find K Pairs with Smallest Sums, Maximize Capital	Max Heap
	Intervals / Meetings Meeting Rooms (III), Employee Free Time, Conference Room Scheduler	Min Heap
	Graphs / Advanced Dijkstra's Algorithm, Prim's MST, Network Delay Time	Min Heap



Pro Tip

Translate the problem into:
"Which element should come out first?"
→ That is your heap priority.

4 INTERVIEWER TRICKS TO WATCH OUT

- ✗ They never say "Use Heap" explicitly.
- ✗ They mix multiple concepts (e.g., Heap + HashMap).
- ✗ They change the goal (e.g., maximize instead of minimize).
- ✗ They give huge constraints to hint suboptimal solutions will TLE.
- ✗ They ask for real time / online processing → think Heap.
- ✗ They change K during the process (dynamic K).
- ✗ They ask for both min and max → think Two Heaps.

6 AHA MOMENTS (DON'T FORGET)

- ✓ Heap = Priority, NOT Sorting.
- ✓ Heap guarantees the BEST element only.
- ✓ Ask yourself: "What should I discard?"
- ✓ Heap size K keeps only what I care about.
- ✓ Comparator decides priority (not the data structure).
- ✓ **Every Heap problem fits into one of the 4 patterns on Page 2.**



3 HEAP VS OTHER DS (CHOOSE RIGHT TOOL)

Problem Type / Goal	Best Tool	Why?
Get min / max repeatedly	Heap	$O(\log n)$ per operation
Top K elements	Heap	$O(n \log k)$ better than sorting
Kth largest / smallest	Heap / Quickselect	Heap: $O(n \log k)$, Quickselect: $O(n)$ avg
Merge K sorted things	Heap	One candidate per source
FIFO order	Queue	Heap not for order
LIFO order	Stack	Heap not for order
Need sorted output	Sort	Full order required
Range queries	Segment Tree / BIT	Heap not for range aggregation
Dynamic min with delete by value	TreeMap / Balanced BST	Heap can't delete arbitrary element efficiently

5 RECOGNITION SHORTCUT (3 QUESTIONS)

1 What am I optimizing?
(min/max/priority)

2 Do I need only top/bottom K
or keep discarding
irrelevant elements?

3 Is the data coming
continuously or from
multiple sorted sources?

→

If **YES** to any
→ **Think HEAP**
✓



GOLDEN RULE

The best way to solve Heap problems is to **RECOGNIZE** them fast, choose the **RIGHT HEAP**, and **MAINTAIN the INVARIANT**.

**Master Recognition,
Not Just Implementation !**

HEAP - PATTERNS

Top Interview Patterns with Heaps (FAANG Cheat Sheet)

PAGE 2

Max Heap → largest element on top**Min Heap** → smallest element on top**PQ** → PriorityQueue

PATTERN 1 REPEATED MAX / MIN RETRIEVAL (e.g., Last Stone Weight)

When to Use?	Heap to Use	Idea / AHA	Template / Approach (Java)	Examples
- We repeatedly take the largest (or smallest) element. - Do some operation with it. - Put the result back. - Repeat until 1 (or none) left.	Max Heap → largest element on top graph TD 7((7)) → 5((5)) 7 → 6((6)) 5 → 2((2)) 5 → 4((4)) 6 → 1((1)) 6 → 3((3))	 Always care about the current largest (or smallest) element. Heap gives it in O(1).	<pre>PriorityQueue<Integer> maxHeap = new PriorityQueue<> (Collections.reverseOrder()); for (int x : nums) maxHeap.offer(x); while (maxHeap.size() > 1) { int a = maxHeap.poll(); // largest int b = maxHeap.poll(); // 2nd largest if (a != b) maxHeap.offer(a - b); } return maxHeap.isEmpty() ? 0 : maxHeap.peek();</pre>	★ LC 1046 Last Stone Weight Complexity - Time: O(n log n) - Space: O(n)

PATTERN 2 TOP-K ELEMENTS (e.g., Kth Largest, Top K Frequent)

When to Use?	Heap to Use	Idea / AHA	Template / Approach (Java)	Examples
- Need the K largest / smallest / most frequent elements. - K is much smaller than n. - We don't want to sort everything.	Top K Largest → Min Heap (size K) graph TD 3((3)) → 1((1)) 3 → 2((2)) (Keep K=3 largest seen so far) Top K Smallest → Max Heap (size K) graph TD 7((7)) → 9((9)) 7 → 8((8)) (Keep K=3 smallest seen so far)	 Keep only K best candidates in heap. If better element comes, replace root (worst among K).	Top K Largest (Min Heap of size K) <pre>PriorityQueue<Integer> pq = new PriorityQueue<>(); for (int x : nums) { pq.offer(x); if (pq.size() > k) pq.poll(); // remove smallest } // pq contains k largest elements</pre> Top K Smallest (Max Heap of size K) <pre>PriorityQueue<Integer> pq = new PriorityQueue<> (Collections.reverseOrder()); for (int x : nums) { pq.offer(x); if (pq.size() > k) pq.poll(); // remove largest } // pq contains k smallest elements</pre>	- LC 215 Kth Largest Element in an Array - LC 347 Top K Frequent Elements - LC 973 K Closest Points to Origin - LC 692 Top K Frequent Words Complexity - Time: O(n log k) - Space: O(k)

PATTERN 3 MERGE K SORTED LISTS / ARRAYS(e.g., Merge K Sorted Lists)

When to Use?	Heap to Use	Idea / AHA	Template / Approach (Java)	Examples
- We have K sorted lists / arrays. - Need to merge into one sorted output. - Always pick the smallest current candidate.	Min Heap graph LR A1((1)) → A4((4)) → A7((7)) B2((2)) → B5((5)) → B8((8)) C3((3)) → C6((6)) → C9((9)) A1 -.→ MH[Min Heap] B2 -.→ MH C3 -.→ MH MH -.→ R[1 2 3 4 5 6 7 8 9]	 Put the first element of each list into heap. Pop smallest, add its next element (if any). Repeat.	<pre>class Node { int val, list, index; // value, which list, index in list } PriorityQueue<Node> pq = new PriorityQueue<>((a, b) → a.val - b.val); // 1. Add first element of each list for (int i = 0; i < lists.length; i++) { pq.offer(new Node(lists[i].get(0), i, 0)); } List<Integer> res = new ArrayList<>(); while (!pq.isEmpty()) { Node cur = pq.poll(); res.add(cur.val); int nextIdx = cur.index + 1; if (nextIdx < lists[cur.list].size()) { pq.offer(new Node(lists[cur.list].get(nextIdx), cur.list, nextIdx)); } } // res is merged sorted list</pre>	LC 23 Merge k Sorted Lists LC 378 Kth Smallest Element in a Sorted Matrix LC 1246 Palindrome Removal Complexity - Time: $O(N \log k)$ (N = total elements) - Space: $O(k)$

PATTERN 4 TWO HEAPS (MEDIAN FROM DATA STREAM)(e.g., Find Median from Data Stream)

When to Use?	Heap to Use	Idea / AHA	Template / Approach (Java)	Examples
- Need median at any point in a stream. - Insertions happen one by one. - Need $O(\log n)$ insert and $O(1)$ median.	Max Heap (Smaller Half) Min Heap (Larger Half) graph TD 5((5)) → 2((2)) 5 → 3((3)) 2 → 1((1)) 2 → 4((4)) 9((9)) 8 → 10((10))	 Maintain two heaps: - maxHeap (left half) → top = max of left half - minHeap (right half) → top = min of right half Balance size difference ≤ 1. Median is either top of maxHeap or avg of both tops.	<pre>PriorityQueue<Integer> maxHeap = new PriorityQueue<>(Collections.reverseOrder()); PriorityQueue<Integer> minHeap = new PriorityQueue<>(); void addNum(int num) { if (maxHeap.isEmpty() num <= maxHeap.peek()) maxHeap.offer(num); else minHeap.offer(num); // Balance if (maxHeap.size() - minHeap.size() > 1) minHeap.offer(maxHeap.poll()); else if (minHeap.size() - maxHeap.size() > 1) maxHeap.offer(minHeap.poll()); } double findMedian() { if (maxHeap.size() > minHeap.size()) return maxHeap.peek(); else return (maxHeap.peek() + minHeap.peek()) / 2.0; }</pre>	LC 295 Find Median from Data Stream Complexity - Time: $O(\log n)$ per operation - Space: $O(n)$

 RECOGNITION TRIGGERS (If you see these in a question, think HEAP!)Top K / Kth
Largest / SmallestMost Frequent /
Top FrequentMerge K
SortedRunning Median /
Median at any timeContinuously pick
Max / Min**GOLDEN RULE:**

Heaps are all about **PRIORITY**, not **sorting**.
Choose the right heap and maintain the invariant!