

💡 WHY STACKS?

Arrays give random access, but Stacks enforce **LIFO (Last-In, First-Out) order**. This is essential for matching nested structures, expression evaluation, and backtracking memory!

💡 THE ARRAYDEQUE AHA

Never use `java.util.Stack` in Java! It inherits from `Vector` and uses synchronized methods (slow). Always use `Deque stack = new ArrayDeque<>()`!

1 3 CORE VARIANTS

- **Matching / Pair Cancellation:** Valid parentheses, string reduction, asteroid collisions.
- **Monotonic Stack:** Stack of strictly increasing or decreasing elements to find next greater / previous smaller element in $O(N)$!
- **Expression Evaluation:** Reverse Polish Notation (RPN), infix to postfix operators.

2 VISUALIZING MONOTONIC STACK

Decreasing Stack (Next Greater Element):

Array: [73, 74, 75, 71, 69, 72]
Push 73 → Stack: [73]
Element 74 > 73 → Pop 73! Next Greater of 73 is 74.
Push 74 → Stack: [74]
Element 75 > 74 → Pop 74! Next Greater of 74 is 75.
Push 75, 71, 69 → Stack: [75, 71, 69]

📚 PREREQUISITES & COMPLEXITY REASONING

Operation	ArrayDeque Complexity	Deprecated Stack
Push (top insert)	$O(1)$ amortized	$O(1)$ synchronized
Pop (top remove)	$O(1)$	$O(1)$ synchronized
Peek (top view)	$O(1)$	$O(1)$ synchronized
Monotonic Scan	$O(N)$ total	$O(N)$ total

🔥 CLUES THAT SCREAM STACK

1. *"Valid parentheses / matching brackets"* → Character Stack
2. *"Next greater element" / "Daily temperatures"* → Monotonic Decreasing Stack
3. *"Largest rectangle in histogram"* → Monotonic Increasing Stack
4. *"Evaluate arithmetic expression / RPN"* → Operand Stack

1 OPTIMAL ARRAYDEQUE TOOLKIT

```
// Standard FAANG Stack Declaration:
Deque<Integer> stack = new ArrayDeque<>();

stack.push(val); // Push onto top of stack
int top = stack.pop(); // Pop from top of stack
int peek = stack.peek(); // View top without popping
boolean empty = stack.isEmpty();
```

💡 `ArrayDeque` uses resizable circular array, zero garbage collector node allocations!

2 MIN STACK WITH TWO STACKS

```
class MinStack {
    private Deque<Integer> stack = new ArrayDeque<>();
    private Deque<Integer> minStack = new ArrayDeque<>();

    public void push(int val) {
        stack.push(val);
        if (minStack.isEmpty() || val ≤ minStack.peek()) {
            minStack.push(val);
        }
    }
    public void pop() {
        if (stack.pop().equals(minStack.peek())) minStack.pop();
    }
    public int top() { return stack.peek(); }
    public int getMin() { return minStack.peek(); }
}
```

3 PARENTHESIS MATCHING MAP

```
public static boolean isValidPair(char open, char close)
{
    return (open == '(' && close == ')') ||
           (open == '[' && close == ']') ||
           (open == '{' && close == '}');
}
```

4 MONOTONIC INDEX POP LOOP

```
// Monotonic Decreasing Stack loop (Find Next Greater Element)
while (!stack.isEmpty() && nums[stack.peek()] < nums[i])
{
    int prevIndex = stack.pop();
    result[prevIndex] = i - prevIndex; // Distance to next greater!
}
stack.push(i);
```

PATTERN 1 PARENTHESES & BRACKET MATCHING e.g. Valid Parentheses (LC 20), Backspace String Compare (LC 844)

WHEN TO USE
Push opening brackets '(', '[', '{'. When closing bracket encountered, verify top of stack matches and pop!

TEMPLATE — LC 20

```
public boolean isValid(String s) {
    Deque<Character> stack = new ArrayDeque<>();
    for (char c : s.toCharArray()) {
        if (c == '(') stack.push('(');
        else if (c == '{') stack.push('{');
        else if (c == '[') stack.push '['');
        else if (stack.isEmpty() || stack.pop() != c) return false;
    }
    return stack.isEmpty();
}
```

PATTERN 2 PAIR CANCELLATION & SIMULATION e.g. Asteroid Collision (LC 735), Remove All Adjacent Duplicates

WHEN TO USE
Simulate collision/cancellation between incoming elements and previous active elements at top of stack.

TEMPLATE — LC 735

```
public int[] asteroidCollision(int[] asteroids) {
    Deque<Integer> stack = new ArrayDeque<>();
    for (int a : asteroids) {
        while (!stack.isEmpty() && a < 0 && stack.peek() > 0) {
            int diff = a + stack.peek();
            if (diff < 0) stack.pop(); // Incoming destroys top
            else if (diff == 0) { stack.pop(); a = 0; } // Both destroyed
            else a = 0; // Incoming destroyed
        }
        if (a != 0) stack.push(a);
    }
    int[] res = new int[stack.size()];
    for (int i = res.length - 1; i >= 0; i--) res[i] = stack.pop();
    return res;
}
```

PATTERN 3

MONOTONIC DECREASING STACK (Next Greater Element)

e.g. Daily Temperatures (LC 739), Next Greater Element I & II

WHY O(N) TOTAL TIME

Every index is pushed onto the stack exactly once and popped at most once. Total push/pop operations across N elements $\leq 2N \rightarrow O(N)$!

TEMPLATE — LC 739

```
public int[] dailyTemperatures(int[] temperatures) {
    int n = temperatures.length;
    int[] res = new int[n];
    Deque<Integer> stack = new ArrayDeque<>(); // stores indices
    for (int i = 0; i < n; i++) {
        while (!stack.isEmpty() && temperatures[i] > temperatures[stack.peek()]) {
            int prevIndex = stack.pop();
            res[prevIndex] = i - prevIndex;
        }
        stack.push(i);
    }
    return res;
}
```

PATTERN 4

MONOTONIC STACK WITH MONOTONIC VALUES (Car Fleet)

e.g. Car Fleet (LC 853)

CAR FLEET INTUITION

Sort cars by position descending. Calculate arrival time $(target - pos) / speed$. If a car behind arrives $\leq$ car ahead, it merges into fleet (pop)!

TEMPLATE — LC 853

```
public int carFleet(int target, int[] position, int[] speed) {
    int n = position.length;
    double[][] cars = new double[n][2];
    for (int i = 0; i < n; i++) {
        cars[i] = new double[]{position[i], (double)(target - position[i]) / speed[i]};
    }
    Arrays.sort(cars, (a, b) -> Double.compare(b[0], a[0]));
    Deque<Double> stack = new ArrayDeque<>();
    for (double[] car : cars) {
        double time = car[1];
        if (!stack.isEmpty() && time <= stack.peek()) continue; // Merges!
        stack.push(time);
    }
    return stack.size();
}
```

PATTERN
5

LARGEST RECTANGLE IN HISTOGRAM (Monotonic Increasing Stack)

e.g. Largest Rectangle in Histogram (LC 84), Maximal Rectangle

MONOTONIC INCREASING STACK MECHANICS
When `heights[i]` is smaller than stack top, the popped height's right boundary is `i`, and left boundary is current stack top!

TEMPLATE — LC 84

```
public int largestRectangleArea(int[] heights) {
    int n = heights.length, maxArea = 0;
    Deque<Integer> stack = new ArrayDeque<>();
    for (int i = 0; i <= n; i++) {
        int h = (i == n) ? 0 : heights[i];
        while (!stack.isEmpty() && h < heights[stack.peek()]) {
            int height = heights[stack.pop()];
            int width = stack.isEmpty() ? i : i - stack.peek() - 1;
            maxArea = Math.max(maxArea, height * width);
        }
        stack.push(i);
    }
    return maxArea;
}
```

PATTERN 6

EVALUATE REVERSE POLISH NOTATION (Postfix Operators)

e.g. Evaluate Reverse Polish Notation (LC 150)

WHEN TO USE

Push numbers. When operator (+, -, *, /) encountered, pop second operand `b`, pop first operand `a`, evaluate `a op b`, push result!

TEMPLATE — LC 150

```
public int evalRPN(String[] tokens) {
    Deque<Integer> stack = new ArrayDeque<>();
    for (String t : tokens) {
        if (t.equals("+")) stack.push(stack.pop() + stack.pop());
        else if (t.equals("-")) { int b = stack.pop(), a = stack.pop(); stack.push(a - b); }
        else if (t.equals("*")) stack.push(stack.pop() * stack.pop());
        else if (t.equals("/")) { int b = stack.pop(), a = stack.pop(); stack.push(a / b); }
        else stack.push(Integer.parseInt(t));
    }
    return stack.pop();
}
```

PATTERN 7

DECODE STRING (Nested Multipliers & String Stack)

e.g. Decode String (LC 394) — `3[a2[c]]` → `accaccacc`

NESTED STACK STRATEGY


Use count stack & string stack. On `[`, push current multiplier and string buffer. On `]`, pop multiplier and repeat string!

TEMPLATE — LC 394

```
public String decodeString(String s) {
    Deque<Integer> countStack = new ArrayDeque<>();
    Deque<StringBuilder> stringStack = new ArrayDeque<>();
    StringBuilder curr = new StringBuilder(); int k = 0;
    for (char c : s.toCharArray()) {
        if (Character.isDigit(c)) k = k * 10 + (c - '0');
        else if (c == '[') {
            countStack.push(k); stringStack.push(curr);
            curr = new StringBuilder(); k = 0;
        } else if (c == ']') {
            StringBuilder prev = stringStack.pop(); int count = countStack.pop();
            for (int i = 0; i < count; i++) prev.append(curr);
            curr = prev;
        } else curr.append(c);
    }
    return curr.toString();
}
```

STACK — WHICH PATTERN TO USE?

Start: What is the stack problem type?



TRIGGER WORDS DIRECTORY

Trigger Word	Variant	Action
"Valid parentheses", "Matching brackets"	Matching Stack	Push closing bracket onto stack
"Next greater", "Daily temperatures"	Monotonic Decreasing	Pop stack while `stack.peek() < num`
"Histogram", "Max rectangle"	Monotonic Increasing	Pop stack while `stack.peek() > height`
"RPN", "Postfix evaluation"	Operand Stack	Pop b then a, apply `a op b`

INTERVIEW TRADE-OFFS & FOLLOW-UPS

Interviewer Asks	Your Answer
Why `ArrayDeque` over `java.util.Stack`?	`java.util.Stack` is legacy, thread-synchronized, and inherits from Vector. `ArrayDeque` is unsynchronized array-backed O(1)!
How to implement O(1) Min Stack?	Maintain a parallel `minStack` storing current minimum at each push!

EASY & MEDIUM — Parentheses & Min Stack

LC 20 · Valid Parentheses

EASY

Pattern: Parenthesis Match

Key Insight: Push expected closing character.

```
public boolean isValid(String s) {
    Deque<Character> st = new ArrayDeque<>();
    for (char c : s.toCharArray()) {
        if (c == '(') st.push(')');
        else if (c == '{') st.push('}');
        else if (c == '[') st.push(']');
        else if (st.isEmpty() || st.pop() != c) return false;
    }
    return st.isEmpty();
}
```

LC 155 · Min Stack

MEDIUM

Pattern: Dual Stack

Key Insight: Auxiliary stack tracks minimum value.

```
class MinStack {
    Deque<Integer> st = new ArrayDeque<>();
    minSt = new ArrayDeque<>();
    public void push(int val) {
        st.push(val);
        if (minSt.isEmpty() || val <= minSt.peek()) minSt.push(val);
    }
    public void pop() { if (st.pop().equals(minSt.peek())) minSt.pop(); }
    public int top() { return st.peek(); }
    public int getMin() { return minSt.peek(); }
}
```

LC 150 · Evaluate RPN

MEDIUM

Pattern: RPN Operand Stack

Key Insight: Pop `b` then `a`, apply `a op b`.

```
public int evalRPN(String[] tokens) {
    Deque<Integer> st = new ArrayDeque<>();
    for (String t : tokens) {
        if (t.equals("+")) st.push(st.pop() + st.pop());
        else if (t.equals("-")) { int b=st.pop(), a=st.pop(); st.push(a-b); }
        else if (t.equals("*")) st.push(st.pop() * st.pop());
        else if (t.equals("/")) { int b=st.pop(), a=st.pop(); st.push(a/b); }
        else st.push(Integer.parseInt(t));
    }
    return st.pop();
}
```

MEDIUM — Monotonic Decreasing & Fleets

LC 739 · Daily Temperatures

MEDIUM

Pattern: Monotonic Decreasing

Key Insight: Stack stores indices. Pop when warmer!

```
public int[] dailyTemperatures(int[] T) {
    int[] res = new int[T.length];
    Deque<Integer> st = new ArrayDeque<>();
    for (int i = 0; i < T.length; i++) {
        while (!st.isEmpty() && T[i] > T[st.peek()]) {
            int prev = st.pop(); res[prev] = i - prev;
        }
        st.push(i);
    }
    return res;
}
```

LC 853 · Car Fleet

MEDIUM

Pattern: Time Stack

Key Insight: Sort by position desc. Time <= top merges.

```
public int carFleet(int target, int[] pos, int[] speed) {
    int n = pos.length; double[][] cars = new double[n][2];
    for (int i = 0; i < n; i++) cars[i] = new double[]{pos[i], (double)(target - pos[i]) / speed[i]};
    Arrays.sort(cars, (a,b) -> Double.compare(b[0], a[0]));
    Deque<Double> st = new ArrayDeque<>();
    for (double[] c : cars) {
        if (!st.isEmpty() && c[1] <= st.peek()) continue;
        st.push(c[1]);
    }
    return st.size();
}
```


MEDIUM & HARD — Asteroids & Decoding

LC 735 · Asteroid Collision

MEDIUM

Pattern: Collision Simulation

Key Insight: Destroy smaller top when incoming is negative.

```
public int[] asteroidCollision(int[] ast) {
    Deque<Integer> st = new ArrayDeque<>();
    for (int a : ast) {
        while (!st.isEmpty() && a < 0 && st.peek() > 0) {
            int diff = a + st.peek();
            if (diff < 0) st.pop();
            else if (diff == 0) { st.pop(); a = 0; }
            else a = 0;
        }
        if (a != 0) st.push(a);
    }
    int[] res = new int[st.size()];
    for (int i = res.length - 1; i >= 0; i--) res[i] = st.pop();
    return res;
}
```

HARD — Largest Rectangle in Histogram

LC 84 · Largest Rectangle in Histogram

HARD

Pattern: Monotonic Increasing

Key Insight: Width $= i - \text{stack.peek()}$ - 1\$.

```
public int largestRectangleArea(int[] heights) {
    int n = heights.length, maxArea = 0;
    Deque<Integer> st = new ArrayDeque<>();
    for (int i = 0; i <= n; i++) {
        int h = (i == n) ? 0 : heights[i];
        while (!st.isEmpty() && h < heights[st.peek()]) {
            int height = heights[st.pop()];
            int width = st.isEmpty() ? i : i - st.peek() - 1;
            maxArea = Math.max(maxArea, height * width);
        }
        st.push(i);
    }
    return maxArea;
}
```

LC 394 · Decode String

MEDIUM

Pattern: Nested Dual Stack

Key Insight: Push buffer on '[', repeat on ']'.

```
public String decodeString(String s) {
    Deque<Integer> countSt = new ArrayDeque<>();
    Deque<StringBuilder> strSt = new ArrayDeque<>();
    StringBuilder curr = new StringBuilder();
    int k = 0;
    for (char c : s.toCharArray()) {
        if (Character.isDigit(c)) k = k * 10 + (c - '0');
        else if (c == '[') {
            countSt.push(k); strSt.push(curr);
            curr = new StringBuilder(); k = 0;
        } else if (c == ']') {
            StringBuilder prev = strSt.pop();
            int cnt = countSt.pop();
            for (int i = 0; i < cnt; i++) prev.append(curr);
            curr = prev;
        } else curr.append(c);
    }
    return curr.toString();
}
```

LC 22 · Generate Parentheses

MEDIUM

Pattern: Backtracking Stack

Key Insight: Add '(' if open < N, add ')' if close < open.

```
public List<String> generateParenthesis(int n) {
    List<String> res = new ArrayList<>();
    backtrack(res, new StringBuilder(), 0, 0, n);
    return res;
}
private void backtrack(List<String> res, StringBuilder sb, int open, int close, int n) {
    if (sb.length() == 2 * n) { res.add(sb.toString()); return; }
    if (open < n) { sb.append('('); backtrack(res, sb, open + 1, close, n); sb.deleteCharAt(sb.length() - 1); }
    if (close < open) { sb.append(')'); backtrack(res, sb, open, close + 1, n); sb.deleteCharAt(sb.length() - 1); }
}
```

COMPLETE STACK PROBLEM LADDER SUMMARY					
LC #	Problem	Pattern	Time	Space	Diff
20	Valid Parentheses	Parenthesis Match	O(N)	O(N)	E
155	Min Stack	Dual Stack Minimum	O(1) all ops	O(N)	M
150	Evaluate RPN	Operand Stack	O(N)	O(N)	M
739	Daily Temperatures	Monotonic Decreasing	O(N)	O(N)	M
853	Car Fleet	Time Stack	O(N log N)	O(N)	M
735	Asteroid Collision	Collision Simulation	O(N)	O(N)	M
394	Decode String	Nested Dual Stack	O(N)	O(N)	M
84	Largest Rectangle in Histogram	Monotonic Increasing	O(N)	O(N)	H

🔍 DRY RUN — Daily Temperatures ([73, 74, 75, 71, 69, 72])

Index	Temp	Stack State (Indices)	Action / Result Assignment
0	73	[0]	Push 0
1	74	[1]	$74 > 73 \rightarrow \text{Pop 0! } \text{res}[0] = 1 - 0 = 1$. Push 1
2	75	[2]	$75 > 74 \rightarrow \text{Pop 1! } \text{res}[1] = 2 - 1 = 1$. Push 2
3	71	[2, 3]	$71 < 75 \rightarrow \text{Push 3}$
4	69	[2, 3, 4]	$69 < 71 \rightarrow \text{Push 4}$
5	72	[2, 5]	$72 > 69 \rightarrow \text{Pop 4! } \text{res}[4]=1$. $72 > 71 \rightarrow \text{Pop 3! } \text{res}[3]=2$. Push 5

✅ MASTERY CHECKLIST — CAN YOU DO THIS?

- ☐ Use `ArrayDeque` instead of `java.util.Stack`
- ☐ Code Valid Parentheses (LC 20) in 2m
- ☐ Implement Min Stack $O(1)$ operations
- ☐ Code Daily Temperatures with Monotonic Stack
- ☐ Write RPN Evaluator (LC 150)
- ☐ Code Car Fleet sorting by position desc
- ☐ Code Largest Rectangle in Histogram (LC 84)
- ☐ Prove why Monotonic Stack is $O(N)$

📐 MATHEMATICAL PROOF — $O(N)$ MONOTONIC STACK

Claim: The inner `while (!stack.isEmpty() && ...)` loop does not make Monotonic Stack $O(N^2)$.

Proof: Each element is pushed onto the stack exactly once. An element can be popped from the stack at most once. Total pops across entire execution $\leq N$. Total operations $= N \text{ pushes} + \text{at most } N \text{ pops} = 2N \rightarrow$ **Strictly $O(N)$ Time!**

📦 GOLDEN RULES — NEVER FORGET

- Rule 1 — Store Indices, Not Values**

In Monotonic Stack problems calculating distances (e.g. Daily Temperatures, Histogram width), store **ARRAY INDICES** in the Stack!
- Rule 2 — Sentinel 0 Height**

In Largest Rectangle in Histogram, append a dummy 0 height at index N to force popping all remaining elements from the stack!