

Specification for HTPA8x8L2.85/0.9HiM(UDP)

Rev.0: 2014.10.15 Fg



The HTPA8x8L/_M(UDP) is a fully calibrated, low cost thermopile array module, with fully digital UDP interface. The module delivers an electrical offset and ambient temperature compensated output stream, which can be already used for image processing, pattern recognition and presence detection purposes. Object temperatures can be easily obtained by this data stream.


Order Code Example

HTPA32x31	L10 / 0.8	F8-14	Hi	M(SPI)	[Si]
Type:	HTPA32x31	Please contact support for all available HTPA and module combinations.			
Output:	d	HTPA sensor with digital output			
	Not declared	HTPA sensor with analogous output			
Optics:	L	Focal length: In example L2,1 = 2,1 mm focal length			
	/	F-Number: In example /0.85			
		For optics see also "HTPA standard optics"			
Filter:	F	Filter characteristics. In example F8-14 (µm, Bandpass)			
	Not declared	Broad band ARC			
Sensitivity:	Hi	Increased sensitivity			
	Not declared	Standard sensitivity			
Version:	A	Application set: comes with GUI, housing, power supply.			
		Always UDP Interface.			
	M	Module: HTPA sensor soldered to PCB, calibrated stream			
	S	HTPA sensor only. Raw voltage output, not calibrated			
Interface:	SPI	SPI device; Two variants:			
		Analog HTPA, 14bit ADC			
		Digital HTPA, 12bit ADC			
	LC	SPI, Only Analogous HTPA.			
		low speed, external processing required			
	UDP	Ethernet, CAT5 cable connection			
Lens Material:	Si	Silicon			
	Not declared	Germanium			

For modules, M(UART) and M(LC) are not recommended anymore. M(SPI) and M(UDP) offer a wider input voltage range, better ADC resolution and a wider measurement range.

Pinout

Pin Assignment HTPA32x31M(UDP)			
Pin	Name	Description	Type
1	TPOut+	Differential Signal Output	Digital Output
2	VDD	Positive supply voltage	Power
3	TPOut-	Differential Signal Output	Digital Output
4	TPIn+	Differential Signal Input	Digital Input
5		not connected	
6	TPIn-	Differential Signal Input	Digital Input
7		not connected	
8	VSS	Ground reference	Power



HEIMANN Sensor GmbH
Maria-Reiche-Str. 1
D-01109 Dresden / Germany

Contact / Customer Support
Phone 49 (0) 6123 60 50 30
Fax 49 (0) 6123 60 50 39

Internet
www.heimannsensor.com
mail: info@heimannsensor.com

Specification for HTPA8x8L2.85/0.9HiM(UDP)

Rev.0: 2014.10.15 Fg




Ethernet-Interface:

Protocol Specifications:

Protocol type: UDP
All communication on Port: 30444


Power connection at Ethernet device:



1	VSS (-)	GND
2	VDD (+)	Supply (+3.3V DC)


Power Supply: 3.3 VDC +/- 5%, 300mA

HTPA8x8L2.85/0.9M(UDP) Optical Orientation of Pixels:



Communication and Timings:

Proposed flow chart of communication. (Master is referred as μ C, Slave as HTPA module)



Communication:

Communication via Terminal / UDP																																																																																																																																	
Sent Char	HTPA8x8	HTPA16x16	HTPA32x31	HTPA64x62	Result/Received message																																																																																																																												
'a'	X	X	X		Decreases the operating frequency of the array																																																																																																																												
'A'	X	X	X		Increases the operating frequency of the array																																																																																																																												
'b'	X	X	X		Measure VDD (referenced to VREF1225)																																																																																																																												
'C'	X	X			Capture single voltage frame. Use ADC of ASIC. Output via ASCII if sent via UART, binary if sent via UDP.																																																																																																																												
'c'	X	X	X		Capture single voltage frame. Use ADC of μ C. Output via ASCII if sent via UART, binary if sent via UDP.																																																																																																																												
'd'/'D'	X	X			Toggle POR_N																																																																																																																												
'f'	X	X	X		Toggle Resetbit																																																																																																																												
'F'	X	X			Analog operating point is at start of AD-range, only positive signals convertible																																																																																																																												
'G'	X	X			Analog operating point is in the middle of AD-range, positive and negative signals convertible																																																																																																																												
'g'	X	X			Analog operating point is at end of AD-range, only negative signals convertible																																																																																																																												
'h'	X	X	X		pushes binary EEDATA out																																																																																																																												
'i'			X		Read single voltage frame. Output in ASCII format. Serial order: Pixeldata[K*10], el. Offsets, Ambient Temperature																																																																																																																												
'T'			X		Read single temperature frame. Output in ASCII format. Serial order: Pixeldata[K*10], el. Offsets, Ambient Temperature																																																																																																																												
'J'	X	X	X		Toggle Amplification																																																																																																																												
'k'	X	X	X		Read single temperature frame. Output in binary format.																																																																																																																												
'K'	X	X	X		send continous binary temperature datastream(μ C-ADC)[K*10] Output of a complete cycle in this order: <div>HTPA 8x8 and HTPA16x16: Pixel0,Pixel1, ...,PixelX, el.Offset0, el.Offset1,..., el.OffsetY,PTAT0,PTAT1,...,PTATZ HTPA32x31: see Table2. For a detailed Description of the serial order see Table2.</div> <div>16x16 Array: 8x8 Array: X=255; Y=7; Z=7 X=63; Y=4; Z=4</div> <div>One dataset has exactly 2 bytes: first the low-Byte is send, then the high-byte. Each Dataset contains the measured Temperature in Kelvin*10. The first 4 datasets el.Offset0...el.Offset3 after the last Pixel voltage PixelX transmit additional the current VDD in the MSB's:</div> <table><tr><th colspan="10">VDD and T_{Amb} for HTPA8x8 and HTPA16x16:</th></tr><tr><th>Dataset</th><th>Bit15</th><th>Bit14</th><th>Bit13</th><th>Bit12</th><th>Bit11</th><th>Bit10</th><th>...</th><th>Bit1</th><th>Bit0</th></tr><tr><td>elOff0</td><td>MSB VDD</td><td>...</td><td>...</td><td>Bit12 VDD</td><td>MSB elOff0</td><td>...</td><td>...</td><td>...</td><td>LSB elOff0</td></tr><tr><td>elOff1</td><td>Bit11 VDD</td><td>...</td><td>...</td><td>Bit8 VDD</td><td>MSB elOff1</td><td>...</td><td>...</td><td>...</td><td>LSB elOff1</td></tr><tr><td>elOff2</td><td>Bit7 VDD</td><td>...</td><td>...</td><td>Bit4 VDD</td><td>MSB elOff2</td><td>...</td><td>...</td><td>...</td><td>LSB elOff2</td></tr><tr><td>elOff3</td><td>Bit3 VDD</td><td>...</td><td>...</td><td>LSB VDD</td><td>MSB elOff3</td><td>...</td><td>...</td><td>...</td><td>LSB elOff3</td></tr></table> <div>The Sensor temperature is available in the datasets after el.Offset3:</div> <table><tr><th>Dataset</th><th>Bit15</th><th>Bit14</th><th>Bit13</th><th>Bit12</th><th>Bit11</th><th>Bit10</th><th>...</th><th>Bit1</th><th>Bit0</th></tr><tr><td>elOff3+1</td><td>MSB T_{Amb}</td><td>...</td><td>...</td><td>Bit12 T_{Amb}</td><td>MSB elOff3+1</td><td>...</td><td>...</td><td>...</td><td>LSB elOff3+1</td></tr><tr><td>elOff3+2</td><td>Bit11 T_{Amb}</td><td>...</td><td>...</td><td>Bit8 T_{Amb}</td><td>MSB elOff3+2</td><td>...</td><td>...</td><td>...</td><td>LSB elOff3+2</td></tr><tr><td>elOff3+3</td><td>Bit7 T_{Amb}</td><td>...</td><td>...</td><td>Bit4 T_{Amb}</td><td>MSB elOff3+3</td><td>...</td><td>...</td><td>...</td><td>LSB elOff3+3</td></tr><tr><td>elOff3+4</td><td>Bit3 T_{Amb}</td><td>...</td><td>...</td><td>LSB T_{Amb}</td><td>MSB elOff3+4</td><td>...</td><td>...</td><td>...</td><td>LSB elOff3+4</td></tr><tr><td>elOff3+5</td><td>0</td><td>0</td><td>0</td><td>0</td><td>MSB elOff3+5</td><td>...</td><td>...</td><td>...</td><td>LSB elOff3+5</td></tr></table>					VDD and T _{Amb} for HTPA8x8 and HTPA16x16:										Dataset	Bit15	Bit14	Bit13	Bit12	Bit11	Bit10	...	Bit1	Bit0	elOff0	MSB VDD	Bit12 VDD	MSB elOff0	LSB elOff0	elOff1	Bit11 VDD	Bit8 VDD	MSB elOff1	LSB elOff1	elOff2	Bit7 VDD	Bit4 VDD	MSB elOff2	LSB elOff2	elOff3	Bit3 VDD	LSB VDD	MSB elOff3	LSB elOff3	Dataset	Bit15	Bit14	Bit13	Bit12	Bit11	Bit10	...	Bit1	Bit0	elOff3+1	MSB T _{Amb}	Bit12 T _{Amb}	MSB elOff3+1	LSB elOff3+1	elOff3+2	Bit11 T _{Amb}	Bit8 T _{Amb}	MSB elOff3+2	LSB elOff3+2	elOff3+3	Bit7 T _{Amb}	Bit4 T _{Amb}	MSB elOff3+3	LSB elOff3+3	elOff3+4	Bit3 T _{Amb}	LSB T _{Amb}	MSB elOff3+4	LSB elOff3+4	elOff3+5	0	0	0	0	MSB elOff3+5	LSB elOff3+5
VDD and T _{Amb} for HTPA8x8 and HTPA16x16:																																																																																																																																	
Dataset	Bit15	Bit14	Bit13	Bit12	Bit11	Bit10	...	Bit1	Bit0																																																																																																																								
elOff0	MSB VDD	Bit12 VDD	MSB elOff0	LSB elOff0																																																																																																																								
elOff1	Bit11 VDD	Bit8 VDD	MSB elOff1	LSB elOff1																																																																																																																								
elOff2	Bit7 VDD	Bit4 VDD	MSB elOff2	LSB elOff2																																																																																																																								
elOff3	Bit3 VDD	LSB VDD	MSB elOff3	LSB elOff3																																																																																																																								
Dataset	Bit15	Bit14	Bit13	Bit12	Bit11	Bit10	...	Bit1	Bit0																																																																																																																								
elOff3+1	MSB T _{Amb}	Bit12 T _{Amb}	MSB elOff3+1	LSB elOff3+1																																																																																																																								
elOff3+2	Bit11 T _{Amb}	Bit8 T _{Amb}	MSB elOff3+2	LSB elOff3+2																																																																																																																								
elOff3+3	Bit7 T _{Amb}	Bit4 T _{Amb}	MSB elOff3+3	LSB elOff3+3																																																																																																																								
elOff3+4	Bit3 T _{Amb}	LSB T _{Amb}	MSB elOff3+4	LSB elOff3+4																																																																																																																								
elOff3+5	0	0	0	0	MSB elOff3+5	LSB elOff3+5																																																																																																																								
'l'	X	X	X		Get Ambient Temperature (Calculates the Ambient Temperature from the last measured Frame)																																																																																																																												
'm'	X	X	X		Toggle usage of μ C-Buffer for el. Offsets (Stack depth = 64 for HTPA8x8 and HTPA16x16; Stack depth = 32 for HTPA32x31)																																																																																																																												
'M'	X	X	X		Shows current and calibration settings. Device prints the following stream: "HTPA series responded! I am Arraytype X" Possible values for X: "0"=HTPA8x8, "1"=HTPA16x16, "3"=HTPA32x31 "Firmware v.X.XX written by B.Forg; Heimann Sensor GmbH; YYYY-MM-DD" Version information. "I am running on XXXX.X kHz" Actual MCLK-setting in kHz "Amplification is X" Actual set amplification. Possible strings for X: "low" or "high" "MAC-ID: X IP: Y DevID: Z\r\n" (Only Ethernet devices show a MAC-ID, DevID is shown in any case) X= MAC-ID of the device, i.e. "00.97.FF.00.10.08"; Y=current IP of the device, Z=user settable ID, range 00000...65535 "PIXCvsTA X . BFL3 X . F8_14 X . THvsTA X IGNORE_ELOFF32 X SBY Y FC X EXP Z"																																																																																																																												

Table 1a: Control Characters

Specification for HTPA8x8L2.85/0.9HiM(UDP)

Rev.0: 2014.10.15 Fg



Communication via Terminal / UDP																																																											
Sent Char	HTPA8x8	HTPA16x16	HTPA32x31	HTPA64x62	Result/Received message																																																						
'o'		X	X		Use external reference voltages																																																						
'O'		X	X		Use internal reference voltages																																																						
'q'/'Q'	X	X	X	X	Allow Changes (required for Calibration)																																																						
't'	X	X	X	X	<p>Continuous binary voltage data of the μC-ADC is transmitted. Output of a complete cycle in this order:</p> <p style="text-align: center;"><i>HTPA 8x8 and HTPA16x16: Pixel0, Pixel1, ..., PixelX, el.Offset0, el.Offset1, ..., el.OffsetY, PTAT0, PTAT1, ..., PTATZ</i> <i>HTPA32x31: see Table2.</i> <i>For a detailed Description of the serial order see Table2.</i></p> <p>16x16 Array: 8x8 Array: X=255; Y=7; Z=7 X=63; Y=4; Z=4</p> <p>One dataset has exactly 2 bytes: first the low-Byte is send, then the high-byte. Each Dataset contains the ADC-Data in digits and The first 4 datasets <i>el.Offset0...el.Offset3</i> after the last Pixel voltage <i>PixelX</i> transmit additional the current VDD in the MSB's:</p> <p style="text-align: center;">VDD for HTPA8x8 and HTPA16x16:</p> <table border="1"> <thead> <tr> <th>Dataset</th><th>Bit15</th><th>Bit14</th><th>Bit13</th><th>Bit12</th><th>Bit11</th><th>Bit10</th><th>...</th><th>Bit1</th><th>Bit0</th></tr> </thead> <tbody> <tr> <td>elOff0</td><td>MSB VDD</td><td>...</td><td>...</td><td>Bit12 VDD</td><td>MSB elOff0</td><td>...</td><td>...</td><td>...</td><td>LSB elOff0</td></tr> <tr> <td>elOff1</td><td>Bit11 VDD</td><td>...</td><td>...</td><td>Bit8 VDD</td><td>MSB elOff1</td><td>...</td><td>...</td><td>...</td><td>LSB elOff1</td></tr> <tr> <td>elOff2</td><td>Bit7 VDD</td><td>...</td><td>...</td><td>Bit4 VDD</td><td>MSB elOff2</td><td>...</td><td>...</td><td>...</td><td>LSB elOff2</td></tr> <tr> <td>elOff3</td><td>Bit3 VDD</td><td>...</td><td>...</td><td>LSB VDD</td><td>MSB elOff3</td><td>...</td><td>...</td><td>...</td><td>LSB elOff3</td></tr> </tbody> </table>					Dataset	Bit15	Bit14	Bit13	Bit12	Bit11	Bit10	...	Bit1	Bit0	elOff0	MSB VDD	Bit12 VDD	MSB elOff0	LSB elOff0	elOff1	Bit11 VDD	Bit8 VDD	MSB elOff1	LSB elOff1	elOff2	Bit7 VDD	Bit4 VDD	MSB elOff2	LSB elOff2	elOff3	Bit3 VDD	LSB VDD	MSB elOff3	LSB elOff3
Dataset	Bit15	Bit14	Bit13	Bit12	Bit11	Bit10	...	Bit1	Bit0																																																		
elOff0	MSB VDD	Bit12 VDD	MSB elOff0	LSB elOff0																																																		
elOff1	Bit11 VDD	Bit8 VDD	MSB elOff1	LSB elOff1																																																		
elOff2	Bit7 VDD	Bit4 VDD	MSB elOff2	LSB elOff2																																																		
elOff3	Bit3 VDD	LSB VDD	MSB elOff3	LSB elOff3																																																		
'T'	X	X			Continuous binary data of the ASIC-ADC is transmitted. Output order is equal to 't'.																																																						
'u'	X	X			Continuous binary data of the ASIC-ADC is transmitted. PTAT-Voltages are sampled with the uC-ADC. Output order is equal to 't'.																																																						
'U'	X	X			Capture single frame. Use ADC of ASIC. Output via ASCII. PTAT-Voltages are sampled with the uC-ADC.																																																						
'v'	X	X	X		Announce IP (Only Ethernet devices)																																																						
'V'	X	X	X		Device awaits control message (only non-Ethernet devices)																																																						
'w'	X	X	X		shows Calibration-constants																																																						
'W'	X	X	X	X	Calibration. ATTENTION! Old Dataset cannot be restored!																																																						
'x'	X	X	X		Stops Stream without prompt.																																																						
'X'	X	X	X		Stops Stream by sending "STOP!\r\n"																																																						
'y'	X	X	X		switch off ASIC-Supply (5V)																																																						
'Y'	X	X	X		switch on ASIC-Supply (5V)																																																						

Table 1b: Control Characters (continuation)

Please be aware, that the source and destination port has to be 30444

Serial order of data in stream:

HTPA8x8 Temperature Mode	
Dataset	Value
0	Temperature of Pixel0 in K*10
1	Temperature of Pixel1 in K*10
2	Temperature of Pixel2 in K*10
3	Temperature of Pixel3 in K*10
...	...
63	Temperature of Pixel63 in K*10
64	4 bits of VDD and eOff0 in digits (refer to Table1)
65	4 bits of VDD and eOff1 in digits (refer to Table1)
66	4 bits of VDD and eOff2 in digits (refer to Table1)
67	4 bits of VDD and eOff4 in digits (refer to Table1)
68	4 bits of T Amb and PTAT0 in digits (refer to Table1)
68	4 bits of T Amb and PTAT1 in digits (refer to Table1)
68	4 bits of T Amb and PTAT2 in digits (refer to Table1)
68	4 bits of T Amb and PTAT3 in digits (refer to Table1)

HTPA8x8 Voltage Mode	
Dataset	Value
0	absolute Voltage of Pixel0 in digits
1	absolute Voltage of Pixel1 in digits
2	absolute Voltage of Pixel2 in digits
3	absolute Voltage of Pixel3 in digits
...	...
63	absolute Voltage of Pixel63 in digits
64	4 bits of VDD and eOff0 in digits (refer to Table1)
65	4 bits of VDD and eOff1 in digits (refer to Table1)
66	4 bits of VDD and eOff2 in digits (refer to Table1)
67	4 bits of VDD and eOff4 in digits (refer to Table1)
68	4 bits of T Amb and PTAT0 in digits (refer to Table1)
68	4 bits of T Amb and PTAT1 in digits (refer to Table1)
68	4 bits of T Amb and PTAT2 in digits (refer to Table1)
68	4 bits of T Amb and PTAT3 in digits (refer to Table1)

Table 2: Serial order of data in stream

Each dataset consists of a 16 bit value. If a frame consists out of more than one packet, packets are appended.

Specification for HTPA8x8L2.85/0.9HiM(UDP)

Rev.0: 2014.10.15 Fg



Pixel Map:

0	1	2	3	4	5	6	7
8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23
24	25	26	27	28	29	30	31
32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47
48	49	50	51	52	53	54	55
56	57	58	59	60	61	62	63

Table 3: Pixelmap

Packets (UDP, only Ethernet device):

Number of packets	Packet size [byte]	HTPA type	Comments
1	144	HTPA8x8	-
1	544	HTPA16x16	-
2	1058+1054	HTPA32x31	see below for details
8	1101+493	HTPA64x62	see below for details

Packet details for HTPA32x31		
Packet No.	Packet size	Packet contains
1	1058	Data of Pixel0 - Pixel528
2	1054	Data of Pixel529 to end of frame

Packet details for HTPA64x62		
Packet No.	Packet size	Packet contains
1	1101	Packet index 1 (8bit), data of Pixel0-Pixel550
2	1101	Packet index 2 (8bit), data of Pixel551-Pixel1101
3	1101	Packet index 3 (8bit), data of Pixel1102-Pixel1652
4	1101	Packet index 4 (8bit), data of Pixel1653-Pixel2203
5	1101	Packet index 5 (8bit), data of Pixel2204-Pixel2754
6	1101	Packet index 6 (8bit), data of Pixel2755-Pixel3305
7	1101	Packet index 7 (8bit), data of Pixel3306-Pixel3856
8	493	Packet index 8 (8bit), data of Pixel3857 to end of frame

Each dataset (except of packet index) consists out of a 16 bit value. For serial order of the datasets refer to section “serial order in Frame”.

Control Messages:

In the set of control messages, expressions in angled braces have to be substituted by following strings:

[IP]	insert IP in ASCII format, i.e.: "192.168.240.122"										
[MACID]	insert MAC ID in ASCII format and hexadecimal, i.e.: "00.1A.22.33.44.55"										
[AT]	insert index of array types in ASCII format										
	<table> <tr> <th>Array type</th><th>Index</th></tr> <tr> <td>HTPA 8x8</td><td>"0"</td></tr> <tr> <td>HTPA 16x16</td><td>"1"</td></tr> <tr> <td>HTPA 32x31</td><td>"3"</td></tr> <tr> <td>HTPA 64x62</td><td>"5"</td></tr> </table>	Array type	Index	HTPA 8x8	"0"	HTPA 16x16	"1"	HTPA 32x31	"3"	HTPA 64x62	"5"
Array type	Index										
HTPA 8x8	"0"										
HTPA 16x16	"1"										
HTPA 32x31	"3"										
HTPA 64x62	"5"										
[MCLK]	insert Frequency of MCLK in ASCII format and kHz, i.e.: "1050.1"										
[AMP]	insert state of amplification in ASCII format:										
	<table> <tr> <th>State</th><th>String</th></tr> <tr> <td>Low</td><td>"low"</td></tr> <tr> <td>High</td><td>"high"</td></tr> </table>	State	String	Low	"low"	High	"high"				
State	String										
Low	"low"										
High	"high"										
[MSK]	insert subnet mask in ASCII format, i.e.: "255.255.255.000"										
[DEVID]	insert 5 digit device ID in ASCII format, i.e. "00197" Range: 00000... 65535										

Set of control messages:

Message1:	"Calling HTPA series devices"	(only Ethernet device)
Conditions:	Can be sent as Broadcast, or if device already known as normal packet.	
Answer:	"HTPA series responded! I am Arraytype [AT]" Firmware version, date and author information. "I am running on [MCLK] kHz" "Amplification is [AMP]\r\n" "MAC-ID: [MACID] IP: [IP]\r\n" A second packet with calibration depending information is send.	

Message2:	"x Release HTPA series device"	(only Ethernet device)
Result:	Device disables hardware IP filter. All packets except ARP's, DHCP requests, Broadcasts, Message1, Message3 and Message4 are discarded.	
Answer:	"HW-Filter released\r\n"	

Message3:	"HTPA device IP change request to [IP].[MSK]."	(only Ethernet device)
Result:	The device changes the IP and the subnet mask to the given value and writes it to EEPROM. The IP becomes the default IP, therefore the device will use it at the next reset, if no DHCP is found.	
Answer:	"Device changed IP to [IP]. and Subnet to [MSK].\r\n"	

Message4:	"Bind HTPA series device"	(only Ethernet device)
Result:	Device enables hardware IP filter. Only packets from sender IP, ARP's, DHCP requests and Broadcasts are accepted. Device accepts now the control characters listed in Table 1 .	
Answer:	"HW Filter is [IP] MAC [MACID]\n\r" Insert in the above string the IP and MAC-ID of the Sender from Message4.	

Control Messages [continued]:

Message5: "Set EEPROM data"

Conditions: Only possible if Message 4 already successful sent.

ATTENTION! Calibration data is overwritten!!!

Result: Writes the next received packets into EEPROM, if packet size is equal to 1024 bytes. Device writes to EEPROM, until EEPROM is completely filled.
EEPROM size depends on Device type: HTPA8x8, HTPA16x16 and HTPA32x31: 16384 byte; HTPA64x62: 65536 byte.

Answer: "Write was successful.\n\r"

Message6: "Set DeviceID to [DEVID]"


Result: The given Device ID [DEVID] is written to EEPROM. This ID is shown on receive of 'M'. The eDevice ID can be used for customer specific purposes.

Answer: "DeviceID changed to [DEVID]\r\n"

Rev.0: 2014.10.15 Fg



Dimensions:



HEIMANN Sensor GmbH
Maria-Reiche-Str. 1
D-01109 Dresden / Germany

Contact / Customer Support
Phone 49 (0) 6123 60 50 30
Fax 49 (0) 6123 60 50 39

Internet
www.heimannsensor.com
 mail: info@heimannsensor.com