

In [1]:

#문제1

```
import numpy as np
```

```
arr2 = np.array([[1,2,3],[4,5,6]])  
arr2 = arr2.flatten()*2  
arr2
```

Out[1]:

```
array([ 2,  4,  6,  8, 10, 12])
```

In [2]:

```
print(arr2)
```

```
[ 2  4  6  8 10 12]
```

In [3]:

#문제3

```
import numpy as np
```

```
arr = np.arange(5,31,5)  
arr
```

Out[3]:

```
array([ 5, 10, 15, 20, 25, 30])
```

In [11]:

#문제4

```
arr1 = np.zeros([2,3], dtype=int)  
print(arr1)  
print(arr1.shape)  
print(arr1.ndim)  
print(arr1.dtype)  
print(arr1.size)
```

```
[[0 0 0]  
 [0 0 0]]  
(2, 3)  
2  
int32  
6
```

In [13]:

#문제5

```
arr1 = np.array([[1,2,3],  
                 [4,5,6],  
                 [7,8,9]])
```

```
print(arr1)
```

```
print(arr1[1])
```

```
print(arr1[2,2])
```

```
print(arr1[1:3])
```

```
print(arr1[arr1 <= 5])
```

```
[[1 2 3]
```

```
 [4 5 6]
```

```
 [7 8 9]]
```

```
[4 5 6]
```

```
9
```

```
[[4 5 6]
```

```
 [7 8 9]]
```

```
[1 2 3 4 5]
```

In []: