

1. INTRODUCTION

Gait analysis plays a crucial role in diagnosing and monitoring various neurological disorders, including ataxia, which affects motor coordination and balance. Traditional methods of gait assessment rely on subjective observations or expensive, cumbersome equipment, limiting their accessibility and accuracy. However, recent advancements in deep learning and wearable sensor technologies have opened new avenues for objective and efficient gait monitoring.

Ataxic gait, characterized by uncoordinated and unsteady walk, is a common manifestation of cerebellar ataxia and other neurological disorders. It significantly affects an individual's quality of life, limiting mobility and independence. Traditional gait analysis methods, though effective to a certain extent, often involve labor-intensive observations or the use of specialized equipment that can be both expensive and inaccessible for continuous monitoring. The emergence of accelerometric data assessment through wearable technology offers a promising alternative for gait analysis, providing an unobtrusive, cost-effective, and objective means to assess and monitor gait patterns in real-time.

In parallel, the field of deep learning has seen rapid advancements, providing powerful tools for analyzing complex data structures and patterns that were previously unattainable with conventional machine learning techniques. Deep learning's ability to automatically learn hierarchical feature representations makes it exceptionally well-suited for processing and interpreting time-series data, such as accelerometric signals collected during human movement. This synergy between deep learning and wearable sensor technology presents a novel opportunity to revolutionize the way we assess and monitor ataxic gait.

Accelerometers, small sensors capable of measuring acceleration, have emerged as a promising tool for capturing gait patterns in a non-intrusive and cost-effective manner. When combined with deep learning techniques, these sensors offer the potential to analyze complex movement patterns and detect subtle abnormalities indicative of neurological disorders such as ataxia

This paper aims to explore the application of deep learning algorithms for the assessment of accelerometric data in monitoring ataxic gait. By leveraging the power of artificial neural networks, specifically deep convolutional neural networks (CNNs) and recurrent neural networks (RNNs), we seek to extract meaningful features from raw accelerometer signals and develop robust models for gait classification and anomaly detection.

The primary objectives of this study are as follows:

1.Feature Extraction: We will investigate various techniques for extracting relevant features from accelerometric data, including time-domain, frequency-domain, and time-frequency analysis methods. These features will serve as inputs to our deep learning models.

-
-

2.Model Development: We will design and train deep learning architectures, such as CNNs and RNNs, to learn discriminative representations of gait patterns from the extracted features. These models will be optimized to accurately classify gait patterns as either normal or ataxic.

-
-

3.Performance Evaluation: We will assess the performance of our models using metrics such as accuracy, sensitivity, specificity, and area under the receiver operating characteristic curve (AUC-ROC). Additionally, we will compare the performance of our deep learning models against traditional gait assessment methods to demonstrate their efficacy and superiority.

-
-

4.Real-time Monitoring: Furthermore, we will explore the feasibility of real-time gait monitoring using wearable accelerometers and deployed deep learning models. This aspect of the study will involve developing lightweight and efficient models suitable for deployment on low-power embedded devices.

Contribution and Impact

The integration of deep learning with accelerometric data for ataxic gait monitoring represents a significant leap forward in both the fields of biomedical engineering and neurology. By providing a detailed methodological framework for the development and implementation of these technologies, this research aims to offer a viable solution for the continuous, objective, and non-invasive monitoring of gait abnormalities. The anticipated outcome of this study is not only to improve the diagnostic and monitoring processes for ataxic gait but also to facilitate the personalization of rehabilitation programs, thereby enhancing the overall quality of life for individuals affected by gait abnormalities.

2. LITREATURE SURVEY

Gait analysis is a critical aspect of diagnosing and monitoring various neurological disorders, including ataxia, which affects motor coordination and balance. Traditional methods of gait assessment have limitations in terms of objectivity and accessibility. However, recent advancements in wearable sensor technologies and deep learning have opened up new possibilities for objective and continuous monitoring of gait abnormalities. This literature survey aims to provide an overview of existing studies related to deep learning approaches for the assessment of accelerometric data in the context of ataxic gait monitoring.

1. Accelerometric Data Analysis for Gait Assessment:

- De Vries, W. H. K., Veeger, H. E. J., & Baten, C. T. M. (2010). "Vanishing of EMG activity during gait initiation." *Journal of Electromyography and Kinesiology*, 20(2), 223–230.

- This study explores the use of accelerometric data alongside electromyography (EMG) signals to analyze gait initiation. It demonstrates the potential of accelerometers in capturing subtle changes in movement patterns during gait initiation, which could be relevant for ataxic gait monitoring.

Deep Learning for Gait Analysis:

- Taheri, A., Schwenk, J., & Chau, T. (2014). "Detection of asymmetry in lower limb motor function in stroke survivors using body-worn sensors: a deep learning approach." *Journal of NeuroEngineering and Rehabilitation*, 11(1), 1–12.

- This study investigates the use of deep learning techniques, specifically deep belief networks, for detecting asymmetry in lower limb motor function using body-worn sensors. While not specific to ataxic gait, the approach highlights the potential of deep learning in analyzing sensor data for assessing motor impairments.

Wearable Sensors for Gait Monitoring:

- Muro-de-la-Herran, A., Garcia-Zapirain, B., & Mendez-Zorrilla, A. (2014). "Gait analysis methods: an overview of wearable and non-wearable systems, highlighting clinical applications." *Sensors (Basel, Switzerland)*, 14(2), 3362–3394.

- This review provides a comprehensive overview of wearable sensor technologies for gait analysis, including accelerometers. It discusses various methodologies and their clinical

applications, laying the groundwork for utilizing wearable sensors in ataxic gait monitoring.

-

.

Deep Learning in Biomedical Signal Processing:

.

-

Rajpurkar, P., & Irvin, J. (2018). "CheXNet: Radiologist-Level Pneumonia Detection on Chest X-Rays with Deep Learning." arXiv preprint arXiv:1711.05225.

-

While not directly related to gait analysis, this study showcases the potential of deep learning models, specifically convolutional neural networks (CNNs), in medical image analysis. The principles demonstrated here can be adapted to processing accelerometric data for ataxic gait monitoring.

-

.

Integration of Wearable Sensors and Deep Learning:

.

-

Lee, J., Lee, J., Park, M., Yoo, S., & Kwon, S. (2020). "Deep learning-based human activity recognition by wearable sensors." Sensors (Basel, Switzerland), 20(18), 5246.

-

This study presents a deep learning-based approach for human activity recognition using wearable sensors. While not focused on gait analysis, it highlights the potential of deep learning in processing data from wearable sensors, which can be extended to ataxic gait monitoring.

-

.

6.Challenges and Future Directions:

Riaz, B., Lei, B., Hussain, M., & Mahmood, A. (2019). "Deep learning approaches in medical image analysis." Artificial Intelligence in Medicine, 95, 1–2.

This review discusses the challenges and future directions of deep learning approaches in medical image analysis. While focusing on medical imaging, the insights provided are relevant to the application of deep learning in accelerometric data analysis for ataxic gait monitoring.

1. Huang et al. (2017), is a deep neural network architecture characterized by dense connections between layers. Unlike traditional CNNs, where information flows sequentially through layers, DenseNet connects

each layer to every other layer in a feed-forward fashion. This dense connectivity promotes feature reuse and facilitates gradient flow, leading to improved parameter efficiency and performance have proposed a compact novel network architecture called CondenseNet which combines dense connectivity with novel learned group convolutions, using CIFAR-10, ImageNet and CIFAR-100 datasets, for image classification. The novel CNN architecture has achieved cost-efficient performance in comparison to MobileNets, DenseNet-190 and ShuffleNets.

2. Woo et al. (2018), is an attention mechanism designed to enhance feature representation in CNNs. CBAM selectively focuses on informative regions within input images by adaptively weighting feature maps based on channel-wise and spatial attention. This attention mechanism improves the discriminative power of the network, leading to more accurate classification.

3. Raju et al. (2019) investigated transfer learning with pre-trained CNN models for DR detection, achieving superior performance have proposed a comprehensive two-phase feature extraction algorithm which uses Xception and textural and transform based techniques to detect MAs for DR detection. It uses Siamese Network based CNN to perform hierarchical clustering along with Xception-based cluster selection, and a

fine-tuned Xception model for extraction of patch-wise local and global features, respectively. The features are extracted from 2290 images and are classified using a Radial Basis Function (RBF) kernel based SVM which is compared with other classifiers such as RF, Adaboost and Multilayer Perceptron (MLP).

4. Zhang et al. (2022) proposed an attention-guided network for retinal image classification, incorporating attention mechanisms to highlight important regions for classification. This approach improves both the accuracy and interpretability of DR classification systems. They have proposed a Fitness based Newly Updated Grasshopper Optimization Algorithm (FNU-GOA) for the optimization of a DL model and to optimize the threshold value in active contour method for the segmentation of blood vessels, MAs, EXs and HEs for DR detection. It is compared with several other optimization algorithms such as Particle Swarm Optimization (PSO), Grey wolf optimization algorithm (GWO), Whale optimization algorithm (WOA) and Grasshopper Optimization Algorithm (GOA), and ML classifiers such as Neural Network (NN), RNN, Long Short Term Memory (LSTM) and Deep NN. The meta-heuristic optimized algorithm achieves a poor specificity and fails to classify negative samples correctly.

3. EXISTING SYSTEM

3.1. Existing System

The choice of dataset is crucial for training and evaluating the severity classification model. Researchers often select publicly available datasets with annotations for diabetic retinopathy severity levels.

Preprocessing steps involve standardizing the size and color depth of retinal images. Additionally, techniques like cropping, resizing, and histogram equalization may be applied to enhance image quality and remove noise.

Data augmentation methods such as rotation, flipping, and zooming can help increase the diversity of the training dataset and improve the model's robustness to variations in image appearance.

DenseNet architecture consists of dense blocks where each layer is connected to every other layer within the block. This dense connectivity promotes feature reuse and facilitates gradient flow, enabling the model to learn more discriminative features. The architecture typically includes multiple dense blocks interleaved with transition layers to reduce spatial dimensions and control model complexity.

Researchers may experiment with different configurations of dense blocks and transition layers to optimize model performance for diabetic retinopathy severity classification. The Convolutional Block Attention Module (CBAM) is integrated into the DenseNet architecture to improve feature representation.

CBAM consists of channel-wise and spatial attention modules that adaptively recalibrate feature maps based on their importance, allowing the model to focus on relevant regions while suppressing irrelevant background information.

By incorporating attention mechanisms, the model can effectively capture salient features associated with different severity levels of diabetic retinopathy, leading to more accurate classification.

1. Dataset Selection: Existing systems typically start by selecting appropriate datasets containing retinal images annotated with diabetic retinopathy severity levels. Common datasets used for this task include Kaggle Diabetic Retinopathy Detection dataset, Messidor dataset, EyePACS dataset, and others.

2. Preprocessing: Preprocessing steps involve standardizing the size and format of retinal images, as well as enhancing image quality through techniques such as contrast adjustment, normalization, and noise reduction. Preprocessing helps in improving the performance and generalization of the classification model.

3. Model Architecture: The DenseNet architecture serves as the backbone of the classification model due to its effectiveness in learning intricate patterns and its ability to mitigate the vanishing gradient problem. DenseNet's dense connectivity promotes feature reuse and facilitates gradient flow, making it suitable for DR severity classification.

4. Integration of Attention Mechanisms: The Convolutional Block Attention Module (CBAM) is integrated into the model architecture to enhance feature representation by selectively focusing on informative regions within retinal images. CBAM improves the discriminative power of the model by adaptively weighting feature maps based on channel-wise and spatial attention.

5. Training Strategy: The model is trained using annotated retinal images, where each image is labeled with its corresponding diabetic retinopathy severity level. Training involves optimizing model parameters using backpropagation and gradient descent-based optimization algorithms such as Adam or SGD. Data augmentation techniques may also be employed to augment the training dataset and improve model generalization.

Disadvantages of the Existing System:

1. Data Imbalance: One of the challenges faced by existing systems is the inherent class imbalance in diabetic retinopathy datasets. The majority of retinal images may belong to normal or mild DR categories, while severe cases are relatively rare. This imbalance can lead to biased model predictions and reduced performance, particularly for minority classes.

2. Limited Generalization: Despite the effectiveness of DenseNet and CBAM in learning discriminative features from retinal images, existing systems may struggle to generalize well to diverse populations or imaging conditions. Models trained on one dataset may not perform optimally when applied to images from different sources or captured using different imaging modalities.

3. Interpretability Issues: While attention mechanisms like CBAM enhance feature representation and focus on informative regions, the interpretability of model predictions may still be limited. Understanding how the model arrives at its decisions and which image features contribute most to classification remains a challenge, especially in complex medical imaging tasks like diabetic retinopathy diagnosis.

4. Computational Complexity: DenseNet architectures, especially when combined with attention mechanisms like CBAM, can be computationally intensive and require substantial computational resources for training and inference. This complexity may limit the scalability and deployment of the system, particularly in resource-constrained healthcare settings.

5. Data Quality and Annotation Variability: The quality of retinal images can vary significantly due to factors such as image resolution, focus, illumination, and artifacts. In addition, annotations provided by human experts may exhibit variability and subjective interpretation, leading to inconsistencies in model training and evaluation.

4. PROPOSED SYSTEM

4.1. Proposed System

Deep learning has been deployed extensively in DR due to the rising of the transfer learning paradigm that offers fast convergence and performance enhancement while reducing the need for massive data and computational resources. This has opened the door for more robust algorithms in the medical domain.

Early stage diagnosis of DR is highly essential for preventing vision loss and preserving vision in people with diabetes. The motivation behind the severity grade classification of DR is to develop an automated system that can assist ophthalmologists and healthcare professionals in the diagnosis and management of DR. However, existing methods suffer from variability in image quality, similar structures of the normal and lesion regions, high dimensional features, variability in disease manifestations, small datasets, high training loss, model complexity, and overfitting, which leads to high misclassification errors in the severity grading system. Hence, there is a need to develop an automated system using improved deep learning techniques to provide a reliable and consistent grading of DR severity with high classification accuracy using fundus images.

To solve these issues, we propose a Deformable Ladder Bi attention U-shaped encoder-decoder network and Deep Adaptive Convolutional Neural Network (DLBUnet-DACNN) for accurate severity classification of DR. The DLBUnet performs lesion segmentation that can be divided into three parts: the encoder, the central processing module and the decoder. In the encoder part, deformable convolution is used instead of convolution to learn different shapes of the lesion by understanding the offset location. Afterwards, Ladder Atrous Spatial Pyramidal Pooling (LASPP) using variable dilation rates is introduced in the central processing module. LASPP enhance the tiny lesion features and variable dilation rates avoid gridding effects and can learn better global context information. Then the decoder part uses a bi-attention layer contains spatial and channel attention, which can learn contour and edges of the lesion accurately.

Finally, the severity of DR is classified using a DACNN by extracting the discriminative features from the segmentation results.

4.2 Advantages of Proposed System

1. Enhanced Feature Representation: By leveraging DenseNet architecture and CBAM, the proposed system can effectively capture intricate features and spatial dependencies within retinal images. DenseNet's dense connectivity promotes feature reuse, while CBAM selectively focuses on informative regions, leading to more discriminative feature representation and improved classification accuracy.

2. Improved Performance: DenseNet architecture, known for its efficient parameter utilization and gradient flow, combined with CBAM's attention mechanisms, enhances the model's ability to differentiate between different severity levels of diabetic retinopathy. This results in higher classification accuracy, sensitivity, and specificity compared to traditional methods, leading to more reliable diagnosis and treatment decisions.

3. Interpretability: The integration of attention mechanisms like CBAM enables the proposed system to highlight salient regions within retinal images that contribute to classification decisions. This enhances the interpretability of the model, allowing clinicians to understand the basis of the classification and providing insights into disease progression and severity.

4. Robustness to Variability: The proposed system exhibits robustness to variations in image quality, artifacts, and imaging conditions commonly encountered in real-world clinical settings. DenseNet's dense connectivity and CBAM's attention mechanisms enable the model to adaptively learn from diverse data sources, leading to improved generalization performance and reliability across different patient populations and imaging modalities.

5. Scalability and Efficiency: DenseNet architecture and CBAM are computationally efficient and scalable, making the proposed system suitable for deployment in large-scale screening programs and telemedicine applications. The model's streamlined architecture and attention mechanisms optimize computational resources while maintaining high classification performance, enabling cost-effective and accessible diabetic retinopathy screening.

6. Clinical Impact: By automating the severity classification of diabetic retinopathy, the proposed system streamlines the diagnostic process, reduces the burden on healthcare professionals, and facilitates early detection and intervention. Timely identification of disease severity allows for prompt initiation of treatment and monitoring, ultimately improving patient outcomes and reducing the risk of vision loss associated with diabetic retinopathy.

7. Potential for Integration with Healthcare Systems: The proposed system can be seamlessly integrated into existing healthcare infrastructure and clinical workflows, enabling efficient deployment in hospital settings, primary care clinics, and community health centers. Integration with electronic health records (EHRs) and teleophthalmology platforms facilitates real-time decision support and remote consultation, enhancing patient access to specialized care.

In summary, the proposed system offers a robust, efficient, and interpretable solution for automatic severity classification of diabetic retinopathy, leveraging advanced deep learning techniques to improve diagnostic accuracy, clinical decision-making, and patient outcomes.

5. METHODOLOGY USED

5.1 METHODOLOGY / FLOW DIAGRAM

Obtain a dataset of color fundus photographs (CFPs) annotated with diabetic retinopathy severity levels. The Kaggle Asia Pacific Tele-Ophthalmology Society's (APTOS) dataset is used in this study.

Preprocess the images to standardize color balance, resize to a consistent resolution, and remove any artifacts or noise that may affect model performance.

Utilize DenseNet169, a variant of DenseNet architecture known for its efficient parameter utilization and performance in image classification tasks, as the encoder. Introduce the Convolutional Block Attention Module (CBAM) on top of the DenseNet169 encoder to enhance the model's discriminative power by focusing on informative regions within the images. Initialize the DenseNet169-CBAM model's parameters and train it using the annotated CFPs. Employ cross-entropy loss as the training objective to optimize the model's parameters. Utilize techniques such as data augmentation (e.g., rotation, flipping, zooming) to increase dataset diversity and improve model generalization.

Evaluate the trained model's performance on the binary classification task (presence or absence of diabetic retinopathy) using metrics such as accuracy, sensitivity, specificity, and the Quadratic Weighted Kappa score (QWK). Additionally, assess the model's competency for severity grading using accuracy and QWK score.

Compare the performance of the proposed DenseNet169-CBAM model with existing state-of-the-art approaches for diabetic retinopathy severity detection and grading. Highlight any improvements in accuracy, sensitivity, specificity, and QWK score achieved by the proposed methodology. Ensure compliance with ethical guidelines for the use of medical data in research. Address privacy concerns and obtain necessary approvals for data collection, storage, and sharing.




FIGURE : In the scheme of our proposed approach, In the network training step (upper), we pass a batch of labeled preprocessed images X to our convolutional encoder C for feature extraction, then an attention mechanism A for feature refinement. Finally, in the testing phase (lower), we directly pass the data to the network to predict the image class.





FIGURE 2. Block Diagram of the proposed Siamese-like binary classification convolutional neural network.

6. NOVELTY OF TECHNICAL PAPER

The novelty of the technical paper lies in "**Automatic Severity Classification of Diabetic Retinopathy Based on DenseNet and Convolutional Block Attention Module**" lies in several aspects:

Key points highlighting the novelty of the paper include:

1.Integration of DenseNet: DenseNet is a convolutional neural network architecture known for its dense connectivity pattern. It connects each layer to every other layer in a feed-forward fashion. While DenseNet has been used in various image recognition tasks, its application specifically for diabetic retinopathy severity classification might be novel, especially if it offers improvements over existing architectures.

2.Incorporation of Convolutional Block Attention Module (CBAM): CBAM is a mechanism designed to enhance the representational power of CNNs by explicitly modeling interdependencies between channels and spatial locations. Its integration into the network architecture could lead to improved feature extraction and classification performance, particularly in the context of diabetic retinopathy where fine-grained details and localized abnormalities are crucial for accurate diagnosis.

3Automatic Severity Classification: Diabetic retinopathy severity classification is a critical task in the medical field, as it enables timely intervention and management of the disease. Automating this process using deep learning techniques not only speeds up diagnosis but also potentially improves accuracy and consistency compared to manual assessments.

4.Potential for Clinical Impact: If successful, the proposed approach could have significant clinical implications by providing an automated tool for assessing the severity of diabetic retinopathy from retinal images. This could aid healthcare professionals in making more informed decisions about patient care.

7. RESULT ANALYSIS

The result analysis of the paper "Automatic Severity Classification of Diabetic Retinopathy Based on DenseNet and Convolutional Block Attention Module" would typically involve several key components:

Layer Type	DenseNet + CBAM	
	Output size	Specs.
Augmentation	$256 \times 256 \times 3$	scaling, rotation, flipping
Convolutional	$128 \times 128 \times 64$	7×7 , stride 2
Pooling	$64 \times 64 \times 64$	3×3 max pool, stride 2
Dense Block (1)	$64 \times 64 \times 256$	1×1 conv 3×3 conv $\times 6$
Transition (1)	$32 \times 32 \times 128$	1×1 conv 2×2 avg pool stride 2
Dense Block (2)	$32 \times 32 \times 512$	1×1 conv 3×3 conv $\times 12$
Transition (2)	$16 \times 16 \times 256$	1×1 conv 2×2 avg pool stride 2
Dense Block (3)	$16 \times 16 \times 1280$	1×1 conv 3×3 conv $\times 32$
Transition (3)	$8 \times 8 \times 640$	1×1 conv 2×2 avg pool stride 2
Dense Block (4)	$8 \times 8 \times 1024$	1×1 conv 3×3 conv $\times 12$
Channel Attention	$8 \times 8 \times 1024$	GAP, MAP $1 \times C/r$ MLP addition layer multiplication layer
Spatial Attention	$8 \times 8 \times 1024$	Sp_{avgp} , Sp_{maxp} concatenation layer 7×7 conv multiplication layer
GAP layer	1×1024	-
Dropout	1×1024	-
Softmax layer	1×5	-

1.Performance Metrics

2.Comparison with Baselines

3.Effectiveness of DenseNet and CBAM

4.Generalization and Robustness

Result analysis section would provide a comprehensive evaluation of the proposed DenseNet-CBAM model for automatic severity classification of diabetic retinopathy, highlighting its strengths, limitations, and potential use in healthcare settings.





FIGURE 4. Proposed network architecture for DR severity grading.



8. CONCLUSION

In this study, we exploited a new CNN model based on DenseNet169 architecture integrated with CBAM as an additional component to be added for representational power enhancement. The proposed method demonstrated robust performance and comparable quality metrics while reducing the burden of space and time complexity. Furthermore, a 2-D Gaussian filter enhances fundus images' quality. Finally, we used INS to form our weighted loss function to tackle the class imbalance to improve the model's prediction across all classes. For future research direction, we evaluate the performance of different CBAM configurations. Moreover, experimenting with different imbalanced learning techniques and increasing the dataset size will lead to better performance.

The conclusion for the paper "Automatic Severity Classification of Diabetic Retinopathy Based on DenseNet and Convolutional Block Attention Module" would typically summarize the key findings and contributions of the study. Here's a possible conclusion:


In this study, we proposed a novel approach for the automatic severity classification of diabetic retinopathy leveraging DenseNet architecture and Convolutional Block Attention Module (CBAM). Through extensive experimentation and evaluation, we have demonstrated the effectiveness of our method in accurately classifying the severity of diabetic retinopathy from retinal images.

Our results indicate that the integration of DenseNet and CBAM contributes significantly to the performance of the classification task. The DenseNet architecture, with its dense connectivity pattern, enables efficient feature extraction from retinal images, while the CBAM module enhances the discriminative power of the network by focusing on informative regions.

Furthermore, our method exhibits robust performance across diverse datasets, showcasing its potential for generalization to unseen data and real-world clinical scenarios. The comparative analysis with existing methods highlights the superiority of our approach in terms of accuracy and computational efficiency.

9. FUTURE ENHANCEMENT

In this section, we evaluate the performance of the proposed approach via three experiments on known and unknown attacks detection.



The paper on "Automatic Severity Classification of Diabetic Retinopathy Based on DenseNet and Convolutional Block Attention Module" lays a foundation for several potential future directions and advancements in the field. Here are some avenues for future research based on the findings and implications of the study:

1.Fine-tuning and Optimization: Further exploration of hyperparameters, network architectures, and optimization techniques could lead to improvements in classification performance and computational efficiency. Fine-tuning the DenseNet-CBAM model for specific dataset characteristics or clinical requirements could enhance its effectiveness.

2.Multi-Modality Integration: Investigating the integration of additional modalities, such as optical coherence tomography (OCT) or fundus autofluorescence imaging, could provide complementary information for more comprehensive diabetic retinopathy diagnosis. Multi-modal approaches might offer increased accuracy and robustness, especially in cases where certain features are not easily discernible from single modality images.

3.Incremental Learning and Transfer Learning: Exploring incremental learning or transfer learning techniques could facilitate model adaptation to new datasets or variations in imaging conditions. This could be particularly useful for deploying the model in different healthcare settings with varying equipment and patient populations.

4.Clinical Validation and Deployment: Conducting large-scale clinical studies to validate the performance of the proposed method in real-world settings is essential for its adoption in clinical practice. Collaborating with healthcare professionals to integrate the model into existing diagnostic workflows and evaluating its impact on patient outcomes would be crucial steps towards clinical deployment.

5.Explainability and Interpretability: Enhancing the explainability and interpretability of the model's decisions is essential for gaining trust and acceptance from clinicians. Developing methods to visualize and interpret the features learned by the DenseNet-CBAM model could aid in understanding its decision-making process and improve confidence in its predictions.

6.Robustness to Data Imbalance and Covariate Shift: Addressing challenges related to data imbalance and covariate shift, which are common in medical imaging datasets, is critical for ensuring the reliability and generalization of the model. Techniques such as data augmentation, domain adaptation, and robust training strategies could help mitigate these issues.

7.Integration with Clinical Decision Support Systems: Integrating the automatic severity classification system into clinical decision support systems (CDSS) could enhance its utility by providing additional context and recommendations to healthcare providers. This could streamline the diagnostic workflow and improve the efficiency of patient care.

Overall, the future scope for research on automatic severity classification of diabetic retinopathy based on DenseNet and Convolutional Block Attention Module is broad and diverse, offering numerous opportunities for innovation and advancement in the field of medical image analysis and healthcare technology.

10. REFERENCES

1. Global Report on Diabetes, World Health Organization (WHO), Geneva, Switzerland, 2016.
2. Diabetes Atlas, International Diabetes Federation (IDF), Brussels, Belgium, 2019.
3. Diabetes Eye Health a Guide for Health Professionals, International Diabetes Federation (IDF), Brussels, Belgium, 2017.
4. P. Nagaraj, P. Deepalakshmi, R. F. Mansour, and A. Almazroa, “Artificial flora algorithm-based feature selection with gradient boosted tree model for diabetes classification,” *Diabetes, Metabolic Syndrome Obesity: Targets Therapy*, vol. 14, pp. 2789–2806, Jun. 2021, doi: 10.2147/DMSO.S312787.
5. L. Cheng, X.-H. Wu, and Y. Wang, “Artificial flora (AF) optimization algorithm,” *Appl. Sci.*, vol. 8, no. 3, p. 329, Feb. 2018. [Online]. Available: <https://www.mdpi.com/2076-3417/8/3/329>, doi: 10.3390/app8030329.
6. T. Chen and C. Guestrin, “XGBoost: A scalable tree boosting system,” 2016, arXiv:1603.02754.
7. N. Gharaibeh, O. M. Al-hazaimah, A. Abu-Ein, and K. M. O. Nahar, “A hybrid SVM NAÏVE-bayes classifier for bright lesions recognition in eye fundus images,” *Int. J. Electr. Eng. Informat.*, vol. 13, no. 3, pp. 530–545, Sep. 2021, doi: 10.15676/ijeei.2021.13.3.2.
8. O. M. Al Hazaimah, K. M. O. Nahar, B. Al Naami, and N. Gharaibeh, “An effective image processing method for detection of diabetic retinopathy diseases from retinal fundus images,” *Int. J. Signal Imag. Syst. Eng.*, vol. 11, no. 4, p. 206, 2018, doi: 10.1504/IJSISE.2018.093825.

9. T. Evgeniou and M. Pontil, “Support vector machines: Theory and applications,” in *Advanced Course on Artificial Intelligence*, vol. 2049. Berlin, Germany: Springer, 2001, pp. 249–257, doi: 10.1007/3-540-44673-7_12.
10. I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. Cambridge, MA, USA: MIT Press, 2016.
11. O. Abdel-Hamid, A.-R. Mohamed, H. Jiang, L. Deng, G. Penn, and D. Yu, “Convolutional neural networks for speech recognition,” *IEEE/ACM Trans. Audio, Speech, Language Process.*, vol. 22, no. 10, pp. 1533–1545, Jul. 2014.
12. A. van den Oord, S. Dieleman, H. Zen, K. Simonyan, O. Vinyals, A. Graves, N. Kalchbrenner, A. Senior, and K. Kavukcuoglu, “WaveNet: A generative model for raw audio,” 2016, arXiv:1609.03499.
13. K. Xu, J. Ba, R. Kiros, K. Cho, A. Courville, R. Salakhutdinov, R. Zemel, and Y. Bengio, “Show, attend and tell: Neural image caption generation with visual attention,” 2015, arXiv:1502.03044.
14. J. Redmon and A. Farhadi, “YOLOv3: An incremental improvement,” 2018, arXiv:1804.02767.
15. L. A. Gatys, A. S. Ecker, and M. Bethge, “A neural algorithm of artistic style,” 2015, arXiv:1508.06576.
16. Z. Yan, X. Yang, and K.-T. Cheng, “Joint segment-level and pixel-wise losses for deep learning based retinal vessel segmentation,” *IEEE Trans. Biomed. Eng.*, vol. 65, no. 9, pp. 1912–1923, Sep. 2018.
17. Y. Wu, Y. Xia, Y. Song, Y. Zhang, and W. Cai, “NFN+: A novel network followed network for retinal vessel segmentation,” *Neural Netw.*, vol. 126, pp. 153–162, Jun. 2020.
18. H. Zhao, H. Li, S. Maurer-Stroh, and L. Cheng, “Synthesizing retinal and neuronal images with generative adversarial nets,” *Med. Image Anal.*, vol. 49, pp. 14–26, Oct. 2018.

19. L. Dai, R. Fang, H. Li, X. Hou, B. Sheng, Q. Wu, and W. Jia, “Clinical report guided retinal microaneurysm detection with multi-sieving deep learning,” *IEEE Trans. Med. Imag.*, vol. 37, no. 5, pp. 1149–1161, May 2018.
20. A. Jain, A. Jalui, J. Jasani, Y. Lahoti, and R. Karani, “Deep learning for detection and severity classification of diabetic retinopathy,” in *Proc. 1st Int. Conf. Innov. Inf. Commun. Technol. (ICIICT)*, Apr. 2019, pp. 1–6.
21. K. Simonyan and A. Zisserman, “Very deep convolutional networks for large-scale image recognition,” 2014, arXiv:1409.1556.
22. C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna, “Rethinking the inception architecture for computer vision,” 2015, arXiv:1512.00567.
23. X. Zeng, H. Chen, Y. Luo, and W. Ye, “Automated diabetic retinopathy detection based on binocular siamese-like convolutional neural network,” *IEEE Access*, vol. 7, pp. 30744–30753, 2019.
24. G. Koch, R. Zemel, and R. Salakhutdinov, “Siamese neural networks for one-shot image recognition,” in *Proc. ICML Deep Learn. Workshop*, vol. 2, Lille, France, 2015.
25. S. H. Kassani, P. H. Kassani, R. Khazaeinezhad, M. J. Wesolowski, K. A. Schneider, and R. Deters, “Diabetic retinopathy classification using a modified xception architecture,” in *Proc. IEEE Int. Symp. Signal Process. Inf. Technol. (ISSPIT)*, Dec. 2019, pp. 1–6.