

SudokuForge Netlify Deployment Guide

This guide provides step-by-step instructions on how to build and deploy **SudokuForge** to Netlify.

Since SudokuForge is built with **Vite, React, and TypeScript**, it compiles to a highly optimized set of static assets (HTML, CSS, and JS) located in the `dist/` directory. This makes it extremely fast and lightweight, perfect for Netlify's high-performance CDN.

Included Deployment Files

We have pre-configured and created all necessary deployment configurations in the project workspace:

- [netlify.toml](#): Defines build commands and publish directories.

```
[build]
```

```
command = "npm run build"
```

```
publish = "dist"
```

```
` `
```

- **.netlify/state.json**: Links the local workspace directly to your active Netlify site
- **deploy-netlify.cmd**: Double-clickable Windows Command script that compiles and deploys the app
- **deploy-netlify.ps1**: PowerShell version of the one-click build and deploy script



Deployment Option A: One-Click Local Scripts

You can build and deploy the app directly from your local computer using

Step 1: Run the Script

- On Windows (Command Prompt): Double-click `deploy-netlify.cmd` or run i

```
`cmd
```

```
deploy-netlify.cmd
```

```
`
```

- On Windows (PowerShell): Right-click `deploy-netlify.ps1` and select *R

```
`powershell
```

```
.\deploy-netlify.ps1
```

```
`
```

Step 2: Authentication (First Time Only)

If the Netlify CLI is not already logged in on your machine, the script

Enter your Netlify Auth Token (or press Enter if CLI is already logged in)

- Paste your Netlify Personal Access Token (e.g., nfp_TppU...) and press **Enter**
- The script will compile the TypeScript bundle (npm run build) and immediately



Deployment Option B: Continuous Integration

Setting up continuous deployment from a Git repository (like GitHub or Code

Step 1: Initialize Git and Push to GitHub

- Open your terminal in the sudokuforge directory.

- Initialize and push your repository:

```
`bash
```

```
git init
```

```
git add .
```

```
git commit -m "feat: integrate support ticketing system"
```

```
# Create a repository on GitHub, then link and push it:
```

```
git remote add origin https://github.com/YOUR_USERNAME/sudokuforge.git
```

```
git branch -M main
```

```
git push -u origin main
```

```
`
```

Step 2: Connect to Netlify

- Go to your [Netlify Dashboard](#).
- Click **Add new site** > **Import an existing project**.
- Select **GitHub** (or your Git provider) and authorize Netlify.
- Select your sudokuforge repository.

Step 3: Configure Build Settings

Netlify will automatically detect the settings from netlify.toml. Verify they

- **Build Command:** `npm run build`
- **Publish Directory:** `dist`
- **Branch to Deploy:** `main`

Click **Deploy sudokuforge**. Netlify is now linked to your repository!



Setting Up Environment Variables (Paddle Billing)

If you are using real Paddle Billing v2 configurations, you must set the

For Local Script Deployments (Option A):

Create or edit your `.env` file in the project root:

```
env
```

```
VITE_PADDLE_ENVIRONMENT=sandbox
```

```
VITE_PADDLE_CLIENT_TOKEN=test_client_YOUR_PADDLE_CLIENT_TOKEN
```

```
VITE_PADDLE_MONTHLY_PRICE_ID=pri_monthly_price_id
```

```
VITE_PADDLE_LIFETIME_PRICE_ID=pri_lifetime_price_id
```

```
|
```

```
|`
```

```
|
```

***Note:** Vite embeds variables starting with `VITE_` into the production build during compile time (`npm run build`).*

For Git CI/CD Deployments (Option B) :

- In the Netlify Dashboard, navigate to your site.
- Go to Site Configuration > Environment variables.
- Click Add a variable and add the following keys:
- VITE_PADDLE_ENVIRONMENT
- VITE_PADDLE_CLIENT_TOKEN
- VITE_PADDLE_MONTHLY_PRICE_ID
- VITE_PADDLE_LIFETIME_PRICE_ID
- Re-trigger a deploy or push a commit to rebuild the site with the new credentials.

Custom Domain Setup

To link your custom domain (e.g. `sudokuforge.com`) to your Netlify site:

- In the Netlify Dashboard, click on your site.

- Go to Site Configuration > Domain management.
 - Click Add custom domain and enter your domain address.
 - Update your DNS settings at your domain registrar:
- Add a CNAME record pointing `www.yourdomain.com` to `sudokuforge.netlify.app`.
 - Add an A record pointing `@` (root domain) to Netlify's IP address: `75.101.145.87`.
 - Netlify will automatically generate and renew a free Let's Encrypt SSL certificate for HTTPS security within a few hours.

Troubleshooting & SPA Redirects

- SPA Routing (Refreshes & 404s):

SudokuForge uses Hash Routing (`#!/landing` , `#!/generator` , `#!/admin`), meaning page state is handled via URL hashes. Because of this, refreshing a subpage will never trigger a Netlify 404 error.

(If you switch to Browser Routing in the future, you must create a `_redirects` file in `public/` containing `/* /index.html 200` to prevent 404s on refreshes).

- Windows script execution restrictions:

If PowerShell returns an error about script execution when running `deploy-netlify.ps1` , run this command to temporarily bypass the execution policy:

```
powershell
```

```
Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass
```

```
.\deploy-netlify.ps1
```

```
``
```