



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Experiment 6

Student Name: Rachit Kumar
Branch: BE CSE
Subject Name: Advanced Database
and Management System
Semester: 5th

UID: 23BCS11597
Section: 23BCS_KRG-2/A
Subject Code: 23CSP-333

1. Aim:

Q1: HR-Analytics: Employee count based on dynamic gender passing

TechSphere Solutions, a growing IT services company with offices across India, wants to track and monitor gender diversity within its workforce. The HR department frequently needs to know the total number of employees by gender (Male or Female). To solve this problem, the company needs an automated database-driven solution that can instantly return the count of employees by gender through a stored procedure that:

1. Create a PostgreSQL stored procedure that:
2. Takes a gender (e.g., 'Male' or 'Female') as input.
3. Calculates the total count of employees for that gender.
4. Returns the result as an output parameter.
5. Displays the result clearly for HR reporting purposes.

Q2: Smart Store Automated Purchase System

SmartShop is a modern retail company that sells electronic gadgets like smartphones, tablets, and laptops. The company wants to automate its ordering and inventory management process. Whenever a customer places an order, the system must:

1. Verify stock availability for the requested product and quantity.
2. If sufficient stock is available:
 - o Log the order in the sales table with the ordered quantity and total price.
 - o Update the inventory in the products table by reducing quantity_remaining and increasing quantity_sold.
 - o Display a real-time confirmation message: "Product sold successfully!"
3. If there is insufficient stock, the system must:
 - o Reject the transaction and display: "Insufficient Quantity Available!"

2. Tools Used: PgAdmin

3. Code:

Q1:

```
Q1: -- Create the employee_info table
CREATE TABLE employee_info (
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
id SERIAL PRIMARY KEY,  
name VARCHAR(50) NOT NULL,  
gender VARCHAR(10) NOT NULL,  
salary NUMERIC(10,2) NOT NULL,  
city VARCHAR(50) NOT NULL  
);  
  
-- Insert sample data  
INSERT INTO employee_info (name, gender, salary, city)  
VALUES  
('Alok', 'Male', 50000.00, 'Delhi'),  
('Priya', 'Male', 60000.00, 'Mumbai'),  
('Rajesh', 'Female', 45000.00, 'Bangalore'),  
('Sneha', 'Male', 55000.00, 'Chennai'),  
('Anil', 'Male', 52000.00, 'Hyderabad'),  
('Sunita', 'Female', 48000.00, 'Kolkata'),  
('Vijay', 'Male', 47000.00, 'Pune'),  
('Ritu', 'Male', 62000.00, 'Ahmedabad'),  
('Amit', 'Female', 51000.00, 'Jaipur');  
  
-- Create stored procedure to get employee count by gender  
CREATE OR REPLACE PROCEDURE sp_get_employees_by_gender(  
    IN p_gender VARCHAR(50),  
    OUT p_employee_count INT  
)  
LANGUAGE plpgsql  
AS $$  
BEGIN  
    -- Count total employees by gender  
    SELECT COUNT(id)  
    INTO p_employee_count  
    FROM employee_info  
    WHERE gender = p_gender;  
  
    -- Display the result  
    RAISE NOTICE 'Total employees with gender %: %', p_gender, p_employee_count;  
END;  
$$;  
  
-- Call the procedure  
CALL sp_get_employees_by_gender('Male', NULL);
```

Q2:

```
-- Create products table  
CREATE TABLE products (  
    product_code VARCHAR(10) PRIMARY KEY,  
    product_name VARCHAR(100) NOT NULL,
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
price NUMERIC(10,2) NOT NULL,
quantity_remaining INT NOT NULL,
quantity_sold INT DEFAULT 0
);

-- Create sales table
CREATE TABLE sales (
    order_id SERIAL PRIMARY KEY,
    order_date DATE NOT NULL,
    product_code VARCHAR(10) NOT NULL,
    quantity_ordered INT NOT NULL,
    sale_price NUMERIC(10,2) NOT NULL,
    FOREIGN KEY (product_code) REFERENCES products(product_code)
);

-- Insert sample products
INSERT INTO products (product_code, product_name, price, quantity_remaining,
quantity_sold)
VALUES
    ('P001', 'iPhone 13 Pro Max', 109999.00, 10, 0),
    ('P002', 'Samsung Galaxy S23 Ultra', 99999.00, 8, 0),
    ('P003', 'iPad Air', 55999.00, 5, 0),
    ('P004', 'MacBook Pro 14"', 189999.00, 3, 0),
    ('P005', 'Sony WH-1000XM5 Headphones', 29999.00, 15, 0);

-- Insert sample sales
INSERT INTO sales (order_date, product_code, quantity_ordered, sale_price)
VALUES
    ('2025-09-15', 'P001', 1, 109999.00),
    ('2025-09-16', 'P002', 2, 199998.00),
    ('2025-09-17', 'P003', 1, 55999.00),
    ('2025-09-18', 'P005', 2, 59998.00),
    ('2025-09-19', 'P001', 1, 109999.00);

-- View current tables
SELECT * FROM products;
SELECT * FROM sales;

-- Create stored procedure to buy products
CREATE OR REPLACE PROCEDURE pr_buy_products(
    IN p_product_name VARCHAR,
    IN p_quantity INT
)
LANGUAGE plpgsql
AS $$
DECLARE
    v_product_code VARCHAR(20);
    v_price NUMERIC;
    v_count INT;
BEGIN
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
-- Step 1: Check if product exists and has enough quantity
SELECT COUNT(*)
INTO v_count
FROM products
WHERE product_name = p_product_name
AND quantity_remaining >= p_quantity;

-- Step 2: If sufficient stock
IF v_count > 0 THEN
    -- Fetch product code and price
    SELECT product_code, price
    INTO v_product_code, v_price
    FROM products
    WHERE product_name = p_product_name;

    -- Insert a new record into the sales table
    INSERT INTO sales (order_date, product_code, quantity_ordered, sale_price)
    VALUES (CURRENT_DATE, v_product_code, p_quantity, (v_price * p_quantity));

    -- Update stock details
    UPDATE products
    SET quantity_remaining = quantity_remaining - p_quantity,
        quantity_sold = quantity_sold + p_quantity
    WHERE product_code = v_product_code;

    -- Confirmation message
    RAISE NOTICE 'PRODUCT SOLD..! Order placed successfully for % unit(s) of %.',
        p_quantity, p_product_name;

ELSE
    -- Step 3: If stock is insufficient
    RAISE NOTICE 'INSUFFICIENT QUANTITY..! Order cannot be processed for % unit(s) of
%. ',
        p_quantity, p_product_name;

END IF;
END;
$$;

-- Call the procedure to test
CALL pr_buy_products('MacBook Pro 14"', 1);
```

4. Output

Q1:

Output:

Data Output		Messages
<div> <div></div> <div></div> <div></div> <div></div> <div></div> </div>		
	<p>p_employee_count</p> <p>integer</p>	
1		6

Hard Level Problem

Q2:

	order_id [PK] integer	order_date date	product_code character varying (10)	quantity_ordered integer	sale_price numeric (10,2)
1	1	2025-09-15	P001	1	109999.00
2	2	2025-09-16	P002	2	199998.00
3	3	2025-09-17	P003	1	55999.00
4	4	2025-09-18	P005	2	59998.00
5	5	2025-09-19	P001	1	109999.00
6	6	2025-09-24	P004	1	189999.00

	product_code [PK] character varying (10)	product_name character varying (100)	price numeric (10,2)	quantity_remaining integer	quantity_sold integer
1	P001	IPHONE 13 PRO MAX	109999.00	10	0
2	P002	Samsung Galaxy S23 Ultra	99999.00	8	0
3	P003	IPAD AIR	55999.00	5	0
4	P005	Sony WH-1000XM5 Headphones	29999.00	15	0
5	P004	MacBook Pro 14"	189999.00	2	1

Data Output Messages Notifications

NOTICE: PRODUCT SOLD..! Order placed successfully for 1 unit(s) of MacBook Pro 14".
CALL

Query returned successfully in 79 msec.



5. Learning Outcomes

1. Learn to **create and use PostgreSQL stored procedures** to automate repetitive queries.
2. Understand how to **pass input parameters** to procedures and **return output results** dynamically.
3. Apply **conditional logic** (IF...ELSE) within procedures to handle different scenarios, such as stock availability or gender-based employee count.
4. Gain experience in **updating, inserting, and managing data** across multiple tables within a procedure.
5. Strengthen skills in **database-driven automation, reporting, and real-time messaging** for practical business applications.