OS-KSCATALOG-admin Extension

API v2.0 (Aug 29, 2011)

DRAFT

openstack™

docs.openstack.org

OS-KSCATALOG-admin Extension

API v2.0 (2011-08-29)

Copyright © 2010, 2011 OpenStack All rights reserved.

This document includes details on various operations supported by the OS-KSCATALOG-admin extensions on top of core keystone operations.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

Table of Contents

1. About This Extension 1
1.1. Document Change History 2
2. Extension Operations 3
2.1. OS-KSCATALOG Admin Extension 3
2.1.1. Endpoint Template Operations 4
2.1.2. Endpoint Operations 10

List of Tables

2.1. Authentication Header 3
2.2. List Endpoint Templates parameters 4
2.3. Add Endpoint Template parameters 7
2.4. Get Endpoint Template parameters 9
2.5. Delete Endpoint Template. parameters 10
2.6. List Endpoints parameters 11
2.7. Add Endpoint parameters 13
2.8. Get Endpoint parameters 15
2.9. Delete Endpoint. parameters 16

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

List of Examples

2.1. List Endpont Templates Response: XML 4
2.2. List Endpont Templates Response: JSON 5
2.3. Add Endpoint Template Request: XML 7
2.4. Add Endpoint Template Request: JSON 7
2.5. Add Endpoint Template Response: XML 8
2.6. Add Endpoint Template Response: JSON 8
2.7. Get Endpont Template Response: XML 9
2.8. Get Endpont Template Response: JSON 9
2.9. Delete Endpoint Template Request 10
2.10. List Endponts Response: XML 11
2.11. List Endponts Response: JSON 12
2.12. Add Endpoint Request: XML 14
2.13. Add Endpoint Request: JSON 14
2.14. Add Endpoint Response: XML 14
2.15. Add Endpoint Response: JSON 15
2.16. Get Endpont Response: XML 15
2.17. Get Endpont Response: JSON 16
2.18. Delete Endpoint From a Tenant Request 17

1. About This Extension

Name	OpenStack KSCATALOG Extension
Namespace	http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0
Alias	OS-KSCATALOG-admin
Dependencies	Keystone - OpenStack Identity
Doc Link (PDF)	https://github.com/openstack/keystone/raw/master/keystone/content/admin/OS-KSCATALOG-admin-devguide.pdf
Doc Link (WADL)	https://raw.github.com/openstack/keystone/master/keystone/content/admin/OS-KSCATALOG-admin.wadl
Doc Link (XSD)	https://raw.github.com/openstack/keystone/master/keystone/content/common/xsd/OS-KSCATALOG.xsd
Short Description	OpenStack KSCATALOG Admin Extension to Keystone v2.0 API adds the capability to do CRUD on Endpoint Templates and Endpoints.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

1.1. Document Change History

Revision Date	Summary of Changes
Sep. 09, 2011	• Initial release.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

2. Extension Operations

Verb	URI	Description
Endpoint Template Operations		
GET	`/OS-KSCATALOG/endpointTemplates?serviceId=`*`string`*	List Endpoint Templates.
POST	`/OS-KSCATALOG/endpointTemplates`	Add Endpoint Template.
GET	`/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}`	Get Endpoint Template.
DELETE	`/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}`	Delete a Endpoint Template.
Endpoint Operations		
GET	`/tenants/{tenantId}/OS-KSCATALOG/endpoints`	List Endpoints of a Tenant.
POST	`/tenants/{tenantId}/OS-KSCATALOG/endpoints`	Add Endpoint to a tenant.
GET	`/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}`	Get Endpoint of a Tenant.
DELETE	`/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}`	Delete a Endpoint from a Tenant.

2.1. OS-KSCATALOG Admin Extension

Extension operations.

Table 2.1. Authentication Header

Header Type	Name	Value
HTTP/1.1 Request	X-Auth-Token	txfa8426a08eaf

The following calls are supported by API OS-KSCATALOG Extension on top of Keystone Admin 2.0:

Verb	URI	Description
Endpoint Template Operations		
GET	`/OS-KSCATALOG/endpointTemplates?serviceId=`*`string`*	List Endpoint Templates.
POST	`/OS-KSCATALOG/endpointTemplates`	Add Endpoint Template.
GET	`/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}`	Get Endpoint Template.
DELETE	`/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}`	Delete a Endpoint Template.
Endpoint Operations		
GET	`/tenants/{tenantId}/OS-KSCATALOG/endpoints`	List Endpoints of a Tenant.
POST	`/tenants/{tenantId}/OS-KSCATALOG/endpoints`	Add Endpoint to a tenant.
GET	`/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}`	Get Endpoint of a Tenant.
DELETE	`/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}`	Delete a Endpoint from a Tenant.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

2.1.1. Endpoint Template Operations

Verb	URI	Description
GET	`/OS-KSCATALOG/endpointTemplates?serviceId=`*`string`*	List Endpoint Templates.
POST	`/OS-KSCATALOG/endpointTemplates`	Add Endpoint Template.
GET	`/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}`	Get Endpoint Template.
DELETE	`/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}`	Delete a Endpoint Template.

2.1.1.1. List Endpoint Templates

Verb	URI	Description
GET	`/OS-KSCATALOG/endpointTemplates?serviceId=`*`string`*	List Endpoint Templates.

List Endpoint Templates.

Table 2.2. List Endpoint Templates parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	String. Required.
`serviceId`	query	String. Optional.

Normal Response Code(s)

- endpointTemplates (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.1. List Endpont Templates Response: XML


```
<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplates xmlns="http://docs.openstack.org/identity/api/ext/OS-
KSCATALOG/v1.0">
  <endpointTemplate
   id="1"
   region="North"
   global="true"
   type="compute"
   name="Compute"
   publicURL="https://compute.north.public.com/v1"
   internalURL="https://compute.north.internal.com/v1"
```

```
   enabled="true">
   <version
     id="1"
     list="https://compute.north.public.com/"
     info="https://compute.north.public.com/v1"/>
  </endpointTemplate>
  <endpointTemplate
   id="2"
   region="south"
   type="compute"
   name="Compute"
   publicURL="https://service2.public.com/v1"
   internalURL="https://service2.internal.public.com/v1"
   enabled="false">
   <version
    id="1"
    list="https://service1.public.com/"
    info="https://service1.public.com/v1"/>
  </endpointTemplate>
  <endpointTemplate
   id="3"
   region="DFW"
   global="true"
   type="ext1:service1"
   name="Compute"
   publicURL="https://service1.public.com/v1"
   enabled="true">
   <version
    id="1"
    list="https://service1.public.com/"
    info="https://service1.public.com/v1"/>
  </endpointTemplate>
  <endpointTemplate
   id="4"
   region="ORD"
   type="compute"
   name="Compute"
   publicURL="https://service2.public.com/v1"
   enabled="true">
   <version
    id="1"
    list="https://service1.public.com/"
    info="https://service1.public.com/v1"/>
  </endpointTemplate>
  <endpointTemplate
   id="5"
   global="true"
   type="compute"
   name="Compute"
   publicURL="https://service3.public.com/v1">
   <version
    id="1"
    list="https://service1.public.com/"
    info="https://service1.public.com/v1"/>
  </endpointTemplate>
</endpointTemplates>
```

Example 2.2. List Endpont Templates Response: JSON

```
{
```


DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

```
    "OS-KSCATALOG:endpointsTemplates": [
            {
                "id": 1,
                "region": "North",
                "global": true,
                "type": "compute",
                "publicURL": "https://compute.north.public.com/v1",
                "internalURL": "https://compute.north.internal.com/v1",
                "versionId": "1",
                "versionInfo": "https://compute.north.public.com/v1/",
                "versionList": "https://compute.north.public.com/",
                "enabled": true
            },
            {
                "id": 2,
                "region": "South",
                "type": "compute",
                "publicURL": "https://compute.south.public.com/v1",
                "internalURL": "https://compute.south.internal.com/v1",
                "versionId": "1",
                "versionInfo": "https://compute.south.public.com/v1/",
                "versionList": "https://compute.south.public.com/",
                "enabled": false
            },
            {
                "id": 3,
                "region": "North",
                "global": true,
                "type": "object-store",
                "publicURL": "https://object-store.north.public.com/v1.0",
                "versionId": "1.0",
                "versionInfo": "https://object-store.north.public.com/v1.0/",
                "versionList": "https://object-store.north.public.com/",
                "enabled": true
            },
            {
                "id": 4,
                "region": "South",
                "type": "object-store",
                "publicURL": "https://object-store.south.public.com/v2",
                "versionId": "2",
                "versionInfo": "https://object-store.south.public.com/v2/",
                "versionList": "https://object-store.south.public.com/",
                "enabled": true
            },
            {
                "id": 5,
                "global": true,
                "type": "OS-DNS:DNS",
                "publicURL": "https://dns.public.com/v3.2",
                "versionId": "1.0",
                "versionInfo": "https://dns.public.com/v1.0/",
                "versionList": "https://dns.public.com/",
                "enabled": true
            }
        ],
    "OS-KSCATALOG:endpointsTemplates_links": []
}
```


DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

2.1.1.2. Add Endpoint Template

Verb	URI	Description
POST	`/OS-KSCATALOG/endpointTemplates`	Add Endpoint Template.

Add Endpoint Template.

Table 2.3. Add Endpoint Template parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	String. Required.

Normal Response Code(s)

- endpointTemplate (201)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)
- badMediaType(415)

Example 2.3. Add Endpoint Template Request: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  id="1"
  region="North"
  global="true"
  type="compute"
  name="Compute"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true">
  <version
    id="1"
    info="https://compute.north.public.com/v1/"
    list="https://compute.north.public.com/"
  />
</endpointTemplate>
```

Example 2.4. Add Endpoint Template Request: JSON

```
{
    "OS-KSCATALOG:endpointTemplate":{
```

```
        "id":1,
        "region":"North",
        "global":true,
        "type":"compute",
        "publicURL":"https://compute.north.public.com/v1",
        "internalURL":"https://compute.north.internal.com/v1",
        "versionId":"1",
        "versionInfo":"https://compute.north.public.com/v1/",
        "versionList":"https://compute.north.public.com/",
        "enabled":true
    }
}
```

Example 2.5. Add Endpoint Template Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  id="1"
  region="North"
  global="true"
  type="compute"
  name="Compute"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true">
  <version
    id="1"
    info="https://compute.north.public.com/v1/"
    list="https://compute.north.public.com/"
  />
</endpointTemplate>
```

Example 2.6. Add Endpoint Template Response: JSON

```
{
    "OS-KSCATALOG:endpointTemplate":{
        "id":1,
        "region":"North",
        "global":true,
        "type":"compute",
        "publicURL":"https://compute.north.public.com/v1",
        "internalURL":"https://compute.north.internal.com/v1",
        "versionId":"1",
        "versionInfo":"https://compute.north.public.com/v1/",
        "versionList":"https://compute.north.public.com/",
        "enabled":true
    }
}
```

2.1.1.3. Get Endpoint Template

Verb	URI	Description
GET	`/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}`	Get Endpoint Template.

Get Endpoint Template.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

Table 2.4. Get Endpoint Template parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	String. Required.
`X-Auth-Token`	header	String. Required.
`endpointTemplateId`	template	Int. Optional.

Normal Response Code(s)

- endpointTemplate (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.7. Get Endpont Template Response: XML


```
<?xml version="1.0" encoding="UTF-8"?>

<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  id="1"
  region="North"
  global="true"
  type="compute"
  name="Compute"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true">
  <version
    id="1"
    info="https://compute.north.public.com/v1/"
    list="https://compute.north.public.com/"
  />
</endpointTemplate>
```


Example 2.8. Get Endpont Template Response: JSON


```
{
    "OS-KSCATALOG:endpointTemplate":{
        "id":1,
        "region":"North",
        "global":true,
        "type":"compute",
        "publicURL":"https://compute.north.public.com/v1",
        "internalURL":"https://compute.north.internal.com/v1",
        "versionId":"1",
```

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D


```
        "versionInfo":"https://compute.north.public.com/v1/",
        "versionList":"https://compute.north.public.com/",
        "enabled":true
    }
}
```


2.1.1.4. Delete Endpoint Template.

Verb	URI	Description
DELETE	/OS-KSCATALOG/endpointTemplates/{endpointTemplateId}	Delete a Endpoint Template.

Delete a Endpoint Template.

Table 2.5. Delete Endpoint Template. parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.
X-Auth-Token	header	String. Required.
endpointTemplateId	template	Int. Optional.

Normal Response Code(s)

- (204)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.9. Delete Endpoint Template Request

```
This operation does not require a request body.
```

2.1.2. Endpoint Operations

Verb	URI	Description
GET	/tenants/{tenantId}/OS-KSCATALOG/endpoints	List Endpoints of a Tenant.
POST	/tenants/{tenantId}/OS-KSCATALOG/endpoints	Add Endpoint to a tenant.
GET	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Get Endpoint of a Tenant.
DELETE	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Delete a Endpoint from a Tenant.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

2.1.2.1. List Endpoints

Verb	URI	Description
GET	`/tenants/{tenantId}/OS-KSCATALOG/endpoints`	List Endpoints of a Tenant.

List Endpoints of a Tenant.

Table 2.6. List Endpoints parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	String. Required.
`tenantId`	template	String. Optional.

Normal Response Code(s)

- endpoints (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.10. List Endponts Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<endpoints
    xmlns="http://docs.openstack.org/identity/api/v2.0">
  <endpoint
      id="1"
      type="compute"
      name="Compute"
      region="North"
      publicURL="https://compute.north.public.com/v1"
      internalURL="https://compute.north.internal.com/v1"
      adminURL="https://compute.north.internal.com/v1">
      <version
          id="1"
          info="https://compute.north.public.com/v1/"
          list="https://compute.north.public.com/"
      />
  </endpoint>
  <endpoint
      id="2"
      type="compute"
      name="Compute"
      region="South"
```

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

```
      publicURL="https://compute.north.public.com/v1"
      internalURL="https://compute.north.internal.com/v1"
      adminURL="https://compute.north.internal.com/v1">
      <version
          id="1"
          info="https://compute.north.public.com/v1/"
          list="https://compute.north.public.com/"
      />
  </endpoint>
  <endpoint
      id="3"
      type="compute"
      name="Compute"
      region="East"
      publicURL="https://compute.north.public.com/v1"
      internalURL="https://compute.north.internal.com/v1"
      adminURL="https://compute.north.internal.com/v1"
  />
  <endpoint
      id="4"
      type="compute"
      name="Compute"
      region="West"
      publicURL="https://compute.north.public.com/v1"
      internalURL="https://compute.north.internal.com/v1"
      adminURL="https://compute.north.internal.com/v1">
      <version
          id="1"
          info="https://compute.north.public.com/v1/"
          list="https://compute.north.public.com/"
      />
  </endpoint>
  <endpoint
      id="5"
      type="compute"
      name="Compute"
      region="Global"
      publicURL="https://compute.north.public.com/v1"
      internalURL="https://compute.north.internal.com/v1"
      adminURL="https://compute.north.internal.com/v1">
      <version
          id="1"
          info="https://compute.north.public.com/v1/"
          list="https://compute.north.public.com/"
      />
  </endpoint>
</endpoints>
```

Example 2.11. List Endponts Response: JSON

```
{
    "endpoints":[{
                "id":1,
                "region":"North",
                "type":"compute",
                "publicURL":"https://compute.north.public.com/v1",
                "internalURL":"https://compute.north.internal.com/v1",
                "versionId":"1",
                "versionInfo":"https://compute.north.public.com/v1/",
                "versionList":"https://compute.north.public.com/"
```

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D


```
            },
            {
                "id":2,
                "region":"South",
                "type":"compute",
                "publicURL":"https://compute.north.public.com/v1",
                "internalURL":"https://compute.north.internal.com/v1",
                "versionId":"1",
                "versionInfo":"https://compute.north.public.com/v1/",
                "versionList":"https://compute.north.public.com/"
            },
            {
                "id":3,
                "region":"East",
                "type":"compute",
                "publicURL":"https://compute.north.public.com/v1",
                "internalURL":"https://compute.north.internal.com/v1",
                "versionId":"1",
                "versionInfo":"https://compute.north.public.com/v1/",
                "versionList":"https://compute.north.public.com/"
            },
            {
                "id":4,
                "region":"West",
                "type":"compute",
                "publicURL":"https://compute.north.public.com/v1",
                "internalURL":"https://compute.north.internal.com/v1",
                "versionId":"1",
                "versionInfo":"https://compute.north.public.com/v1/",
                "versionList":"https://compute.north.public.com/"
            },
            {
                "id":5,
                "region":"Global",
                "type":"compute",
                "publicURL":"https://compute.north.public.com/v1",
                "internalURL":"https://compute.north.internal.com/v1",
                "versionId":"1",
                "versionInfo":"https://compute.north.public.com/v1/",
                "versionList":"https://compute.north.public.com/"
            }
        ],
    "endpoints_links":[]
}
```


2.1.2.2. Add Endpoint

Verb	URI	Description
POST	`/tenants/{tenantId}/OS-KSCATALOG/endpoints`	Add Endpoint to a tenant.

Add Endpoint to a tenant.

Table 2.7. Add Endpoint parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	String. Required.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

Name	Style	Description
endpoint	plain	EndpointTemplateWithOnlyId. Optional.
tenantId	template	String. Optional.

Normal Response Code(s)

- endpoint (201)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)
- badMediaType(415)

Example 2.12. Add Endpoint Request: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<endpointTemplate
  xmlns="http://docs.openstack.org/identity/api/ext/OS-KSCATALOG/v1.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:type="EndpointTemplateWithOnlyId"
  id="1"/>
```

Example 2.13. Add Endpoint Request: JSON

```
{
    "OS-KSCATALOG:endpointTemplate":{
        "id":1,
    }
}
```

Example 2.14. Add Endpoint Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<endpoint
            id="1"
            type="compute"
            name="Compute"
            region="North"
            publicURL="https://compute.north.public.com/v1"
            internalURL="https://compute.north.internal.com/v1"
            adminURL="https://compute.north.internal.com/v1"
            xmlns="http://docs.openstack.org/identity/api/v2.0">
            <version
                        id="1"
                        info="https://compute.north.public.com/v1/"
                        list="https://compute.north.public.com/"
            />
</endpoint>
```

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

Example 2.15. Add Endpoint Response: JSON


```
{
  "endpoint": {
  "id": 1,
  "region": "North",
  "type": "compute",
  "publicURL": "https://compute.north.public.com/v1",
  "internalURL": "https://compute.north.internal.com/v1",
  "versionId": "1",
  "versionInfo": "https://compute.north.public.com/v1/",
  "versionList": "https://compute.north.public.com/"
  }
}
```


2.1.2.3. Get Endpoint

Verb	URI	Description
GET	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Get Endpoint of a Tenant.

Get Endpoint of a Tenant.

Table 2.8. Get Endpoint parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	String. Required.
tenantId	template	String. Optional.
endpointId	template	String. Optional.

Normal Response Code(s)

- endpoint (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.16. Get Endpont Response: XML


```
<?xml version="1.0" encoding="UTF-8"?>

<endpoint
            id="1"
            type="compute"
            name="Compute"
```

```
            region="North"
            publicURL="https://compute.north.public.com/v1"
            internalURL="https://compute.north.internal.com/v1"
            adminURL="https://compute.north.internal.com/v1"
            xmlns="http://docs.openstack.org/identity/api/v2.0">
            <version
                        id="1"
                        info="https://compute.north.public.com/v1/"
                        list="https://compute.north.public.com/"
            />
</endpoint>
```

Example 2.17. Get Endpont Response: JSON

```
{
  "endpoint": {
  "id": 1,
  "region": "North",
  "type": "compute",
  "publicURL": "https://compute.north.public.com/v1",
  "internalURL": "https://compute.north.internal.com/v1",
  "versionId": "1",
  "versionInfo": "https://compute.north.public.com/v1/",
  "versionList": "https://compute.north.public.com/"
  }
}
```

2.1.2.4. Delete Endpoint.

Verb	URI	Description
DELETE	/tenants/{tenantId}/OS-KSCATALOG/endpoints/{endpointId}	Delete a Endpoint from a Tenant.

Delete a Endpoint from a Tenant.

Table 2.9. Delete Endpoint. parameters

Name	Style	Description
	Request parameters	
X-Auth-Token	header	String. Required.
tenantId	template	String. Optional.
endpointId	template	String. Optional.

Normal Response Code(s)

- (204)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

- serviceUnavailable(503)
- itemNotFound(404)

Example 2.18. Delete Endpoint From a Tenant Request

```
This operation does not require a request body.
```