Rackspace API Key Authentica

EXT v1.0 (Sep 13, 2011)



DRAFT

openstack™

docs.openstack.org

Rackspace API Key Authentication Extension (Admin Operations)

EXT v1.0 (2011-09-13)
Copyright © 2011 Rackspace US, Inc. All rights reserved.

This document is intended for service developers interested in using the Rackspace API Key Authentication Admin Extension along with the Keystone - OpenStack Identity (API). The document is for informational purposes only and is provided “AS IS.”

RACKSPACE MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, AS TO THE ACCURACY OR COMPLETENESS OF THE CONTENTS OF THIS DOCUMENT AND RESERVES THE RIGHT TO MAKE CHANGES TO SPECIFICATIONS AND PRODUCT/SERVICES DESCRIPTION AT ANY TIME WITHOUT NOTICE. RACKSPACE SERVICES OFFERINGS ARE SUBJECT TO CHANGE WITHOUT NOTICE. USERS MUST TAKE FULL RESPONSIBILITY FOR APPLICATION OF ANY SERVICES MENTIONED HEREIN. EXCEPT AS SET FORTH IN RACKSPACE GENERAL TERMS AND CONDITIONS AND/OR CLOUD TERMS OF SERVICE, RACKSPACE ASSUMES NO LIABILITY WHATSOEVER, AND DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO ITS SERVICES INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT.

Except as expressly provided in any written license agreement from Rackspace, the furnishing of this document does not give you any license to patents, trademarks, copyrights, or other intellectual property.

Rackspace®, Rackspace logo and Fanatical Support® are registered service marks of Rackspace US, Inc. All other product names and trademarks used in this document are for identification purposes only and are property of their respective owners.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT

Table of Contents

1. About This Extension 1
1.1. Document Change History 2
2. Summary of Changes 3
2.1. New Headers 3
2.2. New Faults 3
2.3. New Resources 3
2.4. New Actions 3
2.5. New Element 3
2.5.1. apikeyCredentials 3
2.6. RAX-KSKEY-admin Extension API Operations 4
2.6.1. User Operations 4

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

List of Tables

2.1. Authentication Header 4
2.2. Add user Credential. parameters 4
2.3. List Credentials parameters 6
2.4. Update user credential parameters 7
2.5. Delete user credential parameters 8
2.6. Get user Credentials parameters 9

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

List of Examples

1.1. Extension Query Response: XML ... 2
1.2. Extension Query Response: JSON ... 2
2.1. apikeyCredentials XML ... 3
2.2. apikeyCredentials JSON ... 3
2.3. Add Credentials Request: XML ... 5
2.4. Add Credentials Request: JSON ... 5
2.5. Add Credential Response: XML ... 5
2.6. Add Credential Response: JSON ... 5
2.7. List Credentials Response: XML ... 6
2.8. List Credentials Response: JSON ... 6
2.9. Update Credential Request: XML ... 7
2.10. Update Credential Request: JSON ... 7
2.11. Update Credential Response: XML ... 7
2.12. Update Credential Response: JSON ... 8
2.13. Delete User Credentials ... 8
2.14. Get User Credential Response: XML ... 9
2.15. Get User Credential Response: JSON ... 9

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

1. About This Extension

Name	Rackspace API Key Authentication Admin Extension
Namespace	http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0
Alias	RAX-KSKEY-admin
Dependencies	Keystone - OpenStack Identity OS-KSCATALOG-admin Extension
Doc Link (PDF)	/home/yogi/keystone/content/admin/RAX-KSKEY-admin-devguide.pdf
Doc Link (WADL)	/home/yogi/keystone/keystone/content/admin/RAX-KSKEY-admin.wadl
Doc Link (XSD)	/home/yogi/keystone/content/service/xsd/RAX-KSKEY-credentials.xsd
Short Description	Rackspace extensions to Keystone v2.0 API enabling API Key authentication.

Example 1.1. Extension Query Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<extension  xmlns="http://docs.openstack.org/common/api/v2.0"
            xmlns:atom="http://www.w3.org/2005/Atom"
            name="Rackspace API Key authentication" namespace="http://docs.
rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
            alias="RAX-KSKEY-admin"
            updated="2011-08-14T13:25:27-06:00">
            <description>
                        Rackspace extensions to Keystone v2.0 API
                        enabling API Key authentication.
            </description>
            <atom:link rel="describedby" type="application/pdf"
                        href="https://github.com/openstack/keystone/raw/
master/keystone/content/service/RAX-KSKEY-admin-devguide.pdf"/>
</extension>
```

Example 1.2. Extension Query Response: JSON

```
{
  "extension":{
    "name": "Rackspace API Key Authentication Admin",
    "namespace": "http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0",
    "alias": "RAX-KSKEY-admin",
    "updated": "2011-07-13T13:25:27-06:00",
    "description": "Rackspace extensions to Keystone v2.0 API enabling API Key
 authentication.",
    "links": [{
        "rel": "describedby",
        "type": "application/pdf",
        "href": "https://github.com/openstack/keystone/raw/master/keystone/
content/admin/RAX-KSKEY-service-devguide.pdf"
    }]
   }
}
```

1.1. Document Change History

Revision Date	Summary of Changes
Sep. 13, 2011	• Initial release.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

2. Summary of Changes

The Rackspace API Key Authentication Admin Extension allows crud/listing operations on *`apikeyCredentials`*.

2.1. New Headers

None.

2.2. New Faults

None.

2.3. New Resources

None.

2.4. New Actions

None.

2.5. New Element

2.5.1. apikeyCredentials

This extension allows authentication calls to accept new type of credentials *`apikeyCredentials`*. These are additional type of credentials defined to support rackspace style authentication. Examples of *`apikeyCredentials`* are illustrated below

Example 2.1. apikeyCredentials XML

```
<?xml version="1.0" encoding="UTF-8"?>
<apikeyCredentials
 xmlns="http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
 username="testuser"
 apikey="aaaaa-bbbbb-ccccc-12345678"/>
```

Example 2.2. apikeyCredentials JSON

```
{
    "RAX-KSKEY:apikeyCredentials":{
        "username":"test_user",
        "apikey":"aaaaa-bbbbb-ccccc-12345678"
    }
}
```

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

2.6. RAX-KSKEY-admin Extension API Operations

Table 2.1. Authentication Header

Header Type	Name	Value
HTTP/1.1 Request	X-Auth-Token	txfa8426a08eaf

Following operations are the list of operations whose behavior is altered by Rackspace API Key Authentication Extension:

Verb	URI	Description
User Operations		
POST	`/users/{userId}/credentials`	Adds a credential to a user.
GET	`/users/{userId}/credentials?marker=`*`string`*`&limit=`*`int`*	List credentials.
POST	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Update credentials.
POST	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Delete User credentials.
GET	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Get user credentials.

2.6.1. User Operations

Verb	URI	Description
POST	`/users/{userId}/credentials`	Adds a credential to a user.
GET	`/users/{userId}/credentials?marker=`*`string`*`&limit=`*`int`*	List credentials.
POST	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Update credentials.
POST	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Delete User credentials.
GET	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Get user credentials.

2.6.1.1. Add user Credential.

Verb	URI	Description
POST	`/users/{userId}/credentials`	Adds a credential to a user.

Adds a credential to a user.

Table 2.2. Add user Credential. parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	You need a valid admin token for access. String. Required.

Normal Response Code(s)

- credentials (201)

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- badMediaType(415)
- itemNotFound(404)

Example 2.3. Add Credentials Request: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<apikeyCredentials
 xmlns="http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
 username="testuser"
 apikey="aaaaa-bbbbb-ccccc-12345678"/>
```

Example 2.4. Add Credentials Request: JSON

```
{
    "RAX-KSKEY:apikeyCredentials":{
        "username":"test_user",
        "apikey":"aaaaa-bbbbb-ccccc-12345678"
    }
}
```

Example 2.5. Add Credential Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<apikeyCredentials
 xmlns="http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
 username="testuser"
 apikey="aaaaa-bbbbb-ccccc-12345678"/>
```

Example 2.6. Add Credential Response: JSON

```
{
    "RAX-KSKEY:apikeyCredentials":{
        "username":"test_user",
        "apikey":"aaaaa-bbbbb-ccccc-12345678"
    }
}
```

2.6.1.2. List Credentials

Verb	URI	Description
GET	`/users/{userId}/credentials?marker=`*`string`*`&limit=`*`int`*	List credentials.

List credentials.

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

Table 2.3. List Credentials parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	You need a valid admin token for access. String. Required.
`marker`	query	String. Optional.
`limit`	query	Int. Optional.

Normal Response Code(s)

- credentials (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.7. List Credentials Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<credentials xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns="http://docs.openstack.org/identity/api/v2.0">
    <passwordCredentials username="test_user" password="test"/>
    <apikeyCredentials
 xmlns="http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
 username="testuser"
 apikey="aaaaa-bbbbb-ccccc-12345678"/>
</credentials>
```

Example 2.8. List Credentials Response: JSON

```
{
    "credentials":[{
            "passwordCredentials":{
                "username":"test_user",
                "password":"mypass"
            }
        },
        {
            "RAX-KSKEY:apikeyCredentials":{
                "username":"test_user",
                "apikey":"aaaaa-bbbbb-ccccc-12345678"
            }
        }
    ],
    "credentials_links":[]
}
```

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D

2.6.1.3. Update user credential

Verb	URI	Description
POST	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Update credentials.

Update credentials.

Table 2.4. Update user credential parameters

Name	Style	Description
Request parameters		
`X-Auth-Token`	header	You need a valid admin token for access. String. Required.

Normal Response Code(s)

- credentials (200)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- badMediaType(415)
- itemNotFound(404)

Example 2.9. Update Credential Request: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<apikeyCredentials
 xmlns="http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
 username="testuser"
 apikey="aaaaa-bbbbb-ccccc-12345678"/>
```

Example 2.10. Update Credential Request: JSON

```
{
    "RAX-KSKEY:apikeyCredentials":{
        "username":"test_user",
        "apikey":"aaaaa-bbbbb-ccccc-12345678"
    }
}
```

Example 2.11. Update Credential Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<apikeyCredentials
 xmlns="http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
```

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D


```
username="testuser"
apikey="aaaaa-bbbbb-ccccc-12345678"/>
```

Example 2.12. Update Credential Response: JSON

```
{
    "RAX-KSKEY:apikeyCredentials":{
        "username":"test_user",
        "apikey":"aaaaa-bbbbb-ccccc-12345678"
    }
}
```

2.6.1.4. Delete user credential

Verb	URI	Description
POST	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Delete User credentials.

Delete User credentials.

Table 2.5. Delete user credential parameters

Name	Style	Description
	Request parameters	
`X-Auth-Token`	header	You need a valid admin token for access. String. Required.

Normal Response Code(s)

- (204)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- badMediaType(415)
- itemNotFound(404)

Example 2.13. Delete User Credentials

```
This operation does not require a request body.
```

2.6.1.5. Get user Credentials

Verb	URI	Description
GET	`/users/{userId}/credentials/RAX-KSKEY:apikeyCredentials`	Get user credentials.

Get user credentials.

Table 2.6. Get user Credentials parameters

Name	Style	Description
Request parameters		
X-Auth-Token	header	You need a valid admin token for access. String. Required.

Normal Response Code(s)

- credentials (200 203)

Error Response Code(s)

- identityFault
- badRequest(400)
- unauthorized(401)
- forbidden(403)
- badMethod(405)
- overLimit(413)
- serviceUnavailable(503)
- itemNotFound(404)

Example 2.14. Get User Credential Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<apikeyCredentials
 xmlns="http://docs.rackspace.com/identity/api/ext/RAX-KSKEY/v1.0"
 username="testuser"
 apikey="aaaaa-bbbbb-ccccc-12345678"/>
```

Example 2.15. Get User Credential Response: JSON

```
{
    "RAX-KSKEY:apikeyCredentials":{
        "username":"test_user",
        "apikey":"aaaaa-bbbbb-ccccc-12345678"
    }
}
```


DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - D