



Racktivity developed the E<sup>2</sup>Sensor Family to give you visibility of the environmental situation of your data centers and remote infrastructure.


Whether you are looking to monitor temperature, humidity, water leakage, movement, smoke detection or other parameters we have the E<sup>2</sup>Sensor available to fit your needs. The E<sup>2</sup>Sensor is designed to work with any Racktivity product featuring an R-BUS connector which includes the EnergySwitch smart PDUs, AC<sup>2</sup>Meter and DC<sup>2</sup>Meter.

The E<sup>2</sup>Sensor is a compact environmental sensor of 5cm (2 inches) that comes equipped with an OLED display. Deployment is simple via the standard RJ45 daisy chain connections and features multiple rack mount options. A simple push button allows instant monitoring of all available metrics such as temperature, humidity, leak detection, motion detection, rack door close sensor, smoke indication...


The sensors are fully compatible with our DCPM, a Service Provider Infrastructure & Data Center Performance Management System, allowing you to remotely monitor and manage power and critical environment metrics in your data centers and/or smaller distributed infrastructures.

## .benefits & features

- > In combination with the other Racktivity products, the E<sup>2</sup>Sensor provides highly granular information
- > Full-feature and easy integration with our Data Center Power Management (DCPM) software
- > Integrated sensors for
  - Temperature
  - Humidity
  - Motion detection
- > Supported external environmental measurements include temperature, water leak, dry contact door position and smoke
- > With a simple push on the button you can scroll through the available metrics
- > Integrated info display
- Simple to deploy using standard RJ45 daisy-chain cables
- > Can be equipped with 2 external temperature sensors, water leak detection cable or 2 analog outputs
- > Quick and easy rack mountable: with M5 screws, magnets or cable ties
- Ultra compact design



.M sales@racktivity.com







# .technical specifications

#### **MEASURE & DETECT**


- > Temperature
- > Humidity
- Water leak
- Dry contact door position
- > Smoke detection
- > Motion detection

### CONTROL

- > Racktivity R-BUS connectors for connecting AC<sup>2</sup>Sensors, DC<sup>2</sup>Sensors & EnergySwitch PDUs
- > Integrated info display
- > Scroll through the available metrics with a simple push on the button
- > Visible alarm indicator

#### **OTHER**

- > OLED with control button
- > CE/RoHS Compliant
- Quick and easy rack mountable: with M5 screws, magnets or cable ties
- > Ultra compact design





The back panel features several mounting options to ensure proper installation in almost every situation.
(With either screws, calbe tie or magnets)