

# Truck GPS Data for Freight Performance Measurement, Modeling, and Planning

*presented by*

Abdul Pinjari – University of South Florida (USF)

Jeff Short – American Transportation Research Institute (ATRI)

Akbar Bakhshi Zanjani, Mohammadreza Kamali – USF

Frank Tabatabaee – FDOT

March 27, 2014. Orlando, Florida.




## Acknowledgements

- Vidya Mysore – FHWA
- Lisa Park, Dave Pierce, Dan Murray – ATRI
- Anissa Irmania, Aayush Thakur – Former USF students
- Ramachandran Balakrishna – Caliper Corporation
- Vipul Modi – Citilabs
- Krishnan Viswanathan – CDM Smith



## Background on ATRI Data



## Background: ATRI Board of Directors





## Background: ATRI RAC





## ATRI Truck GPS Dataset

- **Ongoing Truck GPS data research beginning in 2001**
  - **Comprehensive North American Truck GPS dataset**
  - **“Big Data”**
    - Real time data feeds/ significant hardware and software
    - Currently near 100 million data points per day
    - Will approach 1 billion points per week later this year
  - **Fully deployed applications**
    - Performance measurement/management
    - Freight flow and truck trip modeling
  - **Key research areas**
    - Economic competitiveness and supply chains
    - Truck volume/intensity/national travel patterns
    - Weather, parking, emergency events











## ATRI Truck GPS Dataset





## ATRI Truck GPS Dataset











## ATRI Truck GPS Dataset



## ATRI Truck GPS Dataset



## ATRI Truck GPS Dataset



## ATRI Truck GPS Dataset



## ATRI Truck GPS Dataset



## Project Outcomes





## Project Objectives



- Project Objectives
  - Investigate the use of ATRI-FPM data for freight performance measurement and planning in Florida.
  - Use the data for the following applications
    - Derive freight performance measures (speeds) for Florida's highways
    - Convert the raw GPS data into a database of truck trips
    - Understand truck travel characteristics in Florida
    - Derive tuck-trip OD tables for the Florida Statewide Model
  - Other
    - Assess the data – its coverage of freight truck traffic in Florida
    - Exploratory analysis of the use of data for different applications
      - Truck flows from Ports
      - Truck travel time skims
      - Truck routes




## Freight Performance Measurement



- Average speeds on Florida's Strategic Intermodal System (SIS) highways
  - ATRI data used to measure average truck speeds on the entire SIS network
  - Speeds measured for different time-of-day periods for each 1-mile segment on the SIS network (half-mile segments in urban regions)
    - AM peak
    - PM peak
    - Mid day
    - Off peak
    - Daily average
  - Speeds measured based on 3 months of data in year 2010





## Convert GPS Data into Truck Trips



- Algorithms to convert raw GPS data into a database of truck trips
- Product from this task
  - Database of over 2 Million truck trips derived from over 145 Million GPS records
  - 1.27 Million trips starting and/or ending in Florida

	# GPS records (Millions)	# Trucks (Thousands)	# Trips starting and/or ending in Florida (Thousands)
March 2010	39.0	61.7	340
April 2010	35.7	58.7	320
May 2010	35.1	45.6	306
June 2010	35.2	45.4	305
Total	145 Million GPS records		1.27 Million truck trips

- Information available for each trip: Trip start & end times, distance, travel time, Origin and Destination TAZs based on FL statewide model




## Truck Travel Characteristics



- Analyzed the characteristics of truck trips derived from previous task
  - Time of day profiles for trips starting & ending in different regions in FL
  - Travel Distances
  - Measurements of Origin-Destination (OD) Travel Times and Speeds
  - Truck trip travel routes for several OD pairs



## Trip Length Distribution (Trips starting and/or ending in FL)



Range of Trip Length (miles)	Frequency	Percent	Cumulative Percent
1-50	551,201	43.3	43.3
50-100	191,552	15.1	58.4
100-200	196,378	15.4	73.8
200-500	204,230	16.1	89.9
500-1000	86,578	6.8	96.7
1000-2000	38,937	3.1	99.8
2000-3000	2,190	.2	99.9
>3000	754	.1	100.0
Total	1,271,820	100.0	





## OD Travel Time and Speed Measurement




- Product from this task
  - Origin-to-Destination (OD) travel time and speed measurements derived for over 1200 OD pairs
- For each of the 1200 OD pairs...
  - Distribution of travel times (min, max, mean, 5<sup>th</sup>, 15<sup>th</sup>, 50<sup>th</sup>, 85<sup>th</sup> percentile values)
  - Distribution of travel speed (min, max, mean, 5<sup>th</sup>, 15<sup>th</sup>, 50<sup>th</sup>, 85<sup>th</sup> percentile values)
  - Distributions by time-of-day (to the extent possible)
  - Two types of travel times and speeds:
    - Total travel times and speeds, including rest stops
    - Travel times and speeds, excluding rest stops
- Useful for
  - Validating the freight component of Florida Statewide Model
  - Truck travel time skim inputs to the model
- See next few slides for the derived information on a sample OD pair



## Travel Time Measurements for a Sample OD Pair




- Origin TAZ #4526 and Destination TAZ #1863
- 134 trips extracted from the ATRI data for this OD pair



Route choice for 134 trips between Origin TAZ #4526 & Destination TAZ #1863



## Travel Time Measurements for a Sample OD Pair



Distribution of Measured Travel Time Between TAZ #4526 & TAZ #1863



## Travel Time Measurements for a Sample OD Pair



- Origin TAZ #4526 and Destination TAZ #1863 with 134 trips


	Min	5 <sup>th</sup> percentile	15 <sup>th</sup> percentile	Max
ATRI Trip length	55 miles	56.7 miles	57.2 miles	78.4 miles
ATRI Travel Time	62 min	63 min	65 min	165 min

Trip length in FL statewide model	55 miles
Travel time in FL statewide model skims	54 min

- The travel time skims used in the FL statewide model appear to be smaller than those measured using ATRI GPS data
- Travel times in Google maps appear to be smaller than those measured using ATRI GPS data, perhaps because Google measurements are predominantly based on light duty vehicles.
- The ATRI data can be used to update truck travel time skims for models



## ATRI Truck Travel Times Vs. Google Maps



## Truck Travel Routes



- Truck Travel Routes for several trips between over 1200 OD pairs
- Useful for
  - Truck route choice analysis
  - Research on improvements to truck traffic assignment procedures






## Truck OD Flow Patterns



- Product from this task
  - Truck trip OD tables at different levels of geography
    - State-level
    - County-level
    - FL Statewide Model (FLSWM) TAZ level
  - OD tables available for use in the form of spread sheets
  - Generated using 4 months of raw GPS data (March to June 2010)
  - Additional procedures used to remove trucks that are not considered to be freight-carrying heavy trucks
    - Trucks that do not make at least one trip of 100 miles in a month
    - Trucks that remain within an urban region as opposed to travel across regions
    - Truck that make a large number of short trips per day







## Destinations of Trips Starting in FL



Total number of trips starting in FL: 1,102,873








## OD Matrix Estimation of Statewide Truck Flows




- The OD patterns shown so far are from a **sample** of trips (large sample)
- Need to arrive at the **population** of truck flows
- Perform OD Matrix Estimation (ODME) to...  
 “Inflate” the **sample** OD table to a **population** OD table such that, when loaded onto the network, the resulting flows match with observed truck traffic counts at different locations.



## Truck Traffic Count Locations Used for ODME







### Validation of ODME Outputs


**Root Mean Square Error (RMSE):** Measure of the differences between estimated truck traffic volumes and observed traffic counts. Closer to zero, better estimation.

$$RMSE = \sqrt{\frac{\sum_{i=1}^N (V_i - C_i)^2}{N}}$$

**Coefficient of determination ( $R^2$ ):** How well are the observed traffic counts replicated by the ODME results, as the proportion of total variation of traffic counts. Closer to 1, better replication of observed outcomes by the model

$$R^2 = 1.0 - \frac{\sum_{i=1}^N (V_i - C_i)^2}{\sum_{i=1}^N (C_{avg} - C_i)^2}$$

$V_i$  : Estimated truck traffic volume corresponding to counting location  $i$   
 $C_i$  : Observed traffic count value at location  $i$   
 $C_{avg}$  : Average truck traffic count value of the set  
 $N$  : Total number of truck counting locations  $i$  in the set



## Validation of ODME Outputs


### – Preliminary Results


- Estimated vs. observed truck traffic counts **input to ODME**
  - All traffic counting sites in the nation (963 sites)
    - $R^2 = 0.750$ , RMSE = 60%
  - Traffic counting sites in Florida (365 sites):
    - $R^2 = 0.808$ , RMSE = 59%
- Estimated vs. observed truck traffic counts **kept aside for Validation**
  - All traffic counting sites in the nation (85 sites)
    - $R^2 = 0.349$ , RMSE = 84%
  - Traffic counting sites in Florida (48 sites):
    - $R^2 = 0.765$ , RMSE = 58%



## ODME vs. Observed Truck Volumes

### – Preliminary Results





## Summary of Project Outcomes

- Freight Performance Measures
  - Truck travel speeds by time-of-day for each mile on SIS highways
- A large database of truck trips within, to, and from Florida
- Measurements of travel times & speeds between 1200 OD pairs
- Truck flow OD patterns at different geographies
  - FLSWM statewide TAZ level, County-level, State-level
- Exploratory work
  - Analysis of truck travel characteristics in Florida
  - Assessment of the coverage of truck traffic in Florida
  - Exploratory analysis of truck flows from ports and truck routes
- Draft final report to be submitted in April



## Thoughts for Way Forward



- This project focuses on statewide truck movements for FLSWM
- There is an opportunity to use the data to extract truck travel patterns for regional models
  - A small but useful portion of trucks in the data are smaller trucks, which are more likely to be local delivery trucks
  - ATRI's estimate: 11% of their database are trucks of class 7 or lower, 6% are straight trucks or box-trucks
- Most of the project focuses on generating data - truck trips, OD tables, travel times, truck routes, etc.
  - Using the generated data for further analysis, freight modeling and planning applications will be fruitful
  - Examples:
    - Truck travel time skims for all OD pairs in the state
    - Truck route choice analysis



Thank you

Questions and Discussion

[apinjari@usf.edu](mailto:apinjari@usf.edu)

More details about ATRI data and its products derived in this project will be presented at  
 FDOT's **Statewide Transearch & Freight Data Workshop** (Orlando, May 14-15, 2014)

[www.fsutmsonline.net/training\\_register.aspx?id=105](http://www.fsutmsonline.net/training_register.aspx?id=105)



## Other Applications

- Truck Flows from Ports
- Truck travel routes

