**Model: CZL601** **OIML Certified**

| | |
|---|---|
| **Type: single point load cell**<br>**Total Precision: C3 class**<br>**Material: aluminum alloy**<br>**Surface: anodized treatment**<br>**Protection: IP65**<br>**Suggested Platform Size: 350 ×350 mm**<br>**Application: retail, bench and counting scales** |  |
| 1. Rated Load | 5-60 (Kg) |
| 2. Rated Output | 2.0mV/V±5% |
| 3. Zero Balance | ±1%F.S |
| 4. Input Resistance | 405±6Ω |
| 5. Output Resistance | 350±3Ω |
| 6. Excitation Voltage | 9-12VDC |
| 7. Nonlinearity | 0.017%F.S |
| 8. Hysteresis | 0.02%F.S |
| 9. Repeatability | 0.01%F.S |
| 10.Creep(30min) | 0.015%F.S |
| 11.Operating Temperature | -20℃ To +65℃ |
| 12.Temperature Effect on Zero | 0.017%F.S/10℃ |
| 13.Temperature Effect on Span | 0.014%F.S/10℃ |
| 14.Insulation Resistance | 5000MΩ(50VDC) |
| 15. Safe Overload | 150%F.S |
| 16.Ultimate Overload | 200%FS |
| 17. Cable | 420mm(Φ3mm 4-wire shielding cable) |

**Dimensions:**

