

# File Handling

Tuesday, August 5, 2025 7:26 PM

- File: It is a container that holds the data.
- Based on extensions we can classify that our file belongs to which category.
- File handling is the phenomenon of reading the data from the file or writing the data into the file.
- Before performing the operation, accessibility of the file is required.
- Open(): It is the function that is used to provide the accessibility.

Syntax:

Var=open(filename.ext/location, mode)

#passing mode is optional, by default it is in read mode.

- Modes are classified into 3 types:

i. Write

- > Write(w)
- > Write + read(w+)
- > Write binary(wb)
- > Write + read binary(wb+)

ii. Read

- > Read(r )
- > Read + write(r+)
- > Read binary(rb)
- > Read + write binary(rb+)

iii. Append

- > Append(a)
- > Append + read(a+)
- > Append binary(ab)
- > Append + read binary(ab+)

- W R T .txt file:

1. Write(w): Writing in the file can be done with 2 functions.\

i. Write(): used to write single data/1 line.

Var.write('data')

ii. Writelines(): used to write multiple data of lines.

Var.writelines([d1, d2, d3.....])

Eg:

l=open('file1.txt','w')

l.writelines(['good morning/n','good evening/n'])

`l.close()`

- If we don't want to close the file, then the syntax that is used is:

With `open('filename.txt/loc','mode')` as var:

Eg:

```
with open('file2.txt','w') as l:  
    l.write('Hii guys')
```

- If we want to use the path the r (raw string) is used.

Var=`open(r'filename.....loc','mode')`

2. `Read (r)`: Used to read data from the file.

- i. `Read()`: It is used to read everything from file

`Res=var.read()`

- ii. `Readline()`: It is used to read the first line.

`Res=var.readline()`

- iii. `Readlines()`: Read all the data but gives the output in list

`Res=var.readlines()`

Eg:

```
'''with open('file3.txt','r') as l:  
    res=l.read()  
    print(res)'''
```

```
with open('file3.txt','r') as l:  
    res=l.readlines()  
    print(res)
```

3. `Append()`: It is also used to write.

Difference between write and append: If working on existing file, if write function is used it will remove the existing data and then write the new data but if append is used, it will continue writing from the last existing data.

- i. `Write()`: used for writing one line

`Var.write('data')`

- ii. `Writelines()`: used for writing multiple lines

`Var.writelines([d1, d2, d3.....])`

- **WORKING W R T .csv file:**

The file with .csv extension.

- Csv: Comma Separated Value

Eg:

Sname, id, marks

'A',1,75

'B',2,97

In today time, the data that is getting shared is in form of csv file only.

### 1. Write():

- i. Writerow(): It is used to write a single row.
- ii. Writerows(): It is used to write multiple rows.

Syntax:

```
Import csv
```

```
With open(file.csv/loc,'w') as var:
```

```
    Var1=csv.writer(var)
```

```
    Var1.writerow([val1, val2, val3..... Val n])
```

Or

```
    Var1.writerows([[val1, val2, val3...],[val1, val2, val3.....],.....]])
```

Eg:

```
import csv
```

```
with open('file12.csv','w') as a:
```

```
    b=csv.writer(a)
```

```
    b.writerow(['Ename','eid','sal','des'])
```

```
    b.writerows([[ 'A','TCS123',10000,'SE'],[ 'B','TCS345',15000,'SSE']])
```

### 2. Read():

Syntax:

```
Import csv
```

```
With open('filename.csv/loc','r') as var:
```

```
    Var1=csv.reader(var)
```

```
    Print(datatype(var1))
```

Eg:

```
with open('file12.csv','r') as a:
```

```
    b=csv.reader(a)
```

```
    print(list(b))
```

#or

```
    b=[i for i in b if i!=[]][1:]
```

```
    print(b)
```

### 3. Append():

- i. Writerow(): It is used to write a single row.
- ii. Writerows(): It is used to write multiple rows.

Syntax:

```
Import csv
```

```
With open(file.csv/loc,'a') as var:
```

```
    Var1=csv.writer(var)
```

```
    Var1.writerow([val1, val2, val3..... Val n])
```

Or

```
    Var1.writerows([[val1, val2, val3...],[val1, val2, val3.....],.....]])
```

Eg:

```
import csv
```

```
with open('file12.csv','a') as a:
```

```
    b=csv.writer(a)
```

```
    b.writerow(['Ename','eid','sal','des'])
```

```
    b.writerows([[['A','TCS123',10000,'SE'],['B','TCS345',15000,'SSE']]])
```