



## Electrochemical NH3 High-Density Transmitter via USB

# UA54-NH3-1000



- Real-time NH3 density, Temp/RH transmitter
- Electrochemical NH3 gas sensor embedded
- Individual Certificate included
- Operating On Windows / Linux / MacOS
- AT Command Support
- PC Recording Software (Tapaculo Lite)
- Android Recording App. (Tapaculo Mobile)




The UA54-NH3-1000 device has an electrochemical Ammonia(NH3) sensor inside. It transmits measured NH3 density and temperature information in real-time via the USB connector.

The UA Series is automatically recognized as a serial port on the operating system and accessed using the AT command. Multiple USB connections of the UA device could compose the multi-channel sensor. The sensor data is not stored in the UA, but recording in PC and Android device. 128CH real time monitoring software on pc, Tapaculo Lite is downloadable on our website([www.radionode365.com](http://www.radionode365.com)). And android real time recording application is also available from google play store. The optional RN17X model helps UA series for you to setup remote web monitoring system.

### Hardware



### Dimensions



### ⚠ CAUTION!

- Long term exposures and high concentrations may affect the performance characteristics
- Sudden changes in humidity cause short-term transient signals
- Avoid contact with conductors.
- Static electricity can cause distorted values.

### Contact Information

- [www.radionode365.com](http://www.radionode365.com)
- [master@dekist.com](mailto:master@dekist.com)



## Electrochemical NH3 High-Density Transmitter via USB

### UA54-NH3-1000 Specifications

Sensor Channel Info.	<ul style="list-style-type: none"> <li>• CH1: NH3</li> <li>• CH2: Temperature</li> <li>• CH3: Humidity</li> </ul>	
Gas Sensor Type	Electrochemical Cell	
Gas Sensor Filter	Metal Sintering filter	
Body Material	PC(Polycarbonate)	
Measurement Range	<ul style="list-style-type: none"> <li>• NH3: 0 ~ 1000 ppm</li> <li>• Temperature: -10 ~ 50°C (-14 ~ 122°F)</li> <li>• Humidity : 5~95%</li> </ul>	
Measurement Unit (Selection using SW)	<ul style="list-style-type: none"> <li>• NH3: ppm</li> <li>• Temperature: °C(Default), °F</li> <li>• Humidity: %</li> </ul>	
Measurement Cycle	1 sec	
Sensor Resolution	<ul style="list-style-type: none"> <li>• NH3: 1ppm</li> <li>• Temperature: 0.01°C</li> <li>• Humidity: 0.01%</li> </ul>	
Sensor Accuracy (Repeatability)	<ul style="list-style-type: none"> <li>• NH3: &lt; 3% of measured value</li> <li>• Temperature: ±0.2°C</li> <li>• Humidity: ±2.0%</li> </ul>	
Compensation Logic	Temperature	
Baseline Drift	Zero ± 16 ppm	
Long-term Drift	< 5% signal loss / 6 months	
Gas Response Time	T90 < 35 secs	
Warming up Time	< 3mins after power-on	
Operating Condition	<ul style="list-style-type: none"> <li>• Temperature: -10 ~ 50°C (14 ~ 122°F)</li> <li>• Humidity: 15 ~ 90% R.H(non condensing)</li> </ul>	
Lifetime <sup>1)</sup>	More than 12 months @ discontinuous measurement	
Humidity-Sensitivity	< 16 ppm	
Cross-Sensitivity	Interfering Gas	Cross-Sens. [%]
	H2S	< 2.5
Power Consumption	5V (Max. 100mW)	
Calibration Certificate	Individual Certificate. Calibration with 50ppm NH3 calibration gas mixtures	
Calibration Method	Two point Calibration Mode Manual Zero Calibration Mode	

USB Port	USB 2.0 Type A Plug
Output Signal	USB digital, CDC Device (AT Command)
LED	Device Status Indicator <ul style="list-style-type: none"> <li>• BLINK RED &amp; GREEN: Warming-up</li> <li>• RED KEEP ON: USB Connection Failed</li> <li>• BLINK GREEN: Measuring</li> </ul>
Software Support	<ul style="list-style-type: none"> <li>• Tapaculo Mobile 3CH recording software on Android devices Download: Google play store</li> <li>• Tapaculo Lite 128CH recording software on PC Download: <a href="http://www.radionode365.com">www.radionode365.com</a></li> <li>• Calibration Software Calibrator that compensates measuring error. Download: <a href="http://www.radionode365.com">www.radionode365.com</a></li> </ul>

1) Gas sensors have a longer life when measured discontinuously than when measured continuously.

### Application

- Animal Farm
- Industrial safety Monitoring
- Bio-labs
- Sewage Treatment Plant

### Product Components

Model	Component
UA54-NH3-1000	<ul style="list-style-type: none"> <li>• UA54-NH3-1000(1EA)</li> <li>• USB Extension Cable 1.5m(1EA)</li> <li>• Calibration Certificate(1EA)</li> </ul>

### Optional Accessories

Type	Model Number	Spec.
Sensor data transmitter via Ethernet	RN171 WC	<ul style="list-style-type: none"> <li>• Supports cloud monitoring</li> <li>• Supports MODBUS TCP/ HTTP data transmission</li> <li>• Power: PoE 48V, IEEE802.3af/at, DC6V, 1.9W</li> </ul>
Sensor data transmitter via WiFi	RN172 WC-D	<ul style="list-style-type: none"> <li>• Supports cloud monitoring</li> <li>• Supports MODBUS TCP/ HTTP data transmission</li> <li>• Power: DC12V, 5W</li> </ul>