
Design and Analysis of Algorithms 6.3 Dynamic Programming Exercises

Daniel Shannon May 16th, 2022

6.3.2

- You have a sequence of numbers $x_1, x_2, x_3, ..., x_n$
- Find the continuous subsequence $[x_i, ..., x_j]$ with the greatest sum
- Not allowed to skip elements!
- Use dynamic programming to find an O(n) solution

My Answer



example linearized DAG

Similar to largest increasing subsequence, but we track the sum instead of the length.

```
prev(0) = x_1 for all j = 1, 2, ...n, in linearized order do sum_j += max\{S[j] + x_j : (i, j) \in E\} if S[j] < sum_j then S[j] = sum_j prev(j) \cdot (i, j) concat end if end for
```


Solution

```
S[j] maximum sum of a cont subsequence ending at index j S[j] = max\{A[j], S(j-1) + A[j]\} S[0] = 0 for all j = 1, 2, ...n, in linearized order do S[j] = max\{A[j], S(j-1) + A[j]\} end for
```

6.3.4

- You are trying to decide where to build a chain of restaurants along a linear highway.
- At each location i along the highway, you will make a profit of p(i) that depends on the location.
- ullet You are not allowed to put two restaurants within k miles of each other.
- Where should you place the restaurants to maximize profit?
- Hint: Draw the DAG!

My Answer



P[j] max profit ending at index j

 $P[j] = max\{p_j, (i, j) \in E : M(i) + p\}$

P[0] = 0


dist(0) = 0

for all j = 1, 2, ...n, in linearized order do

 $P[j] = max\{p_j - k, (i - k, j) \in E : P(i - k) + p\}$

end for

Solution



6.3.6

- Suppose you have two strings of length n and m
- What is the maximum edit distance between the two strings?

```
E(i,j) \text{ graph of edges between letters } i \text{ of } string_n \text{ and } j \text{ of } string_m for all i=0,1,2,...,m do E(i,0)=i end for for all i=1,2,...,n do E(0,j)=j end for for all i=1,2,...,m do for all i=1,2,...,m do E(i,j)=max\{E(i-1,j)+1,E(i,j-1)+1\}; end for end for
```

[1] Dasgupta, Papadimitriou, Vazirani Algorithms p159