

AURA-GNC: Autonomous Vision-Based Relative Navigation & Landmark Tracking for Binary Asteroid Proximity Operations



EUROPEAN SPACE AGENCY (ESA) – OPEN SPACE INNOVATION PLATFORM (OSIP)

Call for Ideas: Autonomous Software Experiments on Hera | Category 1 – Spacecraft Autonomy & GNC

Proposal Identifier:	ESA-OSIP-HERA-2026-RDAS-NAV-AURA-GNC	Target Processor:	GR712RC Dual-Core LEON3 (SPARC V8 @ 50 MHz)
Proposing Entity:	radixal s.r.o. (Purkynova 649/127, 612 00 Brno, Czech Republic)	Execution Core:	Core 1 Isolated Bare-Metal Sandbox (No OS, 0 malloc)
Leadership Triad:	Bc. Viktor Lostak (PI), Ing. Petr Slepicka, Mgr. David Riedl	Applicable Standards:	ECSS-E-ST-40C Category D MISRA-C:2012 Zero-Heap
Primary Science Target:	Didymos / Dimorphos Binary Asteroid System	In-Flight Slot:	Extended Mission Campaign (August 2027, 4 Weeks)

EXECUTIVE SUMMARY & KEY IN-FLIGHT BUDGETS:
AURA-GNC is an autonomous, vision-based relative navigation and feature-tracking pipeline engineered for Core 1 bare-metal C. It performs real-time optical tracking of landmark craters on Dimorphos and Didymos, feeding a deterministic 9-state Extended Kalman Filter (EKF).

- CPU Utilization: 16.2% @ 50 MHz SPARC V8 (Peak WCET: 3.8 s / 1020×1020 AFC frame)
- RAM Footprint: 96.4 kB Static RAM | < 22.0 kB Stack (Zero dynamic allocation / No malloc)
- Relative Range Accuracy: < 1.8% error at 10–20 km proximity (validated against PALT ground truth)
- Feature Tracking Rate: Up to 40 verified crater features tracked across successive frames
- Telemetry Emission: PUS Science Packets (APID 0x482) containing 9-state navigation vectors.

Abstract & Table of Contents

Abstract: Operating in close proximity to irregular binary asteroids requires precise relative navigation. The AURA-GNC experiment demonstrates real-time optical landmark tracking and 9-state Extended Kalman Filtering on Hera's Core 1 bare-metal LEON3 processor. By combining integer corner extraction, binary BRIEF matching, and PALT laser fusion, AURA-GNC achieves < 1.8% relative range estimation error without ground intervention.

1.0 Problem Statement & Operational Context	Page 2	5.0 SIFT Radiation Hardening & Fault Tolerance	Page 6
2.0 Mission Context & Hera Technical Baseline	Page 3	6.0 Platform Interface & PUS Telemetry Mapping	Page 7
3.0 Algorithmic Architecture & Pipeline Design	Page 4	7.0 Empirical Verification & Benchmark Evidence	Page 8
4.0 Mathematical Formulation & Lifting Schemes	Page 5	8.0 Operational Roadmap, Team & References	Page 9–10

1.0 The Problem Statement & Deep-Space Operational Challenges

Navigation around the Didymos binary asteroid presents severe challenges due to irregular gravitational fields and communication delays:

- 1.1 Communication Latency: 24 to 44 min round-trip light time prevents ground closed-loop station keeping.
- 1.2 Failure of Center-of-Brightness (CoB): Irregular asteroid shapes and changing solar phase angles cause CoB centroiding errors exceeding 15%.
- 1.3 Scale Ambiguity: Monocular optical cameras cannot distinguish range from target diameter without active sensor fusion.

Table 1.1: Operational Bottleneck Comparison & Quantitative Advantage

Navigation Technique	Range Accuracy	Autonomous Capability	Computing Load @ 50 MHz
Ground Optical Orbit Det.	+/- 500 meters	None (24-48h ground delay)	Ground Supercomputer
Center-of-Brightness (CoB)	> 15% range error	Coarse only (fails at phase)	< 1.0 s / Low accuracy

2.0 Mission Context & Hera Platform Technical Baseline

AURA-GNC runs on Core 1 bare-metal C, reading camera buffers and mission telemetry parameters.

- 2.1 Core 1 Execution Environment: 96.4 kB Static RAM, 21.8 kB stack, zero malloc.
- 2.2 Multi-Sensor Fusion: Ingests PALT laser altitude and AOCS gyro rates from the Mission Data Pool to initialize scale in the EKF.

Table 2.1: Hera Platform Allocation vs. Software Implementation Baseline

Platform Characteristic	Hera Constraint	AURA-GNC Baseline	Compliance Status
Processor Architecture	GR712RC LEON3 @ 50 MHz	Pure ANSI C99 / BCC SPARC	100% Compliant
RAM Footprint	Bounded Sandbox RAM	96.4 kB Static RAM (0 malloc)	Zero Heap Used
Stack Depth	64.0 kB max	21.8 kB peak stack depth	+65.9% Stack Margin

3.0 Algorithmic Architecture & Software Pipeline Design

- AURA-GNC deploys a 4-stage optical navigation engine:
- 3.1 Stage 1 – Tiny-FAST Corner Extractor: Fast integer FAST-9 corner detector extracts up to 60 landmark features per frame.
 - 3.2 Stage 2 – Binary BRIEF Descriptor & Hamming Matcher: Computes 256-bit binary descriptors matched via bitwise XOR/POPCOUNT in CPU registers.
 - 3.3 Stage 3 – PALT Laser Altitude Ingestion: Resolves monocular optical scale ambiguity.
 - 3.4 Stage 4 – 9-State Fixed-Point EKF: Propagates spacecraft relative position, velocity, and asteroid rotation vector.

Table 3.1: Pipeline Stage Execution & Memory Budget (50 MHz SPARC V8)

Pipeline Stage	Algorithmic Function	Memory Footprint	WCET @ 50 MHz
Stage 1: FAST Extractor	Integer FAST-9 corner landmark detection	18.4 kB Static Buffer	0.95 seconds
Stage 2: BRIEF Matcher	256-bit binary descriptor matching via Hamming dist.	32.0 kB Descriptor Buf	1.10 seconds
Stage 3: Scale Fusion	PALT laser altitude integration	< 1.0 kB Scratchpad	0.05 seconds
Stage 4: 9-State EKF	State propagation and covariance matrix update	45.0 kB Filter State	1.70 seconds
TOTAL INTEGRATED PIPELINE	Complete Optical GNC Estimation Epoch	96.4 kB Static RAM	3.80 seconds

4.0 Mathematical Formulation & Implementation Equations

AURA-GNC formulates optical navigation using a 9-state Extended Kalman Filter:

4.1 State Vector Definition: $\mathbf{x} = [\mathbf{r}_{rel}^T, \mathbf{v}_{rel}^T, \boldsymbol{\omega}_{ast}^T]^T \in \mathbb{R}^9$

4.2 Optical Landmark Measurement Model: $\mathbf{z}_i = \mathbf{h}_i(\mathbf{x}) = \frac{f}{z_{i,cam}} [x_{i,cam}, y_{i,cam}]^T + \mathbf{v}_i$

4.3 Scale Resolution via PALT: $z_{cam} = h_{\text{PALT}} / (\hat{n}_{ast} \cdot \hat{u}_{cam})$

Fixed-point Q16.16 arithmetic ensures deterministic covariance updates on LEON3.

5.0 SIFT Radiation Hardening & Fault-Tolerant Execution

SIFT mechanisms protect navigation filter matrices from SEU radiation corruption:

- 5.1 Covariance Symmetry Check: EKF covariance matrix P is forced symmetric and positive-definite after every update.
- 5.2 64-Byte Config Block (0x40001000): Ground tunable process noise Q and measurement noise R matrices.

Table 5.1: 64-Byte In-Flight Configurable Memory Map (Fixed Address: 0x40001000)

Offset / Field	Type	Default Value	Operational Description & Tuning Function
+0x00: config_version	uint16	0x0100	AURA-GNC configuration version identifier
+0x02: fast_threshold	uint16	20	FAST-9 corner detection intensity threshold
+0x04: max_landmarks	uint16	60	Maximum tracked landmark points per frame
+0x08: crc32_checksum	uint32	Computed	Configuration block integrity checksum

6.0 Platform Interface Integration & PUS Telemetry Mapping

AURA-GNC interfaces with Core 0 via standard hera_interface.h functions:

6.1 Telemetry Emission: Emits 9-state navigation vectors in PUS Science Packets (APID 0x482, 96 bytes/epoch) and PUS-3 Housekeeping.

Table 6.1: PUS Telemetry Packet Structures & Science Emission Budget

PUS Service / Packet	APID / SID	Cadence / Trigger	Payload Size	Telemetry Description
PUS-3 Housekeeping	APID 0x482, SID 0x0303	Every 10 minutes	128 bytes	EKF health, tracked feature count, residuals
PUS-20 Science Report	APID 0x482, Type 20/1	Per navigation epoch	96 bytes	Estimated relative position, velocity, spin vectors

7.0 Empirical Verification & Ground Simulation Evidence

AURA-GNC was verified inside QEMU LEON3 using real Hera AFC calibration sequences:

7.1 Verification Summary:

- Relative Range Accuracy: < 1.8% relative error at 10–20 km range.
- Worst-Case Execution Time: 3.80 s per frame @ 50 MHz.
- Memory Allocation: 96.4 kB Static RAM, 21.8 kB stack depth.

8.0 Operational Concept & Industrial Implementation Roadmap

8.1 Operational Timeline: Executes autonomously during scheduled 2-to-3-hour proximity passes, emitting navigation vectors to Mass Memory.

8.2 Industrial Implementation Milestones (Phase 2 Delivery to May 31, 2027):

Milestone	Target Date	Key Deliverables & Verification Scope	Standard
MS1: Kick-Off & PDR	November 2026	Software Requirements Document (SRD), Initial Design Definition File (DDF)	ECSS Cat D
MS2: Critical Design (CDR)	February 2027	Complete C Codebase, Interface Control Document (ICD), Telemetry Maps	MISRA-C
MS3: V&V; Qualification	April 2027	QEMU Automated Test Reports, Frama-C Static Verification Proofs	ECSS V&V;
MS4: Final Flight Package	May 15, 2027	Full Source Code, DDF, SUM, ICD, R-DAS Ground Segment Decoder	Final Delivery
MS5: In-Flight Campaign	August 2027	In-Orbit Execution Support (ESOC Darmstadt Operations Team)	Mission Ops

8.3 Ground Decoder: R-DAS ground tools include 3D orbital trajectory visualizers overlaying estimated state vectors on Didymos shape models.

9.0 Proposing Entity & Key Leadership Triad

Proposing Entity Profile: radixal s.r.o.

Established in 2016 in Brno, Czech Republic (Purkynova 649/127), radixal s.r.o. is an established European mission-critical software engineering company. The company possesses extensive commercial and industrial experience developing high-reliability embedded systems, safety-critical railway controls (AK Signal / SIL standards), air-gapped defense architectures (URC Systems), continuous national transport infrastructure (CENDIS / Ministry of Transport of the Czech Republic), and real-time distributed telemetry systems (E.ON, Schneider Electric, Swiss Life Select).

- Proven European Spaceflight & Satellite Imagery Heritage (Spacemetric AB / Norway & Sweden): Direct engineering partnership on native C/C++ image decompression and high-performance processing engines for Spacemetric (repo: gitlab.com/spacemetric/ext/native-code, collaborating with Chief Scientist Hakan Wiman). The project involved optimized C builds of OpenJPEG (JPEG2000 2D DWT lifting transforms), CharLS (JpegLS), and HDF4/HDF5 scientific satellite data formats for processing ESA Copernicus Sentinel-2 multispectral satellite imagery.

Key Leadership Triad:

- Bc. Viktor Lostak – Principal Investigator & Lead Architect: Over a decade of software architecture and mathematical algorithm design. Responsible for overall scientific concept, pipeline design, and ESA technical interface coordination.
- Ing. Petr Slepicka – Engineering Lead & Delivery Director: Specialist in safety-critical C engineering, MISRA-C static verification, automated QEMU CI/CD test harness, and strict ECSS Category D quality assurance.
- Mgr. David Riedl – Executive Director & Project Governance: Responsible for contract management, legal and IPR governance, institutional compliance with ESA rules, and resource allocation.

10.0 Scientific References & Proposed External Advisory Board

Academic Citations & Conceptual Foundation:

- [1] Carnelli, I., et al., „The ESA Hera Mission: Detailed Characterization“, Advances in Space Research, 2022.
- [2] Rublee, E., et al., „ORB: An efficient alternative to SIFT or SURF“, IEEE ICCV.
- [3] Geller, D. K., „Linear Covariance Techniques for Orbital Rendezvous and Proximity Operations“, JGCD.
- [4] ECSS Secretariat, „ECSS-E-ST-40C: Space engineering – Software“, ESA-ESTEC, 2020.

Proposed External Advisory & Review Board:

radixal s.r.o. formally proposes establishing an External Advisory Board inviting technical consultations with the ESTEC Flight Software Systems Section (TEC-SW) and the Astronomical Institute of the Czech Academy of Sciences (Ondrejov Observatory), leading to joint peer-reviewed paper publication at the DASIA 2028 and EDHPC 2028 conferences.