

Project R-DAS: Onboard Deep-Space Autonomy Suite for ESA Hera



ESA Open Space Innovation Platform (OSIP) | Autonomous Software Experiments on Hera

EXECUTIVE SUMMARY & MISSION IMPACT:
radixal s.r.o. (Brno, Czech Republic) submits a comprehensive 6-proposal suite, the Radixal Deep-Space Autonomy Suite (R-DAS), under the ESA OSIP Call for Ideas. Engineered for bare-metal execution on the Frontgrade Gaisler GR712RC (LEON3 @ 50 MHz) Core 1 sandbox of ESA's Hera spacecraft during the August 2027 Extended Mission.

- Key Technological Innovations: Autonomous DART impact crater detection via INT8 Micro-CNN & PALT laser fusion, lossless CDF 5/3 integer wavelet compression (-82.2% bandwidth), in-situ 3D shape mesh building, and passive gravity parameter (GM) inversion.
- In-Flight Benchmark & Ramses Synergy: Executes an in-flight Shadow-Mode GNC benchmark comparing onboard maneuver recommendations against ESOC Flight Dynamics ground truth, establishing TRL 8 flight qualification for the 2029 ESA Ramses mission to asteroid (99942) Apophis.

The 6 Proposals of the R-DAS Suite (Covering All 6 ESA Contest Categories)

Module / Identifier	ESA Category	Primary Function & In-Flight Objective on Hera	Engineering Budget	
ARGOS-AI (Flagship)	Cat. 4: Edge AI	DART crater detection in INT8 Micro-CNN + PALT laser altimeter metric sizing in meters	2.39 s WCET 142 kB RAM	<ParagraphStyle 'T
DEEP-WAVE	Cat. 2: Compression	Reversible CDF 5/3 integer wavelet compression achieving -82.2% downlink bandwidth reduction	2.39 s WCET 38 kB RAM	<ParagraphStyle 'T
AURA-GNC	Cat. 1: Autonomy & GNC	Shadow-Mode 3D landmark mesh building, GM gravity inversion & ESOC ground-truth validation	3.80 s WCET 96 kB RAM	<ParagraphStyle 'T
AEGIS-FDIR	Cat. 5: Resilience	Operationalizing ESTEC HERA-IoD research: Quantized Isolation Forest telemetry anomaly detector	0.12 s WCET 18 kB RAM	<ParagraphStyle 'T
ARES-Planner	Cat. 3: Operations	Autonomous integer CSP solver for multi-payload observation scheduling (+35% science return)	1.40 s WCET 43 kB RAM	<ParagraphStyle 'T
CHRONOS	Cat. 6: Science / Astro	Onboard aperture photometry & Dimorphos lightcurve tracking (Ondrejov Observatory synergy)	0.85 s WCET 29 kB RAM	<ParagraphStyle 'T

Technical Feasibility & Spacecraft Safety (Zero Flight Risk)

Engineered strictly in deterministic ANSI C99 without dynamic memory allocation (0 malloc, < 24 kB stack). The codebase was empirically validated on 2,400+ real Asteroid Framing Camera (AFC) calibration images inside the QEMU LEON3 SPARC V8 emulator. Execution is confined to the isolated Core 1 bare-metal sandbox without actuator authority, ensuring absolute zero risk to Core 0 flight software.

Proposing Entity: radixal s.r.o. & Leadership Triad

radixal s.r.o. (est. 2016 in Brno) holds a 10-year track record in safety-critical systems (AK Signal / SIL railway), satellite image wavelet pipelines for ESA Copernicus Sentinel-2 (Spacemetric AB / Sweden & Norway), defense systems (URC Systems), and national infrastructure.

- Bc. Viktor Lostak (Principal Investigator & Lead Architect): Lead architect and designer of mathematical algorithms.
- Ing. Petr Slepicka (Engineering Lead & Delivery Director): Lead flight software engineer, MISRA-C static verification, and ECSS QA.
- Mgr. David Riedl (Executive Director & Governance): Project governance, legal, and ESA institutional compliance.

Contact: Bc. Viktor Lostak | Email: viktor.lostak@radixal.net | Web: <https://radixal.net> | Git: github.com/radixal-sro/rdas-hera