

# stmglossaries package description

Copyright © 2019 DLR FA STM  
v20191031

Martin Rädcl

2019-10-31

For larger documents, such as reports and thesis, it is nice to have L<sup>A</sup>T<sub>E</sub>X take care of things like a list of acronyms or symbols.

If you write multiple documents you maybe want to make sure that the acronyms and symbols you use throughout all your texts are consistent. And you maybe also want to have the chance to change a symbol at a single location instead of crawling through every equation that might be affected by a change in notation.

This package provides an expendable set of commonly used acronyms as well as symbols in structural mechanics. It is build upon the glossaries package.

## Contents

<b>1. Example</b>	<b>2</b>
<b>2. Contents</b>	<b>2</b>
<b>3. Usage - in the preamble</b>	<b>3</b>
3.1. Load the whole package - acronyms and symbols . . . . .	3
3.1.1. Options . . . . .	3
3.2. Load the acronyms package . . . . .	4
3.2.1. Options . . . . .	4
3.3. Load the symbols package . . . . .	4
3.3.1. Options . . . . .	4
<b>4. Usage - in the document</b>	<b>5</b>
4.1. Acronyms . . . . .	5
4.2. Symbols . . . . .	5
4.2.1. Commands . . . . .	5
4.2.2. Lists . . . . .	5

4.2.3. Combine lists . . . . .	6
<b>5. Styles</b>	<b>6</b>
5.1. Acronym styles . . . . .	6
5.1.1. <code>stmacronymstyle</code> . . . . .	6
5.2. Symbol styles . . . . .	6
5.2.1. <code>stmsymbolstyle</code> . . . . .	6
5.2.2. <code>stmonecolpapersymbolstyle</code> . . . . .	7
5.2.3. <code>stmtwocolpapersymbolstyle</code> . . . . .	7
5.2.4. <code>stmindexstyle</code> . . . . .	7
5.2.5. <code>stmexponentstyle</code> . . . . .	8
5.2.6. <code>stmoperatorstyle</code> . . . . .	8
<b>A. All acronyms</b>	<b>9</b>
<b>B. All symbols</b>	<b>11</b>
<b>C. The code</b>	<b>17</b>
C.1. <code>stmglossaries.sty</code> . . . . .	17
C.2. <code>stmglossariesacronymstyles.sty</code> . . . . .	20
C.3. <code>stmglossariessymbolstyles.sty</code> . . . . .	23

## 1. Example

This is a simple test. It uses an acronym auxiliary power unit (APU). You can use all the acronyms defined in Appendix A. The example also has an equation to test the symbols:

$$F = ma \tag{1}$$

It creates a nice little list of symbols

## Scalars

Symbol	Name	Description
$a$	Acceleration	
$m$	Mass	
$F$	Force	

## 2. Contents

There are multiple packages included:

- `stmglossaries.sty`
- `stmglossariesacronymitems.sty`
- `stmglossariesacronymstyles.sty`
- `stmglossariessymbolitems.sty`
- `stmglossariessymbolstyles.sty`

`stmglossariesacronymitems.sty` contains all acronym definitions. These can be used by the `\gls`-like commands of `glossaries`, see section 6.1 of the `glossaries` documentation.

`stmglossariesacronymstyles.sty` contains implementations for the `style` option in a call to `\printglossary[type=\acronymtype,style=STYLENAME]`. See subsection 5.1 for details.

`stmglossariessymbolitems.sty` contains all symbol definitions. These can be used by the `\glsymbol` command of `glossaries`, see section 6.2 of the `glossaries` documentation.

`stmglossariessymbolstyles.sty` contains implementations for the `style` option in a call to `\printglossary[type=scalarlist,style=STYLENAME]`. See subsection 5.2 for details.

`stmglossaries.sty` is a wrapper around the definitions for `acronyms` and `symbols` and loads both.

### 3. Usage - in the preamble

There are different options to load acronyms, symbols or the whole thing. Additionally, the package offers some predefined styles to set your symbols in a nice way.

#### 3.1. Load the whole package - acronyms and symbols

This way, the acronym as well as the symbol items are loaded. Load the package by adding

```
\usepackage{stmglossaries}
```

to your preamble. In case you have not loaded *glossaries* with your own options beforehand, the package will load the package with the options `acronym`, `nomain` and `toc`.

##### 3.1.1. Options

**Option *loadstyles* and *noloadstyles*** These options are only available for loading the whole package, with

```
\usepackage[noloadstyles]{stmglossaries}
```

`loadstyles` is the default and loads the styles. It is used in case `noloadstyles` is not set explicitly.

**Option *morewrites* and *nomorewrites*** *morewrites* is the default and loads the *morewrites* package. It is used in case *nomorewrites* is not set explicitly.

## 3.2. Load the acronyms package

This way, the acronyms are loaded. Load the package individually by adding

```
\usepackage{stmglossariesacronymitems}
```

to your preamble. In case you have not loaded *glossaries* with your own options beforehand, the package will load the package with the options *acronym*, *nomain* and *toc*.

### 3.2.1. Options

**Option *loadacronymstyles* and *noloadacronymstyles*** Load or do not load the style definitions from *stmglossariesacronymstyles* with

```
\usepackage[loadacronymstyles]{stmglossariesacronymitems}  
\usepackage{stmglossariesacronymitems}
```

or

```
\usepackage[noloadacronymstyles]{stmglossariesacronymitems}
```

*loadacronymstyles* is the default and loads the styles. It is used in case *noloadacronymstyles* is not set explicitly. So the

## 3.3. Load the symbols package

This way, the acronyms are loaded. Load the package individually by adding

```
\usepackage{stmglossariessymbolitems}
```

to your preamble. In case you have not loaded *glossaries* with your own options beforehand, the package will load the package with the options *acronym*, *nomain* and *toc*.

### 3.3.1. Options

**Option *loadsymbolstyles* and *noloadsymbolstyles*** Load or do not load the style definitions from *stmglossariessymbolstyles* with

```
\usepackage[loadsymbolstyles]{stmglossariessymbolitems}  
\usepackage{stmglossariessymbolitems}
```

or

```
\usepackage[noloadsymbolstyles]{stmglossariessymbolitems}
```

*loadacronymstyles* is the default and creates the styles. It is used in case *noloadacronymstyles* is not set explicitly.

## 4. Usage - in the document

### 4.1. Acronyms

Print the list of acronyms with the style *stmacronymstyle* and without number using *nonumberlist* with

```
\printglossary[type=\acronymtype,style=stmacronymstyle,nonumberlist]
```

For a description of acronym styles, see subsection 5.1.

### 4.2. Symbols

#### 4.2.1. Commands

There might be a time where you very locally want to define a symbol without adding it to the global list of symbol. Despite that, you want to make sure that the symbol, e.g. for a vector, a matrix or a state, uses the correct notation style.

Therefore, `stmglossariessymbolitems` defines a couple of useful styling commands

<code>\romanscalarsymbol</code>	A roman scalar symbol
<code>\greekscalarsymbol</code>	A greek scalar symbol
<code>\romanvectorsymbol</code>	A roman vector symbol
<code>\greekvectorsymbol</code>	A greek vector symbol
<code>\romanmatrixsymbol</code>	A roman matrix symbol
<code>\scalarstatesymbol</code>	A greek matrix symbol
<code>\romanvectorstatesymbol</code>	A roman vector state symbol
<code>\romandoublestatesymbol</code>	A roman double state symbol

#### 4.2.2. Lists

`stmglossariessymbolitems` defines a number of lists for different types of symbols:

<code>scalarlist</code>	A list for scalar values
<code>vectorlist</code>	A list for vectors
<code>matrixlist</code>	A list for matrices
<code>statelist</code>	A list for peridynamic states
<code>indexlist</code>	A list for indices
<code>exponentlist</code>	A list for exponents
<code>operatorlist</code>	A list for mathematical operators

### 4.2.3. Combine lists

In case you want to combine the predefined lists and print a single combined list, use

```
\documentclass{...}

\usepackage{stmglossaries}
%\usepackage{stmglossariessymbolitems}

\newglossary[slg1]{symbollist}{syi1}{syg1}{Nomenclature}
\forallglsentries[scalarlist]{\lfoo}{\glsmoveentry{\lfoo}{symbollist}}
\forallglsentries[vectorlist]{\lfoo}{\glsmoveentry{\lfoo}{symbollist}}
\forallglsentries[matrixlist]{\lfoo}{\glsmoveentry{\lfoo}{symbollist}}
\forallglsentries[statelist]{\lfoo}{\glsmoveentry{\lfoo}{symbollist}}
\makeglossaries

\begin{document}

...

\printglossary[type=symbollist,style=YOURSTYLENAME,numberlist]

\end{document}
```

as described in section 16.1 of the `glossaries` documentation.

## 5. Styles

### 5.1. Acronym styles

#### 5.1.1. `stmacronymstyle`

**Description** This is a style for acronyms. It has one item column which is left aligned. The columns are *Abbreviation* and *Description*. Column headings are not printed.

### 5.2. Symbol styles

#### 5.2.1. `stmsymbolstyle`

**Description** This is the basic style for variables. It has one item column which is left aligned. The columns are *Symbol*, *Name* and *Description*. Column headings are printed.

**Example**

## Scalars

Symbol	Name	Description
--------	------	-------------

$a$	Acceleration	
$m$	Mass	
$F$	Force	

### 5.2.2. stmonocolpapersymbolstyle

**Description** This is a style for variables for papers with one centered item column. The columns are *Symbol* and *Name*. Column headings are not printed.

**Example**

## Scalars

$a$	Acceleration
$m$	Mass
$F$	Force

### 5.2.3. stmtwocolpapersymbolstyle

**Description** This is a style for variables for papers with two centered item column. The columns are *Symbol* and *Name*. Column headings are not printed.

**Example**

## Scalars

$a$	Acceleration	$F$	Force
$m$	Mass		

### 5.2.4. stmindexstyle

**Description** This is a style for variable indices with one left align item column. The columns are *Symbol* and *Description*. Column headings are printed.

**Example**

$\varepsilon_0$	(2)
-----------------	-----

## Indices

## Symbol Description

$(\ )_0$       Reference configuration

### 5.2.5. stmexponentstyle

**Description** This is a style for variable exponents with one left align item column. The columns are *Symbol* and *Description*. Column headings are printed.

#### Example

$\varepsilon^e$  (3)

## Exponents

## Symbol Description

$(\ )^e$       Elastic

### 5.2.6. stmoperatorstyle

**Description** This is a style for variable operators with one left align item column. The columns are *Symbol* and *Description*. Column headings are printed.

#### Example

$\nabla$  (4)

## Operators

## Symbol Description

$\nabla(\ )$       Fréchet derivative



## A. All acronyms

### Acronyms

Acronym	Description
ACARE	advisory council for aviation research and innovation in europe
AFP	automated fibre placement
APU	auxiliary power unit
BB	bond-based
BB-PD	bond-based peridynamics
BOM	bill of material
BSD	Berkeley software distribution
CA	consortium agreement
CAGR	compound annual growth rate
CAI	compression after impact
CDR	critical design review
CE	constraint equation
CER	composite engineering requirements
CFRP	carbon fibre reinforced plastic
CLT	classical laminate theory
CM	continuum mechanic
CT	computed tomography
CTT	compact tension test
CZM	cohesive zone model
DCB	double cantilever beam
DELiS	design environment for lightweight structures
DFP	dry fibre placement
DKT	discrete Kirchhoff theory
DOA	design organization approval
DOE	design of experiments
DOF	degree of freedom
DSC	differential scanning calorimeter
E2E	end to end
FBG	fibre bragg grating
FDM	finite difference method

<b>Acronym</b>	<b>Description</b>
FE	finite element
FEM	finite element method
FRP	fiber reinforced plastic
FSDT	first-order shear deformation theory
FTE	full time equivalent
FVC	fibre volume content
FVM	finite volume method
GFEM	global finite element model
GPL	GNU General Public License
IAB	industrial advisory board
IDE	integrated development environment
jCoMoT	Java computational mechanics format translator
jMeS	Java mechanics suite
KPI	key performance indicator
LCA	life cycle assessment
LPS	linear peridynamic solid
MBSE	model-based systems engineering
MDO	multi-disciplinary optimization
MPC	multi-point constraint
MRL	manufacturing readiness level
MRO	maintenance, repair and overhaul
NDA	non-disclosure agreement
NDI	non-destructive inspection
NSB	non-ordinary state-based
NSB-PD	non-ordinary state-based peridynamics
ODE	ordinary differential equation
OHC	open hole compression
OHT	open hole tension
OSB	ordinary state-based
OSB-PD	ordinary state-based peridynamics
PD	peridynamic
PDE	partial differential equation
PMC	project management committee

Acronym	Description
POJO	plain old Java object
RMS	risk mitigation structure
RVE	representative volume element
SAI	shear after impact
SB-PD	state-based peridynamics
SC	steering committee
SEM	scanning electron microscopy
SHM	structural health monitoring
TAI	tension after impact
TGA	thermogravimetric analysis
TMA	thermomechanical analysis
TRL	technology readiness level
WORA	write once, run anywhere
WP	work package
XFEM	extended finite element method

## B. All symbols

### Scalars

Label	Symbol
symp:scalar:acceleration	$a$
symp:scalar:load:bodyforce	$b$
symp:scalar:pd:bond:constant	$c$
symp:scalar:geo:diameter	$d$
symp:scalar:pd:bond:elongation	$e$
symp:scalar:thickness	$h$
symp:scalar:geo:1D:length	$l$
symp:scalar:mass	$m$
symp:scalar:pd:volume:weighted	$m_V$
symp:scalar:pd:stretch	$s$
symp:scalar:pd:stretch:critical	$s_C$
symp:scalar:time	$t$

Label	Symbol
symb:scalar:timestep	$\Delta t$
symb:scalar:displacement	$u$
symb:scalar:displacement:component:global:x	$u_x$
symb:scalar:displacement:component:global:y	$u_y$
symb:scalar:displacement:component:global:z	$u_z$
symb:scalar:velocity	$v$
symb:scalar:pd:bond:energy:potential	$w$
symb:scalar:coord:global:x	$x$
symb:scalar:coord:local:x	$\hat{x}$
symb:scalar:coord:material:x	1
symb:scalar:coord:global:y	$y$
symb:scalar:coord:local:y	$\hat{y}$
symb:scalar:coord:material:y	2
symb:scalar:coord:global:z	$z$
symb:scalar:coord:local:z	$\hat{z}$
symb:scalar:coord:material:z	3
symb:scalar:scalarromannull	
symb:scalar:geo:2D:surface	$A$
symb:scalar:mech:tensor:component:stiffness	$C$
symb:scalar:mat:modulus:young	$E$
symb:scalar:load:force	$F$
symb:scalar:mat:modulus:shear	$G$
symb:scalar:mat:energyreleaserate	$G_0$
symb:scalar:mat:energyreleaserate:critical	$G_{0C}$
symb:scalar:mat:energyreleaserate:mode:I	$G_I$
symb:scalar:mat:energyreleaserate:critical:mode:I	$G_{IC}$
symb:scalar:mat:energyreleaserate:mode:II	$G_{II}$
symb:scalar:mat:energyreleaserate:critical:mode:II	$G_{IIC}$
symb:scalar:pd:family	$\mathcal{H}$
symb:scalar:mat:modulus:bulk	$K$
symb:scalar:load:moment	$M$
symb:scalar:fe:shapefunction	$N$
symb:scalar:mat:strength	$R$
symb:scalar:system:euclidean	$\mathbb{R}$
symb:scalar:temperature	$T$
symb:scalar:geo:3D:volume	$V$
symb:scalar:mech:energy:strain:density	$W$
symb:scalar:pd:function:damage:bond	$\chi$
symb:scalar:pd:horizon	$\delta$
symb:scalar:geo:separation	$\delta_c$
symb:scalar:mech:strain:normal:engineering	$\varepsilon$

## Label

## Symbol

symb:scalar:mech:strain:tensor:component	$\epsilon$
symb:scalar:coord:natural:y	$\eta$
symb:scalar:mech:strain:shear:engineering	$\gamma$
symb:scalar:mat:poissonratio	$\nu$
symb:scalar:domain:partial	$\omega$
symb:scalar:pd:function:influence	$\omega$
symb:scalar:pd:function:influence:radial	$\omega\xi$
symb:scalar:pd:function:damage:family	$\varphi$
symb:scalar:rotation	$\psi$
symb:scalar:mat:density	$\rho$
symb:scalar:mech:stress:normal:engineering	$\sigma$
symb:scalar:mech:stress:shear:engineering	$\tau$
symb:scalar:pd:dilatation	$\theta$
symb:scalar:geo:angle:debonding	$\theta_c$
symb:scalar:coord:natural:x	$\xi$
symb:scalar:pd:bond:undeformed:component	$\xi$
symb:scalar:coord:natural:z	$\zeta$
symb:scalar:scalargreeknull	
symb:scalar:discretization:distance:node	$\Delta x$
symb:scalar:domain:boundary	$\Gamma$
symb:scalar:domain	$\Omega$

## Vectors

## Label

## Symbol

symb:vector:pd:bond:deformed	$\eta$
symb:vector:pd:bond:undeformed	$\xi$
symb:vector:load:bodyforce	$\mathbf{b}$
symb:vector:unit	$\mathbf{e}$
symb:vector:pd:force	$\mathbf{f}$
symb:vector:mech:strain	$\epsilon$
symb:vector:mech:stress:cauchy	$\sigma$
symb:vector:pd:bondforcedensity	$\mathbf{t}$
symb:vector:mech:deformation	$\mathbf{u}$
symb:vector:mech:acceleration	$\ddot{\mathbf{u}}$
symb:vector:mech:velocity	$\dot{\mathbf{u}}$
symb:vector:position:undeformed	$\mathbf{x}$
symb:vector:position:deformed	$\mathbf{y}$

## Matrices & Tensors

Label	Symbol
symb:matrix:laminat:membrane	<b>A</b>
symb:matrix:laminat:coupling	<b>B</b>
symb:matrix:mat:stiffness	<b>C</b>
symb:matrix:mech:tensor:stiffness	<b>K</b>
symb:matrix:laminat:bending	<b>D</b>
symb:matrix:mech:strain:green	<b>E</b>
symb:matrix:mech:gradient:deformation	<b>F</b>
symb:matrix:laminat:shear	<b>H</b>
symb:matrix:mech:gradient:displacement	<b>H</b>
symb:matrix:identity	<b>I</b>
symb:matrix:interpolationoperator	<b>I<sub>r</sub></b>
symb:matrix:jacobian	<b>J</b>
symb:matrix:mech:tensor:shape	<b>K</b>
symb:matrix:stiffness	<b>K</b>
symb:matrix:mass	<b>M</b>
symb:matrix:mech:stress:piolakirchhoff:first	<b>P</b>
symb:matrix:laminat:ply:stiffness	<b>Q</b>
symb:matrix:mat:compliance	<b>S</b>
symb:matrix:mech:stress:piolakirchhoff:second	<b>S</b>
symb:matrix:transformation	<b>T</b>

## States

Label	Symbol
symb:state:scalar:influence	<u><math>\omega</math></u>
symb:state:scalar:extension	<u><math>e</math></u>
symb:state:scalar:force	<u><math>t</math></u>
symb:state:scalar:position:undeformed	<u><math>x</math></u>
symb:state:scalar:position:deformed	<u><math>y</math></u>
symb:state:scalar:stateromannull	
symb:state:vector:force	<u><b>T</b></u>
symb:state:vector:direction:deformed	<u><b>M</b></u>
symb:state:vector:position	<u><b>X</b></u>
symb:state:vector:deformation	<u><b>Y</b></u>
symb:state:vector:stateromannull	
symb:state:double:modulus	<u><b>K</b></u>

## Indices

Label	Symbol
symb:index:load:compression	C
symb:index:load:compression:long	cmp
symb:index:critical	$C$
symb:index:hardening	$H$
symb:index:mat:damage:mode:I	$I$
symb:index:mat:damage:mode:II	$II$
symb:index:init	$init$
symb:index:load:shear	S
symb:index:load:shear:long	shr
symb:index:load:tension	T
symb:index:load:tension:long	ten
symb:index:xyz	$x, y, z$
symb:index:yield	y
symb:index:zero	0

## Exponents

Label	Symbol
symb:exponent:midplane	0
symb:exponent:deviatoric	$d$
symb:exponent:elastic	$e$
symb:exponent:linear	$l$
symb:exponent:nonlinear	$nl$
symb:exponent:plastic	$p$
symb:exponent:volumetric	$v$

## Operators

Label	Symbol
symb:operator:csys:local	$(\hat{\phantom{x}})$
symb:operator:csys:material	$(\bar{\phantom{x}})$
symb:operator:Delta	$\Delta(\phantom{x})$

Label	Symbol
symb:operator:dif	$d( )$
symb:operator:dif:short:time	$(\dot{\phantom{x}})$
symb:operator:dif:short:time2	$(\ddot{\phantom{x}})$
symb:operator:dif:short	$(\phantom{x})_{,x}$
symb:operator:dif:partial	$\partial( )$
symb:operator:div	$\text{div}( )$
symb:operator:product:dot	$\cdot$
symb:operator:kroneckerdelta	$\delta_{ij}$
symb:operator:matrix:inverse	$( )^{-1}$
symb:operator:matrix:transpose	$( )^T$
symb:operator:mean	$(\bar{\phantom{x}})$
symb:operator:derivative:frechet	$\nabla( )$
symb:operator:norm	$\ ( )\ $
symb:operator:product:tensor	$\otimes$



## C. The code

### C.1. stmglossaries.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes the common LaTeX
% glossaries definitions
% (acronyms, glossaries, symbols)
% for structural mechanics
%
% Usage
% - Premble:
%   - \usepackage{stmglossaries}
%   - \makeglossaries
% - Document: e.g. (Adapt to your type of glossary item)
%   - \printglossary[type=\acronymtype] or
%   - \printglossary[type=\acronymtype,nonumberlist]
% - Compilation: e.g. (Adapt to your type of glossary item)
%   - makeindex -s [MYTEXFILENAME].ist -o [MYTEXFILENAME].
%     acr [MYTEXFILENAME].acn
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%             Initial draft
%
% Contact:    Martin Raedel, martin.raedel@dlr.de
%             DLR Composite Structures and Adaptive Systems
%
%             _ _ / | _ _
%             / _ / _ / _ /
%             www.dlr.de/fa/en      | / DLR
%
% Copyright (C) 2019-... DLR Composite Structures and
% Adaptive Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% Declare that this style file requires at least LaTeX
% version 2e.
\NeedsTeXFormat{LaTeX2e}
```

```

% Provide the name of your page, the date it was last updated
% , and a comment about what it's used for
\ProvidesPackage{stmglossaries}[2019/10/27 STMs custom LaTeX
glossaries definitions]

% If not loaded in advance, load the glossaries package with
% some default options
\@ifpackageloaded{glossaries}{%
%
}%{%
\RequirePackage[%
acronym, % create a list of acronyms
nomain, % do not use the main glossary
toc, % add glossary titles to table of contents
]{glossaries}%
}%

%-----
% Options
%-----

% Load morewrites
\newif\ifstmglossaries@morewrites
\DeclareOption{morewrites}{\stmglossaries@morewritestrue}
\DeclareOption{nomorewrites}{\stmglossaries@morewritesfalse}

\ExecuteOptions{morewrites} % default is to load morewrites

% Do not load the styles
% Default behaviour is to load the styles to really have a
% benefit
% https://tex.stackexchange.com/a/135255/44634
% Load the default
\newif\ifstmglossaries@loadstyles
\DeclareOption{loadstyles}{\stmglossaries@loadstylestrue}
\DeclareOption{noloadstyles}{\stmglossaries@loadstylesfalse}

\ExecuteOptions{loadstyles} % default is to load the styles

\ProcessOptions\relax

% Load morewrites
\@ifpackageloaded{morewrites}{%

```

```

%
}{%
  \ifstmglossaries@morewrites
    \RequirePackage{morewrites}
  \fi
}%

% Load the acronyms
\@ifpackageloaded{stmglossariesacronymitems}{%
%
}{%
  %\RequirePackage{stmglossariesacronymitems}%
  \ifstmglossaries@loadstyles
    %\RequirePackage[loadacronymstyles]{
      stmglossariesacronymitems}
    \RequirePackage{stmglossariesacronymitems}
  \else
    \RequirePackage[noloadacronymstyles]{
      stmglossariesacronymitems}
  \fi
}%

% Load the symbols
\@ifpackageloaded{stmglossariessymbolitems}{%
%
}{%
  %\RequirePackage{stmglossariessymbolitems}%
  \ifstmglossaries@loadstyles
    %\RequirePackage[loadsymbolstyles]{
      stmglossariessymbolitems}
    \RequirePackage{stmglossariessymbolitems}
  \else
    \RequirePackage[noloadsymbolstyles]{
      stmglossariessymbolitems}
  \fi
}%

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can
% stop reading this file. LaTeX will ignore anything after

```

```

    this line.
\endinput

```

## C.2. stmglossariesacronymstyles.sty

```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes the common LaTeX
% glossaries style definitions
% (acronyms, glossaries, symbols)
% for structural mechanics
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%              Initial draft
%
% Contact:    Martin Raedel, martin.raedel@dlr.de
%              DLR Composite Structures and Adaptive Systems
%
%              --/|--
%              /_/_/_/_/
%              www.dlr.de/fa/en      |// DLR
%
% Copyright (C) 2019-... DLR Composite Structures and
% Adaptive Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% Declare that this style file requires at least LaTeX
% version 2e.
\NeedsTeXFormat{LaTeX2e}
%
% Provide the name of your page, the date it was last updated
% , and a comment about what it's used for
\ProvidesPackage{stmglossariesacronymstyles}[2019/10/27 STMs
custom LaTeX glossaries style definitions]
%
% Now paste your code from the preamble here
%
% If not loaded in advance, load the glossaries package with
% some default options

```

```

\@ifpackageloaded{glossaries}{%
%
}%{
\RequirePackage[%
  acronym,    % create a list of acronyms
  nomain,     % do not use the main glossary
  toc,        % add glossary titles to table of contents
]{glossaries}%
}%

\@ifpackageloaded{longtable}{}{\RequirePackage{longtable}}%
\@ifpackageloaded{tabu}{}{\RequirePackage{tabu}}%

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Functionality %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Redefine package options %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

%Den Punkt am Ende jeder Beschreibung deaktivieren
\renewcommand*{\glspostdescription}{}
% \renewcommand*{\glspostdescription}{\dotfill}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Own styles %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% -----
% Acronym-styles
% -----

\newglossarystyle{stmacronymstyle}{%
\renewenvironment{theglossary}%
  {\begin{longtabu} to \linewidth {lX}}%
  {\end{longtabu}}%
% Header line
\renewcommand*{\glossaryheader}{%
  %\textbf{Label} & \textbf{Symbol}
  \tabularnewline%
  \tabularnewline%
  \endhead%
  \endfoot%
}

```

```

}%
% indicate what to do at the start of each logical group
%\renewcommand*{\glsgroupheading}[1]{}%
%\renewcommand*{\glsgroupskip}{}% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}% What to do
    between groups
\renewcommand*{\glossaryentryfield}[5]{%
    \glsentryitem{##1}\glstarget{##1}{##2}
    & ##3\glspostdescription ##5% Description
    \tabularnewline%
}
}

% -----
% Style to show the keys
% -----

\newglossarystyle{stmacronymlabelstyle}{%
    \renewenvironment{theglossary}%
        {\begin{longtabu} to \linewidth {lX}}%
        {\end{longtabu}}%
    % Header line
    \renewcommand*{\glossaryheader}{%
        \textbf{Acronym} & \textbf{Description}
        \tabularnewline%
        \tabularnewline%
        \endhead%
        \endfoot%
    }%
    % indicate what to do at the start of each logical group
    %\renewcommand*{\glsgroupheading}[1]{}%
    %\renewcommand*{\glsgroupskip}{}% What to do between groups
    \renewcommand*{\glsgroupskip}{\tabularnewline}% What to do
        between groups
    \renewcommand*{\glossaryentryfield}[5]{%
        \glsentrycounterlabel{##1} &%
        %\glsentryitem{##1}\glstarget{##1}{##2} %&%
        ##3\glspostdescription ##5% Description
        \tabularnewline%
    }
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it %

```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
% Finally, we'll use \endinput to indicate that LaTeX can
% stop reading this file. LaTeX will ignore anything after
% this line.
```

```
\endinput
```

### C.3. stmglossariessymbolstyles.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
% Header %
```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
%
```

```
% This file includes the common LaTeX
```

```
% glossaries style definitions
```

```
% (acronyms, glossaries, symbols)
```

```
% for structural mechanics
```

```
%
```

```
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
```

```
% Initial draft
```

```
%
```

```
% Contact: Martin Raedel, martin.raedel@dlr.de
```

```
% DLR Composite Structures and Adaptive Systems
```

```
%
```

```
% --/|--
```

```
% /_/_/_/_/
```

```
% www.dlr.de/fa/en |// DLR
```

```
%
```

```
% Copyright (C) 2019-... DLR Composite Structures and
```

```
% Adaptive Systems
```

```
%
```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
% Content %
```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
% Declare that this style file requires at least LaTeX
```

```
% version 2e.
```

```
\NeedsTeXFormat{LaTeX2e}
```

```
% Provide the name of your page, the date it was last updated
```

```
% , and a comment about what it's used for
```

```
\ProvidesPackage{stmglossariessymbolstyles}[2019/10/27 STMs
```

```
custom LaTeX glossaries style definitions]
```

```

% Now paste your code from the preamble here

% If not loaded in advance, load the glossaries package with
  some default options
\@ifpackageloaded{glossaries}{%
%
}%{
  \RequirePackage[%
    acronym,      % create a list of acronyms
    nomain,       % do not use the main glossary
    toc,          % add glossary titles to table of contents
  ][glossaries]%
}%

\@ifpackageloaded{longtable}{}{\RequirePackage{longtable}}%
\@ifpackageloaded{tabu}{}{\RequirePackage{tabu}}%

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Functionality %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Redefine package options %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Den Punkt am Ende jeder Beschreibung deaktivieren
\renewcommand*{\glspostdescription}{}
% \renewcommand*{\glspostdescription}{\dotfill}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Own styles %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% -----
% Coordinate-system style
% -----

\newglossarystyle{mycoordinatesystemstyle}{%
  %\renewcommand{\glossarysection}[2][{}]{% no title
  \renewcommand*{\glsclearpage}{}% avoid page break before
    glossary
  \renewenvironment{theglossary}%
    {\begin{longtabu} to \linewidth {cX}}%
    {\end{longtabu}}%

```



```

% Header line
\renewcommand*{\glossaryheader}{%
  % Requires booktabs
  %\toprule%
  \textbf{Symbol} & \textbf{Description}%
  \tabularnewline%
  \tabularnewline%
  %\midrule%
  \endhead%
  %\bottomrule%
  \endfoot%
}%
% indicate what to do at the start of each logical group
%\renewcommand*{\glsgroupheading}[1]{}%
%\renewcommand*{\glsgroupskip}{}% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}% What to do
  between groups
\renewcommand*{\glossentry}[1]{%
  \glsentryitem{##1}% Entry number if required
  \glstarget{##1}{\glossentrysymbol{##1}} &
  %\glossentrysymbol{##1}      & % Symbol
  %\glossentryname{##1}      & % Name
  \glossentrydesc{##1}      %& % Description
  %\glsentryuseri{##1}%      % Unit in User1-Variable
  \tabularnewline%
}%
}

% -----
% Symbols-styles
% -----

\newglossarystyle{stmsymbolstyle}{%
  %\renewcommand{\glossarysection}[2][{}]{% no title
  \renewcommand*{\glsclearpage}{}% avoid page break before
    glossary
  \renewenvironment{theglossary}%
    {\begin{longtabu} to \linewidth {c1X}}{c}}%
    {\end{longtabu}}%
  % Header line
  \renewcommand*{\glossaryheader}{%
    \textbf{Symbol} & \textbf{Name} & \textbf{Description}% &
      \textbf{Unit}%
    \tabularnewline%

```

```

\tabularnewline%
\endhead%
\endfoot%
}%
% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}
\renewcommand*{\glossentry}[1]{%
  \glentryitem{##1}% Entry number if required
  \glstarget{##1}{\glossentrysymbol{##1}} &
  \% \glossentrysymbol{##1} & % Symbol
  \glossentryname{##1} & % Name
  \glossentrydesc{##1} & % Description
  \% \glentryuseri{##1}% Unit in User1-Variable
\tabularnewline%
}%
}

% -----
% Symbols-styles for papers
% -----

\newglossarystyle{stmonecolpapersymbolstyle}{%
  \% \renewcommand{\glossarysection}[2][{}]{% no title
  \renewcommand*{\glsclearpage}{}% avoid page break before
    glossary
  \renewenvironment{theglossary}%
    {\begin{longtabu} to \linewidth {c1Xc1}}%c}}%
    {\end{longtabu}}%
  % Header line
  \renewcommand*{\glossaryheader}{}%
  % indicate what to do at the start of each logical group
  \% \renewcommand*{\glsgroupheading}[1]{}
  % What to do between groups -> no skip
  \renewcommand*{\glsgroupskip}{}
  % How the entry looks like
  \renewcommand*{\glossentry}[1]{
    \glentryitem{##1}% Entry number if required
    \glstarget{##1}{\glossentrysymbol{##1}} & % Symbol
    \glossentryname{##1} & % Name
    \tabularnewline%
  }%
}

% https://tex.stackexchange.com/a/216434/44634

```

```

% needs: \usepackage{multicol}
\newglossarystyle{stmtwocolpapersymbolstyle}{%
  %\renewcommand{\glossarysection}[2][{}]{% no title
  \renewenvironment{theglossary}%
    {\begin{multicols}{2}\raggedright}
    {\end{multicols}}
  % Header line
  \renewcommand*{\glossaryheader}{}%
  \renewcommand*{\glsgroupheading}[1]{% indicate what to do
    at the start of each logical group
  \renewcommand*{\glsgroupskip}{}% What to do between groups
    -> no skip
  \renewcommand*{\glsclearpage}{}% avoid page break before
    glossary
  % set how each entry should appear:
  \renewcommand*{\glossentry}[2]{
    \noindent\makebox[2.5em][c]{\glstarget{##1}{\
      glossentrysymbol{##1}}}% Symbol
    \glossentryname{##1}% Name
    \newline
  }
}

% -----
% Exponent - styles
% -----

\newglossarystyle{stmexponentstyle}{%
  %\renewcommand{\glossarysection}[2][{}]{% no title
  \renewcommand*{\glsclearpage}{}% avoid page break before
    glossary
  \renewenvironment{theglossary}%
    % \extrarowsep=1mm
    {%
      \begin{group}
      \renewcommand{\arraystretch}{1.4}
      \begin{longtabu} to \linewidth {@{\ \ }r@{l}X}
      }{%
      \end{longtabu}
      \end{group}
    }%
  % Header line
  \renewcommand*{\glossaryheader}{%
    \multicolumn{2}{@{}c@{}}{\textbf{Symbol}} & \textbf{

```

```

        Description}%
\tabularnewline%
\tabularnewline%
\endhead%
\endfoot%
}%
% indicate what to do at the start of each logical group
%\renewcommand*{\glsgroupheading}[1]{}%
% What to do between groups
%\renewcommand*{\glsgroupskip}{}
% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}%
\renewcommand*{\glossentry}[1]{%
    \glsentryitem{##1}% Entry number if required
    \protect\ensuremath{\protect\left(\protect\phantom{a}\protect\right)} &
    \glsstarget{##1}{\protect\ensuremath{\protect\vphantom{a}
        }^{\glossentrysymbol{##1}}}} &
    %\glossentrysymbol{##1}          & % Symbol
    %\glossentryname{##1}           & % Name
    \glossentrydesc{##1}           & % Description
    %\glsentryuseri{##1}%           % Unit in User1-Variable
    \tabularnewline%
}%
}

% -----
% Index-styles
% -----

\newglossarystyle{stmindexstyle}{%
    %\renewcommand{\glossarysection}[2][{}]{% no title
    \renewcommand*{\glsclearpage}{}% avoid page break before
        glossary
    \renewenvironment{theglossary}%
        {%
            \begingroup
            \renewcommand{\arraystretch}{1.4}
            \begin{longtabu} to \linewidth {@{\ \ }r@{lX}}
        }{%
            \end{longtabu}
            \endgroup
        }%
    % Header line

```

```

\renewcommand*{\glossaryheader}{%
  \multicolumn{2}{@{}c@{}}{\textbf{Symbol}} & \textbf{Description}%
  \tabularnewline%
  \tabularnewline%
  \endhead%
  \endfoot%
}%
% indicate what to do at the start of each logical group
%\renewcommand*{\glsgroupheading}[1]{}%
% What to do between groups
%\renewcommand*{\glsgroupskip}{}%
% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}
\renewcommand*{\glossentry}[1]{%
  \glstryitem{##1}% Entry number if required
  \protect\ensuremath{\protect\left(\protect\phantom{a}\protect\right)} &
  %\glstarget{##1}{\glossentrysymbol{##1}} &
  \glstarget{##1}{\protect\ensuremath{\protect\vphantom{a}_\{\glossentrysymbol{##1}\}}} &
  %\glossentrysymbol{##1} & % Symbol
  %\glossentryname{##1} & % Name
  \glossentrydesc{##1} & % Description
  %\glstryuseri{##1}% & % Unit in User1-Variable
  \tabularnewline%
}%
}

% -----
% Operator style
% -----

\newglossarystyle{stmoperatorstyle}{%
  %\renewcommand{\glossarysection}[2][{}]{% no title
  % avoid page break before glossary
  \renewcommand*{\glsclearpage}{}
  \renewenvironment{theglossary}%
    % \extrarowsep=1mm
    {%
      \begingroup%
      \renewcommand{\arraystretch}{1.4}%
      %\begin{longtabu} to \linewidth {cX}
      \begin{longtabu} to \linewidth {@{\ \ ;}r@{c@{}}lX}

```

```

    }%
    {%
        \end{longtabu}
        \endgroup
    }%
% Header line
\renewcommand*{\glossaryheader}{%
    \multicolumn{3}{@{}c@{}}{\textbf{Symbol}} & \textbf{
        Description}%
    \tabularnewline%
    \tabularnewline%
    \endhead%
    \endfoot%
}%
% indicate what to do at the start of each logical group
%\renewcommand*{\glsgroupheading}[1]{}%
% What to do between groups
%\renewcommand*{\glsgroupskip}{}%
% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}
\renewcommand*{\glossentry}[1]{%
    \glstryitem{##1}% Entry number if required
    %\glstarget{##1}{\glossentrysymbol{##1}} &
    %\glstarget{##1}{\glossentrysymbol{##1}}&
    \glstryuseri{##1} &
    \glstryuserii{##1} &
    \glstryuseriii{##1} &
    %\glossentrysymbol{##1} & % Symbol
    %\glossentryname{##1} & % Name
    \glossentrydesc{##1} & % Description
    %\glstryuseri{##1}% % Unit in User1-Variable
    \tabularnewline%
}%
}

% -----
% Style to show the keys
% -----

\newglossarystyle{stmsymbollabelstyle}{%
    \renewcommand*{\glsclearpage}{}% avoid page break before
    glossary
    \renewenvironment{theglossary}%
        {\begin{longtabu} to \linewidth {Xc}}%

```

```

    {\end{longtabu}}}%
% Header line
\renewcommand*{\glossaryheader}{%
    \textbf{Label} & \textbf{Symbol}
    \tabularnewline%
    \tabularnewline%
    \endhead%
    \endfoot%
}%
% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}
\renewcommand*{\glossentry}[1]{%
    \glsentryitem{##1}% Entry number if required
    \glsentrycounterlabel{##1} &
    \glstarget{##1}{\glossentrysymbol{##1}}% &
    \tabularnewline%
}%
}

\newglossarystyle{stmoperatorlabelstyle}{%
    %\renewcommand{\glossarysection}[2][{}]{% no title
    % avoid page break before glossary
    \renewcommand*{\glsclearpage}{}
    \renewenvironment{theglossary}%
    {%
        \begingroup%
        \renewcommand{\arraystretch}{1.4}%
        \begin{longtabu} to \linewidth {X@{\ \ ;}r@{}c@{}l}
    }%
    {%
        \end{longtabu}
        \endgroup
    }%
    % Header line
    \renewcommand*{\glossaryheader}{%
        \textbf{Label} & \multicolumn{3}{@{}c@{}}{\textbf{Symbol}}
        }% & %
        \tabularnewline%
        \tabularnewline%
        \endhead%
        \endfoot%
    }%
    % indicate what to do at the start of each logical group
    %\renewcommand*{\glsgroupheading}[1]{%

```

```

% What to do between groups
%\renewcommand*{\glsgroupskip}{}%
% What to do between groups
\renewcommand*{\glsgroupskip}{\tabularnewline}
\renewcommand*{\glossentry}[1]{%
  \glentryitem{##1}% Entry number if required
  \glentrycounterlabel{##1} &
  \glentryuseri{##1} &
  \glentryuserii{##1} &
  \glentryuseriii{##1}% &
  \tabularnewline%
}%
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can
% stop reading this file. LaTeX will ignore anything after
% this line.
\endinput

```