stmdate package description

Copyright © 2026 DLR SY STM

v20260226

Martin Rädel

2026-02-26

These are the date definitions for `stmlatex`. It is build upon the datetime2 package.

Contents

1. Usage **1**
1.1. Load the whole `stmdate` package . . . 1
1.1.1. Description . . . 1
1.1.2. Options . . . 1
1.2. `stmdatestyles` . . . 2
1.2.1. Description . . . 2
1.2.2. Styles . . . 2
1.3. `stmdatecommands` . . . 2
1.3.1. Description . . . 2
1.3.2. Command `\formatdate` . . . 2

A. The code **3**
A.1. `stmdate.sty` . . . 3
A.2. `stmdatebase.sty` . . . 5
A.3. `stmdatecommands.sty` . . . 7
A.4. `stmdatestyles.sty` . . . 9

1. Usage

1.1. Load the whole `stmdate` package

1.1.1. Description

This is an interface package which loads date styles and commands commonly required throughout document creation.

By default the package loads

- `stmdatebase.sty`
- `stmdatecommands.sty`
- `stmdatestyles.sty`

See subsubsection 1.1.2 for options to change the default package behavior.

1.1.2. Options

Option *styles* This is a boolean option. Expected values are either `true` or `false`. It controls whether to load the predefined date styles.

```
\usepackage[styles=true|false]{stmdate}
```

`styles=true` is the default. It is used in case `styles=false` is not set explicitly.

Option *commands* This is a boolean option. Expected values are either `true` or `false`. It enables and disables the loading of specific date commands.

```
\usepackage[commands=true|false]{stmdate}
```

`commands=true` is the default. It is used in case `commands=false` is not set explicitly.

1.2. `stmdatestyles`

1.2.1. Description

This package contains styles for displaying dates in different formats. These can be used by commands from the underlying datetime2 package, e.g. with the style definitions from subsubsection 1.2.2

```
\DTMsetdatestyle{$STYLENAME$}\DTMtoday
```

or use the convenience commands from subsection 1.3.

1.2.2. Styles

These are the date styles and the respective output.

`versiondatestyle`	20260226

1.3. `stmdatecommands`

1.3.1. Description

These are commands to manipulate dates and their display.

1.3.2. Command `\formatdate`

Examples

`\formatdate[versiondatestyle]{\DTMToday}`	20260226
`\formatdate{\today}`	20260226
`\formatdate[versiondatestyle]{\today}`	20260226
`\formatdate{2019}[2][3]`	20190203
`\formatdate[versiondatestyle]{2019}[2][3]`	20190203
`\formatdate[versiondatestyle]{2019}[11][3]`	20191103
`\formatdate{2019}[2]`	20190201
`\formatdate[versiondatestyle]{2019}[2]`	20190201
`\formatdate{2019}[2][]`	20190201
`\formatdate[versiondatestyle]{2019}[2][]`	20190201
`\formatdate{2019}[][]`	20190101
`\formatdate[versiondatestyle]{2019}[][]`	20190101

A. The code

A.1. stmdate.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes date definitions
% Based upon the datetime2 package:
%   https://ctan.org/pkg/datetime2
%
% Usage
%  - Preamble:
%    - \usepackage{stmdate}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                 __/|__
%                                /_/_/_/
%            www.dlr.de/sy/en      |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                            %
```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Declare that this style file requires at least LaTeX version 2e.
\NeedsTeXFormat{LaTeX2e}

% Provide the name of your page, the date it was last updated, and a
    comment about what it's used for
\ProvidesPackage{stmdate}[2023/02/12 STMs custom LaTeX date definitions]

% ---------------------------
% Options
% ---------------------------

% Options package
\@ifpackageloaded{kvoptions}{}{\RequirePackage{kvoptions}}%

% Option group
\SetupKeyvalOptions{%
  family=stmdate,%
  prefix=stmdate@,%
  setkeys=\kvsetkeys,%
}

% Styles
\DeclareBoolOption[true]{commands}

% Styles
\DeclareBoolOption[true]{styles}

% Process options
\ProcessKeyvalOptions{stmdate}

% ---------------------------
% Modules
% ---------------------------

% Load the base package
\@ifpackageloaded{stmdatebase}{}{%
  \RequirePackage{stmdatebase}%
}%

% Commands
\ifstmdate@commands
  \RequirePackage{stmdatecommands}
```

```
\fi

% Styles
\ifstmdate@styles
  \RequirePackage{stmdatestyles}
\fi

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it                          %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can stop reading
    this file. LaTeX will ignore anything after this line.
\endinput
```

A.2. stmdatebase.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes date definitions
% Based upon the datetime2 package:
%   https://ctan.org/pkg/datetime2
%
% Usage
%  - Preamble:
%    - \usepackage{stmdatebase}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                  __/|__
%                                 /_/_/_/
%            www.dlr.de/sy/en       |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                            %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
28
29 % Declare that this style file requires at least LaTeX version 2e.
30 \NeedsTeXFormat{LaTeX2e}
31
32 % Provide the name of your page, the date it was last updated, and a
       comment about what it's used for
33 \ProvidesPackage{stmdatebase}[2023/02/12 STMs custom LaTeX date
       definitions]
34
35 % ---------------------------
36 % Package
37 % ---------------------------
38
39 \@ifpackageloaded{datetime2}{}{\RequirePackage[style=iso]{datetime2}}%
40
41 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
42 % That's it                      %
43 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
44
45 % Finally, we'll use \endinput to indicate that LaTeX can stop reading
       this file. LaTeX will ignore anything after this line.
46 \endinput
```

A.3. stmdatecommands.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                              %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes date definitions
% Based upon the datetime2 package:
%   https://ctan.org/pkg/datetime2
%
% Usage
%  - Preamble:
%    - \usepackage{stmdate}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                 __/|__
%                                /_/_/_/
%            www.dlr.de/sy/en      |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Declare that this style file requires at least LaTeX version 2e.
\NeedsTeXFormat{LaTeX2e}

% Provide the name of your page, the date it was last updated, and a
    comment about what it's used for
\ProvidesPackage{stmdatecommands}[2023/02/12 STMs custom LaTeX date
    commands definitions]

% ---------------------------
% Package
% ---------------------------

\@ifpackageloaded{datetime2}{}{\RequirePackage[style=iso]{datetime2}}%
\@ifpackageloaded{stmdatestyles}{}{\RequirePackage{stmdatestyles}}%
```

```
\@ifpackageloaded{xparse}{}{\RequirePackage{xparse}}%
\@ifpackageloaded{ifmtarg}{}{\RequirePackage{ifmtarg}}%

% ----------------------------
% Commands
% ----------------------------

% https://tex.stackexchange.com/a/33753
\DeclareDocumentCommand{\formatdate}{%
  O{versiondatestyle}%style - optional, default in brackets
  m% date/year
  o% month - optional
  o% day - optional
}{%
  \DTMsetdatestyle{#1}% The first (optional) argument is the style
  \IfNoValueTF{#3}% There is just one argument defined after the style - the date
    {%
      \@ifmtarg{#2}{}{#2}%
    }%
    {%
      \DTMdate{%
        \@ifmtarg{#2}{1}{#2}
        -%
        \IfNoValueTF{#3}{1}{\@ifmtarg{#3}{1}{#3}}%
        -%
        \IfNoValueTF{#4}{1}{\@ifmtarg{#4}{1}{#4}}%
      }%
    }%
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it                          %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can stop reading this file. LaTeX will ignore anything after this line.
\endinput
```

A.4. stmdatestyles.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                              %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes date definitions
% Based upon the datetime2 package:
%   https://ctan.org/pkg/datetime2
%
% Usage
%  - Preamble:
%    - \usepackage{stmdate}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                 __/|__
%                                /_/_/_/
%            www.dlr.de/sy/en      |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Declare that this style file requires at least LaTeX version 2e.
\NeedsTeXFormat{LaTeX2e}

% Provide the name of your page, the date it was last updated, and a
    comment about what it's used for
\ProvidesPackage{stmdatestyles}[2023/02/12 STMs custom LaTeX date style
    definitions]

% ---------------------------
% Package
% ---------------------------

\@ifpackageloaded{datetime2}{}{\RequirePackage[style=iso]{datetime2}}%

```

```
% ---------------------------
% Styles
% ---------------------------

\DTMnewdatestyle{versiondatestyle}{%
  %\renewcommand{\DTMdisplaydate}[4]{\number##1\number##2\number##3}%
  \renewcommand{\DTMdisplaydate}[4]{\number##1\DTMtwodigits##2\
    DTMtwodigits##3}%
  \renewcommand{\DTMDisplaydate}{\DTMdisplaydate}%
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it                       %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can stop reading
    this file. LaTeX will ignore anything after this line.
\endinput
```