stmlistings package description

Copyright © 2026 DLR SY STM

v20260226

Martin Rädel

2026-02-26

These are the listings definitions for `stmlatex`. It is build upon the listings package.

Contents

1. Usage **1**
1.1. Load the whole `stmlistings` package . . . 1
1.1.1. Description . . . 1
1.1.2. Options . . . 1
1.2. `stmlistingsstyles` . . . 2
1.2.1. Description . . . 2
1.2.2. Styles . . . 2
1.3. `stmlistingscommands` . . . 2
1.3.1. Description . . . 2
1.3.2. Command `\inlinecode` . . . 2

A. The code **4**
A.1. `stmlistings.sty` . . . 4
A.2. `stmlistingscommands.sty` . . . 7
A.3. `stmlistingsenvironments.sty` . . . 9
A.4. `stmlistingsstyles.sty` . . . 11

1. Usage

1.1. Load the whole `stmlistings` package

1.1.1. Description

This is an interface package which loads listings styles and commands commonly required throughout document creation.

By default the package loads

- `stmlistingscommands.sty`
- `stmlistingsenvironments.sty`
- `stmlistingsstyles.sty`

See subsubsection 1.1.2 for options to change the default package behavior.

1.1.2. Options

Option *styles* This is a boolean option. Expected values are either `true` or `false`. It controls whether to load the predefined listings styles.

```
\usepackage[styles=true|false]{stmlistings}
```

`styles=true` is the default. It is used in case `styles=false` is not set explicitly.

Option *commands* This is a boolean option. Expected values are either `true` or `false`. It enables and disables the loading of specific listings commands.

```
\usepackage[commands=true|false]{stmlistings}
```

`commands=true` is the default. It is used in case `commands=false` is not set explicitly.

Option *environments* This is a boolean option. Expected values are either `true` or `false`. It enables and disables the loading of specific listings environments.

```
\usepackage[environments=true|false]{stmlistings}
```

`commands=true` is the default. It is used in case `commands=false` is not set explicitly.

1.2. `stmlistingsstyles`

1.2.1. Description

1.2.2. Styles

1.3. `stmlistingscommands`

1.3.1. Description

These are commands and shortcuts for listings.

1.3.2. Command `\inlinecode`

Description Create an code snippet in the current line.

Usage The command arguments are

Nr.	Entity	Type	Default	Description
1	Delimiter	optional	`+`	Defines beginning and end of the code snippet.
2	Color	optional	`verbgraycolor`	Background color
3	Style	optional	`inlinecodestyle`	Listings style
3	Content	mandatory		Code

Examples

- `\inlinecode{Example}`: This is an `Example` for an in line code definition.
- `\inlinecode[+][verbgraycolor][inlinecodestyle]{Example}`: This is an `Example` for an in line code definition.
- `\inlinecode[+][green]{Example}`: This is an `Example` for an in line code definition.
- `\inlinecode[|]{1+2}`: Example for a different delimiter `1+2` in case the default delimiter is used in the expression.

A. The code

A.1. stmlistings.sty

```
%%%
```

```
\@ifpackageloaded{listings}{}{\RequirePackage{listings}}%
\@ifpackageloaded{stmcolors}{}{\RequirePackage{stmcolors}}%
\@ifpackageloaded{kvoptions}{}{\RequirePackage{kvoptions}}%

% ---------------------------
% Options
% ---------------------------

\SetupKeyvalOptions{%
  family=stmlistings,%
  prefix=stmlistings@,%
  setkeys=\kvsetkeys,%
}

% Styles
\DeclareBoolOption[true]{styles}

% Environments
\DeclareBoolOption[true]{environments}

% Commands
\DeclareBoolOption[true]{commands}

% Process options
\ProcessKeyvalOptions{stmlistings}

% ---------------------------
% Modules
% ---------------------------

% Styles
\ifstmlistings@styles
  \@ifpackageloaded{stmlistingsstyles}{}{\RequirePackage{
    stmlistingsstyles}}%
\fi

% Environments
\ifstmlistings@environments
  \@ifpackageloaded{stmlistingsenvironments}{}{\RequirePackage{
    stmlistingsenvironments}}%
\fi

% Commands
\ifstmlistings@commands
```

```
  \@ifpackageloaded{stmlistingscommands}{}{\RequirePackage{
    stmlistingscommands}}%
\fi

% --------------------------
% Preferences
% --------------------------

% http://tex.stackexchange.com/a/64845/44634
\makeatletter
\@ifundefined{KOMAClassName}
  {% true -> no KOMA class
    %
  }%
  {% false -> KOMA class
    \newcaptionname{english}{\lstlistlistingname}{List of \lstlistingname
    s}%
    \newcaptionname{ngerman}{\lstlistlistingname}{Quelltextverzeichnis}%
  }%
\makeatother

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it                         %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can stop reading
    this file. LaTeX will ignore anything after this line.
\endinput
```

A.2. stmlistingscommands.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes listings definitions.
% Based upon the listings package:
%   https://ctan.org/pkg/listings
%
% Usage
%  - Preamble:
%    - \usepackage{stmlistingscommands}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                 __/|__
%                                /_/_/_/
%            www.dlr.de/sy/en      |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                            %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Declare that this style file requires at least LaTeX version 2e.
\NeedsTeXFormat{LaTeX2e}

% Provide the name of your page, the date it was last updated, and a
    comment about what it's used for
\ProvidesPackage{stmlistingscommands}[2023/02/12 STMs custom LaTeX
    listings definitions]

% ---------------------------
% Package
% ---------------------------

\@ifpackageloaded{listings}{}{\RequirePackage{listings}}%
\@ifpackageloaded{stmcolors}{}{\RequirePackage{stmcolors}}%
```

```
41 \@ifpackageloaded{stmlistingsstyles}{}{\RequirePackage{stmlistingsstyles
       }}%
42 \@ifpackageloaded{xparse}{}{\RequirePackage{xparse}}%
43 \@ifpackageloaded{ifmtarg}{}{\RequirePackage{ifmtarg}}%
44
45 % ----------------------------
46 % Commands
47 % ----------------------------
48
49 \newcommand*{\lstcomment}[1]{\hfill\makebox[5.25cm][l]{#1}}%
50
51
52 % https://tex.stackexchange.com/a/33753
53 \DeclareDocumentCommand{\inlinecode}{%
54   O{+}% Delimiters - optional, default in brackets
55   O{verbgraycolor}% Color for the colorbox - optional, default in
       brackets
56   O{inlinecodestyle}% Style definition for code - optional, default in
       brackets
57   m% content
58 }{%
59   \colorbox{#2}{\lstinline[style=#3]#1#4#1}%
60 }
61
62 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
63 % That's it                          %
64 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
65
66 % Finally, we'll use \endinput to indicate that LaTeX can stop reading
       this file. LaTeX will ignore anything after this line.
67 \endinput
```

A.3. stmlistingsenvironments.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes listings definitions.
% Based upon the listings package:
%   https://ctan.org/pkg/listings
%
% Usage
%  - Preamble:
%    - \usepackage{stmlistingsenvironments}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                 __/|__
%                                /_/_/_/
%            www.dlr.de/sy/en      |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                            %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Declare that this style file requires at least LaTeX version 2e.
\NeedsTeXFormat{LaTeX2e}

% Provide the name of your page, the date it was last updated, and a
    comment about what it's used for
\ProvidesPackage{stmlistingsenvironments}[2023/02/12 STMs custom LaTeX
    listings definitions]

% ---------------------------
% Package
% ---------------------------

\@ifpackageloaded{listings}{%
%
```

```
}{%
  \RequirePackage{listings}
}%

\@ifpackageloaded{stmcolors}{%
%
}{%
  \RequirePackage{stmcolors}
}%

% ----------------------------
% Styles
% ----------------------------

\@ifpackageloaded{stmlistingsstyles}{%
%
}{%
  \RequirePackage{stmlistingsstyles}
}%

% ----------------------------
% Environments
% ----------------------------

\lstnewenvironment{code}{%
  \lstset{style=scriptstyle}
}{}

\lstnewenvironment{texcode}{%
  \lstset{style=texcodestyle}
}{}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it                          %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can stop reading
    this file. LaTeX will ignore anything after this line.
\endinput
```

A.4. stmlistingsstyles.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes listings definitions.
% Based upon the listings package:
%   https://ctan.org/pkg/listings
%
% Usage
%  - Preamble:
%    - \usepackage{stmlistingsstyles}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                 __/|__
%                                /_/_/_/
%            www.dlr.de/sy/en      |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                            %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Declare that this style file requires at least LaTeX version 2e.
\NeedsTeXFormat{LaTeX2e}

% Provide the name of your page, the date it was last updated, and a
    comment about what it's used for
\ProvidesPackage{stmlistingsstyles}[2023/02/12 STMs custom LaTeX listings
     style definitions]

% ---------------------------
% Package
% ---------------------------

\@ifpackageloaded{listings}{}{\RequirePackage{listings}}%
\@ifpackageloaded{stmcolors}{}{\RequirePackage{stmcolors}}%
```

```
41
42 % ---------------------------
43 % Styles
44 % ---------------------------
45
46 \lstdefinestyle{basestyle}{
47   backgroundcolor=\color{boxgraycolor},
48   basicstyle=\ttfamily,
49   columns=fullflexible,
50 }
51
52 \lstdefinestyle{inlinecodestyle}{
53   backgroundcolor=\color{boxgraycolor},
54   basicstyle=\ttfamily,
55 }
56
57 \lstdefinestyle{scriptstyle}{
58   style=basestyle,
59   escapechar=\%,% char to escape out of listings and back to LaTeX
60 }
61
62 \lstdefinestyle{texcodestyle}{
63   language=[LaTeX]TeX,
64   style=basestyle,
65   breaklines=true,
66   commentstyle=\color{codecommentgraycolor},
67 }
68
69 \lstdefinestyle{inlinetexcodestyle}{
70   language=[LaTeX]TeX,
71   style=basestyle,
72   upquote=true,% Important for copy-paste
73 }
74
75 \lstdefinestyle{texpackagedocstyle}{
76   style=texcodestyle,%
77   numbers=left,%
78   keepspaces=true,%
79 }
80
81 \lstdefinestyle{javacodestyle}{
82   style=basestyle,
83   basicstyle=\linespread{0.8}\ttfamily,
84   language=Java,
```

```
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it                          %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can stop reading
    this file. LaTeX will ignore anything after this line.
\endinput
```