stmbibliography package description

Copyright © 2025 DLR SY STM

v20250919

Martin Rädel

2025-09-19

This package offers some default preferences for the display of bibliographies. It is build upon the biblatex package [1].

Contents

1. Usage - in the preamble **1**
1.1. Load the whole `stmbibliography` package 1
1.1.1. Description 1
1.1.2. Options 2

2. Usage - in the document **2**

3. Styles **2**
3.1. `default` 2
3.2. `stmdefault` 2

References **2**

Index **3**

A. The code **4**
A.1. `stmbibliography.sty` 4

1. Usage - in the preamble

1.1. Load the whole `stmbibliography` package

1.1.1. Description

This is an interface package which loads the base package and the style choice.

1.1.2. Options

Option *style* This is a string option. A list of possible values is shown in section 3.

```
\usepackage[style=stmdefault]{stmbibliographystyles}
```

`style=stmdefault` is the default. It is used in case no other style is set explicitly.

2. Usage - in the document

To assure that the bibliography is added to the table of contents for all base classes, use `\printbibliography[heading=bibintoc]` instead of a simple `\printbibliography`.

3. Styles

There are different predefined styles available to format your hypertext.

3.1. `default`

This loads the default style from the underlying base package and does not apply individual styles.

3.2. `stmdefault`

This loads the default preferences for STMLaTeX based documents.

References

[1] Philip Kime, Moritz Wemheuer, and Philipp Lehman. *The biblatex Package*. 3.14 2019-12-01. 2019. URL: https://ctan.org/pkg/biblatex.

Index

Style, 2
    default, 2
stmdefault, 2

A. The code

A.1. stmbibliography.sty

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Header                             %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%
% This file includes hyperref setup
% Based upon the biblatex package:
%   https://ctan.org/pkg/biblatex
%
% Usage
%  - Preamble:
%    - \usepackage{stmbibliography}
%
% Revisions: 2019-10-27 Martin Raedel <martin.raedel@dlr.de>
%                       Initial draft
%
% Contact:   Martin Raedel,  martin.raedel@dlr.de
%            DLR Lightweight Systems
%
%                                 __/|__
%                                /_/_/_/
%            www.dlr.de/sy/en      |/ DLR
%
% Copyright (C) 2019-... DLR Lightweight Systems
%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Content                            %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Declare that this style file requires at least LaTeX version 2e.
\NeedsTeXFormat{LaTeX2e}

% Provide the name of your page, the date it was last updated, and a
    comment about what it's used for
\ProvidesPackage{stmbibliography}[2023/02/12 STMs bibliography
    definitions]

% ---------------------------
% Options
% ---------------------------

```

```
% For options
\@ifpackageloaded{kvoptions}{}{\RequirePackage{kvoptions}}%

% Option group
\SetupKeyvalOptions{%
  family=stmbibliography,%
  prefix=stmbibliography@,%
  setkeys=\kvsetkeys,%
}

% Apply style name
\DeclareStringOption[stmdefault]{style}

% Process options
\ProcessKeyvalOptions{stmbibliography}

% ----------------------------
% Modules
% ----------------------------

\@ifpackageloaded{babel}{}{\RequirePackage{csquotes}}
\@ifpackageloaded{polyglossia}{}{\RequirePackage{csquotes}}

\@namedef{stmbibliography@style@default}{%
  \RequirePackage{biblatex}
}

\@namedef{stmbibliography@style@stmdefault}{%

  % These options must be set at the time of \usepackage
  % http://mirrors.ctan.org/macros/latex/contrib/biblatex/doc/biblatex.
    pdf#subsubsection.3.1.1
  \PassOptionsToPackage{%
    backend=biber,%
    style=numeric-comp,%
  }{biblatex}

  % Load the package
  \RequirePackage{biblatex}

  % Preamble options
  % http://mirrors.ctan.org/macros/latex/contrib/biblatex/doc/biblatex.
    pdf#subsubsection.3.1.2
  \ExecuteBibliographyOptions{%
```

```
    sorting=none,%
  }
}

% Evaluate option settings
% https://tex.stackexchange.com/a/249102
\newcommand*{\stmbibliography@evaluate}[1]{%
  % Check, if option value in \<prefix>@<option> exists
  \@ifundefined{stmbibliography@#1}{%
    % Should not happen
    \PackageError{stmbibliography}{Evaluating unknown option `#1'}\@ehc
  }{%
    % Check, if there is an implementation for the value of the option
    % in macro \<prefix>@<option>@<value>
    \@ifundefined{stmbibliography@#1@\csname stmbibliography@#1\endcsname
    }{%
      \PackageError{stmbibliography}{%
        Unknown option setting: #1=%
        \csname stmbibliography@#1\endcsname
      }\@ehc
    }{%
      % Call the implementation for the value
      \csname stmbibliography@#1@%
              \csname stmbibliography@#1\endcsname
      \endcsname
      \relax
    }%
  }%
}

\stmbibliography@evaluate{style}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That's it                          %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% Finally, we'll use \endinput to indicate that LaTeX can stop reading
    this file. LaTeX will ignore anything after this line.
\endinput
```