COMPENG 4DM4 Assignment 1 Report

Aaron Pinto pintoa9 Raeed Hassan hassam41

November 9, 2022

Assumptions


In addition to the assumptions stated in the assignment, the following assumptions are made for all parts of the assignment:

- FP-ADD unit 3-stage pipeline labeled as A1, A2, A3
- FP-MULT unit 6-stage pipeline labeled as FM1, FM2, FM3, FM4, FM5, FM6
- Full forwarding of data from WB stage to any stage
- assume dual-ported memory that allows simultaneous read and/or write on two ports
- we can perform 2 write-backs per clock cycle

Part (a): DAXPY Loop, No Unrolling, with No Scheduling

The timing diagram is shown in Figure 1. The timing diagram is also submitted as 4DM4-Assignment-#2a-Basic-Timing-Table.xlsx. The performance, or MFLOP rating, of the implementation with a 3 GHz clock is $(3 \text{ GHz})^*(2 \text{ FLOP}/19 \text{ cc}) = 315.8 \text{ MFLOP/s}$.

Figure 1: Timing Diagram for DAXPY Loop (No Unrolling, No Scheduling)



Part (b): DAXPY Loop, No Unrolling, with Scheduling

The timing diagram is shown in Figure 2. The timing diagram is also included in the submission as 4DM4-Assignment-#2b-Basic-Timing-Table.xlsx. The performance, or MFLOP rating, of the implementation with a 3 GHz clock is $(3 \text{ GHz})^*(2 \text{ FLOP}/13 \text{ cc}) = 461.5 \text{ MFLOP/s}$.

Figure 2: Timing Diagram for DAXPY Loop (No Unrolling, Scheduling)

Instru	iction				Clock Cyc	le														Comment
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	
loop: L.D	F2, 0(R1)	F1	F2	ID	EX	M1	M2*	WB												forward F2 (from M2* to *FM1) in cc6
L.D	F6, 0(R2)		F1	F2	ID	EX	M1	M2	WB											
MULT.D	F4, F2, F0			F1	F2	ID	stall	*FM1	FM2	FM3	FM4	FM5	FM6**	WB						forward F4 (FM6** to **A1) in cc12
DADDUI	R1, R1, #8				F1	F2	stall	ID	EX*	WB										forward R1 (EX* to *EX) in cc8
DSGTUI	R3, R1, done					F1	stall	F2	ID	*EX	WB									
ADD.D	F6, F4, F6							F1	F2	ID	stall	stall	stall	**A1	A2	A3	WB			
BEQZ	R3, loop								F1	F2	stall	stall	stall	ID						
S.D	0(R2), F6									F1	stall	stall	stall	F2	ID	EX	M1	M2	WB	
DADDUI	R2, R2, #8													F1	F2	ID	EX	WB		

Part (c): DAXPY Loop, With Unrolling, with no Scheduling

The compressed timing diagram is shown in Table 1. The compressed timing diagram is also included in the submission as 4DM4-Assignment-#2c-Compressed-Timing-Table-single-issue.xlsx. The performance, or MFLOP rating, of the implementation with a 3 GHz clock is $(3 \text{ GHz})^*(8 \text{ FLOP}/61 \text{ cc}) = 393.4 \text{ MFLOP/s}$.

Table 1: Compressed Timing Diagram for DAXPY Loop (Unrolling, No Scheduling)

Instruction Slot #1	IF (F1,F2)	ID	EX (Int, FP)	MEM (M1,M2)	WB	Comment/Hazard
loop: L.D F2, 0(R1)	1,2	3	4	5,6*	7	forward F2 (from M2* to *FM1) in cc6
- ` ` ` `			-	0,0	-	forward F4 (FM6** to **A1) in cc12
MULT.D F4, F2, F0	2,3	4	*7,8,9,10,11,12**		13	stall on FM1 waiting for F2
L.D F6, 0(R2)	3,4	7	8	9.10	11	Stair on 1 M1 waiting for 12
E.D 1 0, 0(102)	5,1	'	<u> </u>	0,10		forward F6 (A3* to *M1) in cc15
ADD.D F6, F4, F6	5,7	11	**13,14,15*		16	stall on ID waiting for F6
1100.0 10, 14, 10	0,1	11	10,14,10		10	stall on A1 waiting for F4
S.D 0(R2), F6	7,11	13	14	*16,17	18	stall on M1 waiting for F6
DADDUI R1, R1, #8	11,13	14	16	10,17	17	Stair on WT waiting for Fo
DADDUI R2, R2, #8	13,14	16	17		18	
L.D F2, 0(R1)	14,16	17	18	19,20*	21	forward F2 (from M2* to *FM1) in cc20
L.D F 2, U(R1)	14,10	11	10	19,20		forward F4 (FM6** to **A1) in cc26
MULT.D F4, F2, F0	16,17	18	*21,22,23,24,25,26**		27	stall on FM1 waiting for F2
L D DC 0(Da)	17.10	21	22	02.04	05	stall on FM1 waiting for F2
L.D F6, 0(R2)	17,18	21	22	23,24	25	f 1 Dc (A9* + *M1): 00
ABB B Bo Bo Bo	40.04	~~	****		00	forward F6 (A3* to *M1) in cc29
ADD.D F6, F4, F6	18,21	25	**27,28,29*		30	stall on ID waiting for F6
G.D. o/Do), Fo	24.25		20	*20.24	22	stall on A1 waiting for F4
S.D 0(R2), F6	21,25	27	28	*30,31	32	stall on M1 waiting for F6
DADDUI R1, R1, #8	25,27	28	30		31	
DADDUI R2, R2, #8	27,28	30	31		32	
L.D F2, 0(R1)	28,30	31	32	33,34*	35	forward F2 (from M2* to *FM1) in cc34
MULT.D F4, F2, F0	30,31	32	*35,36,37,38,39,40**		41	forward F4 (FM6** to **A1) in cc40
		_				stall on FM1 waiting for F2
L.D F6, 0(R2)	31,32	35	36	37,38	39	
						forward F6 (A3* to *M1) in cc43
ADD.D F6, F4, F6	$32,\!35$	39	**41,42,43*		44	stall on ID waiting for F6
						stall on A1 waiting for F4
S.D 0(R2), F6	35,39	41	42	*44,45	46	stall on M1 waiting for F6
DADDUI R1, R1, #8	39,41	42	44		45	
DADDUI R2, R2, #8	41,42	44	45		46	
L.D F2, 0(R1)	42,44	45	46	47,48*	49	forward F2 (from M2* to *FM1) in cc48
MULT.D F4, F2, F0	44,45	46	*49,50,51,52,53,54**		55	forward F4 (FM6** to **A1) in cc54
MOLI.D F4, F2, F0	44,40	40	49,50,51,52,55,54		55	stall on FM1 waiting for F2
L.D F6, 0(R2)	45,46	49	50	51,52	53	
						forward F6 (A3* to *M1) in cc57
ADD.D F6, F4, F6	46,49	53	**55,56,57*		58	stall on ID waiting for F6
						stall on A1 waiting for F4
S.D 0(R2), F6	49,53	55	56	*58,59	60	stall on M1 waiting for F6
DADDUI R1, R1, #8	53,55	56	58		59	-
DADDUI R2, R2, #8	55,56	58	59		60	
DSGTUI R3, R1, done	56,58	59	60*		61	forward R3 (EX* to *ID) in cc60
BEQZ R3, loop	58,59	*61				stall on ID waiting for R3
NO-OP	59,61					branch-delay slot
NO-OP	61,62					branch-delay slot
51	01,02	l				22207 2200

Part (d): DAXPY Loop, With Unrolling, and with Scheduling

The compressed timing diagram is shown in Table 2. The compressed timing diagram is also included in the submission as 4DM4-Assignment-#2d-Compressed-Timing-Table-single-

issue.xlsx. The performance, or MFLOP rating, of the implementation with a 3 GHz clock is (3 GHz)*(8 FLOP/24 cc) = 1000 MFLOP/s.

Table 2: Compressed Timing Diagram for DAXPY Loop (Unrolling, Scheduling)

Instruction Slot #1	IF (F1,F2)	ID	EX (Int, FP)	MEM (M1,M2)	WB	Comment/Hazard
loop: L.D F1, 0(R1)	1,2	3	4	5,6	7	
L.D F4, 8(R1)	2,3	4	5	6,7	8	
L.D F7, 16(R1)	3,4	5	6	7,8	9	
L.D F10, 24(R1)	4,5	6	7	8,9	10	
L.D F3, 0(R2)	5,6	7	8	9,10	11	
L.D F6, 8(R2)	6,7	8	9	10,11	12	
L.D F9, 16(R2)	7,8	9	10	11,12	13	
L.D F12, 24(R2)	8,9	10	11	12,13	14	
MULT.D F2, F1, F0	9,10	11	12,13,14,15,16,17*		18	forward F2 (from FM6* to *A1) in cc17
MULT.D F5, F4, F0	10,11	12	13,14,15,16,17,18*		19	forward F5 (from FM6* to *A1) in cc18
MULT.D F8, F7, F0	11,12	13	14,15,16,17,18,19*		20	forward F8 (from FM6* to *A1) in cc19
MULT.D F11, F10, F0	12,13	14	15,16,17,18,19,20*		21	forward F11 (from FM6* to *A1) in cc20
DADDUI R1, R1, #32	13,14	15	16*		17	forward R1 (from EX* to *EX) in cc16
DSGTUI R3, R1, done	14,15	16	*17		18	
ADD.D F3, F2, F3	15,16	17	*18,19,20		21	
ADD.D F6, F5, F6	16,17	18	*19,20,21		22	
ADD.D F9, F8, F9	17,18	19	*20,21,22		23	
ADD.D F12, F11, F12	18,19	20	*21,22,23		24	
S.D 0(R2), F3	19,20	21	22	23,24	25	
S.D 8(R2), F6	20,21	22	23	24,25	26	
S.D 16(R2), F9	21,22	23	24	25,26	27	
BEQZ R3, loop	22,23	24				
S.D 24(R2), F12	23,24	25	26	27,28	29	
DADDUI R2, R2, #32	24,25	26	27		28	

Part (e): DAXPY Loop, With Unrolling and Scheduling. On Dual-Issue Machine

The compressed timing diagram is shown in Table 3. The compressed timing diagram is also included in the submission as 4DM4-Assignment-#2e-Compressed-Timing-Table-dualissue.xlsx. The performance, or MFLOP rating, of the implementation with a 3 GHz clock is $(3 \text{ GHz})^*(8 \text{ FLOP}/16 \text{ cc}) = 1500 \text{ MFLOP/s}$.

Table 3: Compressed Timing Diagram for DAXPY Loop (Unrolling, Scheduling, Dual Issue)

Instruction Slot #1	Instruction Slot #2	IF	ID	EX1	MEM1	WB1	EX2	MEM2	WB2	Comment/Hazard
loop: L.D F1, 0(R1)	NO-OP	1,2	3	4	5,6*	7	-	-	-	forward F1 (M2* to *FM1) in cc6
L.D F4, 8(R1)	NO-OP	2,3	4	5	6,7*	8	-	-	-	forward F4 (M2* to *FM1) in cc7
L.D F7, 16(R1)	NO-OP	3,4	5	6	7,8*	9	-	-	-	forward F7 (M2* to *FM1) in cc8
L.D F10, 24(R1)	MULT.D F2, F1, F0	4.5	6	7	8.9*	10	*7-12**		13	forward F10 (M2* to *FM1) in cc9
	, ,	4,0	0	'	0,5	10			10	forward F2 (FM6** to **A1) in cc12
L.D F3, 0(R2)	MULT.D F5, F4, F0	5,6	7	8	9,10	11	*8-13**		14	forward F5 (FM6** to **A1) in cc13
L.D F6, 8(R2)	MULT.D F8, F7, F0	6,7	8	9	10,11	12	*9-14**		15	forward F8 (FM6** to **A1) in cc14
L.D F9, 16(R2)	MULT.D F11, F10, F0	7,8	9	10	11,12	13	*10-15**		16	forward F11 (FM6** to **A1) in cc15
L.D F12, 24(R2)	DADDUI R1, R1, #32	8,9	10	11	12,13	14	11*		11	forward R1 (EX* to *EX) in cc11
DADDUI R2, R2, #32	DSGTUI R3, R1, done	9,10	11	12		13	*12		12	
NO-OP	ADD.D F3, F2, F3	10,11	12	-	-	-	**13-15*		16	forward F3 (A3* to *M1) in cc15
NO-OP	ADD.D F6, F5, F6	11,12	13	-	-	-	**14-16*		17	forward F6 (A3* to *M1) in cc16
S.D -32(R2), F3	ADD.D F9, F8, F9	12,13	14	15	*16,17	18	**15-17		18*	forward F9 (WB* to *M1) in cc18
S.D -24(R2), F6	ADD.D F12, F11, F12	13,14	15	16	*17,18	19	**16-18		19*	forward F12 (WB* to *M1) in cc19
BEQZ R3, loop	NO-OP	14,15	16				-	-	-	
S.D -16(R2), F9	NO-OP	15,16	17	18	*19,20	21	-	-	-	
S.D -8(R2), F12	NO-OP	16,17	18	19	*20,21	22	-	-	-	