

COMPENG 4DM4 Assignment 1 Report

Aaron Pinto
pintoa9

Raeed Hassan
hassam41

October 24, 2022

Exercise Part (A) - The 7-stage RISC Pipeline

(A1) There is a 2 clock-cycle stall on LOAD instructions when the instruction following a LOAD instruction uses the value being loaded. The timing diagram can be seen in Figure 1.

(A2) The number of branch-delay-slots following a BRANCH instruction will be 2 clock cycles in both cases considered:

1. If the value R0 being tested is available in a register at the start of the ID stage, then the “branch is resolved” in the ID stage - the ID stage will compare R0 with zero, and generate a “Take-Branch” signal which is sent back to the IF1 stage from the ID stage in clock-cycle 3. In this case, 2 branch-delay-slots will occur, as seen in Figure 2. The compiler can attempt to fill the ”BRANCH+1” and ”BRANCH+2” branch delay slots with useful instructions, otherwise fill with a NO-OP.

2. If the value R0 is being computed in the EX stage, by the previous instruction, and R0 needs to be forwarded to the ID stage, then we do not “stretch the clock” to allow R0 to be tested in the ID stage in the same clock cycle. The system will “stall” the BNEZ for 1 extra clock cycle, waiting for R0 to be computed and forwarded to the ID stage. In this case, 2 branch-delay-slots will occur, as seen in Figure 3. The compiler can attempt to fill the ”BRANCH+1” and ”BRANCH+2” branch delay slots with useful instructions, otherwise fill with a NO-OP.

	Clock Cycle														
Instruction	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
LW R0,0(R1)	IF1	IF2	ID	EX	MEM1	MEM2*	WB				*forward R0 (MEM2* to *EX) in cc6				
ADD R3,R0,R2		IF1	IF2	ID	stall	stall	*EX	MEM1	MEM2	WB					
LOAD+2			IF1	IF2	stall	stall	ID	EX	MEM1	MEM2	WB				
LOAD+3				IF1	stall	stall	IF2	ID	EX	MEM1	MEM2				
LOAD+4					stall	stall	IF1	IF2	ID	EX	MEM1	MEM2			

Figure 1: Timing Diagram for A1

	Clock Cycle											
Instruction	1	2	3	4	5	6	7	8	9	10	11	12
BNEZ R0, loop	IF1	IF2	ID*	EX	MEM1	MEM2	WB		*forward R0 (ID* to *IF1) in cc3			
BRANCH+1		IF1	IF2	ID	EX	MEM1	MEM2	WB				
BRANCH+2			IF1	IF2	ID	EX	MEM1	MEM2	WB			
BRANCH TARGET				*IF1	IF2	ID	EX	MEM1	MEM2	WB		

Figure 2: Timing Diagram for A2 Case 1

	Clock Cycle												
Instruction	1	2	3	4	5	6	7	8	9	10	11	12	13
previous instruction	IF1	IF2	ID	EX*	MEM1	MEM2	WB	*forward R0 (EX* to *ID) in cc4					
BNEZ R0, loop		IF1	IF2	stall	*ID**	EX	MEM1	MEM2	WB	**forward R0 (ID** to **IF) in cc5			
BRANCH+1			IF1	stall	IF2	ID	EX	MEM1	MEM2	WB			
BRANCH+2				stall	IF1	IF2	ID	EX	MEM1	MEM2	WB		
BRANCH TARGET						**IF1	IF2	ID	EX	MEM1	MEM2	WB	

Figure 3: Timing Diagram for A2 Case 2

Exercise Part (B) - Generate RISC Code for The Chacha20 Stream Cipher