

COMPENG 4DN4 Lab 1 Report

Aaron Pinto
pintoa9

Raeed Hassan
hassam41

February 12, 2023

TCP: WireShark

Figure 1: <http://compeng4dn4.mo00.com:50008/photos/351.jpeg>



TCP: Tcpdump

A tcpdump packet capture was started and the scan written to a WireShark compatible pcap file for analysis. The tcpdump terminal output is shown in Listing 1. The Ncat terminal output where the group member's names and MAC ID numbers were echoed is shown below in Listing 2.

Listing 1: Tcpdump Packet Capture of Python Echo Server Connection

```
sudo tcpdump -nnvvX -i 1 -S host compeng4dn4.mo00.com -w mo00_echo.pcap
tcpdump: listening on eth0, link-type EN10MB (Ethernet), snapshot length 262144 bytes
21 packets captured
88 packets received by filter
0 packets dropped by kernel
```

Listing 2: Ncat Connection to Python Echo Server

```
ncat --crlf compeng4dn4.mo00.com 50007
Welcome to COMPENG 4DN4 Echo Server!
Raeed Hassan
Raeed Hassan
400188200
400188200
```

Aaron Pinto
Aaron Pinto
400190637
400190637

The capture displayed in WireShark is shown below in Figure 2. The first three packets (1-3) contain the three way handshake which establishes the TCP connection. The next two packets are (4-5) shows that the server is letting the host know that it is sending some data in packet 4 (the message "Welcome to COMPENG 4DN4 Echo Server!") while acknowledging the last signal with a [PSH, ACK] signal, and that the host acknowledges this in packet 5.

Packets 6-9 are for the first message sent to the server ("Raeed Hassan") which is echoed back to the host. The host sends the message in packet 6, with a [PSH, ACK] signal as discussed earlier, which is then acknowledged by the server in packet 7. The server then does the same when echoing the message back, with a [PSH, ACK] signal in packet 8, which is acknowledged by the host in packet 9.

For the next three messages, the ACK signal from the server (such as in packet 7) is dropped and instead only 3 packets are sent, a [PSH, ACK] signal from the host to the server when sending the message, a [PSH, ACK] signal from the server to the host when it echoes back the signal, and an ACK signal from the host acknowledging the previous signal. Packets 10-12 are for the next message sent to the server ("400188200") which is echoed back to the host. Packets 13-15 are for the next message sent to the server ("Aaron Pinto") which is echoed back to the host. Packets 16-18 are for the next message sent to the server ("400190637") which is echoed back to the host.

The last three packets (19-21) close the TCP connection. The host sending sends a FIN signal in packet 19 to indicate it wishes to finish the TCP connection, which the server acknowledges in packet 20 and sends back it's own FIN signal. The connection is finished as the host acknowledges the server's signal in packet 21.

Figure 2: Tcpcdump Capture of Python Echo Server in WireShark

| No. | Time | Source | Destination | Protocol | Length | Info |
|-----|-----------|---------------|---------------|----------|--------|---|
| 1 | 0.000000 | 192.168.2.55 | 99.236.34.223 | TCP | 74 | 55182 → 50007 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=2269558917 TSecr=0 WS=128 |
| 2 | 0.025617 | 99.236.34.223 | 192.168.2.55 | TCP | 74 | 50007 → 55182 [SYN, ACK] Seq=0 Ack=1 Win=65160 Len=0 MSS=1452 SACK_PERM TSval=389693670 TSecr=2269558917 WS=128 |
| 3 | 0.025660 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [ACK] Seq=1 Ack=1 Win=64256 Len=0 TSval=2269558943 TSecr=389693670 |
| 4 | 0.049202 | 99.236.34.223 | 192.168.2.55 | TCP | 103 | 50007 → 55182 [PSH, ACK] Seq=1 Ack=1 Win=65280 Len=37 TSval=389693696 TSecr=2269558943 |
| 5 | 0.049245 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [ACK] Seq=1 Ack=38 Win=64256 Len=0 TSval=2269558966 TSecr=389693696 |
| 6 | 7.351131 | 192.168.2.55 | 99.236.34.223 | TCP | 80 | 55182 → 50007 [PSH, ACK] Seq=1 Ack=38 Win=64256 Len=14 TSval=2269566268 TSecr=389693696 |
| 7 | 7.375637 | 99.236.34.223 | 192.168.2.55 | TCP | 66 | 50007 → 55182 [ACK] Seq=38 Ack=15 Win=65280 Len=0 TSval=389701019 TSecr=2269566268 |
| 8 | 7.375638 | 99.236.34.223 | 192.168.2.55 | TCP | 80 | 50007 → 55182 [PSH, ACK] Seq=38 Ack=15 Win=65280 Len=14 TSval=389701019 TSecr=2269566268 |
| 9 | 7.375676 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [ACK] Seq=15 Ack=52 Win=64256 Len=0 TSval=2269566293 TSecr=389701019 |
| 10 | 11.683288 | 192.168.2.55 | 99.236.34.223 | TCP | 77 | 55182 → 50007 [PSH, ACK] Seq=15 Ack=52 Win=64256 Len=11 TSval=2269570600 TSecr=389701019 |
| 11 | 11.708132 | 99.236.34.223 | 192.168.2.55 | TCP | 77 | 50007 → 55182 [PSH, ACK] Seq=52 Ack=26 Win=65280 Len=11 TSval=389705352 TSecr=2269570600 |
| 12 | 11.708168 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [ACK] Seq=26 Ack=63 Win=64256 Len=0 TSval=2269570625 TSecr=389705352 |
| 13 | 15.369517 | 192.168.2.55 | 99.236.34.223 | TCP | 79 | 55182 → 50007 [PSH, ACK] Seq=26 Ack=63 Win=64256 Len=13 TSval=2269574286 TSecr=389705352 |
| 14 | 15.395181 | 99.236.34.223 | 192.168.2.55 | TCP | 79 | 50007 → 55182 [PSH, ACK] Seq=63 Ack=39 Win=65280 Len=13 TSval=389709039 TSecr=2269574286 |
| 15 | 15.395306 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [ACK] Seq=39 Ack=76 Win=64256 Len=0 TSval=2269574312 TSecr=389709039 |
| 16 | 19.915362 | 192.168.2.55 | 99.236.34.223 | TCP | 77 | 55182 → 50007 [PSH, ACK] Seq=39 Ack=76 Win=64256 Len=11 TSval=2269578832 TSecr=389709039 |
| 17 | 19.942417 | 99.236.34.223 | 192.168.2.55 | TCP | 77 | 50007 → 55182 [PSH, ACK] Seq=76 Ack=50 Win=65280 Len=11 TSval=389713584 TSecr=2269578832 |
| 18 | 19.942472 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [ACK] Seq=50 Ack=87 Win=64256 Len=0 TSval=2269578859 TSecr=389713584 |
| 19 | 27.040246 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [FIN, ACK] Seq=50 Ack=87 Win=64256 Len=0 TSval=2269585957 TSecr=389713584 |
| 20 | 27.073821 | 99.236.34.223 | 192.168.2.55 | TCP | 66 | 50007 → 55182 [FIN, ACK] Seq=87 Ack=51 Win=65280 Len=0 TSval=389720710 TSecr=2269585957 |
| 21 | 27.073857 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 55182 → 50007 [ACK] Seq=51 Ack=88 Win=64256 Len=0 TSval=2269585991 TSecr=389720710 |

DNS

The nslookup utility was used to do a DNS query on the compeng4dn4.mooo.com server. The terminal output of the DNS query is shown in Listing 3.

Listing 3: DNS Query Terminal Output

```
nslookup compeng4dn4.mooo.com
Server: mynetwork
Address: 192.168.2.1
```

```
Non-authoritative answer:
Name: compeng4dn4.mooo.com
Address: 99.236.34.223
```

The WireShark capture for the DNS query is shown below in Figure 3. The capture was filtered for DNS queries containing `compeng4dn4.mooo.com`, using the display filter `dns.qry.name contains "compeng4dn4.mooo.com"`.

The DNS query first searches for `compeng4dn4.mooo.com` with the DNS suffix `.home`, performing the query with "A" and "AAAA" records, for mapping hostnames to IPv4 and IPv6 addresses. Both DNS queries return "no such name" indicating that the queries are unsuccessful. The DNS query then queries `compeng4dn4.mooo.com` with no suffix, returning the correct IPv4 address for the A record. The AAAA record does not return any address.

Figure 3: DNS Query WireShark Capture

| No. | Time | Source | Destination | Protocol | Length | Info |
|-----|-----------|--------------|--------------|----------|--------|--|
| 202 | 16.449334 | 192.168.2.49 | 192.168.2.1 | DNS | 85 | Standard query 0x0002 A compeng4dn4.mooo.com.home |
| 203 | 16.454914 | 192.168.2.1 | 192.168.2.49 | DNS | 85 | Standard query response 0x0002 No such name A compeng4dn4.mooo.com.home |
| 204 | 16.455021 | 192.168.2.49 | 192.168.2.1 | DNS | 85 | Standard query 0x0003 AAAA compeng4dn4.mooo.com.home |
| 205 | 16.459511 | 192.168.2.1 | 192.168.2.49 | DNS | 85 | Standard query response 0x0003 No such name AAAA compeng4dn4.mooo.com.home |
| 206 | 16.459602 | 192.168.2.49 | 192.168.2.1 | DNS | 80 | Standard query 0x0004 A compeng4dn4.mooo.com |
| 207 | 16.463819 | 192.168.2.1 | 192.168.2.49 | DNS | 96 | Standard query response 0x0004 A compeng4dn4.mooo.com A 99.236.34.223 |
| 208 | 16.465093 | 192.168.2.49 | 192.168.2.1 | DNS | 80 | Standard query 0x0005 AAAA compeng4dn4.mooo.com |
| 209 | 16.469126 | 192.168.2.1 | 192.168.2.49 | DNS | 80 | Standard query response 0x0005 AAAA compeng4dn4.mooo.com |

Traceroute

The traceroute terminal output is shown below in Listing 4. We can see that the traceroute begins first with a hop to the local router at 192.168.2.1, then takes 10 hops to route to 24.156.158.102, with all subsequent hops timing out.

Listing 4: Traceroute Terminal Output

```
tracert compeng4dn4.mooo.com
```

```
Tracing route to compeng4dn4.mooo.com [99.236.34.223]
over a maximum of 30 hops:
```

```
  1      5 ms      5 ms      5 ms    mynetwork [192.168.2.1]
  2     22 ms     15 ms     19 ms    10.11.2.49
  3      *        *        *        Request timed out.
  4     14 ms     21 ms      *        cksnon1673w_lag37.net.bell.ca [142.124.127.44]
  5      9 ms     18 ms     22 ms    cr01-toroonxnhe9-bundle-ether1.net.bell.ca [142.124.127.159]
  6     22 ms     26 ms     24 ms    bx5-torontoxn-ae0.net.bell.ca [64.230.52.229]
  7     29 ms     28 ms     20 ms    rogers_bx5-torontoxn.net.bell.ca [184.150.158.205]
  8     22 ms     20 ms     21 ms    209.148.235.221
  9     23 ms     13 ms     15 ms    3039-dgw01.hstr.rmgt.net.rogers.com [209.148.237.94]
 10     23 ms     33 ms     18 ms    24.156.158.102
 11      *        *        *        Request timed out.
 12      *        *        *        Request timed out.
 13      *        *        *        Request timed out.
 14      *        *        *        Request timed out.
```

```

15      *      *      *      Request timed out.
16      *      *      *      Request timed out.
17      *      *      *      Request timed out.
18      *      *      *      Request timed out.
19      *      *      *      Request timed out.
20      *      *      *      Request timed out.
21      *      *      *      Request timed out.
22      *      *      *      Request timed out.
23      *      *      *      Request timed out.
24      *      *      *      Request timed out.
25      *      *      *      Request timed out.
26      *      *      *      Request timed out.
27      *      *      *      Request timed out.
28      *      *      *      Request timed out.
29      *      *      *      Request timed out.
30      *      *      *      Request timed out.

Trace complete.

```

The WireShark capture was done with a capture filter of `icmp`. The WireShark capture for traceroute is shown below in Figure 4. We can see that what the traceroute command does is continually send ICMP echo requests to the targeted hostname (99.236.34.223) from 192.168.2.49 (the `localhost`). We can also follow the hops in the traceroute by checking the source destination of the "Time-to-live exceeded" ICMP packets, with the first two hops of the traceroute (192.168.2.1 and 10.11.2.49) appearing in the figure.

Figure 4: Traceroute WireShark Capture

| No. | Time | Source | Destination | Protocol | Length | Info |
|-----|-----------|--------------|---------------|----------|--------|--|
| 1 | 0.000000 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=236/60416, ttl=1 (no response found!) |
| 2 | 0.000016 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=236/60416, ttl=1 (no response found!) |
| 3 | 0.005391 | 192.168.2.1 | 192.168.2.49 | ICMP | 134 | Time-to-live exceeded (Time to live exceeded in transit) |
| 4 | 0.006001 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=237/60672, ttl=1 (no response found!) |
| 5 | 0.006013 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=237/60672, ttl=1 (no response found!) |
| 6 | 0.011327 | 192.168.2.1 | 192.168.2.49 | ICMP | 134 | Time-to-live exceeded (Time to live exceeded in transit) |
| 7 | 0.011721 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=238/60928, ttl=1 (no response found!) |
| 8 | 0.011727 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=238/60928, ttl=1 (no response found!) |
| 9 | 0.017607 | 192.168.2.1 | 192.168.2.49 | ICMP | 134 | Time-to-live exceeded (Time to live exceeded in transit) |
| 10 | 1.022108 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=239/61184, ttl=2 (no response found!) |
| 11 | 1.022119 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=239/61184, ttl=2 (no response found!) |
| 12 | 1.044148 | 10.11.2.49 | 192.168.2.49 | ICMP | 134 | Time-to-live exceeded (Time to live exceeded in transit) |
| 13 | 1.044623 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=240/61440, ttl=2 (no response found!) |
| 14 | 1.044629 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=240/61440, ttl=2 (no response found!) |
| 15 | 1.060458 | 10.11.2.49 | 192.168.2.49 | ICMP | 134 | Time-to-live exceeded (Time to live exceeded in transit) |
| 16 | 1.061046 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=241/61696, ttl=2 (no response found!) |
| 17 | 1.061062 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=241/61696, ttl=2 (no response found!) |
| 18 | 1.080493 | 10.11.2.49 | 192.168.2.49 | ICMP | 134 | Time-to-live exceeded (Time to live exceeded in transit) |
| 19 | 7.026845 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=242/61952, ttl=3 (no response found!) |
| 20 | 7.026854 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=242/61952, ttl=3 (no response found!) |
| 21 | 10.974409 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=243/62208, ttl=3 (no response found!) |
| 22 | 10.974426 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=243/62208, ttl=3 (no response found!) |
| 23 | 14.969557 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=244/62464, ttl=3 (no response found!) |
| 24 | 14.969568 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=244/62464, ttl=3 (no response found!) |
| 25 | 18.972363 | 192.168.2.49 | 99.236.34.223 | ICMP | 106 | Echo (ping) request id=0x0001, seq=245/62720, ttl=4 (no response found!) |

Nmap

Standard TCP Connection Scan of compeng4dn4.mooo.com

A standard TCP connection scan (using `-sT` option) of the server `compeng4dn4.mooo.com` over the port range 50000-50009 is performed and shown in Listing 5. The scan showed that ports 50007 and 50008 were open, indicating that [there is an application that will accept](#)

TCP connections, UDP datagrams, or SCTP associated on these ports. The remainder of the ports reported their states as filtered, indicating Nmap could not determine if the port is open. Nmap states that this usually occurs due to [packet filtering preventing Nmap's probes from reaching the port](#). The known services corresponding with each port (from the [nmap-services](#) database) are also listed, with port 50000 being used for IBM Db2 and port 50002 for [Internet/Intranet Input Method Server Framework](#).

Listing 5: Nmap Standard TCP Connection Scan Over Port Range 50000-50009

```
nmap compeng4dn4.mooo.com -Pn -sT -p 50000-50009
Starting Nmap 7.93 ( https://nmap.org ) at 2023-02-11 22:50 Eastern Standard Time
Nmap scan report for compeng4dn4.mooo.com (99.236.34.223)
Host is up (0.030s latency).
rDNS record for 99.236.34.223: cpe382c4a5bff48-cm00fc8db8cbb0.cpe.net.cable.rogers.com

PORT      STATE      SERVICE
50000/tcp  filtered  ibm-db2
50001/tcp  filtered  unknown
50002/tcp  filtered  iiimsf
50003/tcp  filtered  unknown
50004/tcp  filtered  unknown
50005/tcp  filtered  unknown
50006/tcp  filtered  unknown
50007/tcp  open      unknown
50008/tcp  open      unknown
50009/tcp  filtered  unknown

Nmap done: 1 IP address (1 host up) scanned in 3.36 seconds
```

TCP SYN Scan of compeng4dn4.mooo.com

A TCP SYN scan (using -sS option) of the server `compeng4dn4.mooo.com` over the port range 50000-50009 is performed and shown in Listing 6. The scan returns the same information, reporting the same state and services for each of the ports scanned.

Listing 6: Nmap TCP SYN Scan Over Port Range 50000-50009

```
nmap compeng4dn4.mooo.com -Pn -sS -p 50000-50009
Starting Nmap 7.93 ( https://nmap.org ) at 2023-02-11 22:51 Eastern Standard Time
Nmap scan report for compeng4dn4.mooo.com (99.236.34.223)
Host is up (0.032s latency).
rDNS record for 99.236.34.223: cpe382c4a5bff48-cm00fc8db8cbb0.cpe.net.cable.rogers.com

PORT      STATE      SERVICE
50000/tcp  filtered  ibm-db2
50001/tcp  filtered  unknown
50002/tcp  filtered  iiimsf
50003/tcp  filtered  unknown
50004/tcp  filtered  unknown
50005/tcp  filtered  unknown
50006/tcp  filtered  unknown
50007/tcp  open      unknown
50008/tcp  open      unknown
50009/tcp  filtered  unknown

Nmap done: 1 IP address (1 host up) scanned in 1.50 seconds
```


TCP Scans of Open Port 50007

A standard TCP connection scan (using -sT option) and a TCP SYN scan (using -sS option) of the server `compeng4dn4.mooo.com` on the open port 50007 are performed and shown in Listing 7. For both scans, the Nmap scan reported the same information. The scans reported the same information on port 50007 as the earlier scans on the larger port range.

Listing 7: Nmap Scans on Port 50007

```
sudo nmap compeng4dn4.mooo.com -Pn -sT -p 50007
Starting Nmap 7.80 ( https://nmap.org ) at 2023-02-12 21:32 EST
Nmap scan report for compeng4dn4.mooo.com (99.236.34.223)
Host is up (0.031s latency).
rDNS record for 99.236.34.223: cpe382c4a5bff48-cm00fc8db8cbb0.cpe.net.cable.rogers.com

PORT      STATE SERVICE
50007/tcp open  unknown

Nmap done: 1 IP address (1 host up) scanned in 0.15 seconds

sudo nmap compeng4dn4.mooo.com -Pn -sS -p 50007
Starting Nmap 7.80 ( https://nmap.org ) at 2023-02-12 21:32 EST
Nmap scan report for compeng4dn4.mooo.com (99.236.34.223)
Host is up (0.024s latency).
rDNS record for 99.236.34.223: cpe382c4a5bff48-cm00fc8db8cbb0.cpe.net.cable.rogers.com

PORT      STATE SERVICE
50007/tcp open  unknown

Nmap done: 1 IP address (1 host up) scanned in 0.20 seconds
```

Both scans were captured with tcpdump, writing the scan to a WireShark compatible pcap file for analysis. The tcpdump packet capture command of the scans is shown in Listing 8.

Listing 8: Tcpdump Packet Capture of Scans on Port 50007

```
sudo tcpdump -nnvvX -i 1 -S host compeng4dn4.mooo.com -w 50007.pcap
tcpdump: listening on eth0, link-type EN10MB (Ethernet), snapshot length 262144 bytes
7 packets captured
13 packets received by filter
0 packets dropped by kernel
```

The capture displayed in WireShark is shown below in Figure 5. The first four packets (1-4) are from the standard TCP connection scan on port 50007. The last three packets (5-7) are from the TCP SYN scan on port 50007.

The first four packets shows the [expected behaviour of a TCP connection scan on an open port](#). The host (192.168.2.55) sends a SYN signal to the destination (port 50007 on 99.236.34.223). The destination lets the host know that the port is open by returning a SYN/ACK signal. The host then establishes the connection and sends an ACK signal. Finally, the host will kill the connection with a RST signal.

The last three packets shows the [expected behaviour of a TCP SYN scan on an open port](#). The first two packets are the same as before, however the host sends a RST signal on the third packet to let the destination know it will not be establishing a connection.

Figure 5: Tcpdump Capture of Port 50007 in WireShark

| No. | Time | Source | Destination | Protocol | Length | Info |
|-----|-----------|---------------|---------------|----------|--------|---|
| 1 | 0.000000 | 192.168.2.55 | 99.236.34.223 | TCP | 74 | 46748 → 50007 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=2265637838 TSecr=0 WS=128 |
| 2 | 0.030798 | 99.236.34.223 | 192.168.2.55 | TCP | 74 | 50007 → 46748 [SYN, ACK] Seq=0 Ack=1 Win=65160 Len=0 MSS=1452 SACK_PERM TSval=385772596 TSecr=2265637838 WS=128 |
| 3 | 0.030899 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 46748 → 50007 [ACK] Seq=1 Ack=1 Win=64256 Len=0 TSval=2265637869 TSecr=385772596 |
| 4 | 0.030960 | 192.168.2.55 | 99.236.34.223 | TCP | 66 | 46748 → 50007 [RST, ACK] Seq=1 Ack=1 Win=64256 Len=0 TSval=2265637869 TSecr=385772596 |
| 5 | 17.701279 | 192.168.2.55 | 99.236.34.223 | TCP | 58 | 62988 → 50007 [SYN] Seq=0 Win=1024 Len=0 MSS=1460 |
| 6 | 17.725210 | 99.236.34.223 | 192.168.2.55 | TCP | 60 | 50007 → 62988 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1452 |
| 7 | 17.725278 | 192.168.2.55 | 99.236.34.223 | TCP | 54 | 62988 → 50007 [RST] Seq=1 Win=0 Len=0 |

TCP Scans of Closed Port 50009

The filtered ports were assumed to be closed, and the scans were performed on the port 50009. A standard TCP connection scan (using -sT option) and a TCP SYN scan (using -sS option) of the server `compeng4dn4.mooo.com` on the closed port 50009 are performed and shown in Listing 9. For both scans, the Nmap scan reported the same information. The scans reported the same information on port 50009 as the earlier scans on the larger port range.

Listing 9: Nmap Scans on Port 50009

```
sudo nmap compeng4dn4.mooo.com -Pn -sT -p 50009
Starting Nmap 7.80 ( https://nmap.org ) at 2023-02-12 21:31 EST
Nmap scan report for compeng4dn4.mooo.com (99.236.34.223)
Host is up.
rDNS record for 99.236.34.223: cpe382c4a5bfff48-cm00fc8db8cbb0.cpe.net.cable.rogers.com

PORT      STATE      SERVICE
50009/tcp  filtered  unknown

Nmap done: 1 IP address (1 host up) scanned in 2.12 seconds

sudo nmap compeng4dn4.mooo.com -Pn -sS -p 50009
Starting Nmap 7.80 ( https://nmap.org ) at 2023-02-12 21:32 EST
Nmap scan report for compeng4dn4.mooo.com (99.236.34.223)
Host is up.
rDNS record for 99.236.34.223: cpe382c4a5bfff48-cm00fc8db8cbb0.cpe.net.cable.rogers.com

PORT      STATE      SERVICE
50009/tcp  filtered  unknown

Nmap done: 1 IP address (1 host up) scanned in 2.18 seconds
```

Both scans were captured with tcpdump, writing the scan to a WireShark compatible pcap file for analysis. The tcpdump packet capture command of the scans is shown in Listing 10.

Listing 10: Tcpdump Packet Capture of Scans on Port 50009

```
sudo tcpdump -nnvvX -i 1 -S host compeng4dn4.mooo.com -w 50009.pcap
tcpdump: listening on eth0, link-type EN10MB (Ethernet), snapshot length 262144 bytes
4 packets captured
10 packets received by filter
0 packets dropped by kernel
```

The capture displayed in WireShark is shown below in Figure 6. The first two packets (1-2) are from the standard TCP connection scan on port 50009. The last two packets (3-4) are from the TCP SYN scan on port 50009.

The first two packets and last two packets both show the [expected behaviour of a Nmap scan on a filtered port](#). The host (192.168.2.55) sends a SYN signal to the destination (port 50009

on 99.236.34.223) but does not receive a reply. After waiting some time (around 1 second in this capture), the host sends another SYN signal to try again. If the timeout period is again exceeded, Nmap will give up and mark the port as filtered.

Figure 6: Tcpdump Capture of Port 50009 in WireShark

| No. | Time | Source | Destination | Protocol | Length | Info |
|-----|-----------|--------------|---------------|----------|--------|--|
| 1 | 0.000000 | 192.168.2.55 | 99.236.34.223 | TCP | 74 | 36270 → 50009 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=2265584398 TSecr=0 WS=128 |
| 2 | 1.000716 | 192.168.2.55 | 99.236.34.223 | TCP | 74 | 36286 → 50009 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=2265585399 TSecr=0 WS=128 |
| 3 | 13.421758 | 192.168.2.55 | 99.236.34.223 | TCP | 58 | 37040 → 50009 [SYN] Seq=0 Win=1024 Len=0 MSS=1460 |
| 4 | 14.422800 | 192.168.2.55 | 99.236.34.223 | TCP | 58 | 37041 → 50009 [SYN] Seq=0 Win=1024 Len=0 MSS=1460 |

Standard TCP Connection Scan of localhost

A standard TCP connection scan (using -sT option) of `localhost` was performed and shown in Listing 11. The scan reports all found open ports, and also states that there are 993 tcp ports that were filtered due to no-response. The services corresponding to each open port is also listed. The purposes of each service on these open ports are discussed in Table 1.

Listing 11: Nmap Standard TCP Connection Scan of localhost

```
nmap localhost -Pn -sT
Starting Nmap 7.93 ( https://nmap.org ) at 2023-02-11 23:39 Eastern Standard Time
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00015s latency).
Other addresses for localhost (not scanned): ::1
Not shown: 993 filtered tcp ports (no-response)
PORT      STATE SERVICE
135/tcp   open  msrpc
445/tcp   open  microsoft-ds
2179/tcp  open  vmrpd
5357/tcp  open  wsddapi
9010/tcp  open  sdr
9080/tcp  open  glrpc
9100/tcp  open  jetdirect

Nmap done: 1 IP address (1 host up) scanned in 44.45 seconds
```

Table 1: Services on Open Ports of localhost

| PORT | SERVICE | PURPOSE |
|----------|--------------|---|
| 135/tcp | msrpc | Microsoft Remote Procedure Call |
| 445/tcp | microsoft-ds | Server Message Block (SMB) |
| 2179/tcp | vmrpd | Microsoft RDP for virtual machines |
| 5357/tcp | wsddapi | Microsoft Network Discovery |
| 9010/tcp | sdr | Secure Data Replicator Protocol |
| 9080/tcp | glrpc | Groove Collaboration software GLRPC |
| 9100/tcp | jetdirect | HP JetDirect (for HP LaserJet printers) |

TCP Scan of Port 8000 on localhost

A standard TCP connection scan (using -sT option) of port 8000 on `localhost` was performed and shown in Listing 12. The scan reports that the port is filtered (likely due to

no response as mentioned in the previous report). The service that typically corresponds to this port is `http-alt`, an alternative HTTP port.

Listing 12: Nmap Standard TCP Connection Scan of Port 8000 on `localhost`

```
nmap localhost -Pn -sT -p 8000
Starting Nmap 7.93 ( https://nmap.org ) at 2023-02-11 23:43 Eastern Standard Time
Nmap scan report for localhost (127.0.0.1)
Host is up.
Other addresses for localhost (not scanned): ::1

PORT      STATE      SERVICE
8000/tcp   filtered   http-alt

Nmap done: 1 IP address (1 host up) scanned in 2.11 seconds
```

TCP Scan of Port 8000 on `localhost` with HTTP Server

A standard TCP connection scan (using `-sT` option) of port 8000 on `localhost` was performed while the HTTP server was running, and the scan is shown in Listing 13. The scan reports that the port is now open. When the web service is accessed through a browser, a page that serves the contents of the directory where the server was launched is shown. The webpage is shown in Figure 7.

Listing 13: Nmap Standard TCP Connection Scan of Port 8000 on `localhost` with HTTP Server

```
nmap localhost -Pn -sT -p 8000
Starting Nmap 7.93 ( https://nmap.org ) at 2023-02-11 23:43 Eastern Standard Time
Nmap scan report for localhost (127.0.0.1)
Host is up (0.0010s latency).
Other addresses for localhost (not scanned): ::1

PORT      STATE      SERVICE
8000/tcp   open       http-alt

Nmap done: 1 IP address (1 host up) scanned in 0.09 seconds
```

Figure 7: localhost:8000

