

ELECENG 3CL4 Lab 5 Pre-lab

Aaron Pinto
pintoa9
L02

Raeed Hassan
hassam41
L02

April 4, 2021

1. The output of the model can be expressed as:

$$Y(s) = \frac{G_c(s)G(s)}{1 + H(s)G_c(s)G(s)}R(s) + \frac{G(s)}{1 + H(s)G_c(s)G(s)}T_d(s) + \frac{H(s)G_c(s)G(s)}{1 + H(s)G_c(s)G(s)}N(s) \quad (1)$$

From Equation 1, we can derive $\frac{Y(s)}{T_d(s)}$ in Equation 2 when $R(s) = 0$ and $H(s) = 1$.

$$\begin{aligned} Y(s) &= \frac{G(s)}{1 + H(s)G_c(s)G(s)}T_d(s) \\ \frac{Y(s)}{T_d(s)} &= \frac{G(s)}{1 + H(s)G_c(s)G(s)} \\ &= \frac{G(s)}{1 + G_c(s)G(s)} \end{aligned} \quad (2)$$

2. The steady-state value of the output with a step disturbance of size A and the absence of any input can be derived through the final value theorem as:

$$\begin{aligned} e_{ss} &= \lim_{s \rightarrow 0} s \frac{G(s)}{1 + G_c(s)G(s)} \frac{A}{s} \\ &= \lim_{s \rightarrow 0} \frac{AG(s)}{1 + G_c(s)G(s)} \\ &= \lim_{s \rightarrow 0} \frac{A \frac{4.7}{s(s+3.2)}}{1 + G_c(s) \frac{4.7}{s(s+3.2)}} \\ &= \lim_{s \rightarrow 0} \frac{4.7A}{s(s+3.2) + 4.7G_c(s)} \\ &= 4.7A \lim_{s \rightarrow 0} \frac{1}{s(s+3.2) + 4.7G_c(s)} \\ &= 4.7A \frac{1}{\lim_{s \rightarrow 0} (s(s+1)) + \lim_{s \rightarrow 0} (4.7G_c(s))} \\ &= 4.7A \frac{1}{0 + 4.7 \lim_{s \rightarrow 0} (G_c(s))} \\ &= \frac{4.7A}{4.7 \lim_{s \rightarrow 0} (G_c(s))} \\ &= \frac{A}{\lim_{s \rightarrow 0} G_c(s)} \end{aligned} \quad (3)$$

3. We can write the expression in Equation 3 for the case of a lead compensator, expressing

it as a function of K_c , z_{lead} , and p_{lead} in Equation 4.

$$\begin{aligned}
&= \frac{A}{\lim_{s \rightarrow 0} G_c(s)} \\
&= \frac{A}{\lim_{s \rightarrow 0} \left(K_c \frac{(s+z_{lead})}{(s+p_{lead})} \right)} \\
&= \frac{A}{K_c \left(\frac{z_{lead}}{p_{lead}} \right)} \\
&= \frac{A}{K_c} \left(\frac{p_{lead}}{z_{lead}} \right)
\end{aligned} \tag{4}$$

4. We can write the expression in Equation 3 for the case of a lead-lag compensator, expressing it as a function of K_c , z_{lead} , p_{lead} , z_{lag} , and p_{lag} in Equation 5.

$$\begin{aligned}
&= \frac{A}{\lim_{s \rightarrow 0} G_c(s)} \\
&= \frac{A}{\lim_{s \rightarrow 0} \left(K_c \frac{(s+z_{lead})}{(s+p_{lead})} \frac{(s+z_{lag})}{(s+p_{lag})} \right)} \\
&= \frac{A}{K_c \left(\frac{z_{lead}}{p_{lead}} \right) \left(\frac{z_{lag}}{p_{lag}} \right)} \\
&= \frac{A}{K_c} \left(\frac{p_{lead}}{z_{lead}} \right) \left(\frac{p_{lag}}{z_{lag}} \right)
\end{aligned} \tag{5}$$

5. The parameters K_c , z_{lead} , and p_{lead} were determined for a phase lead compensator in the pre-lab exercise of Lab 4 and were determined to be $K_c = 62.1$, $z_{lead} = 6$, and $p_{lead} = 15.51$.
- 6.
- 7.
8. The positions of the closed-loop poles of the lead compensated loop in the pre-lab exercise for Lab 4 were closed-loop poles at $-6 + 15j$ and $-6 - 15j$.
9. We can choose values of z_{lag} and p_{lag} that are near the origin. This would not affect the transient performance of the closed loop very much as the transient responses of the zero and pole would decay very quickly.
- 10.