

# Verified Time-Aware Stream Processing

Rafael Castro G. Silva

`razi@di.ku.dk`

Department of Computer Science  
University of Copenhagen

02/11/2023

# What is this PhD/Status seminar about?

- Distributed Systems
  - Stream processing frameworks
    - Dataflow models
    - Time-Aware Computations
- Formal Methods
  - Verification using proof assistants
    - Isabelle proofs
    - Verified and executable code
- Formalization of Time-Aware Stream Processing

- Introduction
- Preliminaries
- Lazy Lists Processors
- Time-Aware Operators
- Case Study
- Next Steps

# Introduction

- Stream Processing
- Dataflow Model
- Time-Aware Computations
- Bugs in Stream Processing

# Preliminaries

- HOL
- Isabelle/HOL

# Isabelle/HOL: (Co)datatypes

- Datatypes and Codatatypes

```
codatatype (lset: 'a) llist = lnull: LNil | LCons (lhd: 'a) (ltl: 'a llist)  
for map: lmap where ltl LNil = LNil
```


- Examples:

- `LNil:: nat llist`
- `LCons (1 :: nat) (LCons 2 (LCons 3 LNil))`
- `LCons (0 :: nat) (LCons 0 (LCons 0 (...)))`

- Induction principle assuming membership in the lazy list

- Coinductive principle for lazy list equality:

- Show that there is a pair of goggles that makes them to look the same, which implies that:
  - The first lazy list is empty iff second is
  - They have the same head
  - Their tail looks the same





# Isabelle/HOL: (Co)datatypes

- Datatypes and Codatatypes

```
codatatype (lset: 'a) llist = lnull: LNil | LCons (lhd: 'a) (ltl: 'a llist)  
for map: lmap where ltl LNil = LNil
```


- Examples:

- `LNil:: nat llist`
- `LCons (1 :: nat) (LCons 2 (LCons 3 LNil))`
- `LCons (0 :: nat) (LCons 0 (LCons 0 (...)))`

- Induction principle assuming membership in the lazy list

- Coinductive principle for lazy list equality:

- Show that there is a pair of goggles that makes them to look the same, which must imply that:
  - The first lazy list is empty iff second is
  - They have the same head
  - Their tail looks the same



# Isabelle/HOL: (Co)datatypes

- Datatypes and Codatatypes

```
codatatype (lset: 'a) llist = lnull: LNil | LCons (lhd: 'a) (ltl: 'a llist)
for map: lmap where ltl LNil = LNil
```


- Examples:

- `LNil:: nat llist`
- `LCons (1 :: nat) (LCons 2 (LCons 3 LNil))`
- `LCons (0 :: nat) (LCons 0 (LCons 0 (...)))`

- Induction principle assuming membership in the lazy list

- Coinductive principle for lazy list equality:

- Show that there is a pair of goggles that makes them to look the same, which must imply that:
  - The first lazy list is empty iff second is
  - They have the same head
  - Their tail looks the same



- Recursion

```
fun lshift :: 'a list  $\Rightarrow$  'a llist  $\Rightarrow$  'a llist (infixr @@ 65) where  
  lshift [] lxs = lxs  
| lshift (x # xs) lxs = LCons x (lshift xs lxs)
```

- While Combinator

```
definition while_option :: ('a  $\Rightarrow$  bool)  $\Rightarrow$  ('a  $\Rightarrow$  'a)  $\Rightarrow$  'a  $\Rightarrow$  'a option where  
  while_option b c s = ...
```

- While rule for invariant reasoning:

- There is something that holds before a step; that thing still holds after the step

# Isabelle/HOL: Corecursion and Friends

- Corecursion is like recursion, but instead of always eventually reducing an argument it always eventually produces something
- Corec:

```
corec lapp :: 'a llist  $\Rightarrow$  'a llist  $\Rightarrow$  'a llist where  
  lapp xs lys = case xs of LNil  $\Rightarrow$  lys | LCons x xs'  $\Rightarrow$  LCons x (lapp xs' lys)
```

- Friendly function
  - Preserves productivity: it may consume at most one constructor to produce one constructor.

```
friend_of_corec lshift where  
  xs @@ xs = (case xs of  
    []  $\Rightarrow$  (case xs of LNil  $\Rightarrow$  LNil | LCons x xs'  $\Rightarrow$  LCons x xs')  
  | x#xs'  $\Rightarrow$  LCons x (xs' @@ xs))  
  by (auto split: list.splits llist.splits) (transfer_prover)  
  
lconcat xs = case xs of LNil  $\Rightarrow$  LNil | LCons x xs'  $\Rightarrow$  lshift x (lconcat xs')
```

# Isabelle/HOL: (Co)inductive Predicates

- Inductive predicate
  - Finite number of introduction rule applications

```
inductive in_llist :: 'a  $\Rightarrow$  'a llist  $\Rightarrow$  bool where  
  In_llist: in_llist x (LCons x lxs)  
| Next_llist: in_llist x lxs  $\Rightarrow$  in_llist x (LCons y lxs)  
  
in_llist (2::nat) (LCons 1 (LCons (2 (...))))
```

- Coinductive predicate
  - Infinite number of introduction rule applications

```
coinductive lprefix :: 'a llist  $\Rightarrow$  'a llist  $\Rightarrow$  bool where  
  LNil_lprefix: lprefix LNil lxs  
| LCons_lprefix: lprefix lxs lxs  $\Rightarrow$  lprefix (LCons x lxs) (LCons x lxs)  
  
lprefix (LCons 1 (LCons (2 (...)))) (LCons 1 (LCons (2 (...))))
```

- Coinduction principle

# Lazy Lists Processors

# Operators

- Operator as a codatatype
  - Taking `'i` as the input type, and `'o` as the output type:

```
codatatype ('o, 'i) op = Logic (apply: ('i  $\Rightarrow$  ('o, 'i) op  $\times$  'o list))
```

- Infinite trees: applying the selector `apply` “walks” a branch of the tree
- Produce function: applies the logic (co)recursively throughout a lazy list
  - The recursive part:

```
definition produce1' op lxs = while_option  
  ( $\lambda$ (op, lxs).  $\neg$  lnull lxs  $\wedge$  snd (apply op (lhd lxs)) = [])  
  ( $\lambda$ (op, lxs). (fst (apply op (lhd lxs)), ltl lxs)) (op, lxs)  
definition produce1 op lxs =  
  (case produce1' op lxs of None  $\Rightarrow$  None  
  | Some (op', lxs')  $\Rightarrow$  if lnull lxs' then None else  
    let (op'', out) = apply op' (lhd lxs') in Some (op'', hd out, tl out, ltl lxs'))
```

# Operators: Example

- Example: counts elements satisfying  $P$ :

```
corec count_op where count_op P n =  
  Logic (λe. if P e then (count_op P (n + 1), [n+1]) else (count_op P n, []))
```

$stream_2 =$ 

$0::nat$	3	3	6	24
----------	---	---	---	----

$produce (count\_op\ is\_even\ 0)\ stream_2 =$ 

1	2	3
---	---	---

Figure: Difference between  $incr\_hist\_op'$  and  $incr\_hist\_op$



# Sequential Composition


- Composition
- Skip  $n$

# Time-Aware Operators


# Monotone and Productive Time-Aware Streams

- Monotone
- Productive

$stream_1 =$



(a) Prefix of  $stream_1$



(b) Corresponding set of collections

Figure: An example stream and its collections (ordered by their time-stamps)

# Building Blocks: Batch Operator

# Batch Operator: Soundness

# Batch Operator: Completeness

- Uses soundness of `batch_op`
- Proof by induction over `n`

$$\begin{aligned} \text{mono\_prod } lxs \ W \longrightarrow & (\exists i \ d. \text{enat } i < \text{llength } lxs \wedge \text{Inth } lxs \ i = \text{DT } t \ d \wedge n = \text{Suc } i) \vee \\ n = 0 \wedge t \in \text{set\_t } buf \longrightarrow & (\forall t' \in \text{set\_t } buf. \text{lfinite } lxs \vee \exists wm \geq t'. \text{WM } wm \in \text{lset } lxs) \longrightarrow \\ \exists wm \ batch. \text{DT } wm \ batch \in \text{lset } & (\text{produce } (\text{batch\_op } buf) \ lxs) \wedge t \in \text{set\_t } batch \vee \\ (\forall k \in \{n .. < \text{the\_enat } (\text{llength } lxs)\} . \neg & (\exists t' \geq t. \text{Inth } lxs \ k = \text{WM } t')) \wedge \text{lfinite } lxs \end{aligned} \quad (1)$$

# Batch Operator: Monotone

# Batch Operator: Productive



# Building Blocks: Incremental Operator

# Batch Operator: Soundness

# Batch Operator: Completeness

# Batch Operator: Monotone

# Batch Operator: Productive



## Case Study

# Histogram



# Histogram: Soundness

# Histogram: Completeness

# Histogram: Monotone

# Histogram: Productive

# Efficient Histogram

- Foo





# Join: Completeness



# Join: Monotone

## Next Steps

# Next Steps

Questions, comments and suggestions