

ISCSI\_SW\_TCP\_TRANSPORT.

↳ **CREATE** CONN = iscsi\_sw\_tcp\_conn\_create()

↳ iscsi\_tcp\_conn\_setup()

↳ iscsi\_conn\_setup()

↳ iscsi\_create\_conn()

timer\_setup(CONN → TRANSPORT\_TIMER)

---

ISCSI\_SW\_TCP\_TRANSPORT

↳ **START** CONN = iscsi\_conn\_start()

↳ MOD\_TIMER (CONN → TRANSPORT\_TIMER)

↳ JIFFIES + (CONN → RECKTIMEOUT)

---

❌ ISCI\_CHECK\_TRANSPORT\_TIMEOUTS()

→

...  
↳ ISCSI\_COMPLETE\_PDU

PDU IS ANSWER  
FROM NOP

↳ ISCI\_NOP\_OUT\_RSP()

↳ MOD\_TIMER (CONN → TRANSPORT\_TIMER)

# \* ISCSI\_CHECK\_TRANSPORT\_TIMEOUTS ()

↳ SESSION → STATE = LOGGED-IN? DONE  
↳ CONN → RECV-TIMEOUT? NO? DONE  
ISCSI-HAS-PING-TIMED-OUT?

↳ ISCSI\_CONN\_FAILURE ()

TIME-BEFORE LAST-RECV + TIMEOUT?  
↳ ISCSI\_SEND\_NOPOUT ()

---

↳ SESSION → STATE = FAILED? RETURN  
↳ STATE = FAILED PING TIMEOUT  
↳ CONN SUSPEND-TX MARKS SESSION AS  
↳ CONN SUSPEND-RX FAILED.

---

BLOCK SCHEDULES WAIT FOR COMPLETION

BLK RUN QUEUE SUBMIT/DISPATCH SCSI-DISPATCH-CMD (SCSI-MQUEUE-HOST-BUSY)  
ISCSI-QUEUE-CMD SESSION FAILED?

ISCSI WORK QUEUE

SCSI CMD → DONE ()

SEND → TASK-COMPUTE ← RECV ←