

SWITCHES

SÉRIE 2000

Gerenciáveis Layer 2

Tabela comparativa

Modelo	S2310G-A	SG 1002 PoE L2+	SG 1602 PoE Max	S2328G-A	S2328G-B	S2328G-PA	S2328G-PB	S2352G-A	S2352G-B	S2352G-PB
Portas Giga	8	8	16	24	24	24	24	48	48	48
Portas SFP	2	2	2	4	-	4	-	4	-	-
Postas SFP +	-	-	-	-	4	-	4	-	4	4
Portas console	1	1	1	1	1	1	1	1	1	1
Backplane	20 Gbps	20 Gbps	32 Gbps	56 Gbps	128 Gbps	56 Gbps	128 Gbps	104 Gbps	176 Gbps	176 Gbps
PoE	-	Portas 1-8	Portas 1-16	-	-	Portas 1-24	Portas 1-24	-	-	Portas 1-48
Potência de alimentação (PoE)	-	70 W	223 W	-	-	370 W	370 W	-	-	370 W
QoS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Spanning tree	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Roteamento estático	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Agregação de link	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Protocolo SNMP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Interface VLAN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
DHCP server	✓	-	-	✓	✓	✓	✓	✓	✓	✓
IPv6	✓	-	-	✓	✓	✓	✓	✓	✓	✓