

Spearman rank correlations: driver inputs vs Δ emissions (repair – linear)
(grey hatched = distance not mechanistically active in scenario)

Input parameter

Lifespan before first repair (wears)	0.81	0.81	0.80	0.80	0.80	0.79	0.81	0.80	0.81	0.81	0.81	0.81	0.81	0.81	0.81	0.81	0.80	0.81
Production emissions (kg CO ₂ e/pair)	-0.47	-0.47	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.47	-0.48	-0.47	-0.47	-0.47	-0.47
Number of repairs	-0.15	-0.15	-0.14	-0.14	-0.14	-0.13	-0.14	-0.14	-0.15	-0.14	-0.14	-0.14	-0.15	-0.14	-0.15	-0.15	-0.14	-0.15
Extra wears per repair	-0.13	-0.13	-0.15	-0.16	-0.16	-0.17	-0.14	-0.15	-0.14	-0.14	-0.14	-0.15	-0.13	-0.14	-0.13	-0.13	-0.15	-0.13
Jeans mass (kg)	0.06	0.06	0.07	0.08	0.07	0.08	0.07	0.08	0.06	0.07	0.06	0.07	0.06	0.07	0.06	0.06	0.06	0.06
Tailor: customer distance (km/repair)																	0.05	0.08
CWb: van distance (km/repair)			0.04	0.05	0.04	0.05	0.03	0.05										
CWb: customer → box distance (km/repair)			0.02	0.03	0.06	0.06												
CWc: van distance (km/repair)									0.01	0.02	0.01	0.02	0.01	0.01				
CWc: customer → postal distance (km/repair)									-0.02	-0.02	-0.00	-0.00						
Use-phase emissions per wash (kg CO ₂ e/wash)	0.01	0.01	0.01	0.01	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
Wears per wash	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.01	0.00	0.01	0.00	0.00	0.01	0.00
CWa: van distance (km/repair)	-0.00	0.01																

CWa door-to-door – van EV
CWa door-to-door – van ICEV
CWb box – EV + van EV
CWb box – EV + van ICEV
CWb box – ICEV + van EV
CWb box – ICEV + van ICEV
CWb box – walk + van EV
CWb box – walk + van ICEV
CWc postal – EV + van EV
CWc postal – EV + van ICEV
CWc postal – ICEV + van EV
CWc postal – ICEV + van ICEV
CWc postal – walk + van EV
CWc postal – walk + van ICEV
Self-repair (no transport)
Tailor – EV car
Tailor – ICEV car
Tailor – walk/bike

