

Spearman rank correlations: driver inputs vs Δ emissions (repair – linear)
(grey hatched = distance not mechanistically active in scenario)

Input parameter

Lifespan before first repair (wears)	0.81	0.81	0.80	0.80	0.80	0.79	0.81	0.80	0.81	0.81	0.81	0.81	0.81	0.81	0.81	0.81	0.80	0.81
Production emissions (kg CO ₂ e/pair)	-0.47	-0.47	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.48	-0.47	-0.48	-0.47	-0.47	-0.47	-0.47
Number of repairs	-0.15	-0.15	-0.14	-0.14	-0.14	-0.13	-0.14	-0.14	-0.15	-0.14	-0.14	-0.14	-0.15	-0.14	-0.15	-0.15	-0.14	-0.15
Extra wears per repair	-0.13	-0.13	-0.15	-0.16	-0.16	-0.17	-0.14	-0.15	-0.14	-0.14	-0.14	-0.15	-0.13	-0.14	-0.13	-0.13	-0.15	-0.13
Jeans mass (kg)	0.06	0.06	0.07	0.08	0.07	0.08	0.07	0.08	0.06	0.07	0.06	0.07	0.06	0.07	0.06	0.06	0.06	0.06
Tailor: customer distance (km/repair)																	0.05	0.08
CWb: van distance (km/repair)				0.04	0.05	0.04	0.05	0.03	0.05									
CWb: customer → box distance (km/repair)				0.02	0.03	0.06	0.06											
CWc: van distance (km/repair)										0.01	0.02	0.01	0.02	0.01	0.01			
CWc: customer → postal distance (km/repair)										-0.02	-0.02	-0.00	-0.00					
Use-phase emissions per wash (kg CO ₂ e/wash)	0.01	0.01	0.01	0.01	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
Wears per wash	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.01	0.00	0.01	0.00	0.00	0.01	0.00
CWa: van distance (km/repair)	-0.00	0.01																

CWa door-to-door – van EV

CWa door-to-door – van ICEV

CWb box – EV + van EV

CWb box – EV + van ICEV

CWb box – ICEV + van EV

CWb box – ICEV + van ICEV

CWb box – walk + van EV

CWb box – walk + van ICEV

CWc postal – EV + van EV

CWc postal – EV + van ICEV

CWc postal – ICEV + van EV

CWc postal – ICEV + van ICEV

CWc postal – walk + van EV

CWc postal – walk + van ICEV

Self-repair (no transport)

Tailor – EV car

Tailor – ICEV car

Tailor – walk/bike

