

<https://profile.intra.42.fr>

SCALE FOR PROJECT CODEXION (/PROJECTS/CODEXION)

You should evaluate 1 student in this team



Git repository

`git@vogsphere.42lisboa.com:vogsphere/intra-uuid-814d8fe2-b01b-4`

Introduction

- Remain polite, courteous, respectful and constructive throughout the evaluation process. The well-being of the community depends on it.
- Identify with the person (or the group) evaluated the eventual dysfunctions of the work. Take the time to discuss and debate the problems you have identified.
- You must consider that there might be some difference in how your peers might have understood the project's instructions and the scope of its functionalities. Always keep an open mind and grade him/her as honestly as possible. The pedagogy is valid only and only if peer-evaluation is conducted seriously.

Guidelines

- Only grade the work that is in the student or group's GiT repository.
- Double-check that the GiT repository belongs to the student or the group. Ensure that the work is for the relevant project and also check that "git clone" is used in an empty folder.
- Check carefully that no malicious aliases was used to fool you and make you evaluate something other than the content of the official repository.
- To avoid any surprises, carefully check that both the evaluating and the evaluated students have reviewed the possible scripts used to facilitate the grading.
- If the evaluating student has not completed that particular project yet, it is mandatory for this student to read the entire subject prior to starting the defence.
- Use the flags available on this scale to signal an empty repository, non-functioning program, a norm error, cheating etc. In these cases, the grading is over and the final grade is 0 (or -42 in case of cheating). However, with the exception of cheating, you are encouraged to continue to discuss your work (even if you have not finished it) in order to identify any issues that may have caused this failure and avoid repeating the same mistake in the future.
- Remember that for the duration of the defence, no segfault, no other unexpected, premature, uncontrolled or unexpected termination of the program, else the final grade is 0. Use the appropriate flag.
You should never have to edit any file except the configuration file if it exists. If you want to edit a file, take the time to explicit the reasons with the evaluated student and make sure both of you are okay with this.
- You must also verify the absence of memory leaks. Any memory allocated on the heap must

be properly freed before the end of execution.
You are allowed to use any of the different tools available on the computer, such as leaks, valgrind, or e_fence. In case of memory leaks, tick the appropriate flag.

- Since this is a concurrency project, you must also check for data races and deadlocks, which are not always visible by simply reading the logs. Use the thread-specific tooling available on the computer, for example:
 - valgrind --tool=helgrind ./codexion ...
 - valgrind --tool=drd ./codexion ...
 - recompiling the project with -fsanitize=thread and running it.
- If any of these tools reports a data race or a lock-ordering deadlock, tick the appropriate flag. Do not simply trust the evaluated student's explanation that the code is thread-safe.

Attachments

 subject.pdf (<https://cdn.intra.42.fr/pdf/pdf/220995/en.subject.pdf>)

Preliminaries

Basics

- This project must be compiling with:
-Wall -Wextra -Werror -pthread
without any warnings.
- Any compilation error, segmentation fault, data race, deadlock, interleaved log line, or memory leak means 0 to the project.
- The program must take exactly the following arguments, in order:
number_of_coders, time_to_burnout, time_to_compile, time_to_debug, time_to_refactor, number_of_compiles_required, dongle_cooldown, scheduler.
- Each coder must be represented by a thread (using pthread_create).
- The scheduler must be either "fifo" or "edf".
- On some slow hardware, precise timing may vary slightly; discuss borderline cases honestly before counting them as failures.
- Verify compilation: make
- The binary must be named "codexion".

 Yes

 No

Global

- Check if there is any global mutable variable used to manage the shared resources (dongles), the scheduling policy, or the logging.
- If you find such a global state, the evaluation stops here.
You can go on and check the code, but do not grade the exercises.

 Yes

 No

README.md file

Does the repository contain a README.md file at its root, and does it include all of the following?

- The first line is italicized and formatted exactly as: *This project has been created as part of the 42 curriculum by <login1>[, <login2>, <login3>[...]]].*
- A "Description" section explaining the project's purpose and providing a brief overview.
- An "Instructions" section with relevant details about compilation, installation, and/or execution.
- A "Resources" section listing references (documentation, tutorials, etc.) and explaining how AI was used, specifying for which tasks and which parts of the project.

- A "Blocking cases handled" section describing all the concurrency issues addressed in the solution.
- A "Thread synchronization mechanisms" section explaining the specific threading primitives used.

✓ Yes

✗ No

Codexion

Codexion testing — Easy

- Do not test with more than 200 coders.
- Do not test with timing values under 60ms.
- number_of_compiles_required must be at least 1: with 0, every coder has already "compiled at startup and the simulation may stop immediately.
- The first case below must burn out (it checks burnout detection); the other cases must run w burnout and complete all required compiles.

Reference behaviour (use these as benchmark cases). Arguments are, in order:
number_of_coders time_to_burnout time_to_compile time_to_debug
time_to_refactor number_of_compiles_required dongle_cooldown scheduler

- ./codexion 1 800 200 200 200 10 0 fifo A single coder has a single dongle but needs two to c coder can therefore never compile and MUST burn out, around timestamp 800.
- ./codexion 5 2000 200 200 200 10 0 fifo time_to_burnout (2000) is well above one compile+c cycle (200+200+200 = 600), so no coder should burn out; the program must stop on its own i coder has compiled at least 10 times.
- ./codexion 5 2000 200 200 200 7 0 edf Same, with the edf scheduler: no burnout, stops after each.

As there is no reference binary, these cases and their expected behaviour
ARE the benchmark. Because of OS scheduling, run each case several times and
expect the correct behaviour in the large majority of runs (allow a small
timing tolerance on borderline cases before counting them as failures).

✓ Yes

✗ No

Codexion testing — Less easy

- Validate burnout edge cases.
- Verify correct logging and timing tolerances.
- Check no dongle duplication, correct state transitions.

Reference behaviour (benchmark cases):

- ./codexion 5 500 200 200 200 10 0 fifo Infeasible by design: one compile+debug+refactor cy 200+200+200 = 600 ms, which is longer than time_to_burnout (500), so a coder cannot start in time and MUST burn out (around timestamp 500). The "burned out" line must be the LAST must appear within 10 ms of the deadline.
- On a feasible run (for example the 5 2000 ... case from the Easy section), check that every "i is immediately preceded by exactly two "has taken a dongle" lines for the same coder, and th lines are ever interleaved on the same line.
- Confirm the same dongle is never held by two coders at the same time (no dongle duplication

✓ Yes

✗ No

Codexion testing — Medium

- Verify cooldown behavior.
- Test scheduler differences (edf vs fifo).
- Validate refactoring timing and log serialization.

Reference behaviour (benchmark cases):

- ./codexion 5 3000 200 200 200 10 400 fifo Cooldown check: after a coder releases a dongle, must not be taken again until 400 ms have elapsed. By reading the timestamps, verify that n dongle" line for a given dongle occurs within 400 ms of its release. time_to_burnout (3000) is coder should burn out and the run should complete.
- ./codexion 5 3000 200 200 200 10 800 fifo then ... edf Run the exact same parameters once once with edf. The large cooldown (800) forces coders to queue for the dongles. Compare th the waiting coders are granted the dongles: under edf, a coder closer to its burnout deadline ahead of one that requested earlier, so the grant order can differ from the strict arrival order s

Intra Projects Codexion Edit

- Verify each coder spends close to time_to_compile / time_to_debug / time_to_refactor in each timing tolerance), and that the output stays correctly serialized even under heavy contention.

✓ Yes

✗ No

Codexion recode — FIFO to LIFO

- Ask the evaluated student to turn the "fifo" scheduler into a "lifo" one: when several coders are on the same dongle, it must now be granted to the coder whose request arrived LAST instead of first.
- This change is observable at runtime, unlike a tie on EDF deadlines. Run the program once before the change and once after, with the SAME contention-heavy parameters (for example: ./codexior 200 10 800 fifo), and compare the order in which the waiting coders acquire the dongles in the two runs.
- The recode is validated if the grant order under "lifo" is the reverse of the arrival order (the first requester is served first), while the rest of the program keeps working: no coder duplicates a task, stays serialized, and, with feasible parameters, no coder burns out.
- Also read the code to confirm the change is made in the scheduler/queue logic itself and not just in the parameters.

✓ Yes

✗ No

Ratings

Don't forget to check the flag corresponding to the defense

✓ Ok

★ Outstanding project

Empty work

📄 Incomplete work

⚙ Invalid compilation

📖 Norme

📄 Cheat

⚠ Concerning situation

💧 Leaks

🚫 Forbidden function

💬 Can't support / not relevant

Conclusion

Leave a comment on this evaluation (2048 chars max)

Finish evaluation