
This article was downloaded by: [UQ Library]
On: 27 September 2013, At: 05:11
Publisher: Taylor & Francis
Informa Ltd Registered in England and Wales Registered Number: 1072954 Registered office: Mortimer House, 37-41 Mortimer Street, London W1T 3JH, UK



International Journal of Geographical Information Science
Publication details, including instructions for authors and subscription information:
http://www.tandfonline.com/loi/tgis20

A parallel computing approach to viewshed analysis of large terrain data using graphics processing units

Yanli Zhao [a b], Anand Padmanabhan [a b c] & Shaowen Wang [a b c d e]

[a] CyberInfrastructure and Geospatial Information Laboratory, University of Illinois at Urbana-Champaign, Urbana, IL, USA

[b] Department of Geography and Geographic Information Science, University of Illinois at Urbana-Champaign, Urbana, IL, USA

[c] National Center for Supercomputing Applications, University of Illinois at Urbana-Champaign, Urbana, IL, USA

[d] Department of Computer Science, University of Illinois at Urbana-Champaign, Urbana, IL, USA

[e] Department of Urban and Regional Planning, University of Illinois at Urbana-Champaign, Urbana, IL, USA

Published online: 10 Sep 2012.

To cite this article: Yanli Zhao , Anand Padmanabhan & Shaowen Wang (2013) A parallel computing approach to viewshed analysis of large terrain data using graphics processing units, International Journal of Geographical Information Science, 27:2, 363-384, DOI: 10.1080/13658816.2012.692372

To link to this article: http://dx.doi.org/10.1080/13658816.2012.692372

PLEASE SCROLL DOWN FOR ARTICLE

Taylor & Francis makes every effort to ensure the accuracy of all the information (the "Content") contained in the publications on our platform. However, Taylor & Francis, our agents, and our licensors make no representations or warranties whatsoever as to the accuracy, completeness, or suitability for any purpose of the Content. Any opinions and views expressed in this publication are the opinions and views of the authors, and are not the views of or endorsed by Taylor & Francis. The accuracy of the Content should not be relied upon and should be independently verified with primary sources of information. Taylor and Francis shall not be liable for any losses, actions, claims, proceedings, demands, costs, expenses, damages, and other liabilities whatsoever or howsoever caused arising directly or indirectly in connection with, in relation to or arising out of the use of the Content.

This article may be used for research, teaching, and private study purposes. Any substantial or systematic reproduction, redistribution, reselling, loan, sub-licensing, systematic supply, or distribution in any form to anyone is expressly forbidden. Terms & Conditions of access and use can be found at http://www.tandfonline.com/page/terms-and-conditions

Downloaded by [UQ Library] at 05:11 27 September 2013

International Journal of Geographical Information Science, 2013
Vol. 27, No. 2, 363–384, http://dx.doi.org/10.1080/13658816.2012.692372

Taylor & Francis
Taylor & Francis Group

A parallel computing approach to viewshed analysis of large terrain data using graphics processing units

Yanli Zhao[a,b], Anand Padmanabhan[a,b,c] and Shaowen Wang[a,b,c,d,e]*

[a]*CyberInfrastructure and Geospatial Information Laboratory, University of Illinois at Urbana-Champaign, Urbana, IL, USA;* [b]*Department of Geography and Geographic Information Science, University of Illinois at Urbana-Champaign, Urbana, IL, USA;* [c]*National Center for Supercomputing Applications, University of Illinois at Urbana-Champaign, Urbana, IL, USA;* [d]*Department of Computer Science, University of Illinois at Urbana-Champaign, Urbana, IL, USA;* [e]*Department of Urban and Regional Planning, University of Illinois at Urbana-Champaign, Urbana, IL, USA*

(*Received 31 December 2011; final version received 4 April 2012*)

Viewshed analysis, often supported by geographic information system, is widely used in many application domains. However, as terrain data continue to become increasingly large and available at high resolutions, data-intensive viewshed analysis poses significant computational challenges. General-purpose computation on graphics processing units (GPUs) provides a promising means to address such challenges. This article describes a parallel computing approach to data-intensive viewshed analysis of large terrain data using GPUs. Our approach exploits the high-bandwidth memory of GPUs and the parallelism of massive spatial data to enable memory-intensive and computation-intensive tasks while central processing units are used to achieve efficient input/output (I/O) management. Furthermore, a two-level spatial domain decomposition strategy has been developed to mitigate a performance bottleneck caused by data transfer in the memory hierarchy of GPU-based architecture. Computational experiments were designed to evaluate computational performance of the approach. The experiments demonstrate significant performance improvement over a well-known sequential computing method, and an enhanced ability of analyzing sizable datasets that the sequential computing method cannot handle.

Keywords: viewshed analysis; general-purpose computation on graphics processing units; parallel computing; spatial data analysis

Downloaded by [UQ Library] at 05:11 27 September 2013

1. Introduction

Viewshed analysis is a widely used spatial analysis, often supported by geographic information systems (GIS) to determine regions of a terrain that are visible from a set of specified locations (Fisher 1993). Many spatial analyses, such as site selection, path planning, navigation, landscape planning, and environmental change detection increasingly require data-intensive computation of viewshed analysis of high-resolution digital elevation datasets (Nagy 1994, De Floriani *et al*. 1994, Franklin and Ray1994, Fisher 1995, De Floriani and Magillo 2003, Jiang *et al.* 2011). For example, an elevation dataset derived from light detection and ranging (LIDAR) instruments with one sample (4 bytes used to

*Corresponding author. Email: shaowen@illinois.edu

© 2013 Taylor & Francis

represent each sample) per 1 m^2 had the size of approximately 689 GB for the state of Washington in the United States (Fishman *et al*. 2009). To analyze spatial data of such a size or even larger, conventional sequential computing approaches become unsuitable, and the use of parallel computing – now a mainstream of scientific computing – is necessary.

When massive spatial data are treated, only a small fraction of input data can be held in the main memory and various levels of caches in a computer at any given time. Hence, data need to be transferred across various levels of storage and memory hierarchy (e.g., disk, memory, and cache), which may contribute a major performance bottleneck to applications. Specifically for viewshed analysis, the basic computation procedure involves the calculation of visibility of a target location from a specific source viewpoint *v*. This calculation is usually implemented by emanating a line-of-sight (LOS) ray from viewpoint *v* to that target location. This procedure, however, may result in irregular accesses to various parts of input terrain data, causing significant cache misses and extensive input/output (I/O) accesses if conducted without optimization or approximation. Therefore, the computation tends to be memory bandwidth-bound and I/O intensive.

I/O-efficient algorithms, also known as external-memory algorithms, can be developed for viewshed analysis to reduce data swapping between disk and main memory of a computer for improving the overall performance of handling large datasets (Magalhaes *et al*. 2007, Fishman *et al*. 2009, Haverkort *et al*. 2009). However, even with these improvements, the computing time of exact algorithms remains significant, primarily because such algorithms were predominantly designed to work on a single-processor computer system. The computation of viewshed analysis against large terrain data entails a massive number of LOS-based calculations, for which conventional sequential computing approaches are unable to support efficiently or effectively.

Parallel computing has become the mainstream of computer architecture with tremendous potential in advancing geographic information science (Wang and Armstrong 2009, Wang and Liu 2009). As for viewshed analysis, parallel processing techniques have been applied to improve computational performance (Mills *et al*. 1992, Teng *et al*. 1993, Strnad 2011, Fang *et al.* 2011, Gao *et al.* 2011). However, these previous work assumed that input data as a whole can be handled within the main memory of a computer. Hence, this assumption is not applicable to processing massive terrain data due to infeasibility of holding all input data within main memory during the computation of an entire analysis. Distributed computing of viewshed analysis was also introduced in literature (De Floriani *et al*. 1994, Ware *et al*. 1998), which used a cluster of computers with each one of them processing a big chunk of decomposed input data based on sequential algorithms. These distributed computing approaches can meet the memory requirement of large input datasets. The performance improvement is, however, rather limited since each computer still uses the sequential algorithms for data processing.

This research focuses on resolving data-intensive challenges in viewshed computation through the general-purpose computation on graphics processing units (GPGPUs). Graphics processing units (GPUs) have been recently used in a large number of application domains, since they can provide significant computational power with affordable cost, and their programmability has improved as well (Owens *et al*. 2007). Generally, GPUs are designed to exploit data parallelism, and it has been reported that GPUs can achieve 10 times more floating-point operations per second (FLOPS) compared to central processing units (CPUs) (Govindaraju *et al*. 2006, Owens *et al*. 2007, Che *et al*. 2008, Ryoo *et al*. 2008, Kirk and Hwu 2010). Furthermore, data-intensive applications can benefit from the high-bandwidth memory of GPUs (Kirk and Hwu 2010). Another advantage of using GPUs is that while GPUs are dedicated to computing tasks,

Downloaded by [UQ Library] at 05:11 27 September 2013

CPUs can be engaged to perform I/O management functions thereby enhancing I/O performance.

The primary purpose of our research is to exploit spatial data parallelism, efficient GPU memory, and I/O access in viewshed analysis of large spatial data. A parallel computing approach, based on GPU using the NVIDIA compute unified device architecture (CUDA), is designed with a focus placed on mitigating the performance bottleneck caused by data transfer across disk, CPU memory, GPU memory, and processors. Our specific strategies include: (1) a two-level spatial domain decomposition that is mapped to the memory hierarchy of a computer system (i.e., disk to CPU main memory to GPU off-chip memory, and GPU off-chip memory to on-chip fast memory); (2) reuse of data transferred from disk; and (3) a massively parallel processing method. These strategies are designed to be portable to any computer system equipped with CUDA-enabled GPUs, either personal computers or high-performance cluster computers. Computational experiments have shown more than 50 times speedup could be obtained without losing accuracy, by comparing our approach to a well-known sequential algorithm – *R3* – (Shapira 1990) on small datasets (<4 GB), as well as the capability to process large datasets that the sequential algorithm cannot handle. Moreover, by efficiently loading data into on-chip shared memory, up to three times of speedup were achieved compared to using off-chip memory only.

In the remainder of this article, Section 2 reviews the background related to this research. Section 3 illustrates the well-known single-processor sequential algorithm for viewshed analysis. Regarding our parallel computing approach based on GPUs, Section 4 describes our specific strategies, implementations, and theoretical analysis. Section 5 details the computational experiments that are designed to evaluate the performance of the GPU-based approach. The concluding section summarizes the findings of this research and future research directions.

Downloaded by [UQ Library] at 05:11 27 September 2013

2. Background

2.1. Visibility

Viewshed analysis of terrain can be based on either of two classes of digital elevation models studied in geographic information science: triangulated irregular networks (TINs) and regular square grids (RSGs) (De Floriani and Magillo 2003). A terrain represented based on TIN consists of a collection of planar, irregular triangular patches. RSG is commonly used for terrain representation, and often consists of equally sized rectangles or grid cells. Results of viewshed analysis based on RSG are usually encoded by marking every grid cell visible or invisible with Boolean values. Such discrete viewshed is sufficiently accurate, since grid-based terrain representation often has fine granularity (De Floriani and Magillo 2003). Furthermore, grid regularity is suitable for supporting the development of parallel processing techniques. Consequently, this research focuses on computing viewshed against RSG-based terrain datasets. The basic step of viewshed analysis of grid terrain involves the calculation of visibility of every grid cell from a given viewpoint v. We will give the definition of visibility on grid terrain and introduce the algorithm we adopt for its calculation.

2.1.1. Problem definition

Let T be a grid terrain represented as a uniform grid of $n \times n$ square cells. Without losing generality, the elevation of each grid cell's center is chosen to represent that of the entire cell (Van Kreveld 1996, Fishman *et al*. 2009, Haverkort *et al*. 2009). Visibility of any grid

cell P, called *target cell*, is based on the LOS emanating from any given viewpoint v to the center point p of P. The elevation angle of P with respect to viewpoint v is defined as

$$\text{ElevAngle}(P) = \arctan\left(\left(E_p - E_v\right)/D_{vp}\right) \tag{1}$$

where E_p and E_v are the elevations of p and v, respectively, and D_{vp} is the distance between p and v (Haverkort *et al*. 2009). We adopt the following definition of visibility: the target cell P is visible from v if and only if the elevation angle of P is larger than the elevation angle of any cell intersected by the LOS from v to p in the projection of T on a horizontal plane, called domain D (see Figure 1) (Van Kreveld 1996, Fishman *et al*. 2009, Haverkort *et al*. 2009). We denote the cells intersected by the LOS from v to p as *intersected cells*.

2.1.2. Amanatides and Woo's traversal algorithm

To calculate the visibility of a target cell, the cells intersected by the projected LOS from v to the center of the target cell need to be identified. Bresenham's line algorithm (Bresenham 1965) and digital differential analyzer (DDA) (Mayorov 1964) are the commonly used algorithms to compute such intersected cells. Bresenham's line algorithm is based on integer arithmetic, considering only integral row and column coordinates of cells. Though fast computation is an advantage, it is not accurate when the endpoints of a line are not at the center of cells, due to rounding errors from converting floating-point to integer coordinates. In contrast, the DDA method employs floating-point arithmetic, which leads to more accurate computation of intersection results compared to Bresenham's line algorithm. In this research, we adopt a variant of the DDA line algorithm – the Amanatides and Woo's traversal algorithm (Amanatides and Woo 1987).

The Amanatides and Woo's algorithm consists of two phases: initialization and incremental traversal (Figure 2). The integer variables X and Y are initialized to the starting cell's column and row coordinates. The *tVertical* variable is initialized as the length of the line segment from the line's starting point to the point where the line crosses the first cell boundary in the vertical direction. *tHorizontal* is initialized in a similar fashion where the line crosses the first cell boundary in the horizontal direction. The variables *tDeltaV* and *tDeltaH* indicate how far the line must move from the current cell to crossing the next cell boundary in vertical and horizontal directions, respectively. The variables *stepX* and *stepY* are initialized to either 1 or −1 indicating whether X and Y are incremented or decremented as the line crosses cell boundaries.




Figure 1. (a) Grid terrain T; (b) Domain D; shaded cells are intersected cells.

Downloaded by [UQ Library] at 05:11 27 September 2013




Figure 2. Amanatides and Woo's traversal algorithm: (a) initialization; (b) incremental traversal.

Downloaded by [UQ Library] at 05:11 27 September 2013

The incremental phase of the traversal algorithm is outlined in the basic loop in Figure 2b. The next intersected cell at any step is determined by comparing the *tVertical* and *tHorizontal* variables that are incrementally updated using *tDeltaV* and *tDeltaH* per iteration. The smaller of these two values indicates whether the line will cross the current cell boundary in vertical or horizontal direction and consequently the identity of the next intersected cell. The impact of this cell on the visibility of the target cell is computed by a function *ProcessCell*() as follows: if the elevation angle of the intersected cell is larger than that of the target cell, then the target cell is marked as invisible, and the loop terminates. Otherwise, it continues to the next iteration. As a result, when the target cell is visible, the algorithm will loop until the end of the line and thus traverse all intersected cells, which equals the number of horizontal and vertical cell boundary crossings. Overall, this algorithm is fast since it requires only one floating-point comparison, one floating-point addition, and one integer addition per iteration.

2.2. GPGPU overview

Our research uses NVIDIA CUDA-enabled GPUs. The processor layout, memory hierarchy, and CUDA thread model are illustrated using Figure 3 (NVIDIA Corporation 2009). We highlight the following features that make them suitable for data-intensive spatial analysis applications like ours.

(1) Massive data parallelism: CUDA-enabled GPUs are designed to exploit massive data parallelism. A large number of processor cores are organized into a set of stream multiprocessors (SMs). These SMs are exploited to achieve high FLOPS by employing massive threads in CUDA. CUDA programming can be deemed as a single program multiple data programming model. Hence, application developers specify data-parallel functions called *kernels* that are invoked by CPU called *host* to run on GPU devices across a large amount of parallel threads, each executing an instance of the kernel. These threads are organized into thread blocks and grids of thread blocks, and each thread is uniquely identified by its block and thread ID.
(2) Dedicated memory interface: Such GPUs also have a large pool of dedicated high-bandwidth global memory, a small amount of fast on-chip memory called shared




Figure 3. An architectural illustration of NVIDIA CUDA-enabled GPUs (NVIDIA Corporation 2009).

memory and a certain number of register files. These memory resources can be flexibly assigned to threads for achieving a desirable memory access performance. In particular, each thread can privately access its register files. Threads within the same thread block are allowed to access on-chip shared memory. Threads from different thread blocks can share the global memory and can communicate via kernel-wide synchronization.

(3) Pipeline scheduling: The massively parallel threads are scheduled to SMs in pipeline that can mitigate global memory access latency. Due to limited hardware resources, such as the size of register files, shared memory, and thread scheduling slots, an SM can hold only a certain number of thread blocks simultaneously. The ratio of active threads residing in the SM to the maximum number of threads supported on an SM of the GPU is called multiprocessor occupancy. For memory bandwidth-bound applications, increasing occupancy can help better mitigate the latency of global memory accesses (NVIDIA Corporation 2010).

In the following sections, we describe our approach to designing and implementing a method for viewshed analysis that will exploit these features of CUDA GPUs to achieve scalable computing and desirable memory performance for analyzing sizable terrain datasets.

3. R3 sequential algorithm

R3 is a well-known sequential algorithm for the viewshed analysis of grid terrain (Shapira 1990, Franklin and Ray 1994, Van Kreveld 1996, Izraelevitz 2003). For example, it is used in the open source GRASS GIS software. The algorithm calculates the visibility of each target cell by running a separate LOS emanating from v to every target cell on the grid terrain, which can be implemented using the method described in Section 2.1.2. Since the target cells can be processed independently, this algorithm is well suited to parallel processing. Though a number of approximation algorithms have been developed in

Downloaded by [UQ Library] at 05:11 27 September 2013

viewshed analysis (Blelloch 1990, Franklin and Ray 1994, De Floriani and Magillo 2003), they are not employed in this article since accuracy of viewshed analysis is an important consideration for a number of applications. Furthermore, enabled by the computational capabilities offered by GPUs, we believe exact computation of viewshed for large datasets can be tractable. Van Kreveld's radial sweep algorithm (1996) presents a fast sequential algorithm for calculating viewshed with accuracy equivalent to the *R3* algorithm; however, a high degree of sequential dependencies in Van Kreveld's algorithm makes it less suitable to exploit parallelism. *R3* is hence chosen as the basis for developing our parallel approach on GPUs.

3.1. Computational challenges of R3 algorithm

R3 algorithm includes four major steps (Figure 4). In step 2, the algorithm loops through every target cell in the input grid, while in step 3 all intersected cells of a target cell are traversed. This traversal can employ the Amanatides and Woo's traversal algorithm. The *R3* algorithm is hence compute-intensive, with a computational complexity of $O(n^3)$ considering an input dataset containing $n \times n$ raster cells. In addition, it is observed that though target cells are processed in a row-major order, their intersected cells are accessed in a sequence defined by LOS during computation. This leads to an irregular data access pattern that is prohibitively expensive because it causes significant cache misses. Furthermore, if an input dataset is too large to be fully loaded in memory, extensive disk I/O accesses are also expected, which may cause the degradation of computational performance.

3.2. Spatial characteristics of R3 algorithm

To improve computational performance while maintaining the accuracy of analysis results, we aim to exploit the spatial characteristics exhibited by the *R3* algorithm. Specifically,




Figure 4. Major steps of *R3* sequential algorithm.

Downloaded by [UQ Library] at 05:11 27 September 2013

these characteristics include: spatial independency, locality, and occlusion, which are described as follows.

(1) Spatial independency: Each target cell can be processed independently. This independence indicates spatial data parallelism that may be exploited to engage many parallel threads to calculate the visibility of many target cells.
(2) Spatial locality: Typically a cell on a grid terrain is intersected by LOS rays to multiple target cells and could be reused. Furthermore, this intersection is more likely when LOS rays to target cells in the same neighborhood are being computed. Consequently, the computation of LOS exhibits spatial locality with respect to neighboring target cells. This spatial locality makes it possible for the neighboring target cells grouped into a larger spatial unit to facilitate data reuse, which has the potential to be exploited to improve data access performance.
(3) Occlusion: Data needed for computing visibility of grouped target cells can be occluded. A *tile* is defined as a regular (e.g., square or rectangle shaped) spatial domain consisting of neighboring target cells and can also be organized as a set of neighboring sub-tiles with each including a smaller number of target cells. To understand occlusion, imagine that a radial line sweeps clockwise around a viewpoint v, and that the point at which the line first intersects the tile is called *start point* of the tile while the *end point* is specified as the radial line that last intersects the identified tile. Then, all the required data for the tile are occluded by the two lines from v to the start point and to the end point of the tile. This characteristic of occlusion is useful to identify what data may be pre-fetched for grouped neighboring target cells, and to make data reuse feasible.

Massive computation, memory, and I/O accesses are three primary challenges of viewshed computation using *R3* algorithm for large datasets. Our GPU-based parallel computing approach described in Section 4 is developed to tackle these challenges.

4. GPU-based parallel computing approach

Our GPU-based parallel computing approach exploits both GPUs' features and spatial characteristics of the *R3* viewshed analysis algorithm. Four specific strategies: coarse-scale spatial domain decomposition, tile-based moving window, fine-scale spatial domain decomposition and scalable parallel processing are developed to resolve the challenges of massive computation, memory, and I/O accesses. The essence of these strategies is three-fold: (1) transfer data in contiguous blocks from disk to global memory to shared memory, which is achieved by the two-level (coarse- and fine-scale) spatial domain decomposition strategies; (2) reuse the transferred data on GPU device whenever possible, which is realized by our two-level decomposition and tile-based moving window strategies; and (3) employ a large number of parallel threads to perform computationally intensive visibility computation efficiently. The first two are designed to reduce the number of memory and I/O accesses, while the third provides the significant computing power demanded by massive computation of the viewshed analysis algorithm.

In the following subsections, we first describe details of these strategies and then conduct a formal analysis of computing intensity.

Downloaded by [UQ Library] at 05:11 27 September 2013




Figure 5. Coarse-scale spatial domain decomposition.

Note: Dark-shaded square is a target tile, and light-shaded squares are intersected tiles of the target tile.

4.1. *Coarse-scale spatial domain decomposition*

When terrain data are large and cannot be held in memory all at once, intersected cells have to be fetched on the fly from disk in a sequence defined by LOS during calculation for each target cell. This irregular disk access may result in extensive long-latency I/O accesses and become a major performance bottleneck. In order to resolve this problem, we decompose an input grid into tiles, each of which consists of a certain number of cells. A *target tile* consists of a set of neighboring target cells. *Intersected tiles* are those occluded by lines from viewpoint v to the *start point* and to the *end point* of the target tile (Figure 5); and they can be identified using the Amanatides and Woo's algorithm. Based on this decomposition, we pre-fetch the required intersected tiles into GPU global memory for each target tile before computation. This achieves the desired regular data access pattern for data to be loaded consecutively from disk to memory. Furthermore, because of the characteristic of spatial locality between target cells, these cells within the same target tile can share and reuse the data pre-fetched. Thus, the number of I/O accesses to disk is reduced.

This decomposition strategy is designed to operate at coarse-scale and aims to place any target tile and all its intersected tiles in the GPU global memory at once, which imposes a limit on tile sizes and the number of tiles that can be loaded. Consequently, we let the upper bound of the number of required intersected tiles for a target tile be equal to the maximum number of tiles allowed in global memory, Max_t, and each tile has $n_t \times n_t$ cells. Then the values of n_t and Max_t can be obtained as follows.

Given an input grid with $n \times n$ cells, without losing generality, we assume that n can be evenly divided by n_t throughout the article, and thus, there are $(n/n_t) \times (n/n_t)$ tiles in the grid. In the worst case, when the viewpoint v is in the corner tile, that is, assume the tile's column and row coordinates in the grid is $(0, 0)$, and the farthest target tile from v is in the other diagonal corner of the grid, $(n/n_t, n/n_t)$, the number of required intersected tiles is maximal and is upper bounded by

$$2\,(n/n_t + n/n_t) = 4\mathrm{n}/n_t \tag{2}$$

Downloaded by [UQ Library] at 05:11 27 September 2013

where $(n/n_t + n/n_t)$ equals the number of horizontal and vertical tile boundary crossings, which is also the maximum number of intersected tiles along a line from v to the farthest target tile in the grid according to the traversal algorithm (see Section 2.1.2). $2(n/n_t + n/n_t)$ denotes that the number of intersected tiles occluded by two lines from v to the start point and the end point of the target tile is at most doubled, since there is no tile completely occluded by the two lines. The proof is illustrated in Figure 5. As a result, the following equation is obtained:

$$\mathrm{Max}_t = 4\mathrm{n}/n_t \tag{3}$$

Let the global memory capacity be M bytes and 4 bytes are used to represent a cell's elevation, then $\mathrm{Max}_t \times n_t^2 \times 4 = 4\mathrm{n}/n_t \times n_t^2 \times 4 \leq M$ and

$$n_t \leq M/16n \tag{4}$$

Hence, in order to process any target tile in global memory, n_t can be at most $M/16n$. In our implementation, we let n_t be its maximal value $M/16n$ so as to minimize the total number of iterations to process $(n/n_t)^2$ target tiles.

4.2. Tile-based moving window

Each time a target tile is processed, the target tile and its intersected tiles need to be transferred to GPU global memory. This may result in large data being transferred to GPU global memory from disk, which could negatively impact computational performance. To reduce the amount of data transferred to global memory, a tile-based moving window strategy is designed to exploit the spatial locality characteristic between neighboring target tiles. The strategy increases the reuse of intersected tiles that are already in the global memory and, thus, reduces the number of I/O accesses.

As illustrated in Figure 6, when a new target tile starts to be processed, the linear indices (row-coordinate $\times$ the number of tiles in a row + column-coordinate) of its intersected tiles are calculated, and compared to a list of indices of tiles that are already in global memory. Intersected tiles required by the new target tile need to be transferred into global memory and add its index to the list only in cases they are not already in. If the maximum number of tiles that can be held in memory is exceeded, tiles in the list that are least-frequently used and not required by the new target tile are removed from global memory. The row-major order of processing target tiles exploits the spatial locality characteristic of the underlying algorithm, which ensures improved performance by increasing data reuse. Compared to this improvement, the cost incurred by this strategy (i.e., comparing and sorting the list of indices of tiles in global memory) is oftentimes trivial, since the maximal list size $\mathrm{Max}_t = 4n/n_t$ is small considering the tile size n_t is usually large.

To implement this strategy, we have designed two array data structures (see Figure 6): *List_Indices* array is the list of linear indices of tiles in global memory, and *List_Tiles* array stores pointers referring to memory addresses of these tiles. *List_Tiles* [i] and *List_Indices* [i] maintain the information of the same tile. This implementation facilitates quick memory reference to access data and thus improves performance. For example, if data in a tile are requested during computation, we first use binary search in *List_Indices* to find its index and return the array entry i, then the data within the tile can be accessed via its memory address *List_Tiles* [i] directly.

Downloaded by [UQ Library] at 05:11 27 September 2013




Figure 6. An example of moving tiles to and from GPU global memory.

Note: For a new target tile, a light shade of color represents its required tiles that are already in global memory, white color denotes a new required tile transferred to memory, and the dark shade of color shows an unrequired tile removed from global memory.

4.3. *Fine-scale spatial domain decomposition*

On CUDA-enabled GPUs, the most favorable regular access pattern is achieved when the same instruction for threads of consecutive IDs accesses consecutive global memory locations. In this case, hardware coalesces these consecutive accesses into a consolidated access to the memory and, thus, can reduce the number of global memory accesses and achieve efficient use of high-bandwidth global memory (Kirk and Hwu 2010). If pre-fetched tiles in global memory are accessed without data rearrangement during computation, however, consecutive threads load their data from global memory in a sequence defined by LOS and these data are oftentimes not consecutively stored. Consequently, it may result in a large amount of irregular data accesses from long-latency global memory and, thus, becomes a performance bottleneck.

To eliminate irregular data accesses from global memory, our fine-scale decomposition strategy takes advantage of fast on-chip shared memory on GPU by emphasizing the importance of exploiting multi-scale spatial parallelism. Specifically, tiles in global memory are further decomposed into sub-tiles that are organized as *target sub-tiles* and *intersected sub-tiles*, as shown in Figure 7. One target sub-tile is processed by a thread block, which pre-fetches its required intersected sub-tiles from global memory to shared memory in the desired regular access pattern, and then accesses pre-fetched data in shared memory on the fly during computation. In this way, we achieve regular data access pattern to long-latency global memory, and shift these irregular accesses to shared memory that is much faster. As a result, an overall efficient memory access is achieved. Furthermore, because of the spatial locality of the *R3* algorithm, data in shared memory can be reused and shared by cells in the same target sub-tile, which can further reduce the number of global memory accesses.

Since the fine-scale decomposition strategy maps each target sub-tile to one thread block, the size of sub-tile is determined based on the size of thread block. This mapping is described in the immediately following Section 4.4. Thread block size is often

Downloaded by [UQ Library] at 05:11 27 September 2013




Figure 7. Fine-scale spatial domain decomposition.

Note: Squares with bold boundary are tiles; the dark-shaded square represents a target sub-tile, and the light-shaded squares are intersected sub-tiles of the target sub-tile.

Downloaded by [UQ Library] at 05:11 27 September 2013

experimentally tuned, oftentimes based on the consideration of hardware specifications such as the size of register files and shared memory. The performance tuning is discussed in Section 5.

4.4. Parallel processing

The spatial data parallelism attributed to the spatial independency characteristic of the *R3* algorithm is exploited for engaging parallel threads to simultaneously process target cells in a tile. Figure 8 shows an example of how target cells can be mapped to threads




Figure 8. An example of mapping data block and thread block: one thread processes one target cell.

Note: The light shade of color represents a thread, and the dark shade of color denotes target cells that the thread processes. *BlockID.y* and *BlockID.x* are row and column indices of thread blocks in a grid, respectively. *threadID.y* and *threadID.x* are row and column indices of threads in a thread block. *BlockDim.y* and *BlockDim.x* are the number of rows and columns in a thread block. (*BlockID.y, BlockID.x, threadID.y, threadID.x*) uniquely identifies a thread. (*row, col*) are row and column indices of target cells in a data block.

in a block. In our approach, fine-scale parallelism is exploited by assigning each thread to process a single target cell. Hence, the total number of threads allocated on GPUs is the same as the number of target cells in the target tile. These threads are organized into thread blocks, and each of them processes one target sub-tile. There is no cooperation between different thread blocks, which are transparently scheduled to GPU SMs in pipeline. Within a thread block, threads can be coordinated through barrier synchronization and sharing data in on-chip shared memory. However, the capacity of shared memory is usually small, so it cannot hold all the intersected sub-tiles required by a target sub-tile. These intersected sub-tiles need to be dynamically loaded from global memory to shared memory through the coordination of a thread block in multiple iterations. Our implementation guarantees that shared memory can contain at least one intersected sub-tile.

The working process of a thread block is as follows. After the thread block has already loaded one intersected sub-tile in shared memory, each thread in this block starts to calculate the visibility of a target cell. In doing so, a thread first finds the starting intersected cell from the intersected sub-tile in shared memory (Figure 9) and then traverses the next intersected cells in this sub-tile if necessary based on the traversal algorithm (see Section 2.1.2). During this process, the threads may finish at different timestamps, but they are eventually synchronized so that all the threads finish processing an intersected sub-tile in shared memory. After the processing of this intersected sub-tile is finished, the block of threads will determine whether to process the next intersected sub-tile or not. If there is at least one thread in the thread block, whose target cell is still deemed to be potentially visible, this thread needs intersected cells in the next intersected sub-tiles and all the threads in the block need to load the next intersected sub-tile from global memory into shared memory. If all cells in the target sub-tile are known as invisible, then it means that the thread block

Downloaded by [UQ Library] at 05:11 27 September 2013




Figure 9. Finding the starting intersected cell from the intersected sub-tile in shared memory for a target cell.

Note: Assuming that the origin (*0, 0*) of a Euclidian coordinate system is at the top left of an input grid, (*x, y*) is coordinates of the starting intersection of LOS ray with the intersected sub-tile and (X_{start}, Y_{start}) is the column and row indices of the starting intersected cell in the grid.

finishes all the work and no more processing is needed. Otherwise, the thread block may continue its computing process until the last intersected sub-tile is processed.

In our implementation, in order to control the synchronization and cooperation, we define a shared Boolean variable *Flag*. Every time after loading one intersected sub-tile into shared memory, it is reset as *0*. After processing this sub-tile, the value of this flag could be either unchanged or updated to 1*;*–1, which indicates that there is at least one cell in the target sub-tile being considered to be possibly visible and all the threads need to load the next intersected sub-tile, while a value of 0 means all cells in the target sub-tile are known as invisible and the thread block finishes all the work. Figure 10 outlines the pseudo code of the computing process. Overheads incurred in the computing process, including instructions for computing intersected sub-tile indices and synchronization of threads, are insignificant compared to performance gains contributed by our parallel computing strategies applied. The performance improvements are described in Section 5.

Downloaded by [UQ Library] at 05:11 27 September 2013

4.5. Computing intensity

The computing intensity of our approach varies as each different viewpoint v is usually associated with a different set of visible cells n_v and invisible cells n_{iv}. For each visible cell P_v, our approach traverses all the intersected cells from v to P_v and, thus, the time of deriving each visible cell increases as the distance between v and P_v increases and is denoted by D_{vP_v}. In contrast, for each invisible cell P_{iv}, the traversal terminates once the first obstruction cell P_{fo} is found and, hence, invisible cells are potentially computed faster than visible cells. The time of deriving each invisible cell also increases with the distance

```
Kernel program for each thread

__shared__ volatile Boolean flag
…….

while the intersected cells in the grid are not traversed to the end
        __syncthreads()    //all the threads in the block are synchronized
        flag = 0
        __syncthreads()

        if the target cell may be visible
        then flag=1

        ……..

        __syncthreads()
        if flag==1
        then load the next intersected sub-tile into shared memory
                while the intersected cells in the intersected sub-tile is not
                traversed to the end
                        if the target cell is not invisible
                            then access its intersected cells in the shared
                            memory and compute its visibility
                        otherwise break
        otherwise break
```

Figure 10. Pseudo-code for the working process of a thread block.

between v and P_{fo} and is denoted by D_{vf_o}. As a result, the total computing time is a function defined as follows:

$$f\left(n^2, \sum D_{vP_v}/n_v, \sum D_{vf_o} n_{iv}\right) \tag{5}$$

where n^2 represents the number of input cells; $\sum D_{vf_v}/n_v$ denotes the average distance from v to all of the visible cells; and $\sum D_{vf_o}/n_{iv}$ denotes the average distance from v to all of the first obstruction cells. Furthermore, the total computing time is positively correlated with each of these three factors. In Section 5, description of a set of experiments shows variations of computing time with different viewpoints specified.

5. Computational experiments

A suite of computational experiments was designed to evaluate computational performance of our parallel computing approach to viewshed analysis of large grid terrain datasets.

We compared among our two GPU-based parallel algorithms and the *R3* sequential algorithm. The two GPU-based algorithms include *GPU-fine*, which has been described in Section 4, and *GPU-coarse*, which has been developed as a baseline to provide effective evaluation of performance gains by the fine-scale spatial domain decomposition strategy. Unlike *GPU-fine*, the *GPU-coarse* algorithm does not exploit on-chip shared memory or fine-scale spatial domain decomposition strategy. To facilitate fair comparisons, all three algorithms are based on the same traversal algorithm described in Section 2.1.2. Single floating-point precision is used for representing elevation features, and computing intersections.

Programming language and computing environment: *R3, GPU-fine*, and *GPU-coarse* were written using the standard ANSI C programming language and CUDA SDK version 4.0, and they were compiled with optimization level –O2. All were tested on the Accelerator Cluster named AC cluster (Kindratenko *et al*. 2009) at the National Center for Supercomputing Applications (NCSA), where we used computing nodes consisting of a CPU (dual-core 2.4 GHz AMD Opteron, 8 GB RAM) and one NVIDIA Tesla S1070 containing 4 GT200 GPUs (each with 240 CUDA cores, 4 GB global memory, 16 KB shared memory, and 16 KB 32-bit register files per SM and CUDA compute capability 1.3). We ran experiments on a single-core of CPU and a single GPU card. To ensure fair comparisons among the three algorithms, we assured that both CPU main memory and GPU global memory have 4 GB capacity.

Datasets: Seven terrain datasets (Figure 11) were used. These datasets cover the state of Utah in the United States and are 1-m rasters sampled from the 30-m National Elevation Dataset (NED) provided by the US Geologic Survey (http://ned.usgs.gov/), using ArcGIS 10 (ESRI 2011) bilinear sampling tool. These datasets represent various sizes of terrains ranging from 400 million to over 5 billion cells (Table 1), and all cells in each dataset have valid elevations. These datasets were chosen because they include mountainous areas that provide a variety of topographic features (e.g., pits, peaks, ridge, and ravine (Lee 1991)) for different viewpoint selections, making them ideal for comparing how these spatial features affect computational performance.

5.1. Performance tuning of GPU-fine and GPU-coarse

Increasing the multiprocessor occupancy (see Section 2.2) can help reduce the influence of the latency of global memory access and, thus, improve computational performance,

Downloaded by [UQ Library] at 05:11 27 September 2013




Figure 11. Test datasets used for the experiments: the bounding boxes of seven test datasets are shown in green.

Table 1. Size of terrain datasets.

Dataset	Cells	Size (bytes)	Maximum elevation (m)	Minimum elevation (m)	Average elevation (m)	Standard deviation (m)
1	20,000 × 20,000	1.49G	1900.29	1419.99	1467.29	32.69
2	28,000 × 28,000	2.92G	2803.43	1410.19	1559.78	195.52
3	33,280 × 33,280	4.13G	2951.91	1407.10	1617.78	247.68
4	46,080 × 46,080	7.91G	2951.91	1387.14	1659.92	261.92
5	57,024 × 57,024	12.11G	2951.91	1387.14	1668.93	244.98
6	65,280 × 65,280	15.88G	2951.91	1387.14	1712.70	277.58
7	74,256 × 74,256	20.54G	3082.65	1387.14	1764.89	316.46

Downloaded by [UQ Library] at 05:11 27 September 2013

especially for memory bandwidth-bound applications such as viewshed analysis. Multiprocessor occupancy can be optimized by tuning the usage of registers and shared memory, and thread block size. Our experiments focused on tuning thread block size so as to maximize the multiprocessor occupancy for both *GPU-coarse* and *GPU-fine* algorithms using CUDA GPU Occupancy Calculator (NVIDIA Corporation 2010). The tuning tests revealed 256 as the optimal numbers of threads per block for both *GPU-coarse* and *GPU-fine* algorithms.

5.2. Performance comparison among R3, GPU-fine, and GPU-coarse

To determine the variation of computation time over different topography, we selected three different kinds of viewpoints for each dataset. One viewpoint was a peak on the terrain, another one was a pit and the last one was selected in areas that do not have significant topographic variation.

The resulting visibility maps of *GPU-coarse* and *GPU-fine* were verified by comparing to those of *R3*. *GPU-coarse* and *R3* produced the same results. There was minor difference between *GPU-fine* and *GPU-coarse* (or *R3*), which are caused by the fine-scale

decomposition requiring the computation of the starting intersected cell every time after loading one intersected sub-tile into the shared memory (see Figure 9). This starting cell is computed using different floating-point operations from those in *GPU-coarse* that identify each intersected cell using the traversal algorithm only (see Section 2.1.2). It should be noted that due to difference in floating-point calculations the intersected cells identified by *GPU-fine* and *GPU-coarse* could be slightly different, resulting in not exactly the same visibility maps. To quantify such difference, we tested all seven datasets for *GPU-fine* and *GPU-coarse* based on the three selected viewpoints and found that the average difference is smaller than 0.00002%.

Table 2 summarizes computation times of the three algorithms for the seven datasets. Overall, benefiting from our parallel computing strategies, *GPU-fine* greatly reduces the accumulative time-span of analyses, comparing to *R3* and *GPU-coarse.* Both *GPU-fine* and *GPU-coarse* are capable of processing sizeable datasets that *R3* cannot handle, which is enabled by our domain decomposition and moving window strategies. For instance, when the dataset is 20.54 GB, five times the memory capacity of 4 GB, our parallel algorithms can still finish computation within reasonable time.

Downloaded by [UQ Library] at 05:11 27 September 2013

5.2.1. Computing performance

Computing times of the three algorithms vary on three different viewpoints selected and input data size *n* (Table 2). Given the same *n*, the computing time for a peak viewpoint is

Table 2. Computation time of *R3, GPU-coarse*, and *GPU-fine* for seven datasets.

		R3(second)		*GPU-coarse (second)*		*GPU-fine (second)*	
Dataset (bytes)	*VP*	*Comp*	*All*	*Comp*	*All*	*Comp*	*All*
1.49G	Pit	16917	16942	203	229	179	205
	Flat	16642	16667	293	319	315	341
	Peak	24971	24996	354	380	357	383
2.92G	Pit	35 *h*	35 *h*	903	997	849	943
	Flat	60 *h*	60 *h*	920	1014	866	960
	Peak	85 *h*	85 *h*	2118	2212	2348	2442
4.13G	Pit			2526	2560	935	969
	Flat			7009	7079	3504	3574
	Peak			7224	7266	3612	3654
7.91G	Pit			1124	1433	425	734
	Flat			5028	5186	2186	2344
	Peak			12,616	12,769	5248	5401
12.11G	Pit			799	1179	348	728
	Flat			14462	14,759	4845	5142
	Peak			22,776	23,003	9138	9365
15.88G	Pit			6159	6921	2340	3102
	Flat			12,707	13627	5124	6044
	Peak			16,586	17,660	5785	6859
20.54G	Pit			353	2074	117	1838
	Flat			11,171	14,119	4311	7259
	Peak			26,030	28,044	8749	10,763

Note: *VP* stands for viewpoint, *Comp* denotes computing time and *All* is the total running time. All the numbers in the table are rounded to nearest integers, and "h" indicates time in hours. Throughout the article, "pit" represents a point in a valley; "peak" is a point at the top of a mountain and "flat" denotes a point selected from an area that does not have significant topographic variation.




Figure 12. Speedup = *GPU-fine* computing time/*R3* computing time, varying two datasets and three selected viewpoints.

larger than that for a pit viewpoint, because selecting a peak viewpoint usually implies larger n_v or possibly larger D_{vf_o} than selecting a pit viewpoint based on Equation (5). Overall, our experiments are consistent with Equation (5).

The computing time speedup of *GPU-fine* compared with *R3* for datasets that are smaller than 4 GB was calculated to highlight the computing performance improvement contributed by massively parallel processing on GPUs. The results showed that significant performance improvement, larger than 50 times speedups, were achieved (Figure 12).

5.2.2. *Memory performance*

When datasets are large (>4 GB) and cannot be fit into global memory all at once (Figure 13b), up to three times speedups were achieved by comparing the computing time of *GPU-fine* against *GPU-coarse* (Figure 14), although there is no obvious speedup




Figure 13. *GPU-coarse* global memory access patterns: (a) when input data can fit into global memory; (b) when input data cannot fit into global memory.

Note: Squares with bold boundary are tiles, dark shade of color represents target cells processed by consecutive threads, and light shade of color shows intersected cells required by the consecutive threads at any point in time.

Downloaded by [UQ Library] at 05:11 27 September 2013




Figure 14. Speedup = *GPU-coarse* computing time/*GPU-fine* computing time, varying five datasets and three selected viewpoints.

observed when datasets are small (<4 GB) and can be processed in global memory (Table 2).

The speedups demonstrate that the memory performance gains of *GPU-fine* from the fine-scale spatial domain decomposition strategy is more significant when datasets are larger, primarily due to the fact that reads from global memory likely perform worse when large datasets are treated. The reason for the worse performance is when, as shown in Figure 13b, datasets are large, the coarse-scale decomposition is applied, and tiles are stored in different chunks of global memory. Consequently, intersected cells to which consecutive threads access are less likely to be contiguously stored in global memory than when processing smaller datasets (Figure 13a). Therefore, when input grid is larger, the worse global memory access leads to more performance loss and necessitates the application of the fine-scale spatial domain decomposition strategy (i.e., implemented in the *GPU-fine* algorithm) to improve memory access performance. Overall, the results of memory performance evaluation demonstrated the effectiveness of our fine-scale spatial domain decomposition strategy, and the desirable performance of using on-chip shared memory.

6. Concluding discussion and future work

The primary contribution of this research includes a cohesive set of spatially explicit strategies for using GPUs to address data-intensive viewshed analysis. In particular, a parallel computing approach has been developed to compute the viewshed of large grid terrain datasets. Specifically, our GPU-based parallel approach encompasses four interrelated major strategies: coarse-scale spatial domain decomposition, tile-based moving window, fine-scale spatial domain decomposition and massively parallel processing. These strategies have greatly enhanced memory access performance and empowered the geospatial analysis that would otherwise be considered infeasible. In doing so, the spatial characteristics of the underlying *R3* algorithm and GPU parallel computing architecture features are synergistically taken into account by our approach.

Computational experiments were conducted on a supercomputer to evaluate the strategies. More than 50 times speedups over the *R3* sequential algorithm were gained for

Downloaded by [UQ Library] at 05:11 27 September 2013

datasets of modest sizes. Furthermore, the coarse-scale spatial domain decomposition and moving window strategies make our approach scalable to large datasets that the sequential algorithm cannot handle. The experiments also demonstrated that while global memory can achieve good performance in some scenarios where memory access can make full use of its high-bandwidth, in most cases, the utilization of fast on-chip shared memory reaps superior performance.

GPUs are particularly useful for spatial data analyses that often have significant data parallelism to potentially take advantage of many-core resources and dedicated high-bandwidth memory. While this study focuses on GPU-based parallel viewshed analysis, the strategies (for regularizing memory access, reusing transferred data and exploiting massive spatial parallelism) are designed to address generic cases of data-intensive spatial analysis. These strategies provide guiding principles to effectively extract spatial patterns of data intensity and efficiently map such patterns to underlying modern parallel computer architecture for high-quality spatial analysis results and desirable computational performance. Furthermore, our approach is portable to any computer system (e.g., personal or high-performance computer) equipped with CUDA-enabled GPUs.

Our ongoing work investigates the integration of our GPU-based algorithms into a cyberinfrastructure-based geospatial problem-solving environment (Wang 2010). This integration will allow data-intensive viewshed analysis to be used as a set of application services and accessed simultaneously by a large number of users through reaping the benefits of dynamically harnessing on-demand cyberinfrastructure resources. In our future work, we will investigate how to further optimize our strategies, for example, for reducing the cost for synchronization of threads; and study how to adapt our strategies to other sequential algorithms for viewshed analysis such as the radial sweep algorithm (Van Kreveld 1996, Fishman *et al*. 2009, Haverkort *et al*. 2009).

Downloaded by [UQ Library] at 05:11 27 September 2013

Acknowledgments

This work is supported in part by the National Science Foundation grants: BCS-0846655 and OCI-1047916, and a fellowship from the China Scholarship Council. The authors thank Dr. Wen-mei W. Hwu and John Stratton for their kind assistance on accessing computational resources. They are also grateful for helpful comments by Guofeng Cao and Eric Shook within the CyberInfrastructure and Geospatial Information Laboratory at the University of Illinois at Urbana-Champaign.

References

Amanatides, J. and Woo, A., 1987. A fast voxel traversal algorithm for ray tracing. *In*: G. Marechal, ed. *Proceedings of the European Computer Graphics Conference and Exhibition*, 24–28 August 1987, Amsterdam. New York: Elsevier Science, 3–10.

Blelloch, G.E., 1990. *Vector models for data-parallel computing*. Cambridge: MIT Press.

Bresenham, J.E., 1965. Algorithm for computer control of a digital plotter. *IBM Systems Journal*, 4 (1), 25–30.

Che, S., *et al*., 2008. A performance study of general-purpose applications on graphics processors using CUDA. *Journal of Parallel and Distributed Computing*, 68 (10), 1370–1380.

De Floriani, L. and Magillo, P., 2003. Algorithms for visibility computation on terrains: a survey. *Environment and Planning B: Planning and Design*, 30 (5), 709–728.

De Floriani, L., Montani, C., and Scopigno, R., 1994. Parallelizing visibility computations on triangulated terrains. *International Journal of Geographical Information Systems*, 8 (6), 515–531.

Fang, C., *et al*., 2011. Parallel algorithm for viewshed analysis on a modern GPU. *International Journal of Digital Earth*, 4 (6), 471–486.

ESRI, 2011. *ArcGIS desktop: release 10*. Redlands, CA: Environmental Systems Research Institute.

Fisher, P.F., 1993. Algorithm and implementation uncertainty in viewshed analysis. *International Journal of Geographical Information Science*, 7 (4), 331–347.

Fisher, P.F., 1995. An exploration of probable viewsheds in landscape planning. *Environment and Planning B: Planning and Design*, 22 (5), 527–546.

Fishman, J., Haverkort, H., and Toma, L., 2009. Improved visibility computation on massive grid terrains. *In: Proceedings of the 17th ACM SIGSPATIAL international conference on advances in geographic information systems,* 4–6 November 2009, Seattle. New York: ACM, 121–130.

Franklin, W.R. and Ray, C., 1994. Higher is not necessarily better: visibility algorithms and Experiments. *In*: T.C. Waugh and R.G. Healey, eds. *Advances in GIS research: sixth international symposium on spatial data handling*. London: Taylor and Francis, 751–770.

Gao, Y., *et al*., 2011. Optimization for viewshed analysis on GPU. *In: 19th international conference on geoinformatics,* 24–26 June 2011 Shanghai. IEEE, 1–5.

Govindaraju, N., *et al*., 2006. GPUTeraSort: high performance graphics co-processor sorting for large database management. *In*: S. Chaudhuri, V. Hristidis and N. Polyzotis, eds. *Proceedings of the 2006 ACM SIGMOD international conference on management of data,* 27–29 June 2006, Chicago. New York: ACM, 325–336.

Haverkort, H., Toma, L., and Zhuang, Y., 2009. Computing visibility on terrains in external memory. *Journal of Experimental Algorithmic*, 13 (5), 1–23.

Izraelevitz, D., 2003. A fast algorithm for approximate viewshed computation. *Photogrammetric Engineering & Remote Sensing*, 69 (7), 767–774.

Jiang, B., *et al*., 2011. Data-intensive geospatial computing. *International Journal of Geographical Information Science*, 25 (8), 1217–1322.

Kindratenko, V., *et al*., 2009. GPU clusters for high-performance computing. *In: Proceeding of workshop on parallel programming on accelerator clusters*, 31 August 2009, New Orleans. IEEE, 1–8.

Kirk, D.B. and Hwu, W., 2010. *Programming massively parallel rrocessors: a hands-on approach*. 1st ed. San Francisco, CA: Morgan Kaufmann Publishers.

Lee, J., 1991. Analysis of visibility sites on topographic surfaces. *International Journal of Geographic Information Systems*, 5 (4), 413–425.

Magalhães, M.A., *et al*., 2007. An efficient algorithm to compute the viewshed on DEM terrains stored in the external memory. *In: Proceedings of the IX Brazilian Symposium on GeoInformatics*, 25–28 November 2007, Campos do Jordão, Brazil. INPE, 183–194.

Mayorov, F.V., 1964. *Electronic digital integrating computers: digital differential analyzers*. London: Iliffe Books Ltd.

Mills, K., Fox, G., and Heimbach, R., 1992. Implementing an intervisibility analysis model on a parallel computing system. *Computers & Geosciences*, 18 (8), 1047–1054.

Nagy, G., 1994. Terrain visibility. *Computers & Graphics*, 18 (6), 763–773.

NVIDIA Corporation, 2009. *White paper NVIDIA's next generation CUDA compute architecture: Fermi* [online]. Available from: http://www.nvidia.com/content/PDF/fermi_white_papers/NVIDIA_Fermi_Compute_Architecture_Whitepaper.pdf [Accessed 10 August 2011].

NVIDIA Corporation, 2010. *CUDA occupancy calculator* [online]. Available from: http://developer.download.nvidia.com/compute/cuda/CUDA_Occupancy_calculator.xls [Accessed 10 August 2011].

Owens, J.D., *et al*., 2007. A survey of general-purpose computation on graphics hardware. *Computer Graphics Forum*, 26 (1), 80–113.

Ryoo, S., *et al*., 2008. Optimization principles and application performance evaluation of a multithreaded GPU using CUDA. *In*: S. Chatterjee and M.L. Scott, eds. *Proceedings of the 13th ACM SIGPLAN symposium on principles and practice of parallel programming,* 20–23 February 2008, Salt Lake City. New York: ACM, 73–82.

Shapira, A., 1990. *Visibility and terrain labeling*. Thesis (Master). Department of Electrical, Computer, and System Engineering, Rensselaer Polytechnic Institute, Troy, NY.

Strnad, D., 2011. Parallel terrain visibility calculation on the graphics processing unit. *Concurrency and Computation: Practice and Experience*, 23 (18), 2452–2462.

Teng, Y.A., Dementhon, D., and Davis, L.S., 1993. Region-to-region visibility analysis using data parallel machines. *Concurrency and Computation: Practice and Experience*, 5 (5), 379–406.

Van Kreveld, M., 1996. Variations on sweep algorithms: efficient computation of extended viewsheds and classifications. *In*: M. Kraak and M. Molenaar, eds. *Proceedings of the 7th international symposium on spatial data handling*, 12–16 August 1996, Delft, The Netherlands. Delft: Faculty of Geodetic Engineering, Delft University of Technol, 13A.15–13A.27.

Downloaded by [UQ Library] at 05:11 27 September 2013

Wang, S., 2010. A CyberGIS framework for the synthesis of cyberinfrastructure, GIS, and spatial analysis. *Annals of the Association of American Geographers*, 100 (3), 535–557.

Wang, S. and Armstrong, M.P., 2009. A theoretical approach to the use of cyberinfrastructure in geographical analysis. *International Journal of Geographical Information Science*, 23 (2), 169–193.

Wang, S. and Liu, Y., 2009. TeraGrid GIScience gateway: bridging cyberinfrastructure and GIScience. *International Journal of Geographical Information Science*, 23 (5), 631–656.

Ware, J.A., Kidner, D.B., and Rallings, P.J., 1998. Parallel distributed viewshed analysis. *In*: R. Laurini, K. Makki and N. Pissinou, eds. *Proceedings of the 6th ACM international symposium on advances in geographic information systems,* 6–7 November 1998, Washington, D.C. New York: ACM, 151–156.

Downloaded by [UQ Library] at 05:11 27 September 2013