```
/*
 * Task.h
 *
 *  Created on: May 19, 2019
 *      Author: julian
 */

#ifndef EXAMPLES_C_SAPI_RTOS_FREERTOS_STATIC_MEM_FREERTOS_01_BLINKY_INC_TASK_H_
#define EXAMPLES_C_SAPI_RTOS_FREERTOS_STATIC_MEM_FREERTOS_01_BLINKY_INC_TASK_H_

#include "FreeRTOS.h"
#include "task.h"
#include "sapi.h"
#include "queue.h"
#include "semphr.h"
#include "string.h"
#include "stdlib.h"
#include "DriverDinamicMemoryRTOS.h"

/*offset apartir del SOF*/
#define OFFSET_OP        1
#define OFFSET_TAMANO    2
#define OFFSET_DATO      4
#define MIN_LOWER       65
#define MAX_LOWER       90
#define MIN_UPPER       97
#define MAX_UPPER       122
#define UP_LW_LW_UP     32

#define NUM_ELEMENTOS_REST_FRAME 6  /* SOF OP T(2) EOF Y \0 */

/*HexBcd to Decimal*/
#define HEXBCD_TO_DECIMAL(X) (X/10)*16 + (X%10)   /*96 ascii = 57 54 = 1001 0100 en Bcd 96 lo
conviert a decimal para que de el 96 en decimal*/

/** ======= Datos para llenar buffer local=======================================*/
typedef struct {
    char Buffer[106];
    uint8_t Ready;
    uint8_t Index;
    uint8_t StartFrame;
}DataFrame_t;
extern volatile DataFrame_t Data;

/** =======Operaciones a usar=====================================================*/
typedef enum{
    OP0 = 0,    /* Convertir los caracteres recibidos a mayúsculas. (CMD/RTA)*/
    OP1,        /*Convertir los caracteres recibidos a minúsculas. (CMD/RTA)*/
    OP2,        /*Reportar stack disponible (RTA)*/
    OP3         /*Reportar heap disponible. (RTA)*/
}Enum_Op_t;

/** =======Parametros de la trama de  llegada ====================================*/
typedef struct {
    char _SOF;
    Enum_Op_t Operation;
    uint8_t T[2];
    char* Datos;
    char* BufferAux;
    char _EOF;
}Frame_parameters_t;

extern volatile Frame_parameters_t Frame_parameters;

extern SemaphoreHandle_t SemTxUart;
```

```
extern SemaphoreHandle_t SemRxUart;
extern SemaphoreHandle_t SemMutexUart;
extern Module_Data_t ModuleData;
extern TaskHandle_t xTaskHandle_RxNotify ;

extern QueueHandle_t xPointerQueue_OP0;
extern QueueHandle_t xPointerQueue_OP1;
extern QueueHandle_t xPointerQueue_OP2;
extern QueueHandle_t xPointerQueue_OP3;
extern QueueHandle_t xPointerQueue_3;

void TaskService( void* taskParmPtr );
void TaskTxUart( void* taskParmPtr );
void CallbackRx( void *noUsado );
void Transmit_UART ( void* noUsado );

void Task_ToMayusculas_OP0( void* taskParmPtr );
void Task_ToMinusculas_OP1( void* taskParmPtr );
void Task_ReportStack_OP2( void* taskParmPtr );
void Task_ReportHeap_OP3( void* taskParmPtr );



#endif /* EXAMPLES_C_SAPI_RTOS_FREERTOS_STATIC_MEM_FREERTOS_01_BLINKY_INC_TASK_H_ */
```