BayesianEstimationTool (BET) Cheat Sheet

Purpose: `Estimator` organizes hierarchical Bayesian estimation for datasets containing multiple related entries. Models may contain global parameters shared across entries and standardized local Zs that vary by entry. `Train` infers the population/global posterior, training local Zs, and local-Z correlation. `Test` carries the learned population state to new entries and can either sample locals from the trained population or infer them from new observations with a method. `ScoreTrainSamples` and `ScoreTestSamples` evaluate predictions. `Save` and `Load` preserve the learned state and the settings needed to reconstruct how estimation was performed. Inference is supplied through an Method interface; built-in methods include NUTS and SVI.
Dependencies: jax, numpyro, numpy
Installation: Install in editable mode with `python -m pip install -e "/path/to/BayesianEstimationTool"` then import with `import BayesianEstimationTool as bet`. Editable installation means repository code changes are used without reinstalling. For repository examples, the parent folder may instead be added to `sys.path`.

Conventions

`import BayesianEstimationTool as bet` - Public import; construct the main object with `bet.Estimator(...)` and supply inference through the `Method` argument.
`arg{}` - dictionary whose values have no entry dimension; used for one entry's data, local Zs, model output, globals, or other named values.
`arg{[]}` - dictionary containing arrays spanning multiple entries or posterior samples.
`arg[]` - 1D sequence.
`Fn(...) -> value` - function argument or method together with the value it returns.
`globalDistributions{}` - global-parameter prior dictionary: `{name: NumPyro distribution}`. BET creates the NumPyro sample sites internally; the dictionary keys become the global parameter names.
`likelihoods{}` - single-entry likelihood dictionary: `{name: (observation, distribution)}`. BET vectorizes it across entries and creates the NumPyro observation sites internally.
Italic arguments - accept `None` as a valid input.

Main Functions

Estimator(data{[]}, ModelFn(globalParams{}, localZs{}, data{}) -> modelOut{}, *localZNames[]*, *GlobalPriorFn(dataShapes{}) -> globalDistributions{}*, lkjConcentration=2.0, *rngSeed*) -> Estimator: Creates an Estimator. **localZNames** defines standardized entry-level parameters. With multiple locals, the Estimator learns their correlation with an LKJ Cholesky prior controlled by **lkjConcentration**. **GlobalPriorFn** receives the per-entry shapes of the full data and returns `{name: NumPyro distribution}`. BET creates the named NumPyro sample sites and passes their sampled values to **ModelFn** and likelihood functions as `globalParams{}`. **rngSeed** initializes the Estimator's persistent RNG.

Train(trainDataIdxs[], TrainLikelihoodFn(globalParams{}, localZs{}, data{}, modelOut{}) -> likelihoods{}, Method=method, printSummary=False, *rngSeed*, saveLocalZs=True, saveModelOut=False) -> methodOutput: Fits **trainDataIdxs** using **Method**. **TrainLikelihoodFn** is evaluated one entry at a time and returns `{name: (observation, NumPyro distribution)}`; BET batches the returned observations/distributions and creates the observation sites internally. A Method instance supplies an explicit configuration. A Method class reconstructs the saved training Method arguments; if its class name differs from the saved Method name, BET warns and still attempts reconstruction. The Estimator stores global posterior samples and the learned Cholesky state; **saveLocalZs** stores transformed training-local Z samples and **saveModelOut** stores model-output samples. **printSummary** uses the Estimator's generic posterior summary unless the Method replaces or augments it.

Test(testDataIdxs[], *TestLikelihoodFn(globalParams{}, localZs{}, data{}, modelOut{}) -> likelihoods{}*, *Method=method*, *nGlobalSamples*, nLocalZSamples=2000, printSummary=False, *rngSeed*, saveModelOut=False) -> None | methodOutput[]: Tests on new entries. **TestLikelihoodFn**, when supplied, follows the same single-entry `{name: (observation, distribution)}` contract as training. **nGlobalSamples=None** uses the median trained global/Cholesky state; a positive integer samples that many trained states. With **TestLikelihoodFn=None**, no Method is needed and the Estimator draws **nLocalZSamples** locals from the trained population. With a likelihood, a Method instance supplies an explicit configuration. A Method class reconstructs saved arguments: BET uses the previous Method-based test configuration when available, otherwise the training configuration. If the supplied class name differs from the saved Method name, BET warns and still attempts reconstruction.

ScoreTrainSamples(ScoreFn(modelOut{}, data{}) -> score{}, *nSamples*, *rngSeed*) -> scores{[]}: Scores training predictions. **nSamples=None** uses all available joint training-posterior samples; otherwise the Estimator selects that many. Saved model outputs are reused when available, otherwise they are regenerated from saved parameters.

ScoreTestSamples(ScoreFn(modelOut{}, data{}) -> score{}, *nSamples*, *rngSeed*) -> scores{[]}: Scores the latest test state. **nSamples=None** uses all stored local Z samples; otherwise that many are selected for each stored global state. Saved model outputs are reused when available, otherwise they are regenerated.

Save(*fileName*, saveTrainLocalZs=True, saveTestLocalZs=True, saveTrainModelOut=False, saveTestModelOut=False, saveAllData=False) -> None | record{}: Writes compressed `.npz` state, or returns a nested record when **fileName=None**. Saved metadata includes method class names and constructor arguments so the estimation setup can be reconstructed without serializing method machinery. Functions are not serialized.

Estimator.Load(fileName, *ModelFn*, *GlobalPriorFn*, *data*) -> Estimator | record{}: Loads saved state. With **ModelFn=None**, returns the saved record without reconstructing an Estimator. Otherwise model functions are supplied explicitly; **data** is required unless the data were saved with `saveAllData=True`.

Nuts(numWarmup=2000, numSamples=2000, numChains=4, acceptProb=0.95, denseMass=False, medianSamples=50) -> Nuts: Creates a NUTS inference Method, exposed as `bet.Nuts`. Pass `bet.Nuts(...)` for an explicit configuration or `bet.Nuts` to reconstruct saved Method arguments. **medianSamples** controls `init_to_median`; **acceptProb** is the target acceptance probability. NUTS retains posterior samples from the MCMC trajectory and prints NumPyro convergence diagnostics including n_eff and r_hat.

Svi(numSteps=10000, numSamples=2000, stepSize=0.01, numParticles=1, progressBar=True, medianSamples=50, multivariate=False) -> Svi: Creates an SVI inference Method, exposed as `bet.Svi`. Pass `bet.Svi(...)` for an explicit configuration or `bet.Svi` to reconstruct saved Method arguments. Uses `init_to_median`; **numSamples** is the number of posterior samples drawn from the fitted guide for the Estimator. By default the guide is mean-field `AutoNormal`; **multivariate=True** uses `AutoMultivariateNormal`, which can represent posterior covariance but scales less favorably for large latent spaces.