Python Automata Library (PAL) Cheat Sheet

import PythonAutomataLibrary as pal · Safe mode is default. Call **pal.FastMode**() before constructing any PAL object. Put substantive model kernels under **@pal.njit(cache=True)**.

Create state

pal.NewGrid(dims, dtype): Create one value per site; supports bool, fixed-width integer, and float dtypes.

pal.NewAgentGrid(dims, numAgentProps=0, isStackable=False): Create mobile agents with per-agent properties. isStackable permits multiple agents per site; dims=() makes a nonspatial collection.

pal.NewPopGrid(dims, capacity=None): Store integer population counts per site; capacity limits total population.

pal.NewPDEgrid(dims): Create a continuous field with queued synchronous updates and diffusion/advection operators.

pal.NewIList(): Create a mutable integer list for collecting/reusing query results.

pal.NewMultinomial(): Create a sampler for binomial/multinomial population draws.

Shared lattice geometry

Properties: xDim / yDim / zDim: axis sizes; nDims: number of axes; wrapX / wrapY / wrapZ: wrapping flags.

ToI(x...): Convert coordinates to a linear site index; inverse methods are ItoX/Y/Z(i).

grid.Hood(hood, x...): Apply relative coordinate offsets, e.g. ((x1,y1),(x2,y2),...), at x.... Special-case hoods: **pal.MooreHood**(*),...

Grid / common indexing

Indexing: grid[i] reads/writes by linear index; grid[x...] uses dimensional coordinates.

Slices: Return detached NumPy copies, not views; write back explicitly to change the grid.

Box(x1,x2,...): Select a rectangular region: (xLow,xHigh,yLow,yHigh,...), with exclusive upper bounds.

Draw / output

pal.StartPixWindow(...): Create a pixel buffer and display window; headless=True supports noninteractive rendering.

pix[x,y] = RGB: Set a pixel color in the shared pixel buffer.

Color utilities: pal.RGB(r,g,b) packs red, green, and blue channels into a color; pal.GetR(color), pal.GetG(color), and pal.GetB(color) extract...

PixWindow controls: win.Update() refreshes the display; win.Save(path,block=True) saves an image; win.Close() releases the window.

PixWindow GIF: win.StartGif(path,delay=100) starts recording; win.AddGifFrame(block=False) appends a frame; win.StopGif() finishes.

pal.StartOpenGLWindow(xDim,yDim,zDim=None,width=800,height=800,...): Create the renderer and return (draw, win): draw collects primitives; win handles display, updates, and output. Omit zDim for...

draw.Circle(rad,color,x,y,z=None): Add a circle or sphere-like primitive with the given radius and color.

draw.Box(xLen,color,x,y,z=None,yLen=None,zLen=None): Add a box centered at a position; specify axis lengths to control its size.

draw.BoxSQ(color,x,y,z=None): Add a box aligned to a lattice site.

Draw / output

draw.Line(width,color,x1,y1,x2,y2,z1=None,z2=None): Add a line segment between two 2D/3D points.

draw.Borders(width,color): Draw grid borders with the requested line width and color.

win.Camera(x,y,z,yaw=None,pitch=None): Set the camera position and optional yaw/pitch angles for a 3D scene.

OpenGL frame: win.Background(color) sets the background; draw.Clear() clears collected primitives; win.Clear() clears the scene; win.Update()...

OpenGL output: win.IsOpen() checks the window; win.Save(path,block=False) saves an image; win.Close() releases resources.

OpenGL GIF: win.StartGif(...) begins recording; win.AddGifFrame(...) adds a frame; win.StopGif(...) finishes.

Lists + randomness

IList methods: Append(i) adds an integer; Clear() empties the list; Random() picks an entry; Shuffle() reorders entries; All() copies the list;...

RNG methods: pal.Seed(seed) seeds PAL's RNG; pal.Random() draws uniform [0,1); pal.RandInt(n) draws an integer in [0,n). PAL's RNG is...

Multinomial methods: m.Binomial(n,p) draws a binomial count; m.Setup(...) configures multinomial probabilities; m.Sample(...) draws counts.

AgentGrid

NewAgentSQ(x...) / **MoveSQ**(a,x...): Create/move agents by integer site coordinates; linear-site variants are also available.

NewAgent(x...) / **Move**(a,x...): Create/move agents by continuous coordinates (off-lattice).

grid[a,p]: Read or write property p for agent a.

Agent position: I(a) gives the linear site index; XSQ/YSQ/ZSQ(a) give lattice coordinates; X/Y/Z(a) give continuous coordinates.

Alive(a) / **Dispose**(a): Check whether an agent is still valid, or remove it from the grid.

GetPop(): Count agents currently in the grid.

AgentsAt(x...) / **LastAgent**(x...): Query all agents at a site or just its last agent; useful for stackable grids.

AgentsInRadius(...): Find nearby agents, respecting periodic boundaries.

counts[x...]: Read site occupancy counts without modifying them.

Iteration: agents.All() returns a detached snapshot, safe for iteration while adding or disposing agents.

DispWrapX/Y/Z(p1,p2): Compute the shortest displacement along a periodic axis.

PopGrid + PDEgrid

Synchronous updates: Add(v,...) queues a change; Update() applies queued changes together; Reset() clears current and pending values. Indexed...

pop.GetPop(): Return total population across all sites.

pop.All(): Return occupied site indices (not their counts).

PDE setup: field.SetTimeSpaceStep(dt, dx[,dy,dz]) sets time and axis spacing; explicit updates require stable time steps.

Diffusion methods: Diffusion(...) uses the standard scheme; DiffusionMask(...) applies a mask; DiffusionField(...) uses spatially varying...

Advection methods: Advection(...) uses constant velocity; AdvectionField(...) uses spatially varying velocity; AdvectionInterfaces(...) specifies...