

Python Automata Library (PAL) Cheat Sheet

```
import PythonAutomataLibrary as pal · Safe mode
is default. Call pal.FastMode() before constructing
any PAL object. Put substantive model kernels under
@pal.njit(cache=True).
```

Create state

pal.NewGrid(dims, dtype) — typed lattice

pal.NewAgentGrid(dims, numAgentProps=0, isStackable=False) — individual agents; **dims=()** is nonspatial

pal.NewPopGrid(dims, capacity=None) — integer population counts

pal.NewPDEgrid(dims) — continuous field

pal.NewList() · **pal.NewMultinomial()** — integer query list · random-count sampler

Dimensions — 1–3 axes; a negative dimension wraps that axis, e.g. **(-nx, ny)**.

Shared lattice geometry

Properties — **xDim/yDim/zDim, nDims, wrapX/Y/Z**

Index conversion — **Tol(x[,y,z])**; **ltoX/Y/Z(i)**

Regions — **Box(lo..., hi...)** uses half-open bounds; **Hood(hood, x[,y,z])** maps relative offsets to coordinates.

Neighborhoods — **pal.MooreHood(dim, includeOrigin)** · **pal.VonNeumannHood(dim)** · **pal.CircleHood(dim, rad)**

Grid / common indexing

Read/write — **g[x,y]**, **g[x,y]=v**; slices return detached NumPy copies.

Pattern — **g = pal.NewGrid((40,40), float)** · **g[10,12] = 1.0** · **v = g[10,12]**

AgentGrid

Create / move — **NewAgentSQ(x,y)** / **MoveSQ(a,x,y)** for lattice positions; **NewAgent(x,y)** / **Move(a,x,y)** for continuous positions.

Agent state — **grid[a,p]** property; **l(a)**, **XSQ/YSQ/ZSQ(a)** lattice; **X/Y/Z(a)** continuous; **Alive(a)**, **Dispose(a)**.

Queries — **GetPop()**, **AgentsAt(...)**, **LastAgent(...)**, **AgentsInRadius(...)**, **counts[...]**.

Iteration — **for a in agents.All()**: ... is a snapshot and is safe for structural mutation such as **Dispose**.

Wrapping — **DispWrapX/Y/Z(p1,p2)** gives wrapped displacement.

PopGrid + PDEgrid

Transactional update — **Add(v, ...)** changes pending state; **Update()** applies it simultaneously; **Reset()** clears current + pending. Direct **grid[...] = v** changes current state immediately.

Population — **pop.GetPop()** total; **pop.All()** nonzero site indices. **capacity** limits total population.

PDE setup — **field.SetTimeSpaceStep(dt, dx[,dy,dz])**

Diffusion — **Diffusion, DiffusionMask, DiffusionField, DiffusionInterfaces, DiffusionADI**; radial 1D: **DiffusionRadialCircle/Sphere**.

Advection — **Advection, AdvectionField, AdvectionInterfaces**.

Lists + randomness

lList — **Append(i)**, **Clear()**, **Random()**, **Shuffle()**, **indexing/len**; **All()** detached copy; **Iter()** no-copy iteration.

RNG — **pal.Seed(seed)** · **pal.Random()** · **pal.RandInt(n)** → 0..n-1; use PAL RNG for shared-stream reproducibility.

Multinomial — **m.Binomial(n,p)**; **Setup(...)** then **Sample(...)** for repeated multinomial draws.

Draw / output

Pixels — **pix, win = pal.StartPixWindow(xDim,yDim,scale=1,title='PAL',headless=False)**; set **pix[x,y]=RGB**; **win.Update()**; **win.Save(path, block=True)**; **win.Close()**.

GIF — **StartGif(path,delay=100)** · **AddGifFrame(block=False)** · **StopGif()**; call **Update()** before capture.

OpenGL — **pal.StartOpenGLWindow(...)**; draw with **Circle, Box, BoxSQ, Line, Borders**; scene controls include **Camera, Background, Clear**.

More detail: [Manual](#) · [API Guide](#) · [API Reference \(Documentation/\)](#).