



TECHNICAL DESCRIPTION & API SPECIFICATION

www.hostedsms.pl

TABLE OF CONTENTS

1. Introduction	3
2. HostedSMS system – Basic parameters	3
Availability	3
Characters definition and SMS messages length	3
3. SECURITY	4
4. Available interfaces	4
Webserwis2SMS interface	4
Web service methods.....	4
Web service methods turned on by support	5
Method sygnatures	5
Customer authentication	11
Method parameters/ Delivery Report structure fields/ InputSMS.	12
SMS Delivery report	15
Received SMS	16
Interface SimpleApi	17
SendSMS method	18
AntiSpam mechanism	18
Examples	19
FullApi interface	21
Authorization	21
FullApi Methods	21
Operation mapping	21
OBJECTS USED IN MMSES	23
Method parameters / Field structure	24
Passing the parameter Phone/Phones	24
Examples	25

1. INTRODUCTION

HostedSMS System (HSMS for short) is designed to send SMS messages in bulk. The system will be provided to the Customer as a service. DCS is responsible for the development and maintenance of the system in the DCS infrastructure as well as providing appropriate GSM network connection.

2. HOSTEDSMS SYSTEM – BASIC PARAMETERS

AVAILABILITY

DCS guarantees that the availability of the HSMS System will not be less than 99.5% per calendar month. Any planned technical brakes agreed with the Customer are not considered as system unavailability.

CHARACTERS DEFINITION AND SMS MESSAGES LENGTH

HSMS System is capable of sending SMS messages of up to 4000 characters in length. This corresponds to 27 SMS messages restricted to characters from GSM7¹ basic alphabet or 60 characters from the full UNICODE alphabet.

Using extended GSM7 characters does not change the message to UNICODE, but each character from the extended alphabet is encoded with two characters from the basic alphabet².

- 612 characters if the message contains only GSM7 characters

Number of characters in SMS	Number of SMS messages received by the recipient	Number of text messages shown in the billing for the Customer
1-160	1	1
161-306	1	2
307-459	1	3
460-612	1	4
Over 612	1 ³	(Characters count / 153) - rounded up

- 272 characters if the message contains UNICODE characters

Number of characters in SMS	Number of SMS messages received by the recipient	Number of text messages shown in the billing for the Customer
1-70	1	1

¹ Basic GSM7 alphabet is the „Basic Character Set” table included in the GSM 03.38 specification

² Extended GSM7 alphabet is a set of characters: ^{ } \ [~] | € as listed in the „Extended Character Set” included in the GSM 03.38 specification

³ NOTE – Not all devices have the feature of sending SMS messages consisting of two or more segments. It is not advised to send messages longer than 10 segments.

71-134	1	2
135-201	1	3
202-268	1	4
Over 269	1 ⁴	(Characters count / 67) - rounded up

3. SECURITY

Access to the Interface will require authorization with a login (email address) and password. All communication between DCS and the Client will be encrypted using certificates issued by a trusted certification authority.

Additionally, the system features functionality known as a White List of IP addresses. By default, this functionality is disabled. To secure the account, it is necessary to configure a list of allowed IP numbers in the Client Panel (configuration available to users with Administrator privileges) by adding at least one IP address to the list. Once the list of allowed IP numbers is enabled, all requests coming from addresses outside the list will be blocked.

4. AVAILABLE INTERFACES

WEBSERWIS2SMS INTERFACE

The Webserwis2SMS interface can be used to automate SMS sending directly via the Customer's systems as well as enables receiving SMS delivery reports.⁵

Webserwis2SMS Interface will be available under:

- <https://api.hostedsms.pl/WS/SmsSender.asmx> - primary DCS processing center
- <https://api2.hostedsms.pl/WS/SmsSender.asmx> - backup DCS processing center

WEB SERVICE METHODS

SENDSMS - sends a single SMS message. This method returns true if the DCS system has received a message to send.

SENDSMSES – sends a SMS message to a group of mobile devices. This method returns true if the DCS system has received all the messages to send. This operation is transactional – either all messages will be received to send or none.

GETUNREADDELIVERYREPORTS – returns all of Customer's unread delivery reports and marks them as read. The maximum of 100 reports is returned at once. An empty array indicates that there are no available reports to download.

⁴ NOTE – Not all devices have the feature of sending SMS messages consisting of two or more segments. It is not advised to send messages longer than 10 segments.

⁵ There is a possibility to launch an interface that will forward SMS messages sent via cell phones to the Customer. To activate two-way version of the interface, please contact DCS.

GETDELIVERYREPORTS – Returns a group of SMS delivery reports for the given message identifiers. The result of this method is an array of type `DeliveryReport`.

GETUNREADINPUTSMSSES – returns all unread SMS messages and marks them as read. The maximum of 100 SMS messages is returned at once. An empty array indicates that there are no available messages to download.

GETINPUTSMSSES – returns a group of received messages for a set rules of search filter. The result of this method is an array of type `InputSms`.

GETVALIDSENDERS – returns a group of valid senders name

CHECKPHONES- function checks the validity of the provided phone numbers. This functionality is analogous to checking numbers when loading a file for sending messages - it returns information about which numbers are valid, which are blocked, which are duplicates, and which are on the blacklist.

CONVERTTOGSM7- normalizes text to GSM7 by removing Polish diacritical marks.

CUSTOMERINFO - returns the current counter status of available SMS messages for the logged-in client and the account expiration date.

GETUNREADMMSDELIVERYREPORTS - returns all unread MMS delivery reports for the client while marking them as read. A maximum of 100 MMS reports are returned at a time. An empty array indicates that there are no available MMS reports to retrieve.

GETMMSDELIVERYREPORTS - returns a group of MMS delivery reports for the given message identifiers. An array of type `DeliveryReport` is returned.

Method for MMS delivery reports (**GETUNREADMMSDELIVERYREPORTS**, **GETMMSDELIVERYREPORTS**) needs MMS feature turned on for client.

WEB SERVICE METHODS TURNED ON BY SUPPORT

Following methods are turned off by default. To turn them on – please contact customer support.

GETOUTPUTSMSSES - returns a group of sent SMS messages based on the specified search criteria. An array of type `OutputSms` is returned. Optionally, it marks the returned SMS messages as viewed.

GETUNREADOUTPUTSMSSES - returns a group of sent SMS messages that have not been marked as viewed, based on the specified search criteria. An array of type `OutputSms` is returned (maximum of 100 records per call).

METHOD SYGNATURES

```
public bool SendSmses (
    string UserEmail,
    string Password,
    string[] Phones,
    string Message,
    string Sender,
```

```

        string TransactionId,
        DateTime? ValidityPeriod,
        int Priority,
        bool FlashSms,
        string CostCenter,
        bool? ConvertMessageToGSM7,
        out string ErrorMessage,
        out DateTime CurrentTime,
        out Guid[] MessageIds
    )

public bool SendSms (
    string UserEmail,
    string Password,
    string Phone,
    string Message,
    string Sender,
    string TransactionId,
    DateTime? ValidityPeriod,
    int Priority,
    bool FlashSms,
    string CostCenter,
    bool? ConvertMessageToGSM7,
    out string ErrorMessage,
    out DateTime CurrentTime,
    out Guid? MessageId
)

public bool GetUnreadDeliveryReports (
    string UserEmail,
    string Password,
    public int? Limit,

```

```

        out string ErrorMessage,

        out DateTime CurrentTime,

        out DeliveryReport[] DeliveryReports
    )

public bool GetDeliveryReports(
    string UserEmail,
    string Password,
    Guid[] MessageIds,
    bool MarkAsRead,
    out string ErrorMessage,
    out DateTime CurrentTime,
    out DeliveryReport[] DeliveryReports
)

public bool GetInputSmses(
    string UserEmail,
    string Password,
    DateTime? From,
    DateTime? To,
    string Recipient,
    bool MarkAsRead,
    out string ErrorMessage,
    out DateTime CurrentTime,
    out InputSms[] InputSms
)

public bool GetUnreadInputSmses(
    string UserEmail,
    string Password,
    public int? Limit,
    out string ErrorMessage,
    out DateTime CurrentTime,

```

```

        out InputSms[] InputSms

    )

    public bool GetValidSenders(
        string UserEmail,
        string Password,
        out string[] Senders,
        out string ErrorMessage,
        out DateTime CurrentTime
    )

    public bool CheckPhones(
        string UserEmail,
        string Password,
        string[] Phones,
        out string[] ValidPhones,
        out string[] InvalidPhones,
        out string[] Duplicates,
        out string[] BlockedPhones,
        out string ErrorMessage,
        out DateTime CurrentTime
    )

    public bool ConvertToGsm7(
        string UserEmail,
        string Password,
        string Text,
        out string Gsm7Text,
        out string ErrorMessage,
        out DateTime CurrentTime
    )

    public bool CustomerInfo (
        string UserEmail,

```



```

        string Password,

        out DateTime? CustomerValidTo,

        out long? SmsCounter,

        out string ErrorMessage,

        out DateTime CurrentTime

    )

```

```

public bool GetOutputSmses (
    string UserEmail,
    string Password,
    DateTime? From,
    DateTime? To,
    string Recipient,
    bool MarkAsRead,
    public int? Limit,
    out string ErrorMessage,
    out DateTime CurrentTime,
    out OutputSms[] OutputSms

)

```

```

public bool GetUnreadOutputSmses (
    string UserEmail,
    string Password,
    DateTime? From,
    DateTime? To,
    public int? Limit,
    out string ErrorMessage,
    out DateTime CurrentTime,
    out OutputSms[] OutputSms

)

```

```

public bool GetUnreadMmsDeliveryReports (

```

```

        string UserEmail,

        string Password,

        public int? Limit,

        out string ErrorMessage,

        out DateTime CurrentTime,

        out MmsDeliveryReport[] DeliveryReports

    )

public bool GetMmsDeliveryReports(

    string UserEmail,

    string Password,

    Guid[] MessageIds,

    bool MarkAsRead,

    out string ErrorMessage,

    out DateTime CurrentTime,

    out MmsDeliveryReport[] DeliveryReports

)

public struct DeliveryReport
{

    public Guid ReportId;

    public string Phone;

    public Guid MessageId;

    public int Status;

    public DateTime DeliveryTime;

}

public struct MmsDeliveryReport
{

    public Guid MessageId;

    public string Phone;

```

```

        public int Status;

        public DateTime DeliveryTime;
    }

    public struct InputSms
    {
        public Guid MessageId { get; set; }

        public string Phone { get; set; }

        public string Recipient { get; set; }

        public string Message { get; set; }

        public DateTime ReceivedTime { get; set; }
    }

    public struct OutputSms
    {
        public Guid MessageId { get; set; }

        public DateTime SentTime { get; set; }

        public DateTime? DeliveryTime { get; set; }

        public string UserName { get; set; }

        public string Sender { get; set; }

        public string Phone { get; set; }

        public string MessageStatus { get; set; }

        public string DeliveryStatus { get; set; }

        public string Interface { get; set; }

        public string CostCenter { get; set; }

        public string Body { get; set; }

        public int SmsCount { get; set; }
    }

```

CUSTOMER AUTHENTICATION

The Customer is authenticated by the UserEmail/Password pair which uniquely identifies the HSMS service Customer.

PHONE NUMBER

```
string Phone,  
string[] Phones,  
out string[] ValidPhones,  
out string[] InvalidPhones,  
out string[] Duplicates,  
out string[] BlockedPhones
```

The phone number must be provided in international form, e. g. 48xxxxxxxxxx. In the case of sending multiple messages, an array of phone numbers should be provided, according to the above format.

For the CheckPhones method, it returns numbers categorized as valid (Valid), invalid (Invalid), duplicates (Duplicates), and blocked (BlockedPhones).

SENDER NAME

```
string Sender  
out string[] Senders,
```

An alphanumeric string that will be passed to the operator as the sender name. Keep in mind that different networks may have different settings regarding the allowed format of the sender name.

The list of all allowed sender overwrites assigned to the client is returned by the GetValidSenders method. If you need to use other overwrites, you must contact DCS for activation.

RECIPIENT

```
string Recipient
```

The phone number the input message was sent to.

Can be provided as parameter while filtering received messages.

TEXT MESSAGE CONTENT

```
string Message  
string Body
```

The system will automatically encode SMS messages as GSM7 or Unicode, depending on whether there are any characters outside the GSM7 set in the content.

The maximum length of SMS messages in HSMS is 4000 characters

TRANSACTION IDENTIFIER

```
string TransactionId
```

Unique string identifying an attempt to send an SMS / SMS group. Subsequent attempts with the same identifier:

- Will return true and the same output parameters if the call was made with the same input parameters.
- Will return false and an error message if the parameters differed.

Max. length of 128 characters.

SMS VALIDITY PERIOD

```
DateTime? ValidityPeriod
```

SMS validity time given as a moment in time. In case the current time is greater than the validity time of the SMS, the sending attempt will be rejected.

The HSMS will not send an SMS after the expiry date.

In case of providing NULL value, the DCS will assume that the validity time has not been set and the validity of the SMS message will be set to the default one for the given GSM network.

The validity period must be given according to the time in Warsaw.

PRIORITY

```
int Priority
```

A number between 0 and 3, where 0 is the lowest priority and 3 the highest.

A lower-priority message will only be sent if there are no higher-priority messages waiting to be sent in the system.

FLASH SMS

```
bool FlashSms,
```

The **true** value means that the message will be sent as a Flash SMS. A Flash SMS is displayed on the phone immediately upon receipt and is not stored in the phone memory.

Due to technical limitations of the GSM standard, a Flash SMS can consist of only one segment and contain only GSM7 characters. The maximum length of Flash SMS is 160 characters.

CONVERT MESSAGE TO GSM7 FORMAT

```
bool? ConvertMessageToGSM7
```

A value of **True** indicates that the message will be converted to GSM7 format before being sent, meaning that Polish diacritical marks will be removed and replaced with their Latin equivalents. Other symbols outside the GSM7 alphabet will also be removed.

If no value is provided or **False** is specified, no conversion will occur.

COST CENTER

```
string CostCenter,
```

The name of cost center. To use a cost center, it must first be configured in the customer panel. Only values from the list of created cost centers are allowed.

In case of the functionality being disabled, the field should take the null value

MARK AS READ

```
bool MarkAsRead,
```

Mark as read. When retrieving delivery reports, sent, or received SMS messages for specific messages, there is an option to mark them as read so they are no longer returned using the `GetUnreadDeliveryReports`, `GetUnreadMmsDeliveryReports`, or `GetUnreadOutputSmses` methods.

SCOPE OF TIME

```
DateTime? From,
```

```
DateTime? To,
```

Parameters used in searching for received SMS.

ERROR DESCRIPTION

```
out String ErrorMessage
```

Textual description of an error, in a human-readable form, in English. In case of a correct operation the field should be empty. All interface methods return a **True/False** logical value indicating the correct completion of the operation. The `ErrorMessage` value is only relevant if a method returned **False**.

Output variable.

CURRENT TIME.

```
out DateTime CurrentTime
```

In order to bypass time problems, the DCS system gives the time according to its own clock.

Output variable.

MESSAGE IDENTIFIER

```
out Guid? MessageId
```

```
out Guid[] MessageId
```

```
Guid[] MessageIds,
```

The message identifier given as Guid, used to match the message with the delivery report. The variable is only relevant if SendSms or SendSmses methods return **True**

Output variable for SendSms and SendSmses methods and input variable for GetDeliveryReports and GetMmsDeliveryReports method.

LIMITOWANIE ODPOWIEDZI

```
public int? Limit { get; set; }
```

Maximum number of rows. If empty or more than 100 – there will be returned first 100 rows.

SMS DELIVERY REPORT

```
public struct DeliveryReport
{
    Guid ReportId;
    string Phone;
    Guid MessageId;
    int Status;
    DateTime DeliveryTime;
}
```

A structure containing information with a single description of an SMS delivery report. The meaning of the fields is explained in the following sections.

DELIVERY REPORT IDENTIFIER

```
Guid ReportId;
```

Uniquely identifies the SMS message delivery report.

MMS DELIVERY REPORT

```
public struct MmsDeliveryReport
{
    string Phone;
    Guid MessageId;
    int Status;
    DateTime DeliveryTime;
}
```

A structure containing information with a single description of an MMS delivery report. The meaning of the fields is explained in the following sections.

It differs from the SMS delivery report by the absence of the ReportId field. The MMS delivery report is part of the MMS message status rather than a separate entity, as in the case of SMS.

DELIVERY STATUS

```
int Status
```

- 1 Message not delivered (final).
- 2 Message not delivered due to exceeding the delivery time limit. The message was not delivered in the given time ValidityPeriod.
- 3 Message rejected by the operator.
- +1 Message delivered.
- 0 Undefined state, should not occur.

As a rule, condition >0 and <0 can be examined. Subsequent statuses, if added, will follow the principle that negative values refer to non-delivery of messages and positive values refer to delivery of messages.

DELIVERY TIME

```
DateTime DeliveryTime
```

Time to mark the SMS as delivered / finally not delivered. According to the Warsaw time.

CLIENT ACCOUNT EXPIRATION DATE

```
DateTime? CustomerValidTo
```

The date until which the client account remains valid in HSMS. After this date, using HSMS services will no longer be possible. A **null** value means the client account does not expire.

SMS COUNTER STATUS

```
long? SmsCounter
```

A value indicating how many SMS messages the logged-in client can still send without needing to top up the account. A null value means there is no limit.

RECEIVED TIME

```
DateTime ReceivedTime
```

The time when the SMS was saved in the DCS system.

RECEIVED SMS

```
public struct InputSms  
{  
  
    public Guid MessageId { get; set; }  
  
    public string Phone { get; set; }  
}
```



```

    public string Recipient { get; set; }

    public string Message { get; set; }

    public DateTime ReceivedTime { get; set; }
}

```

All fields conform to the definitions given earlier.

SENT SMS

```

    public struct OutputSms
    {

        public Guid MessageId { get; set; }

        public DateTime SentTime { get; set; }

        public DateTime? DeliveryTime { get; set; }

        public string UserName { get; set; }

        public string Sender { get; set; }

        public string Phone { get; set; }

        public string MessageStatus { get; set; }

        public string DeliveryStatus { get; set; }

        public string Interface { get; set; }

        public string CostCenter { get; set; }

        public string Body { get; set; }

        public int SmsCount { get; set; }

    }

```

The MessageStatus field for a sent message will have the value "Sent".

The DeliveryStatus field contains a short description of the current state of the sent message, e.g., "Delivered" or "Expired".

The Interface field indicates the application interface from which the message was sent, in this case, "WS".

The SmsCount field specifies how many SMS messages were used to send the message.

All other fields follow the definitions provided earlier.

INTERFACE SIMPLEAPI

Interface SimpleAPI is designed for customers who want to send SMS messages in the easiest possible way and do not need the advanced capabilities of WebService2SMS.

The interface is available at the following addresses:

- <https://api.hostedsms.pl/SimpleApi> - primary DCS processing centre
- <https://api2.hostedsms.pl/SimpleApi> - backup DCS processing centre

The interface has been made using ASP.NET Web API⁶ technology.

SENDSMS METHOD

The interface offers single method SendSms with the following parameters:

- UserEmail – System login
- Password – System password
- Sender – Sender name assigned to the Customer
- Phone – Recipient's telephone number
- Message – Message content
- v – Optional parameter used in anti-spam mechanism (see below)
- ConvertMessageToGSM7 - Optional parameter for converting the content of the message to GSM7 format.

In response, the system returns one of the following two values:

- MessageId – Message identifier.
- ErrorMessage – Error Message.

The meaning of the parameters is exactly the same as for the interface WebService2SMS

Queries are executed using HTTP POST. Formatting the query and answer is done using the Content-Type and Accept headers (see examples below)

SendSms method in SimpleApi not allows setting SMS priority, cost center, validity period or sending as Flash Sms. If there is a need of set this field – please use Web Service or FullApi.

ANTISPAM MECHANISM

To protect the SMS recipient from mass SMS messages, the API is equipped with an anti-spam mechanism.

Calling the API again on the same day with the same parameters will cause the saved response to be returned and will not send an SMS.

If there is a need to send a second SMS with the same content to the same phone number, this can be done by setting the optional parameter “v”; to any unique value

⁶ See: <http://www.asp.net/web-api>

EXAMPLES

ASP.NET WEB API technology allows you to perform queries in different formats. Below is an example for a call in the form of Request – FormData / Response – Json:

EXAMPLE – FORMDATA / JSON

The following example shows a service call using the Form Data format and the JSON format.

In both cases the answer will be the same and will be returned in JSON format

Invoke (FORM DATA):

```
POST https://api.hostedsms.pl/SimpleApi HTTP/1.1
Accept: */*
Content-Type: application/x-www-form-urlencoded; charset=UTF-8

UserEmail=useremail%40dcs.pl&Password=correctpassword&Sender=TEST&Phone=48xxxxxxxx&Message=TEST
```

Invoke (JSON)

```
POST https://api.hostedsms.pl/SimpleApi HTTP/1.1
Accept: application/xml
Content-Type: application/json; charset=UTF-8

{"UserEmail":"useremail@dcs.pl","Password":"correctpassword","Sender":"TEST","Phone":"48502505988","Message":"TEST712"}
```

Positive Response:

```
HTTP/1.1 200 OK
Cache-Control: no-cache
Pragma: no-cache
Content-Type: application/json; charset=utf-8
Expires: -1
Server: Microsoft-IIS/7.0
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Date: Tue, 25 Feb 2014 15:59:38 GMT
Content-Length: 52

{"MessageId":"ebc789b2-d111-4e9c-8a0e-d3ae0896364c"}
```

Negative Response:

```
HTTP/1.1 200 OK
Cache-Control: no-cache
Pragma: no-cache
Content-Type: application/json; charset=utf-8
Expires: -1
Server: Microsoft-IIS/7.0
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Date: Tue, 25 Feb 2014 15:55:42 GMT
Content-Length: 38
```

```
{"ErrorMessage":"Invalid Credentials"}
```

EXAMPLE - XML

Below the equivalent of the previous example in XML format

Invoke

POST https://api.hostedsms.pl/SimpleApi HTTP/1.1

Accept: application/xml

Content-Type: application/xml; charset=UTF-8

```
<SimpleSms>
  <UserEmail>useremail@dcs.pl</UserEmail>
  <Password>correctpassword</Password>
  <Sender>TEST</Sender>
  <Phone>48xxxxxxxx</Phone>
  <Message>TEST712</Message>
</SimpleSms>
```

NOTE: When calling XML, the order of parameters is important.

Positive Response:

HTTP/1.1 200 OK

Cache-Control: no-cache

Pragma: no-cache

Content-Type: application/xml; charset=utf-8

Expires: -1

Server: Microsoft-IIS/8.0

X-AspNet-Version: 4.0.30319

X-SourceFiles: =?UTF-8?B?QzpcHJvamVjdHNCRENTLkhvc3RlZFNTc1xEQ1MuSFNNUy5TaW1wbGVBCGk=?=

X-Powered-By: ASP.NET

Date: Mon, 03 Mar 2014 16:06:32 GMT

Content-Length: 138

```
<MessageSend xmlns:i="http://www.w3.org/2001/XMLSchema-instance"><MessageId>1eba6eb2-888f-41cb-
b146-9a1debd8621</MessageId></MessageSend>
```

Negative Response:

HTTP/1.1 200 OK

Cache-Control: no-cache

Pragma: no-cache

Content-Type: application/xml; charset=utf-8

Expires: -1

Server: Microsoft-IIS/8.0

X-AspNet-Version: 4.0.30319

X-SourceFiles: =?UTF-8?B?QzpcHJvamVjdHNCRENTLkhvc3RlZFNTc1xEQ1MuSFNNUy5TaW1wbGVBCGk=?=

X-Powered-By: ASP.NET

Date: Mon, 03 Mar 2014 16:11:55 GMT

Content-Length: 115

```
<Error xmlns:i="http://www.w3.org/2001/XMLSchema-instance"><ErrorMessage>Invalid
Credentials</ErrorMessage></Error>
```

FULLAPI INTERFACE

The FullApi interface is the REST version of the full Web Service interface. Any operation that can be performed in the web service interface can also be performed using the FullApi interface. A client for the interface is prepared in a of a Nuget package – HostedSms FullApi Client.

The FullApi interface is also available on the Swagger platform, which allows convenient usage of it in a web browser.

The interface is available at the following addresses:

- <https://api.hostedsms.pl/FullApi/> - primary DCS processing center
- <https://api2.hostedsms.pl/FullApi/> - backup DCS processing center
- <https://api.hostedsms.pl/FullApi/swagger/ui/index> - FullApi interface on the Swagger platform

AUTHORIZATION

Authorization in FullApi is of BASIC type.

The server will also accept the header Authorization in the form of username:password without Base64 encoding.

FULLAPI METHODS

FullApi supports all Web Service operations and also includes one operation that is not currently available in the Web Service:

MMSES - sends an MMS message to a specified phone number. This operation takes a FullMms object as input. The method returns an MmsMessageSend object containing the template ID and a list of new message IDs if the DCS system has accepted the message for sending. Currently, sending messages is supported for only one phone number.

OPERATION MAPPING

Operations are mapped into Rest objects according to the following table:

Operation	Object	Method	Notes
<i>SendSmses</i> <i>SendSms</i>	<i>Smses</i>	POST	The interface has only one method for sending SMS messages. To send a single SMS, use the Phones table with one element

<i>GetUnreadDeliveryReports</i> <i>GetDeliveryReports</i>	<i>DeliveryReports</i>	GET	GetDeliveryReports method is called if MessageIds and/or MarkAsRead parameters are supplied. Otherwise GetUnreadDeliveryReports is called
GetUnreadInputSmses GetInputSmses	InputSmses	GET	If any parameter is supplied, GetInputSmses is called. In case of no parameters supplied, GetUnreadInputSmses is called
GetUnreadOutputSmses GetOutputSmses	<i>OutputSmses</i>	GET	GetOutputSms is called if MarkAsRead and Recipient parameters are supplied. Otherwise GetUnreadOutputSmses will be called. MarkAsRead and Recipient parameters should be both set or both omitted. Warning – these method are turned off by default. Please contact support to turn it on.
GetValidSenders	ValidSenders	GET	
ConvertToGsm7	Gsm7	POST	
CheckPhones	CheckPhones	POST	
CustomerInfo	<i>CustomerInfo</i>	GET	
<i>GetUnreadMmsDeliveryReports</i> <i>GetMmsDeliveryReports</i>	<i>MmsDeliveryReports</i>	GET	If the MessageIds parameter is provided, the GetMmsDeliveryReports method is called. Otherwise, the GetMmsUnreadDeliveryReports method is used. Warning – these methods requires MMS feature turned on

			for client.
<i>Mmses</i> ⁷	<i>MmsMessageSend</i>	POST	Only single MMS message sending is supported. Requests containing more than one phone number will be rejected .

OBJECTS USED IN MMSES

```
public struct FullMms
{
    public string[] Phones { get; set; }
    public string Sender { get; set; }
    public string TransactionId { get; set; }
    public string CostCenter { get; set; }
    public Guid? TemplateId { get; set; }
    public Content Content { get; set; }
}
```

```
public struct Content
{
    public string Subject { get; set; }
    public Slide[] Slides { get; set; }
}
```

```
public struct Slide
{
    public string Text { get; set; }
    public string PictureMime { get; set; }
    public string Picture { get; set; }
}
```

⁷ Operacja dostępna tylko z użyciem interfejsu FullApi.

```
public struct MmsMessageSend
{
    public Guid TemplateId { get; set; }
    public Guid[] MessageIds { get; set; }
}
```

METHOD PARAMETERS / FIELD STRUCTURE

Most fields follow the descriptions from the [WebService method parameters](#). New fields are described below..

TEMPLATEID

```
Guid? TemplateId
```

MMS Template ID – optional parameter. When sending an MMS without using a template, the ID of the newly created template is returned.

By providing the parameter in the MMSES method, you can skip defining the message content.

PICTURE

```
string Picture
```

Base64 encoded image. Allowed images up to 100kb. This field is optional, but if provided, the image type must be specified in the `PictureMime` field.

PICTUREMIME

```
string PictureMime
```

Picture MIME type – the MIME type of the image provided in the `Picture` parameter, e.g., `image/png`, `image/jpeg`, or `image/gif`. This field is required only when the `Picture` parameter is provided.

PASSING THE PARAMETER PHONE/PHONES

If XML formatting is used, the `Phones` table must be supplied:

```
<Phones>
```

```
<Phone>Telefon1</Phone>
```

```
<Phone>Telefon1</Phone>
```

```
</Phones>
```


In case of formatting the form data subsequent phones should be given in the form of:

Phone=Telefon1&Phone=Telefon2

For JSON, the Phone parameter (which can be an array) must be passed on as

"Phone":["Telefon1","Telefon2"]

The query and answer formats are shown in the following examples:

EXAMPLES

AUTHORIZATION – FORMDATA/JSON

Query without authorization:

```
GET https://api.hostedsms.pl/FullApi/ValidSenders HTTP/1.1  
User-Agent: Fiddler
```

401 Server response

```
HTTP/1.1 401 Unauthorized  
Cache-Control: no-cache  
Pragma: no-cache  
Content-Type: application/json; charset=utf-8  
Expires: -1  
Server: Microsoft-IIS/8.0  
WWW-Authenticate: Basic  
X-AspNet-Version: 4.0.30319  
X-SourceFiles: =?UTF-  
8?B?QzpcCHJvamVjdHNcRENTLkhvc3RlZFhtc1xEQ1MuSFNNUy5GdWxsQXBpXFZhbGlkU2VuZGVycw==?=  
X-Powered-By: ASP.NET  
Date: Fri, 24 Jul 2015 14:13:56 GMT  
Content-Length: 94  
  
{ "ErrorMessage": "Invalid Login or Password", "CurrentTime": "2015-07-24T16:13:56.5601277+02:00" }
```

Query with Basic authorization

```
GET https://api.hostedsms.pl/FullApi/ValidSenders HTTP/1.1  
User-Agent: Fiddler  
Authorization: Basic c2RlX2FwaUBkY3MucGw6cXdIMTlzcXdl
```

Server response

```
HTTP/1.1 200 OK  
Cache-Control: no-cache  
Pragma: no-cache  
Content-Type: application/json; charset=utf-8  
Expires: -1  
Server: Microsoft-IIS/8.0  
X-AspNet-Version: 4.0.30319  
X-SourceFiles: =?UTF-  
8?B?QzpcCHJvamVjdHNcRENTLkhvc3RlZFhtc1xEQ1MuSFNNUy5GdWxsQXBpXFZhbGlkU2VuZGVycw==?=  
X-Powered-By: ASP.NET
```

Date: Fri, 24 Jul 2015 13:17:19 GMT
Content-Length: 30

{"Senders":["TEST","SDUSOFT"]}

EXAMPLES – XML

Invoke – GetValidSenders

GET <https://api.hostedsms.pl/FullApi/ValidSenders HTTP/1.1>
User-Agent: Fiddler
Authorization: Basic c2R1X2FwaUBkY3MucGw6cXdlMTIzcXdl
Accept: application/xml
Host: localhost:53596

Response - GetValidSenders

HTTP/1.1 200 OK
Cache-Control: no-cache
Pragma: no-cache
Content-Type: application/xml; charset=utf-8
Expires: -1
Server: Microsoft-IIS/8.0
X-AspNet-Version: 4.0.30319
X-SourceFiles: =?UTF-8?B?QzpcCHJvamVjdHNCRENTLkhvc3RIZFNtc1xEQ1MuSFNNUy5GdWxsQXBpXFZhbGlkU2VuZGVycw==?=
X-Powered-By: ASP.NET
Date: Fri, 24 Jul 2015 14:16:43 GMT
Content-Length: 205

<ValidSenders xmlns:i="http://www.w3.org/2001/XMLSchema-instance"><CurrentTime>2015-07-24T16:16:43.6298734+02:00</CurrentTime><Senders><Sender>TEST</Sender><Sender>SDUSOFT</Sender></Senders></ValidSenders>

Invoke – GetInputSms

GET <https://api.hostedsms.pl/FullApi/InputSmses?From=2014-07-09+18%3a00%3a00&To=2014-07-09+18%3a00%3a10&MarkAsRead=False HTTP/1.1>
User-Agent: Fiddler
Authorization: Basic c2R1X2FwaUBkY3MucGw6cXdlMTIzcXdl
Accept: application/xml
Host: localhost:53596

Response – GetInputSms:

HTTP/1.1 200 OK
Cache-Control: no-cache
Pragma: no-cache
Content-Type: application/xml; charset=utf-8
Expires: -1
Server: Microsoft-IIS/8.0
X-AspNet-Version: 4.0.30319
X-SourceFiles: =?UTF-8?B?QzpcCHJvamVjdHNCRENTLkhvc3RIZFNtc1xEQ1MuSFNNUy5GdWxsQXBpXElucHV0U21zZXM=?=
X-Powered-By: ASP.NET

Date: Fri, 24 Jul 2015 14:38:59 GMT
Content-Length: 60429

```
<InputSmsResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"><CurrentTime>2015-07-24T16:38:59.5690067+02:00</CurrentTime><InputSmses><InputSms><Message>@£$¥èëùìòçøøÅå_ÆæßÉ!\ "#%&'()*,-./0123456789:;&lt;=&gt;?¡ABCDEFGHIJKLMN O PQRSTU VWXYZÄÖÑÛÜ$¿abcdefghijklmnopqrstuvwxyzäönüa^{~}|€ </Message><MessageId>0fc068ca-a0d6-4b94-b5c8-0049694dd5a2</MessageId><Phone>48620000333</Phone><ReceivedTime>2014-07-09T15:48:38.317</ReceivedTime><Recipient>102</Recipient></InputSms><InputSms><Message>@£$¥èëùìòçøøÅå_ÆæßÉ!\ "#%&'()*,-./0123456789:;&lt;=&gt;?¡ABCDEFGHIJKLMN O PQRSTU VWXYZÄÖÑÛÜ$¿abcdefghijklmnopqrstuvwxyzäönüa^{~}|€ </Message><MessageId>8315e6a3-b360-416b-9305-03e94408fb51</MessageId><Phone>48620000259</Phone><ReceivedTime>2014-07-09T15:48:32.553</ReceivedTime><Recipient>102</Recipient></InputSms></InputSmsResponse>
```

Invoke – GetDeliveryReports:

GET [https://api.hostedsms.pl/FullApi/DeliveryReports?MessageIds\[\]=ebc789b2-d111-4e9c-8a0e-d3ae0896364c&MessageIds\[\]=69827e59-8bfa-4e39-94b5-b992aabab1e1&MarkAsRead=False](https://api.hostedsms.pl/FullApi/DeliveryReports?MessageIds[]=ebc789b2-d111-4e9c-8a0e-d3ae0896364c&MessageIds[]=69827e59-8bfa-4e39-94b5-b992aabab1e1&MarkAsRead=False) HTTP/1.1
User-Agent: Fiddler
Host: localhost:53596
Authorization: Basic c2R1X2FwaUBkY3MucGw6cXdIMTlzcXdl
Accept: application/xml

Response – GetDeliveryReports:

HTTP/1.1 200 OK
Cache-Control: no-cache
Pragma: no-cache
Content-Type: application/xml; charset=utf-8
Expires: -1
Server: Microsoft-IIS/8.0
X-AspNet-Version: 4.0.30319
X-SourceFiles: =?UTF-8?B?QzpcCHJvamVjdHNcRENTLkhvc3RlZFhtc1xEQ1MuSFNNUy5GdWxsQXBpXERlbGl2ZXJ5UmVwb3J0cw==?=
X-Powered-By: ASP.NET
Date: Fri, 24 Jul 2015 15:56:02 GMT
Content-Length: 686

```
<DeliveryReportResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"><CurrentTime>2015-07-24T17:56:02.9738596+02:00</CurrentTime><DeliveryReports><DeliveryReport><DeliveryTime>2013-10-03T16:42:21.693</DeliveryTime><MessageId>69827e59-8bfa-4e39-94b5-b992aabab1e1</MessageId><Phone>48502506086</Phone><ReportId>6bd24782-f4c2-49f1-bfea-0000082dc8a4</ReportId><Status>1</Status></DeliveryReport><DeliveryReport><DeliveryTime>2014-02-25T16:00:50.147</DeliveryTime><MessageId>ebc789b2-d111-4e9c-8a0e-d3ae0896364c</MessageId><Phone>48502505988</Phone><ReportId>ef8104a8-2b32-4cb0-942f-5bfb88004beb</ReportId><Status>1</Status></DeliveryReport></DeliveryReports></DeliveryReportResponse>
```

Invoke – SendSmses:

POST <https://api.hostedsms.pl/FullApi/Smses> HTTP/1.1
User-Agent: Fiddler
Host: localhost:53596
Authorization: Basic c2R1X2FwaUBkY3MucGw6cXdIMTlzcXdl

Content-Type: application/xml;charset=UTF-8
Accept: application/xml
Content-Length: 256

```
<FullSms>
<Phones>
  <Phone>48502505988</Phone>
</Phones>
<Message>Test</Message>
<Sender>TEST</Sender>
<TransactionId>sdfwavtydwfe</TransactionId>
<Priority>1</Priority>
<CostCenter>test</CostCenter>
<FlashSms>true</FlashSms>
</FullSms>
```

Response – SendSmses:

```
HTTP/1.1 200 OK
Cache-Control: no-cache
Pragma: no-cache
Content-Type: application/xml; charset=utf-8
Expires: -1
Server: Microsoft-IIS/8.0
X-AspNet-Version: 4.0.30319
X-SourceFiles: =?UTF-8?B?QzpcHJvamVjdHNCRENTLkhvc3RlZFNtc1xEQ1MuSFNNUy5GdWxsQXBpXFNtc2Vz?=-
X-Powered-By: ASP.NET
Date: Fri, 24 Jul 2015 16:51:59 GMT
Content-Length: 223

<MessageSend xmlns:i="http://www.w3.org/2001/XMLSchema-instance"><CurrentTime>2015-07-
24T18:51:59.2935229+02:00</CurrentTime><MessageIds><MessageId>1c80140f-a1fe-45e8-854b-
056405a86097</MessageId></MessageIds></MessageSend>
```

Example invocation of the CheckPhones method (without headers):

```
<CheckPhonesRequest>
<Phones>
  <Phone>48502505988</Phone>
  <Phone>502505988</Phone>
  <Phone>12333dddwww</Phone></Phones>
</CheckPhonesRequest>
```

Response to CheckPhones (without headers):

```
<CheckPhonesRequest>
<Phones>
  <Phone>48502505988</Phone>
  <Phone>502505988</Phone>
  <Phone>12333dddwww</Phone></Phones>
</CheckPhonesRequest>
```

Response CheckPhones (without headers):

```
<CheckPhonesResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
  <CurrentTime>2020-06-12T09:54:53.4757295+02:00</CurrentTime>
```

```
<ValidPhones>
  <Phone>48502505988</Phone>
</ValidPhones>
<InvalidPhones>
  <Phone>12333dddwww</Phone>
</InvalidPhones>
<Duplicates>
  <Phone>48502505988</Phone>
</Duplicates>
<BlockedPhones/>
</CheckPhonesResponse>
```

Invocation of Gsm7 (without headers):

```
<Gsm7Request>
<Text>żąć</Text>
</Gsm7Request>
```

Response from Gsm7 (without headers):

```
<Gsm7Response xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
  <CurrentTime>2020-06-12T10:41:12.3962847+02:00</CurrentTime>
  <Gsm7Text>zac</Gsm7Text>
</Gsm7Response>
```

Invoke CustomerInfo:

```
GET /DCS.HSMS.FullApi/CustomerInfo HTTP/1.1
Accept: application/xml
Authorization: Basic aHVIZXJ0LnNvcn9rYUBkY3MucGw6JHJmdmJndDU2eWhO
Host: localhost
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like
Gecko) Chrome/122.0.0.0 Safari/537.36
```

Response CustomerInfo (without headers):

```
<CustomerInfoResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
  <CurrentTime>2024-03-28T09:04:29.0930801+01:00</CurrentTime>
  <CustomerValidTo>2025-12-20T12:22:05</CustomerValidTo>
  <SmsCounter>1</SmsCounter>
</CustomerInfoResponse>
```

Invoke GetUnreadOutputSmses:

```
GET /DCS.HSMS.FullApi/OutputSmses?request.from=2024-05-24T00%3A00%3A00&request.to=2024-06-06T00%3A00%3A00 HTTP/1.1
Host: localhost
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:126.0) Gecko/20100101 Firefox/126.0
Accept: application/xml
Authorization: Basic aHVIZXJ0LnNvcn9rYUBkY3TaBGw6JHJmdmJndDU2eWhO
```

Response GetUnreadOutputSmses without headers):

```
<OutputSmsResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
  <CurrentTime>2024-06-04T12:50:27.2654973+02:00</CurrentTime>
```

```

<OutputSmses>
  <OutputSms>
    <Body i:nil="true" />
    <CostCenter i:nil="true" />
    <DeliveryStatus i:nil="true" />
    <DeliveryTime i:nil="true" />
    <Interface>FULLAPI</Interface>
    <MessageId>8d333df0-38ac-4d9e-9158-3cb691039597</MessageId>
    <MessageStatus>Sent</MessageStatus>
    <Phone>48123456789</Phone>
    <Sender>test</Sender>
    <SentTime>2024-05-29T13:06:29.963</SentTime>
    <SmsCount>2</SmsCount>
    <UserName>testusername</UserName>
  </OutputSms>
</OutputSmses>
</OutputSmsResponse>

```

Invoke GetOutputSmses:

```

GET /DCS.HSMS.FullApi/OutputSmses?request.markAsRead=false&request.from=2024-05-
24T00%3A00%3A00&request.to=2024-06-06T00%3A00%3A00&request.recipient=48123456789 HTTP/1.1
Host: localhost
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:126.0) Gecko/20100101 Firefox/126.0
Accept: application/xml
Authorization: Basic aHVlZXJ0LnNvcmlrYUBkY3TaBGw6JHJmdmJndDU2eWhO

```

Response GetOutputSmses (without headers):

```

<OutputSmsResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
  <CurrentTime>2024-06-04T12:54:37.4832432+02:00</CurrentTime>
  <OutputSmses>
    <OutputSms>
      <Body i:nil="true" />
      <CostCenter i:nil="true" />
      <DeliveryStatus i:nil="true" />
      <DeliveryTime i:nil="true" />
      <Interface>FULLAPI</Interface>
      <MessageId>39a71c84-bb95-4787-938f-9ab38b849214</MessageId>
      <MessageStatus>Sent</MessageStatus>
      <Phone>48123456789</Phone>
      <Sender>test</Sender>
      <SentTime>2024-05-29T12:36:43.727</SentTime>
      <SmsCount>2</SmsCount>
      <UserName>testusername</UserName>
    </OutputSms>
    <OutputSms>
      <Body i:nil="true" />
      <CostCenter i:nil="true" />
      <DeliveryStatus i:nil="true" />
      <DeliveryTime i:nil="true" />
      <Interface>FULLAPI</Interface>
      <MessageId>8d333df0-38ac-4d9e-9158-3cb691039597</MessageId>
      <MessageStatus>Sent</MessageStatus>
      <Phone>48123456789</Phone>
      <Sender>test</Sender>
    </OutputSms>
  </OutputSmses>
</OutputSmsResponse>

```

```
<SentTime>2024-05-29T13:06:29.963</SentTime>
<SmsCount>2</SmsCount>
<UserName>testusername</UserName>
</OutputSms>
</OutputSmses>
</OutputSmsResponse>
```

Invoke GetUnreadMmsDeliveryReports:

```
GET /DCS.HSMS.FullApi/MmsDeliveryReports?request.markAsRead=false
```

HTTP/1.1 Host: localhost

User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:126.0) Gecko/20100101 Firefox/126.0

Accept: application/xml

Authorization: Basic aHVIZXJ0LnNvcn9rYUBkY3TaBGw6JHJmdmJndDU2eWhO

Response GetUnreadMmsDeliveryReports (without headers):

```
<MmsDeliveryReportResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
  <CurrentTime>2024-07-03T07:53:43.4931959+02:00</CurrentTime>
  <DeliveryReports>
    <MmsDeliveryReport>
      <DeliveryTime>2024-06-19T14:11:14.867</DeliveryTime>
      <MessageId>d833ea39-da90-430c-896b-4028436521b4</MessageId>
      <Phone>48123456789</Phone>
      <Status>1</Status>
    </MmsDeliveryReport>
    <MmsDeliveryReport>
      <DeliveryTime>2024-06-19T14:11:14.867</DeliveryTime>
      <MessageId>f6862738-8f42-4f60-a456-af6ff3fb8f9e</MessageId>
      <Phone>481234567893</Phone>
      <Status>-1</Status>
    </MmsDeliveryReport>
    <MmsDeliveryReport>
      <DeliveryTime>2024-06-19T14:11:14.867</DeliveryTime>
      <MessageId>197ab95e-7118-4acf-b4ee-6a968531bbc6</MessageId>
      <Phone>48123456789</Phone>
      <Status>0</Status>
    </MmsDeliveryReport>
  </DeliveryReports>
</MmsDeliveryReportResponse>
```

Invoke GetMmsDeliveryReports:

```
GET /DCS.HSMS.FullApi/MmsDeliveryReports?request.markAsRead=false&request.messageIds=f6862738-8f42-4f60-a456-af6ff3fb8f9e&request.messageIds=d833ea39-da90-430c-896b-4028436521b4
```

HTTP/1.1 Host: localhost

User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:126.0) Gecko/20100101 Firefox/126.0

Accept: application/xml

Authorization: Basic aHVIZXJ0LnNvcn9rYUBkY3TaBGw6JHJmdmJndDU2eWhO

Response GetMmsDeliveryReports (without headers):

Example of Mmses invocation (without headers):

Version 1.9.9


```

32qcmEf2y40nQZ2uG42uMbOQmmupgq5m4+od0SWSZlIYLWn37UX9nbtVUKfriUnHmHlIPaCpCrp5jssXZKHSrHJ
ES3qHRDeLR91i5iHR6g1UQcvJRv2OWJvjVjliJf1YfK9xYc6r/1VrorGKfr9zzEwkLsZp8A0o/QhtP3Zfxi3bJQYeHq8zDNc
0moFdp5h5SDzSMZBfma2cqNmD/r3iLdvFBx7i888iPzaaqUqXmJkIR1C1eXiN9tVUfr4Z0nrr0FtL2stuulR9BxdYmZi
GJ2Aj014RPorarMwkWldeltJiwmLPtvNPeEOMXOhW8G16B2SheiypE2R3xsW0mLKbjel83o9pi50P16rW9iW6ei+
Fdhm6NurGwpabmodCFe69uMbo2ZjegEfBE9IP3E5zP9BnUdbClpuUwqz8nc/gFbY+YivGh79Q2OWIbEXPE0/G5Ic
Kdwc0n7iVbnZOS6iG0xsxEbmJZzlfKdTM2tgdaRlp+qBv2zd8oVreyHi3dL8WkreMtMbMRu2MRzIUaZaHZI51Hbgs
WM71posfiPpHoN+WubdDi76Yt4y0xsxEZdFSHdiUs7UvloX5Q1Vfx/+htwTu9YbwM3+TIWcqj3OP6WbCfJ+JfT9oS
MxeRQcc4WPdxDeOgWha6vnxskjerdiATXT3MYc4vn1zW/yab90ftNebDCZbHNibae+2p/tjO1Lz7zlvbEzvfZ8wHExt
0bEq0TcfZj8HHdhY85PhRE857nHTfMTNS/PPx9dffLQ+y75//e319/eTlboxoTAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAQnqvmXZZOhYnVf8AAAAASUVORK5CYII=</Picture>
</Slide>
</Slides>
</Content>
</FullMms>

```

Example of Mms Response (without headers):

```

<MmsMessageSend xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
  <CurrentTime>2024-07-19T15:21:01.552578+02:00</CurrentTime>
  <MessageIds>
    <MessageId>bfb064f7-b444-4adb-9f28-a25da65c103c</MessageId>
  </MessageIds>
  <TemplateId>928796a2-a1f3-4282-aa01-ff19f043586a</TemplateId>
</MmsMessageSend>

```

EXAMPLES – JSON / FORM DATA

Invoke SendSms (Form Data):

```

POST https://api.hostedsms.pl/FullApi/Smses HTTP/1.1
User-Agent: Fiddler
Authorization: Basic c2R1X2FwaUBkY3MucGw6cXdIMTlzcXdl
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
Host: localhost:53596
Content-Length: 133

Phone=48502505988&Phone=48502505989&Message=Test&Sender=TEST&TransactionId=sefsfasdwdfgdf3&
Priority=1&FlashSms=true&CostCenter=Test

```

Invoke SendSms (JSON):

```

POST https://api.hostedsms.pl/FullApi/Smses HTTP/1.1
User-Agent: Fiddler
Authorization: Basic c2R1X2FwaUBkY3MucGw6cXdIMTlzcXdl
Content-Type: application/json; charset=utf-8
Host: localhost:53596
Content-Length: 161

{"Phone":["48502505988","48502505989"],"Message":"Test","Sender":"TEST","TransactionId":"sefsfasdwdfgdf3","Priority":"1","FlashSms":"true","CostCenter":"Test"}

```

Response:

```

HTTP/1.1 200 OK

```

Cache-Control: no-cache
Pragma: no-cache
Content-Type: application/json; charset=utf-8
Expires: -1
Server: Microsoft-IIS/8.0
X-AspNet-Version: 4.0.30319
X-SourceFiles: =?UTF-8?B?QzpcHJvamVjdHNCRENTLkhvc3RIZFNtc1xEQ1MuSFNNUy5GdWxsQXBpXFNtc2Vz?=
X-Powered-By: ASP.NET
Date: Mon, 27 Jul 2015 08:37:26 GMT
Content-Length: 144

{"MessageIds":["8ef5a0b2-8bb8-41da-b70a-0753d3ad1609","1eb3c387-cc29-4d78-9c4b-30c8646b1cbe"],"CurrentTime":"2015-07-27T10:37:26.8137627+02:00"}