

CDA

ZCL_CRM_BAL_LOG

Release 740

Sistema

Classe: ZCL_CRM_BAL_LOG
Status: Ativo

Características

Descrição: BAL Log
Geração instância: Público
Não final
Não liberado
Aritmética em ponto fixo
Categoria: Tipo de objeto geral
Pacote: ZCRM
Idioma original: EN
Criado por: P000520
Criado em: 29.12.2014

Atributos
Atributos públicos

| Atributo | | Tp. | Descrição |
|-------------|--|-----|-----------|
| Tipo ref. | | | |
| Val.inicial | | | |

| | | |
|--------------------|-------------------|------------------------------|
| AV_OBJECT | Mant (só leitura) | Application log: Object name |
| (Application code) | CTG. BALOBJ_D | |
| AV_EXTNUM | Mant (só leitura) | Application Log: External ID |
| CTG. BALNREXT | | |

Atributos protegidos

| Atributo | | Tp. | Descrição |
|-------------|--|-----|-----------|
| Tipo ref. | | | |
| Val.inicial | | | |

| | | |
|-----------|------------------------|--|
| AO_HANDLE | Mant | BAL logging procedures control through the log |
| handle | | |
| CTG.REF.A | ZCL_CRM_BAL_LOG_HANDLE | |

Métodos
Métodos públicos

CONSTRUCTOR
Descrição: CONSTRUCTOR
Mét.instância
Parâmetro importaç.

P_OBJECT TYPE BALOBJ_D (Application log: Object name
(Application code))
P_EXTNUM TYPE BALNREXT (Application Log: External ID)

METHOD constructor.
me->av_object = p_object.
me->av_extnum = p_extnum.
ENDMETHOD.

PUT_MESSAGES
Descrição: Adds messages to the log.
Mét.instância

| | | | |
|-----|-----------------|-------------|---------|
| | 09.03.2015 | 11:17:34 | |
| 1 | | | |
| | ZCL_CRM_BAL_LOG | Release 740 | Sistema |
| CDA | | | |

Parâmetro importaç.
PT_MESSAGES TYPE BAPIRET2_T (Return parameter table)
Exceções
CX_BAPI_ERROR (BAPI Error Exception: Migrated Error Messages
Type "E")

METHOD put_messages.
DATA lx_error TYPE REF TO cx_bapi_error.
TRY .
IF me->ao_handle IS INITIAL.
me->set_handle().
ENDIF.
me->ao_handle->put_messages(pt_messages).
CATCH cx_bapi_error INTO lx_error.
RAISE EXCEPTION lx_error.
ENDTRY.
ENDMETHOD.

SAVE_LOG
Descrição: Saves messages in log to database.
Mét.instância

```
Exceções
CX_BAPI_ERROR  (BAPI Error Exception: Migrated Error Messages
Type "E")
METHOD save_log.
  DATA  lx_error TYPE REF TO cx_bapi_error.
  TRY .
    IF me->ao_handle IS INITIAL.
      me->set_handle( ).
    ENDIF.
    me->ao_handle->save_log( ).
  CATCH cx_bapi_error INTO lx_error.
    RAISE EXCEPTION lx_error.
  ENDTRY.
ENDMETHOD.
```

SHOW_MESSAGES
Descrição: Shows messages stored in this log.
Mét.instância

Parâmetro importaç.
P_TITLE TYPE BALTITLE (Application Log: Screen title)
P_MODE TYPE CHAR03 (Exhibition mode)

```
Exceções
CX_BAPI_ERROR  (BAPI Error Exception: Migrated Error Messages
Type "E")

METHOD show_messages.
  DATA: lo_api  TYPE REF TO lcl_api,
        lx_error TYPE REF TO cx_bapi_error.
  lo_api ?= me->get_api( ).
  TRY .
    lo_api->show_messages( p_object = me->av_object
                          p_extnum = me->av_extnum
                          p_title  = p_title
                          p_mode   = p_mode          ).
  CATCH cx_bapi_error INTO lx_error.
    RAISE EXCEPTION lx_error.
  ENDTRY.
ENDMETHOD.
```

| | | | |
|-------|-----------------|-------------|---------|
| <hr/> | | | |
| 2 | 09.03.2015 | 11:17:34 | |
| | | | |
| CDA | ZCL_CRM_BAL_LOG | Release 740 | Sistema |
| | | | |
| <hr/> | | | |
| <hr/> | | | |

```
CATCH cx_bapi_error INTO lx_error.
  RAISE EXCEPTION lx_error.
ENDTRY.
ENDMETHOD.

CLEAN_UP_MESSAGES
Descrição: Deletes from database entries older than a given date
```

Mét.instância

Parâmetro importaç.

P_DATE TYPE SYDATUM (System Date)

Exceções

CX_BAPI_ERROR (BAPI Error Exception: Migrated Error Messages
Type "E")

METHOD clean_up_messages.

DATA: lo_api TYPE REF TO lcl_api,
lx_error TYPE REF TO cx_bapi_error.

lo_api ?= me->get_api().

TRY .

lo_api->clean_up_log(p_object = me->av_object
p_date = p_date).

CATCH cx_bapi_error INTO lx_error.

RAISE EXCEPTION lx_error.

ENDTRY.

ENDMETHOD.

Métodos protegidos

GET_API

Descrição: Returns an instance of an API calls mediator.

Mét.instância

Parâmetro retorno

VALUE(RO_API) TYPE REF TO OBJECT (API calls mediator.)

METHOD get_api.

DATA lo_api TYPE REF TO lcl_api.

lo_api = NEW lcl_api().

IF lo_api IS BOUND.

ro_api = lo_api.

ENDIF.

FREE lo_api.

ENDMETHOD.

SET_HANDLE

Descrição: Sets the log handle.

Mét.instância

Exceções

CX_BAPI_ERROR (BAPI Error Exception: Migrated Error Messages
Type "E")

METHOD set_handle.

DATA: lo_api TYPE REF TO lcl_api,
lx_error TYPE REF TO cx_bapi_error,
lv_handle TYPE balloghndl.

lo_api ?= me->get_api().

09.03.2015

11:17:34

ZCL_CRM_BAL_LOG
CDA

Release 740

Sistema

```

        TRY .
            lo_api->get_log_handle( EXPORTING p_object      = me-
>av_object
                                     p_extnumber = me-
>av_extnum
                                     RECEIVING r_handle    = lv_handle
        ).
            CATCH cx_bapi_error INTO lx_error.
                FREE lo_api.
                RAISE EXCEPTION lx_error.
            ENDTRY.
            me->ao_handle = NEW zcl_crm_bal_log_handle( lv_handle ).
            FREE lo_api.
        ENDMETHOD.

```

Métodos redefinidos

Tipos locais

```

*** use this source file for any type of declarations (class
*** definitions, interfaces or type declarations) you need for
*** components in the private section

```

Definições classes locais

```

*** use this source file for the definition and implementation of
*** local helper classes, interface definitions and type
*** declarations

```

-----*

```

* Specification structure:
* .Classes:
*   ..OVERVIEW clause: A conceptual description of the class.
*   .Methods and Procedures (Sub-routines):
*   ..REQUIRES clause: states a precondition, e.g., a an
obligation on
*                               the client (ie, the caller of the
method).
*                               It?s a condition over the state in which
the
*                               method is invoked. If the precondition
does not
*                               hold, the implementation of the method is
free
*                               to do anything (including not
terminating,
*                               throwing an exception, returning
arbitrary
*                               results, making arbitrary modifications,
etc).
*   ..EFFECTS clause: states a postcondition, e.g., an
obligation on
*                               the implementor of the method. If the

```

```

state,
postcondition,
or not
structures may
-----*
-----*
* Class LCL_API
* OVERVIEW: Objects of this class mediates API calls. It aims to
* isolate this development from external dependencies,
as
private
By

```

precondition holds for the invoking
the method is obliged to obey the
by returning appropriate values,
throwing specified exceptions, modifying
modifying objects, and so on.
..MODIFIES clause: identifies which objects or data
be modified.

09.03.2015 11:17:34
4

ZCL_CRM_BAL_LOG Release 740 Sistema
CDA

```

appropriated
LCL_API,
-----*
-----*
CLASS lcl_api DEFINITION.
PUBLIC SECTION.
METHODS: get_log_handle IMPORTING p_object TYPE
balobj_d p_extnumber TYPE
balnrext RETURNING VALUE(r_handle) TYPE
balloghndl RAISING cx_bapi_error,
-----*
-----*

```

redefining the method GET_API one can provide
stubs, which must redefine the desired methods of
instead of accessing the real APIs.

```

* Method GET_LOG_HANDLE
*-----*
----*
* REQUIRES: The log object and the external identifier must be
provided.
* EFFECTS.: If the API BAL_LOG_CREATE returns an error, this
method
*           raises the exception type CX_BAPI_ERROR, otherwise
returns
*           the log handle.
*-----*
----*
* ->   P_OBJECT      Application log: Object name (Application
code).
* ->   P_EXTNUMBER   Instance Identification in Persistent
Object
*
*           References.
* <-   R_HANDLE      Application Log: Log Handle.
*-----*
----*
          show_messages IMPORTING p_object TYPE balobj_d
                           p_extnum TYPE balnrext
                           p_title  TYPE baltitle
                           p_mode   TYPE char03 OPTIONAL
                           RAISING   cx_bapi_error,
*-----*
----*
* Method SHOW_MESSAGES
*-----*
----*
* REQUIRES: The log object, the external identifier and the
window
*           title must be provided.
* EFFECTS.: If the API BAL_DSP_LOG_DISPLAY returns an error
raises
*           exception CX_BAPI_ERROR, otherwise shows the related
log
*           messages.
*-----*
----*
* ->   P_OBJECT      Application log: Object name (Application
code).
* ->   P_EXTNUMBER   Instance Identification in Persistent
Object
*
*           References.
* ->   P_TITLE       Application Log: Screen title.
* ->   P_MODE        Presentation mode (default STD).
*-----*
----*
          clean_up_log IMPORTING p_object TYPE balobj_d
                               p_date   TYPE sydatum
                               RAISING   cx_bapi_error.
*-----*
----*
* Method CLEAN_UP_LOG
*-----*
----*
*
* REQUIRES: The cut date must be provided.
*
* EFFECTS.: If the API BAL_DB_DELETE returns an error
raises

```

```

*               exception CX_BAPI_ERROR, otherwise deletes from
*               database entries older than the date provided.
*-----*
-----*

```

```

5      09.03.2015      11:17:34

```

```

CDA      ZCL_CRM_BAL_LOG      Release 740      Sistema

```

```

code).  * ->    P_OBJECT      Application log: Object name (Application
up.     * ->    P_DATE       Date up to which the log will be cleaned
*-----*
-----*
        PROTECTED SECTION.
        METHODS: get_search_arguments IMPORTING pw_lfil      TYPE
bal_s_lfil                                RETURNING VALUE(rt_lhdr) TYPE
balhdr_t                                RAISING    cx_bapi_error,
*-----*
-----*
        * Method GET_SEARCH_ARGUMENTS
*-----*
-----*
        *      REQUIRES: Log header filter criteria must be provided.
        *      EFFECTS.: If the API BAL_DB_SEARCH returns an error
raises   *
sorted  *      exception CX_BAPI_ERROR, otherwise returns a
        *      table of related log headers.
*-----*
-----*
        * -->    PW_LFIL      Log filter criteria
        * <--    RT_LHDR      Application Log: Log header data table
*-----*
-----*
        load_logs IMPORTING pw_lfil TYPE bal_s_lfil
                    RAISING    cx_bapi_error,
*-----*
-----*
        * Method LOAD_LOGS
*-----*
-----*
        *      REQUIRES: Log filter criteria must be provided.
        *      EFFECTS.: If the API BAL_DB_LOAD returns an error raises

```



```

*               exception CX_BAPI_ERROR.
*      MODIFIES: Loads the related log messages into memory.
*-----*
*  -->  PW_LFIL      Log filter criteria
*-----*
*               get_std_profile RETURNING VALUE(rw_dsprof) TYPE bal_s_prof
*                      RAISING   cx_bapi_error,
*-----*
*  Method GET_STD_PROFILE
*-----*
*      EFFECTS.: If the API BAL_DSP_PROFILE_STANDARD_GET returns
an
*               error raises exception CX_BAPI_ERROR, otherwise
*               returns standard format profile
*-----*
*  <--  RW_DSPROF      Log Output Format Profile
*-----*
*               get_pop_profile RETURNING VALUE(rw_dsprof) TYPE bal_s_prof
*                      RAISING   cx_bapi_error.
*-----*
*  Method GET_POP_PROFILE
*-----*
*      EFFECTS.: If the API BAL_DSP_PROFILE_POPUP_GET returns an
*               error raises exception CX_BAPI_ERROR, otherwise
*               returns standard format profile
*-----*
*  <--  RW_DSPROF      Log Output Format Profile
*-----*
*
*  ENDCLASS.
*  CLASS lcl_api IMPLEMENTATION.

```

```

09.03.2015      11:17:34
6

```

```

ZCL_CRM_BAL_LOG      Release 740      Sistema
CDA

```

```

METHOD get_log_handle.
  DATA: lw_log      TYPE bal_s_log,      "Log header data

```

```

        lvc_dummy(1) TYPE c,
        lw_return    TYPE bapiret2,
        lt_return    TYPE bapiret2_t.
* define some header data of this log
    lw_log-extnumber = p_extnumber.
    lw_log-object    = p_object.
    lw_log-aldate    = sy-datum.
    lw_log-altime    = sy-uzeit.
    lw_log-aluser    = sy-uname.
    lw_log-alprog    = sy-repid.
    CALL FUNCTION 'BAL_LOG_CREATE'
        EXPORTING
            i_s_log                = lw_log
        IMPORTING
            e_log_handle           = r_handle
        EXCEPTIONS
            log_header_inconsistent = 1
            OTHERS                  = 2.
    IF sy-subrc <> 0.
        m_raise_fm_exception sy-msgid sy-msgty sy-msgno
                               sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
    ENDIF.
ENDMETHOD.
METHOD show_messages.
    DATA: lr_object          TYPE          bal_s_obj,
           lr_extnumber       TYPE          bal_s_extn,
           lw_log_filter      TYPE          bal_s_lfil,
           lw_display_profile TYPE          bal_s_prof,
           lvc_dummy(1)      TYPE          c,
           lw_return          TYPE          bapiret2,
           lt_return          TYPE          bapiret2_t,
           lx_error           TYPE REF TO cx_bapi_error,
           lv_mode            TYPE          char03.
* create a filter with all relevant criteria:
    lr_object-sign = 'I'.
    lr_object-option = 'EQ'.
    lr_object-low = p_object.
    APPEND lr_object TO lw_log_filter-object.
    lr_extnumber-sign = 'I'.
    lr_extnumber-option = 'EQ'.
    lr_extnumber-low = p_extnum.
    APPEND lr_extnumber TO lw_log_filter-extnumber.
    TRY .
* Load logs into memory
        load_logs( lw_log_filter ).
* Initilizes the displaying profile
    IF p_mode IS SUPPLIED.
        lv_mode = p_mode.
    ELSE.
        lv_mode = 'STD'.
    ENDIF.
    CASE lv_mode.

```

CDA ZCL_CRM_BAL_LOG

Release 740

Sistema

```

        WHEN 'POP'.
            lw_display_profile = get_pop_profile( ).
        WHEN OTHERS.
            lw_display_profile = get_std_profile( ).
        ENDCASE.
        CATCH cx_bapi_error INTO lx_error.
        RAISE EXCEPTION lx_error.
    ENDTRY.
* use grid and detail level for display
    lw_display_profile-title = p_title.
* call display function module
    CALL FUNCTION 'BAL_DSP_LOG_DISPLAY'
        EXPORTING
            i_s_display_profile = lw_display_profile
            i_s_log_filter      = lw_log_filter
        EXCEPTIONS
            profile_inconsistent = 1
            internal_error       = 2
            no_data_available    = 3
            no_authority         = 4
            OTHERS               = 5.
    IF sy-subrc <> 0.
        m_raise_fm_exception sy-msgid sy-msgty sy-msgno
                             sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
    ENDIF.
ENDMETHOD.
METHOD load_logs.
    DATA: lt_log_header TYPE balhdr_t,
           lx_error      TYPE REF TO cx_bapi_error,
           lvc_dummy(1) TYPE c,
           lw_return     TYPE bapiret2,
           lt_return     TYPE bapiret2_t.
* search on DB for the logs
    TRY .
        lt_log_header = get_search_arguments( pw_lfil ).
        CATCH cx_bapi_error INTO lx_error.
        RAISE EXCEPTION lx_error.
    ENDTRY.
* load messages into memory
    CALL FUNCTION 'BAL_DB_LOAD'
        EXPORTING
            i_t_log_header = lt_log_header[]
        EXCEPTIONS
            no_logs_specified = 1
            log_not_found     = 2
            log_already_loaded = 3.
    IF sy-subrc <> 0.
        m_raise_fm_exception sy-msgid sy-msgty sy-msgno
                             sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
    ENDIF.

```

```

ENDMETHOD.
METHOD get_search_arguments.
  DATA: lvc_dummy(1) TYPE c,
         lw_return     TYPE bapiret2,

```

| | | | |
|--|------------|----------|--|
| | 09.03.2015 | 11:17:34 | |
|--|------------|----------|--|

| | | | |
|---|--|--|--|
| 8 | | | |
|---|--|--|--|

| | | | |
|--|-----------------|-------------|---------|
| | ZCL_CRM_BAL_LOG | Release 740 | Sistema |
|--|-----------------|-------------|---------|

| | | | |
|-----|--|--|--|
| CDA | | | |
|-----|--|--|--|

```

        lt_return     TYPE bapiret2_t.
CALL FUNCTION 'BAL_DB_SEARCH'
  EXPORTING
    i_s_log_filter     = pw_lfil
  IMPORTING
    e_t_log_header     = rt_lhdr
  EXCEPTIONS
    log_not_found      = 1
    no_filter_criteria = 2.
IF sy-subrc <> 0.
  m_raise_fm_exception sy-msgid sy-msgty sy-msgno
                      sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
ENDIF.
ENDMETHOD.
METHOD get_std_profile.
  DATA: lvc_dummy(1) TYPE c,
         lw_return     TYPE bapiret2,
         lt_return     TYPE bapiret2_t.
CALL FUNCTION 'BAL_DSP_PROFILE_STANDARD_GET'
  IMPORTING
    e_s_display_profile = rw_dsprof
  EXCEPTIONS
    OTHERS              = 1.
IF sy-subrc <> 0.
  m_raise_fm_exception sy-msgid sy-msgty sy-msgno
                      sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
ENDIF.
rw_dsprof-use_grid    = 'X'.
rw_dsprof-bydetlevel = 'X'.
ENDMETHOD.
METHOD get_pop_profile.
  DATA: lvc_dummy(1) TYPE c,
         lw_return     TYPE bapiret2,
         lt_return     TYPE bapiret2_t.
CALL FUNCTION 'BAL_DSP_PROFILE_POPUP_GET'
  IMPORTING
    e_s_display_profile = rw_dsprof
  EXCEPTIONS

```

```

        OTHERS                        = 1.
    IF sy-subrc <> 0.
        m_raise_fm_exception sy-msgid sy-msgty sy-msgno
                               sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
    ENDIF.
ENDMETHOD.
METHOD clean_up_log.
    DATA: lr_object                  TYPE      bal_s_obj,
           lr_date                    TYPE      bal_s_date,
           lw_log_filter              TYPE      bal_s_lfil,
           lw_display_profile         TYPE      bal_s_prof,
           lt_log_header              TYPE      balhdr_t,
           lx_error                   TYPE REF TO cx_bapi_error,
           lvc_dummy(1)              TYPE      c,
           lw_return                  TYPE      bapiret2,
           lt_return                  TYPE      bapiret2_t.

```

| | |
|------------|----------|
| 09.03.2015 | 11:17:34 |
|------------|----------|

9

| | | |
|-----------------|-------------|---------|
| ZCL_CRM_BAL_LOG | Release 740 | Sistema |
|-----------------|-------------|---------|

CDA

```

* create a filter with all relevant criteria:
    lr_object-sign = lr_date-sign = 'I'.
    lr_object-option = 'EQ'.
    lr_object-low   = p_object.
    APPEND lr_object TO lw_log_filter-object.
    lr_date-option = 'LE'.
    lr_date-low    = p_date.
    APPEND lr_date TO lw_log_filter-aldate.
* search on DB for the logs
    TRY .
        lt_log_header = get_search_arguments( lw_log_filter ).
        CATCH cx_bapi_error INTO lx_error.
        RAISE EXCEPTION lx_error.
    ENDTRY.
* Delete the log
    IF lt_log_header[] IS NOT INITIAL.
        CALL FUNCTION 'BAL_DB_DELETE'
            EXPORTING
                i_t_logs_to_delete = lt_log_header[]
*                i_in_update_task   = 'X'
*                i_with_commit_work = 'X'
            EXCEPTIONS
                no_logs_specified = 1
                OTHERS            = 2.
    IF sy-subrc <> 0.
        m_raise_fm_exception sy-msgid sy-msgty sy-msgno

```

```

                                sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
        ENDIF.
    ENDIF.
    ENDMETHOD.
ENDCLASS.
Macros
*** use this source file for any macro definitions you need
*** in the implementation part of the class
DEFINE m_raise_fm_exception.
    message id &1
           type &2
           number &3
           with &4 &5 &6 &7
           into lvc_dummy.
    lw_return-type      = sy-msgty.
    lw_return-id        = sy-msgid.
    lw_return-number    = sy-msgno.
    lw_return-message_v1 = sy-msgv1.
    lw_return-message_v2 = sy-msgv2.
    lw_return-message_v3 = sy-msgv3.
    lw_return-message_v4 = sy-msgv4.
    append lw_return to lt_return.
    raise exception type cx_bapi_error
    exporting
        status = lt_return[].
END-OF-DEFINITION.
```

| | | | |
|-------|-----------------|-------------|---------|
| <hr/> | | | |
| 10 | 09.03.2015 | 11:17:34 | |
| | | | |
| CDA | ZCL_CRM_BAL_LOG | Release 740 | Sistema |
| | | | |
| <hr/> | | | |
| <hr/> | | | |

| | | |
|---|----------------------|--|
| | Síntese | |
| | Características | |
| 1 | | |
| | Atributos | |
| 1 | | |
| | Atributos públicos | |
| 1 | | |
| | Atributos protegidos | |
| 1 | | |
| | Métodos | |
| 1 | | |

| | | |
|---|---------------------------|--|
| | Métodos públicos | |
| 1 | CONSTRUCTOR | |
| 1 | PUT_MESSAGES | |
| 1 | SAVE_LOG | |
| 2 | SHOW_MESSAGES | |
| 2 | CLEAN_UP_MESSAGES | |
| 3 | Métodos protegidos | |
| 3 | GET_API | |
| 3 | SET_HANDLE | |
| 3 | Métodos redefinidos | |
| 4 | | |
| | Tipos locais | |
| 4 | | |
| | Definições classes locais | |
| 4 | | |
| | Macros | |

| | | |
|----|------------|----------|
| 11 | 09.03.2015 | 11:17:34 |
|----|------------|----------|