NO.:
DATE:

Variable Name	Data Type	Variable Type	Stored In
employeeCount	int	Static / Class	Method Area
name	String	Instance	Heap
salary	double	Instance	Heap
e1	Employee	Local	Stack
e2	Employee	Local	Stack
e3	Employee	Local	Stack

Statement	what happens	Memory Impact
e1 = new Employee ("Anna", 20000)	new object is created with name "Anna" salary → 20000 Adds to employee count	Heap new Employee Allocated Stack stores its address
e2 = new Employee ("Brian", 25000)	new object created Add to Employee count	new Employee ~~Allocated~~ ~~stack: stores its address~~
e3 = e1	points to same object as e1	stores same address as e1
e3.salary = 22000	since e3 and e1 is the same Anna's salary is now 22,000	updated object 20000 → 22000
e2 = e1	points to Anna's Brian has no more reference	eligible for garbage collection

VICTORY

NO.:
DATE:

e3. Increasesalary(e2)	Anna's salary is now 27000 Employee count 2+1 = 3	Employee count is now 3 And Anna's salary is now 27000
e2 = null	no longer references Any object	Anna object still Alive (e3 references it)
e3.display()	Print's Anna's Name salary and EmployeeCount	No memory change

OUTPUT = Anna 27000.0 3